

## تنظیمات امنیتی Weblogic

- فعال سازی تنظیم امنیتی **Set cookie with HttpOnly and Secure**

### Weblogic در flag

تگ های xml زیر را به فایل weblogic.xml واقع در مسیر

accounting/WEB-INF/weblogic.xml

اپلیکیشن خود بیفزایید:

```
<wls:session-descriptor>  
<cookie-name>oimjsessionid</cookie-name>  
<wls:cookie-secure>true</wls:cookie-secure>  
<wls:cookie-http-only>true</wls:cookie-http-only>  
<wls:url-rewriting-enabled>false</wls:url-rewriting-enabled>  
</wls:session-descriptor>
```

- تنظیم امنیتی weblog برای جلوگیری از حملات DOS

برای این کار ابتدا وارد کنسول وب لاجیک شده از سمت چپ بر روی Lock & Edit کلیک کنید. حال بر روی علامت + گزینه Enviroment کلیک کرده و گزینه Server را انتخاب و در صفحه اصلی طبق شکل زیر AdminServer را انتخاب کنید سپس بر روی تب Protocols کلیک کرده و تنظیمات زیر را اعمال نمایید:

مقدار Complete Message Timeout: را ۱۰ قرار داده و گزینه save را بزنید.

## Settings for AdminServer

Configuration **Protocols** Logging Debug Monitoring Control Deployments Services Security Notes

**General** HTTP jCOM IIOP Channels

Save

Use this page to configure connection settings for various communication protocols that this server can use. All settings on this page can be overridden for each channel. Each channel can override these settings.

**Complete Message Timeout:**

60

**Idle Connection Timeout:**

65

☐ **Enable Tunneling**

**Tunneling Client Ping:**

45

**Tunneling Client Timeout:**

40

**Maximum Message Size:**

10000000

Save