

## Interprocess Synchronization

### Concurrent Access To Shared Memory : Race Problems

If a memory variable is shared by different processes and these processes modify it concurrently, then this might lead to a final erroneous result ! The goal in the following exercise is to show these possible errors.

1. Using two tasks, create a shared variable 'i' (using shmget and shmat) and initialize it 65; one task should increment the variable and the other one should decrement it
2. Explain why the following code could lead to an error.

```
Reg = i

sleep(for_some_time) // your choice

Reg++ (or Reg--); // depending on the task

i = Reg;
```

### Solving the Problem : Synchronizing access using semaphores

1. Use semaphores to enforce mutual exclusion (sem\_init, sem\_wait, sem\_post)
  - a. Use P and V to enforce mutual exclusion and solve the race problem in the first exercise
  - b. What if we had more than two processes ? Is there something else to do to enforce mutual exclusion ? Explain and experiment using three processes.
2. Use semaphores to run 3 different applications (firefox, emacs, vi) in a predefined sequence no matter in which order they are launched.
3. Use semaphores to implement the following parallelized calculation  $(a+b)*(c-d)*(e+f)$   
T1 runs (a+b) and stores the result in a shared table (1st available spot)  
T2 runs (c+d) and stores the result in a shared table (1st available spot)  
T3 runs (e+f) and stores the result in a shared table (1st available spot)  
T4 awaits for two tasks to end and does the corresponding calculation  
T4 awaits for the remaining task to end and does the final calculation then displays the result
4. Implement a synchronized solution to the barber problem using semaphores

