DEPLOYMENT RUNBOOK · MILESTONE 0

AgentOps Studio
Azure VM Setup & Deployment

The complete tab-by-tab configuration, Linux deployment, troubleshooting, verification, cost budget, and cleanup record

Application: AgentOps Studio

Repository: hafiz475/agentops-ai-workflow-platform

Azure resource group: rg-agentops-demo

VM: vm-agentops-demo · Central India

Deployment date: 6 November 2026

Final deployed commit: 15f1212

Prepared as a reproducible deployment record. Generated passwords and the SSH private key are intentionally not included.

Contents

1. Final outcome and architecture
2. Why this deployment design was chosen
3. Create the Azure virtual machine
4. Exact settings on every Azure VM tab
5. Cloud-init and Linux deployment
6. Automatic startup with systemd
7. API health-check failure and permanent fix
8. Deployment verification
9. Create the Azure budget
10. Railway cleanup
11. Daily operations and maintenance
12. Security, limitations, and shutdown

1. Final outcome and architecture

> **Deployment result:** the full Milestone 0 application is running successfully on one Azure Linux VM. The frontend, API, AI service, PostgreSQL, and Redis containers start automatically after reboot.

Item	Final value
Resource group	`rg-agentops-demo`
Virtual machine	`vm-agentops-demo`
Region / image	Central India / Ubuntu Server 24.04 LTS, x64 Gen2
VM size	Standard B2ls v2 — 2 vCPUs, 4 GiB RAM
Public IP at deployment	`4.247.145.108`
Frontend	`http://4.247.145.108:3000/`
API health	`http://4.247.145.108:3001/health`
API readiness	`http://4.247.145.108:3001/ready`

Container	Purpose	Port exposure
web	React/Vite production build served by Nginx	Public TCP 3000 → container 80
api	Fastify control-plane API	Public TCP 3001
ai-service	FastAPI execution service	Host 8000; blocked by Azure NSG
postgres	PostgreSQL 16 data store	Private Compose network only, 5432
redis	Redis 7 cache/coordination	Private Compose network only, 6379

2. Why this design was chosen

- **One VM:** Railway's free-plan resource limit could not host the API, AI service, PostgreSQL, and Redis together. One Azure VM could run all five containers and use the available Azure credit.
- **Docker Compose:** the repository already defined all services, health checks, dependency order, volumes, and internal DNS names.
- **Standard B2ls v2:** the originally preferred B2s SKU was unavailable for this subscription in Central India. B2ls v2 was deployable and provided the required 2 vCPUs and 4 GiB RAM.
- **Standard SSD:** enough for a Milestone 0 demo while keeping storage cost lower than Premium SSD.
- **Ports 3000 and 3001 only:** users need the frontend and API. PostgreSQL, Redis, and the Python service do not need direct internet access.
- **SSH restricted to one IP:** prevents the whole internet from attempting SSH login.
- **Systemd:** makes the Compose stack return automatically after a VM restart.

3. Create the Azure virtual machine

1. Sign in to the Azure portal.
2. Use the top search bar to search for **Virtual machines**.
3. Open **Virtual machines** under Services, then select **Create** → **Azure virtual machine**.
4. Complete each tab using the settings in the next section. Do not use the ARM64 Ubuntu image; the selected application deployment used x64.

4. Exact settings on every Azure VM tab

4.1 Basics

Field	Configured value	Reason
Subscription	Azure subscription 1	Subscription containing the $200 promotional credit.
Resource group	Create new: `rg-agentops-demo`	Keeps every demo resource together for cost tracking and one-step cleanup.
VM name	`vm-agentops-demo`	Clear, application-specific name.
Region	Central India	Chosen region close to the operator; SKU availability was checked manually.
Availability	No infrastructure redundancy required	Single-VM demo; avoids additional resources and cost.
Security type	Trusted launch virtual machines	Enables Secure Boot and vTPM.
Image	Ubuntu Server 24.04 LTS, x64 Gen2	Long-term-support Linux with Docker compatibility.
Architecture	x64	Matches the selected container/runtime path.
Size	Standard B2ls v2	B2s was unavailable; this SKU supplied 2 vCPUs and 4 GiB RAM.
Spot discount	Off / On-demand	Avoids eviction during the demo.
Authentication	SSH public key	Safer than password authentication.
Username	`azureuser`	Linux administrator account used for SSH.
SSH key source	Generate new key pair	Azure generated the public/private pair.
Key type / name	RSA / `agentops-demo-key`	Compatible OpenSSH key.
Public inbound ports	None	Custom, restricted rules were created on the Networking tab.

> **SSH private key:** Azure downloaded it once during VM creation. Store it securely. Never upload it to GitHub, paste it into cloud-init, or include it in documentation.

4.2 Disks

Field	Configured value
Encryption at host	Off (not registered for the subscription)
OS disk size	Image default — 30 GiB
OS disk type	Standard SSD (StandardSSD_LRS)
Delete with VM	Enabled
Ultra Disk compatibility	Disabled
Key management	Platform-managed key
Data disks	None
Ephemeral OS disk	None

4.3 Networking

Field	Configured value
Virtual network	New `vnet-centralindia-1`
Subnet	New `snet-centralindia-1`, `172.16.0.0/24`
Public IP	New `vm-agentops-demo-ip`
NIC network security group	Advanced → new `vm-agentops-demo-nsg`
Delete public IP and NIC with VM	Enabled
Accelerated networking	Enabled/required by selected size
Load balancing	None

Inbound rule 1 — restricted SSH

Setting	Value
Source	My IP address: `115.97.8.157/32`
Source port range	`1-65535` (the portal rejected `*` during this session)
Destination / service	Any / SSH
Destination port / protocol	22 / TCP
Action / priority	Allow / 900
Name	`default-allow-ssh`

Inbound rule 2 — public frontend and API

Setting	Value
Source / source ports	Any / `1-65535`
Destination / service	Any / Custom
Destination ports / protocol	`3000,3001` / TCP
Action / priority	Allow / 1010
Name / description	`allow-agentops-web-api` / Public AgentOps frontend and API

> **Intentionally not opened:** 8000 (AI service), 5432 (PostgreSQL), and 6379 (Redis). They remain unavailable from the internet.

4.4 Management

Setting	Value
System-assigned managed identity	On
Microsoft Entra ID login	Off
Auto-shutdown	Off during creation
Periodic assessment	Off
Patch orchestration	Image default
Hibernation	Off
Backup / Site Recovery	Off

4.5 Monitoring

Setting	Value
Recommended alert rules	Off
Boot diagnostics	Enabled with managed storage account
OS guest diagnostics	Off
Application health monitoring	Off

4.6 Advanced

Setting	Value
Extensions	None
VM applications	None
Custom data	Cloud-init deployment script (see Section 5)
NVMe optimization	Off / unsupported for selected size
Install SQL Server	Off
Capacity reservation	None

4.7 Tags

Applied to all selectable resources:

Name	Value
`application`	`agentops-studio`
`environment`	`demo`
`milestone`	`0`

4.8 Review + create

1. Confirm validation passes and the size is **Standard B2ls v2**.
2. Review the displayed compute estimate: **$0.0448 USD/hour**, approximately **$32.70/month** for the VM. Disk, public IP, monitoring, tax, and bandwidth can add cost.
3. Select **Create**, then download the generated private key when prompted.
4. Wait for **Your deployment is complete**, then select **Go to resource**.

5. Cloud-init and Linux deployment

The VM bootstrap installed Git, Docker Engine, and Docker Compose v2; cloned the `main` branch; created a protected `.env` with a generated PostgreSQL password; built the containers; and started the stack.

> **Secret handling:** the real generated PostgreSQL password is stored only on the VM and is omitted here. The following is the sanitized, reproducible form of the deployment procedure.

```
#!/usr/bin/env bash
set -euo pipefail

apt-get update
apt-get install -y ca-certificates curl git openssl
curl -fsSL https://get.docker.com | sh
usermod -aG docker azureuser

git clone --branch main \
  https://github.com/hafiz475/agentops-ai-workflow-platform.git \
  /opt/agentops-ai-workflow-platform
cd /opt/agentops-ai-workflow-platform

POSTGRES_PASSWORD="$(openssl rand -hex 24)"
install -m 600 /dev/null .env
printf 'POSTGRES_USER=agentops\nPOSTGRES_DB=agentops\nPOSTGRES_PASSWORD=%s\n' \
  "$POSTGRES_PASSWORD" > .env

docker compose up -d --build
docker compose ps
```

The equivalent custom-data field begins with `#cloud-config` and invokes these commands under `runcmd`. Azure processed the custom data with cloud-init during first boot.

Ways to run Linux commands later

Azure portal: VM → Operations → Run command → RunShellScript. This was used to inspect and repair the deployment without opening an unrestricted SSH rule.

SSH from the allowed IP:

```
ssh -i .\agentops-demo-key.pem azureuser@4.247.145.108
```

If the home/public IP changes, update the SSH NSG source to the new exact `/32` address before attempting SSH. Never change it to Any or `0.0.0.0/0`.

6. Automatic startup with systemd

A service unit was created at `/etc/systemd/system/agentops-compose.service`:

```
[Unit]
Description=AgentOps Studio Docker Compose
Requires=docker.service
After=docker.service network-online.target

[Service]
Type=oneshot
RemainAfterExit=yes
WorkingDirectory=/opt/agentops-ai-workflow-platform
ExecStart=/usr/bin/docker compose up -d
ExecStop=/usr/bin/docker compose stop
TimeoutStartSec=0

[Install]
WantedBy=multi-user.target
```

```
sudo systemctl daemon-reload
sudo systemctl enable agentops-compose.service
sudo systemctl start agentops-compose.service
sudo systemctl status agentops-compose.service --no-pager
```

Why: Docker restarts with the VM, and systemd reliably recreates/starts the Compose application in dependency order.

7. API health-check failure and permanent fix

Observed symptoms

- PostgreSQL, Redis, and the AI service were healthy.
- The API answered successfully from the VM, but Docker marked it unhealthy.
- The web container did not start because it depends on a healthy API.
- The systemd unit failed because `docker compose up -d` reported that dependency failure.

Diagnosis commands

```
cd /opt/agentops-ai-workflow-platform
sudo docker compose ps
sudo docker compose logs --tail=100 api
sudo docker compose exec api wget -qO- http://localhost:3001/ready
sudo docker compose exec api wget -qO- http://127.0.0.1:3001/ready
sudo journalctl -u agentops-compose.service -n 100 --no-pager
```

`localhost` resolved to IPv6 inside the API container while Fastify was reachable over IPv4. Therefore the readiness request worked at `127.0.0.1` but failed at `localhost`.

Permanent repository fix

The API health check in `docker-compose.yml` was changed from:

```
http://localhost:3001/ready
```

to:

```
http://127.0.0.1:3001/ready
```

The change was committed and pushed to GitHub:

```
15f1212 fix: use IPv4 for API container healthcheck
```

Update the VM

```
cd /opt/agentops-ai-workflow-platform
sudo git pull --ff-only origin main
sudo docker compose up -d --build
sudo systemctl daemon-reload
sudo systemctl restart agentops-compose.service
sudo docker compose ps
```

The VM fast-forwarded from `ffbeac5` to `15f1212`. The temporary override used during diagnosis was removed, leaving the native Compose file as the source of truth.

8. Deployment verification

On the VM

```
cd /opt/agentops-ai-workflow-platform
sudo docker compose ps
sudo systemctl is-enabled agentops-compose.service
sudo systemctl is-active agentops-compose.service
curl -fsS http://127.0.0.1:3000/ >/dev/null && echo "frontend: ok"
curl -fsS http://127.0.0.1:3001/health
curl -fsS http://127.0.0.1:3001/ready
curl -fsS http://127.0.0.1:8000/health
```

Expected results:

- All five containers are Up; API, AI service, PostgreSQL, and Redis report healthy.
- The service reports `enabled` and `active`.
- API health and readiness return `{"status":"ok",...}`.

From a browser

- `http://4.247.145.108:3000/` — dashboard loads.
- `http://4.247.145.108:3001/health` — API health is OK.
- `http://4.247.145.108:3001/ready` — dependencies are ready.

> **Verified final state:** all containers healthy, systemd enabled and active, frontend reachable, and both API probes returning OK.

9. Create the Azure budget

1. In Azure, open **Resource groups**.
2. Open `rg-agentops-demo`.
3. Open **Cost Management** → **Budgets**.
4. Select **Add/Create budget**.
5. Set the budget name to `agentops-demo-budget`, reset period to **Monthly**, and amount to **$150 USD**.
6. Add an **Actual cost** alert at **75%**.
7. Add a **Forecasted cost** alert at **90%**.
8. Leave Action group as **None** and add the deployment-owner email once. If Azure shows “Unique email address is required,” delete the invalid/duplicate row, enter the address in the empty row, and press Tab once.
9. Save the budget and confirm it appears in the resource-group budget list.

> **Important:** an Azure budget sends notifications; it does not automatically stop the VM or prevent charges. Stop/deallocate or delete resources when they are not needed.

10. Railway cleanup

After Azure was fully verified, the unused Railway project was deleted. This removed the Railway PostgreSQL and Redis instances, their volumes, and the staged API service. It did not affect Azure because the Azure VM uses its own local Compose volumes and services.

1. Open the Railway project `fantastic-bravery`.
2. Open Project Settings → Danger Zone.
3. Select Delete Project and confirm the exact project name.
4. Verify that the old project and resources no longer appear.

11. Daily operations and maintenance

Check status

```
cd /opt/agentops-ai-workflow-platform
sudo docker compose ps
sudo systemctl status agentops-compose.service --no-pager
```

View logs

```
sudo docker compose logs --tail=200
sudo docker compose logs -f api
sudo journalctl -u agentops-compose.service -n 200 --no-pager
```

Deploy a new commit from main

```
cd /opt/agentops-ai-workflow-platform
sudo git pull --ff-only origin main
sudo docker compose up -d --build
sudo docker compose ps
```

Restart application

```
sudo systemctl restart agentops-compose.service
```

Stop or start the VM to control cost

Use Azure VM Overview → **Stop** and wait until the status is **Stopped (deallocated)**. A shutdown performed only inside Linux may leave compute allocated. Start it again from the same Azure page.

The public IP can change after deallocation unless it is configured as static. Re-check the VM Overview page before using the URLs.

12. Security, limitations, and final checklist

Security controls in place

- SSH key authentication; no password login.
- SSH restricted to `115.97.8.157/32` at deployment time.
- Only ports 3000 and 3001 are publicly allowed for the app.
- Database, Redis, and AI execution ports are not allowed by the Azure NSG.
- PostgreSQL password generated on the VM and protected with file mode 600.
- Trusted Launch, Secure Boot, and vTPM enabled.
- OS disk, NIC, and public IP configured for cleanup with VM deletion.

Current limitations

- The site uses raw HTTP and a public IP; HTTPS and a domain are not configured.
- Milestone 0 has no application authentication or authorization.
- The frontend is a dashboard shell; workflow execution/model invocation belongs to later milestones.
- One VM is a single point of failure and is intended for a demo, not a highly available production deployment.
- PostgreSQL and Redis data reside in Docker volumes on the VM's OS disk; no independent backup was configured.
- The Azure promotional credit expires; the budget only alerts.

Final checklist

Status	Check
Complete	VM running in Central India
Complete	Five-container Compose stack healthy
Complete	Frontend and API reachable publicly
Complete	API readiness verifies PostgreSQL, Redis, and AI service
Complete	Systemd enabled and active
Complete	IPv4 health-check fix committed and pushed
Complete	Azure budget saved
Complete	Unused Railway project deleted
