

</> HTML

CheatSheet

Tafseeli Roman Urdu Edition



In this Cheatsheet, hum HTML tags, elements, aur attributes ki bunyadi (basics) baatein bohot gehrai se cover karenge. Hum mukammal examples provide karenge taa ke aap samajh sakein ke ye elements kaise kaam karte hain aur inhein apne khud ke web development projects mein kaise use karna hai. Chahe aap bilkul shuruati (beginner) hon ya experienced developer, ye PDF aapke liye ek bohat faida mand reference guide saabit hogi. Ise bachon ki tarah samjhaya gaya hai ta k ek ek cheez dimaagh mein baith jaye.

HTML

HTML (Hypertext Markup Language) ek standard markup language hai jo web pages banane ke liye use hoti hai. Yeh web par mojud content (jaise text, images, aur dusre multimedia elements) ko dhancha (structure) aur format dene ke liye istamal hoti hai. HTML mukhtalif elements se mil kar banti hai jinhein "tags" ke zariye darshaya jata hai. Yeh tags batate hain ke webpage ka dhancha kaisa hoga.

HTML web development ke amal (process) ka aik bunyadi hissa hai. Internet par mojud taqreeban har website ka bunyadi dhancha HTML mein hi banaya jata hai.

HTML COMPONENTS

Aaiye sab se pehle bunyadi tags (Basic Structure) ko dekhein:

- **<html> tag:** Yeh tag ek container ki tarah kaam karta hai jisme document ka har ek element mojood hota hai siwaye `<!DOCTYPE html>` tag ke. Yeh HTML document ka jadd (root) hai.
- **<head> tag:** Isme document ka tamam metadata shamil hota hai. Metadata aisi malumat hoti hai jo screen par nahi dikhti (jaise SEO tags, CSS links, page title).
- **<title> tag:** Yeh document ka title (naam) define karta hai jo browser ke title bar (tab) mein show hota hai.
- **<body> tag:** Yeh document ke us hisse ka container hai jo content (matan, tasweerein, buttons) user ko browser ki screen par nazar aata hai.

This is how it all comes together (Yeh sab mil kar kaise lagta hai):

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title> Code Help HTML Cheat Sheet </title>
  </head>
  <body> .... </body>
</html>
```

<!DOCTYPE html> batata hai ke hum ek HTML5 document ke sath kaam kar rahe hain.

Mandarja zail (Following) tags HTML document mein izafi malumat (extra information) faraham karte hain:

- **<meta> tag:** Yeh tag webpage ke bare mein mazeed malumat (additional information) define karne ke liye use hota hai. (Jaise character set aur viewport).
- **<link> tag:** Document ko kisi bairooni zariye (external resource jese CSS file) se jorne ke liye istemal hota hai.
- **<style> tag:** Document ke andar hi styles (design) define karne ke liye istamal hota hai.
- **<script> tag:** Code snippets (ziyada tar JavaScript) likhne ke liye ya kisi external script ko link karne ke liye use hota hai.

STRUCTURE OF A HTML DOCUMENT

Apna HTML document banate waqt, aap uski saakht (structure) bananane ke liye makhsoos tags use kar sakte hain. The **<h1>** se **<h6>** tags headings (surkhiyon) ke mukhtalif levels darshate hain, jisme **<h1>** sab se bara (highest) level aur **<h6>** sab se chota (lowest) level hota hai.

```
<head>
  <meta charset="UTF-8" />
  <meta http-equiv="X-UA-Compatible" content="IE=edge" />
  <meta name="viewport" content="width=device-width, initial-
scale=1.0" />
  <link rel="stylesheet" href="style.css" />
  <title>Code Help HTML Cheat Sheet</title>
  <style>
    *{
      font-size: 40px;
    }
  </style>
  <script>
    alert ('message');
  </script>
</head>

<h1> Heading 1 </h1>
<h2> Heading 2 </h2>
<h3> Heading 3 </h3>
<h4> Heading 4 </h4>
<h5> Heading 5 </h5>
```

Aap ek paragraph (pehra) banane ke liye **<p>** tag use karte hain.

```
<p> This is a paragraph </p>
```

<div> tag document ke mukhtalif hisson ko taqseem (segment) aur style karne ke liye istamal hota hai. Yeh document ke doosre elements ke liye ek parent container (bada dabba) ke tor par bhi kaam karta hai.

This is how it works:

```
<div class="About Us">
  <h1> This is the About Us section </h1>
  <p> Welcome to the About Us section! </p>
</div>

<div class="Contact Us">
  <h1> This is the Contact Us section </h1>
  <p> Contact us on 0123456789 </p>
</div>
```

Hamare paas **** tag bhi hai. Yeh **<div>** jaisa hi hai lakin aap ise inline container (line k andar hi lapetne k lie) k tor par use karte hain.

```
<p> Hello <span class="span1"> World! </span></p>
```

Yahan **
** tag hai, jise hum document mein line breaks (nayi line par jane) ke liye istamal karte hain. Is tag ko closing tag ki zaroorat nahi hoti.

```
<p> Welcome to <br/> Code Help </p>
```

The **<hr/>** tag ek ufuqi line (horizontal line) lagane ke liye use hota hai. Iska bhi koi closing tag nahi hota.

```
<p> Welcome to <hr/> Code Help </p>
```


IMAGES IN HTML

HTML mein, hum tasweerein (images) insert karne ke liye **** tag ka istamal karte hain.

Yahan **** tag ke kuch attributes hain:

- **src:** yeh aapke computer ya internet par image ki location (pata) set karne ke liye istamal hota hai. Ye batana laazmi hai warna image nahi ayegi.
- **alt:** yeh woh mutabadil text (alternative text) batata hai jo tab dikhta hai agar image theek se load na ho sake. Yeh text andhay logon ke screen readers ke liye bhi madadgar hota hai.
- **height:** image ki oonchai (height) tay karta hai.
- **width:** image ki chaurai (width) tay karta hai.
- **border:** image ke ird gird border ki motai batata hai. Agar add na karein, to ye default 0 hota hai.
- **loading="lazy":** Ek extra aur advanced attribute. Is se image tabhi load hoti hai jab page ko scroll kar k us image tk pohnta jaye, is se website ki speed tez hoti hai.

```

```

TEXT FORMATTING IN HTML

HTML text ko format (sazane) karne ke mutadid tareeqe faraham karta hai. Aaiye un par ek mukhtasir nazar dalte hain:

- The **<i>** tag text ko italics (tircha) karta hai.
- The **** tag text ko bold (mota) karta hai.
- The **** tag bhi text ko bold karta hai aur ahem malumat (important information) ko numaya (emphasize) karne ke liye istamal hota hai.
- The **** tag ek aur emphasis tag hai jo text ko italics mein format karta hai.
- The **<sub>** tag text ko subscript mein likhta hai, jaise Carbon Dioxide CO₂.
- The **<sup>** tag text ko superscript mein likhta hai, jaise kisi number ki power, 2³.
- The **<small>** tag text ka size chota karta hai.
- The **** tag text ko aise format karta hai jaise mita (delete) diya gaya ho, yani us par line pherdeta hai (strike-through).
- The **<address>** tag musannif (author) ki contact information (pata wagera) dikhane ke liye istamal hota hai. Yeh text ko italic kar deta hai.
- The **<abbr>** tag kisi mokhaffaf (abbreviation) ko darshata hai. Is par hover karne se uska full form dikhta hai.
- The **<code>** tag text ko code snippets ke tor par format karta hai. (Font monospace ho jata hai).
- The **<mark>** tag text ko highlight karta hai (jaise peela background laga dena).
- The **<ins>** tag text ko aise dikhata hai jaise abhi insert kia gaya ho, aam tor par ye text ke neeche line laga deta hai (underline).

- The **<blockquote>** tag kisi doosre source se liye gaye quote (kisi ki kahi hui ahem baat) ke text section ko band karne (enclose) ke liye use hota hai.
- The **<q>** tag chotay inline quotes (jismein text line me hi rehta hai) ke liye use hota hai aur khud inverted commas laga deta hai.
- The **<cite>** tag kisi quote ke musannif (author) ka hawala (cite) dene ke liye istamal hota hai.

Upar di gayi malumat ka code dekhein:

```
<p><i> Italic </i></p>
<p><b> Bold </b></p>
<p><strong> Strong </strong></p>
<p><em> Strong </em></p>
<p><sub> Subscript </sub></p>
<p><sup> Superscript </sup></p>
<p><small> Small </small></p>
<p><del> Delete </del></p>
<p><address> Address </address></p>
<p><abbr> Inserted Abbreviation </abbr></p>
<p><code> Code Snippet </code></p>
<p><mark> Marked Text </mark></p>
<p><ins> Insert </ins></p>
<p><blockquote> Quoted </blockquote></p>
<p><q> Short Quoted </q></p>
<p><cite> Cited </cite></p>
```

LINKS IN HTML

The **<a>** tag, jise anchor tag bhi kaha jata hai, hyperlinks (links) ban banane ke liye istamal hota hai. Yeh doosre pages (bairooni web pages shamil hain) ya usi page ke kisi makhsoos hisse se link karne ke kaam aata hai.

Yahan **<a>** tag ke kuch ahem attributes hain:

- The **href** attribute us URL (pata) ko batata hai jahan click karne par user ko le jaya jayega. Agar ye na den to link link nahi banega!
- The **download** attribute batata hai ke click kiya gaya target ya resource ek downloadable file hai (jaise koi PDF ya MP3 jise browse nahi balkay save karna ho).
- The **target** attribute ye tay karta hai ke linked document kahan khulna chahiye. Yeh usi window (`_self`) mein khul sakta hai ya ek nayi window ya tab (`_blank`) mein. Agar aap `_blank` use karte hain, to security k liye hamesha `rel="noopener"` bhi lagayein.
- **title**: Jab user is link ke upar mouse lata hai, to ye ek chota sa peela tooltip (hint text) dikhata hai.
- **Special Paths**: Agar aap `href="mailto:abc@xyz.com"` likhein, to uspar click karne se email app khul jati hai. Agar `href="tel:+1234"` likhein, to mobile ka dialer khul jata hai.

```
<a href="https://www.thecodehelp.in/" target="_blank"> Code Help
</a>
```

LISTS IN HTML

HTML humein 3 qisam ki fehristein (lists) banane ki ijazat deta hai. Ziyada tar 2 hi istamal hoti hain:

- The **** tag ek tarteeb war list (ordered list - numbers wali) banata hai. Isme attributes like `type="1"`, `type="A"`, `type="I"` lagaye jasakte hain. `start="5"` se numbering 5 se shuru hoti hai.
- The **** tag ek be-tarteeb list (unordered list - bullets/dots wali) banata hai.
- The **** tag list mein items (points) shamil karne ke liye use hota hai. (List Item).
- The **<dl>** (Description List), **<dt>** (Term) aur **<dd>** (Definition) dictionary jaisi lists banane ke kaam ate hain.

```
<!-- Unordered List -->
<ul>
  <li> Course 1 </li>
  <li> Course 2 </li>
  <li> Course 3 </li>
</ul>

<!-- Ordered List -->
<ol>
  <li> Course 1 </li>
  <li> Course 2 </li>
  <li> Course 3 </li>
</ol>
```

FORMS IN HTML

The **<form>** element HTML mein ek form banane ke liye istamal hota hai. Forms user se malumat (input) jama karne ke liye banaye jate hain (Jaise Login ya Registration page).

Form **<form>** element ke sath jure (associated) kuch attributes yeh hain:

- The **action** attribute batata hai ke jab form submit kiya jaye to data (malumat) kahan bheja jana chahiye (kis server ya page par).
- The **target** attribute batata hai ke form ki response (jawabi page) kahan dikhani hai (maslan naye tab me ya usi tab me).
- The **autocomplete** attribute on ya off set kiya ja sakta hai aur yeh tay karta hai ke browser ko pehle se bhari hui information (naam, email) automatically fill karni chahiye ya nahi.
- The **novalidate** attribute lagane se yeh batata hai ke form submit karte waqt use validate (check) na kiya jaye.
- The **method** attribute form ka data bhejte waqt istamal hone wala HTTP method (tariqa) batata hai (yani **GET** ya **POST**). Passwords k liye hamesha POST use hota hai. Agar aap user se file upload karwa rahe hain to `enctype="multipart/form-data"` lagana BOHAT LAZMI hai!
- The **name** attribute form ka naam define karta hai.

Form Inputs Aur Unke Attributes:

- The **required** attribute lagane se koi bhi input box khali nahi chora ja sakta, user k lye usay bharna lazmi (mandatory) ho jata hai.
- The **autofocus** attribute input element ko page load hotay hi khud focus (cursor wahan blink karne lagta hai) kar deta hai.
- The **disabled** attribute kisi input element ko na-qabil e istemal (disable) kar deta hai, jisse user usme kuch likh nahi sakta (wo grey ho jata hai) aur iska data submit bhi nahi hota. Agar sirf **readonly** lagaein to edit to nai hoga lakin data submit ho jayega.
- The **placeholder** attribute user ko hint (ishara) dene ke liye use hota hai k is box mein kis tarah ki malumat likhni hai. Jab user likhna shuru krta hai to ye halka text chup jata hai.
- The **name** attribute har input box par lagana LAZMI hai, kyunke isi naam se data server tak pohnchta hai.

Forms mein istamal hone wale deegar elements ye hain:

- **<textarea>**: users ko mutadid lines (multiple lines) wala text (jaise lamba message ya pata) likhne ki ijazat deta hai. Isme `rows="5"` `cols="20"` use hota hai box ka size set karne k lye.
- **<select>**: users ke liye ek list banata hai jisme se wo intakhab (choose) kar saktay hain. Iske andar hum `<option>` tags lagate hain.
- **<option>**: ek `<select>` element ke andar akaila option (intekhab) banata hai.
- **<input>**: users ke liye malumat enter karne ka input box banata hai. The **type** attribute (e.g., `type="text"`, `"password"`, `"email"`, `"number"`, `"radio"`, `"checkbox"`, `"date"`, `"color"`, `"file"`) batata hai ke kis tarah ka data darj kia jayega.
- **<button>**: ek button banata hai jis par click kar k koi kaam (action) kiya ja sake, jaise form submit karna. Iski jagah `<input type="submit">` bhi use ho sakta hai.

Uper di hui tafseel ka mukammal code form example (Misaal) yeh hai:

```
<form action="/Submit_URL/" method="post">
  <label for="FirstName"> First Name: </label>
  <input type="text"
    name="FirstName"
    id="FirstName"
    placeholder="First Name"
    required >

  <label for="LastName"> Last Name: </label>
  <input type="text"
    name="LastName"
    id="LastName"
    placeholder="Last Name"
    required >

  <label for="add"> Address: </label>
  <textarea name="add" id="add"></textarea>

  <label for="age"> Age: </label>
  <select name="age" id="age">
    <option value="11-20">11-20</option>
    <option value="21-30">21-30</option>
    <option value="31-40">31-40</option>
    <option value="41-50">41-50</option>
  </select>

  <input type="submit" value="Submit">
</form>
```

Advanced Tip: `<label for="id">` lagana zaroori hai is se jab aap text par click karte hain to input box automatically open ya tick ho jata hai! (Mobile users ke liye behtareen UX).

ADVANCED FORM INPUTS & VALIDATION

HTML5 ne boht se naye `<input type="...">` ta-aruf karwaye hain jo data collection aur validation ko behad asaan banate hain:

- **type="email"**: Sirf wahi data qabool karega jisme '@' aur '.com' jaisi format ho.
- **type="number"**: Sirf numbers (hindsay) likhne dega. Aap isme `min="1"` aur `max="10"` laga kar range bhi limit kar sakte hain.
- **type="date"**: Browser mein ek khoobsurat calendar khol deta hai jahan se user tareekh chun sakta hai.
- **type="time"**: Waqt chunne ke liye (AM/PM ke sath).
- **type="color"**: Ek color picker (rangon ka dabba) open karta hai jisse user rang select kar sake.
- **type="range"**: Ek slider banata hai jise user agay peche kheench sakta hai (Volume kam zyada karne jaisa).
- **type="file"**: User ko apne mobile ya computer se file (jaise PDF ya image) upload karne ki ijazat deta hai. Aap `accept=".jpg, .png"` laga kar sirf tasweerein allow kar sakte hain.
- **type="checkbox"**: Chote dibbe (boxes) jinpar tick lagaya ja sakta hai. Jab aapko ek se zyada options (multiple choices) select karne hon.
- **type="radio"**: Gol dibbe. Inka istemal tab hota hai jab bohat sare options mein se sirf ek (single choice) select karna ho (Jaise Gender: Male / Female). In sabka **name** attribute same hona chahiye.

Validation Attributes (Ghaltiyan Rokne Ke Liye):

- **required:** Form tab tak submit nahi hoga jab tak yeh box fill na ho.
- **minlength aur maxlength:** Text input mein kam se kam aur zyada se zyada kitne haroof (characters) allowed hain (Jaise password ke liye minlength="8").
- **pattern:** Isme Regex code likh kar makhsoos rules tay kiye jate hain (Jaise phone number mein sirf 11 digits hon).

TABLES IN HTML

The **<table>** tag ek HTML table define karta hai. Columns aur Rows ka grid data dikhane ke kaam ata hai.

- **<thead>**: table mein har column ke liye header ki malumat (information) define karta hai.
- **<tbody>**: table ki main body ya data content ko define karta hai.
- **<tfoot>**: table ki footer (nichli) malumat define karta hai (jaise Total likhna).
- **<tr>**: (Table Row) table mein ek ufuqi (sidhi lumbi) line yani row banata hai.
- **<td>**: (Table Data) table mein ek cell (box) ko darshata hai jahan asal data likha jata hai.
- **<th>**: (Table Heading) columns ke liye heading (surkhi) ko darshata hai. (Ye mota/bold aur center align hota hai default mein).
- **Advanced Attributes**: `colspan="2"` kisi ek cell ko bara kar ke do columns ki jagah dedeta hai. `rowspan="2"` cell ko lamba kar k 2 lines ki jagah deta hai.

```
<table>
  <thead>
    <tr>
      <th> Name </th>
      <th> CGPA </th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td> Koushik Sadhu </td>
      <td> 9.66 </td>
    </tr>
    <tr>
      <td> Pranay Gupta </td>
      <td> 9.72 </td>
    </tr>
  </tbody>
  <tfoot>
    <tr>
      <td> Nidhi Gupta </td>
      <td> 10 </td>
    </tr>
  </tfoot>
</table>
```

MEDIA ELEMENTS (AUDIO, VIDEO, IFRAME)

HTML5 ke aane ke baad websites mein Audio aur Video lagana bohat aasaan ho gaya hai. Ab aapko kisi third-party plugin ki zaroorat nahi parti.

- **<audio>**: Gaane ya sound files chalane ke liye.
- **<video>**: Video files chalane ke liye.
- **Media Attributes:**
 - **controls**: User ko play, pause, aur volume ke buttons dikhane ke liye. (Ye lagana lazmi hai warna video/audio dikhegi nahi).
 - **autoplay**: Page khulte hi media khud chalne lagta hai (yad rahe k browsers bina 'muted' ke autoplay rok dete hain).
 - **loop**: Media khatam hone ke baad dobara shuru ho jata hai.
 - **muted**: Media ki awaz shuru mein band (mute) hoti hai.
 - **poster**: Video shuru hone se pehle jo tasweer (thumbnail) dikhti hai (sirf video tag par).
- **<iframe>**: Apni website ke andar kisi dusri website, YouTube video, ya Google Map ko shamil (embed) karne ke liye. Isme `src` (link k liye) aur `width`, `height` attributes istamal hote hain.

```
<!-- Video Example -->
<video src="video.mp4" controls muted poster="thumbnail.jpg"
width="500"></video>

<!-- Audio Example -->
<audio src="song.mp3" controls loop></audio>

<!-- Iframe (YouTube Video) Example -->
```

```
<iframe src="https://www.youtube.com/embed/xyz123" width="560"  
height="315"></iframe>
```

GLOBAL ATTRIBUTES IN HTML

Global attributes aisey attributes hote hain jo taqreeban har HTML element par lagaye ja sakte hain. Yeh tags ko izafi (extra) malumat ya khususiyaat dete hain.

- **id:** Kisi element ko ek munfarid (unique) naam dene ke liye use hota hai. Ek webpage mein ek id sirf ek hi baar istamal ho sakti hai. Yeh CSS aur JavaScript mein us element ko target karne ke kaam aati hai.
- **class:** Ek ya ek se zyada elements ko ek jaisa naam dene ke liye use hoti hai. Yeh CSS styling mein boht aam hai (maslan boht se buttons ko aik jaisa design dena).
- **style:** Kisi element par inline CSS (uske tag ke andar hi design) lagane ke liye. Jaise `style="color: red;"`.
- **title:** Jab user us element par mouse laye to ek choti si tool-tip (hint) dikhane ke liye.
- **hidden:** Kisi element ko screen se chupane (hide karne) ke liye. `<p hidden>`.
- **dir:** Text ki simt (direction) tay karne ke liye. (Jaise "ltr" Left-to-Right English ke liye aur "rtl" Right-to-Left Urdu/Arabic ke liye).
- **contenteditable:** Agar isay "true" kar diya jaye, to user us element ke text ko website par hi click kar ke tabdeel (edit) kar sakta hai!

```
<p id="para1" class="text-bold" style="color: blue;" title="Hover text">
```

Yeh ek paragraph hai jisme boht se global attributes lagaye gaye hain.

```
</p>
```


HTML COMMENTS

HTML mein comments likhna bohat ahem hai. Yeh code ko samajhne mein madad dete hain, khas tor par jab aapka code bohat lamba ho jaye. Comments browser mein show nahi hote, yeh sirf developers ke parhne ke liye hote hain.

- Kisi bhi code ko comment karne ke liye hum `<!--` se shuru karte hain aur `-->` par khatam karte hain.
- Aap comments ko kisi bhi naye section ki nishandahi (identification) ke liye ya kisi code ko aarzi (temporarily) band karne ke liye istamal kar sakte hain.

```
<!-- Yeh ek HTML comment hai jo browser par nahi dikhega -->  
<p> Yeh text show hoga! </p>  
<!-- <p> Yeh paragraph abhi hide kar diya gaya hai </p> -->
```

TAGS IN HTML (HTML5)

Puranay zamane mein har cheez ke liye `div` (dabba) use hota tha, jisse code messy ho jata tha. Phir HTML5 ne "Semantic" (Bamaqsad) tags taruf (introduce) karwaye. Ye kaam to div wala hi karte hain lakin inka naam padh kar browser aur Google ko samajh aa jata hai ke andar malumat kis kism ki hai (Ye SEO ke liye ek Master Trick hai!).

The following tags were introduced in HTML5:

- **<header> tag:** webpage ke sab se upar wale (header) section ko define karta hai (yahan title, logo aur menu aata hai).
- **<nav> tag:** navigation links (menu jahan se doosre pages me jaya jaye) ko contain karne ke liye use hota hai.
- **<main> tag:** kisi webpage ke markazi mawad (main content) section ko darshata hai. Pure page me ye tag 1 hi baar ana chahiye.
- **<article> tag:** azaad aur khudmukhtar (standalone) content ka hissa define karta hai, jaise koi akhbari article ya blog post.
- **<section> tag:** webpage ko mutadid (various) sections ya hisson mein baant'nay ke liye define hota hai (jaise "Our Services" ka ek section).
- **<aside> tag:** aksar sidebar mein rakhe gaye content ke liye istamal hota hai. (Jaise deegar links ya Ishtiharat/Ads).
- **<footer> tag:** webpage ka sab se nichla (footer) section jahan Copyright aur address ki malumat hoti hai.
- **<meter> tag:** kisi makhsoos range mein data (values) mapne (measure) ke liye istamal hota hai.
- **<progress> tag:** kisi kaam ki takmeel (completion) ko dikhane wale progress bar ke tor par use hota hai. (Jaise Downloading: 50%).
- **<dialog> tag:** ek dialog box ya popup window banane ke liye use hota hai.

- **<audio> aur <video> tags:** Webpage mein moseeqi (audio file) aur video ko embed (shamil) karne ke liye.
- **<time> tag:** tareekh (dates) aur auqat (times) ko format karne ke liye. Screen readers isko pehchan lete hain.
- **<figure> tag:** charts, graphs, tasweerein (images) jaisi figures ko cover karne ke liye istamal hota hai.
- **<figcaption> tag:** ek **<figure>** ki tasweer ke niche tafseel (description ya caption) faraham karta hai.
- **<details> aur <summary> tags:** Ye donon mil kar ek "Accordion" (Khulne aur band hone wala patti) banate hain. FAQ section banane ke liye lajawab hain aur inhein Javascript ki zaroorat nahi parti.

Semantic tags ko istemal karne ki aik asaan misaal yahan dekhein:

```
<header>
  <h1> Welcome to CodeHelp! </h1>
</header>
<nav>
  <ul>
    <li><a href="#">About Us</a></li>
    <li><a href="#">Courses</a></li>
    <li><a href="#">Contact</a></li>
  </ul>
</nav>
<article>
  <h1> About CodeHelp </h1>
  <p> This is all about CodeHelp. </p>
  <aside>
    <p> Book your seat now. </p>
  </aside>
</article>
<progress min="0" max="100" value="10"> </progress>
<footer> Copyright © 2026 CodeHelp. All Rights Reserved. </footer>
```

CHARACTER AND SYMBOLS

HTML documents mein, kuch nishanat (symbols) bar-e-raast keyboard par dastiyab nahi hote, ya phir browser unhein ghalti se HTML ka apna tag samajh leta hai (Jaise '<' aur '>'). Tahaam, ek document mein in symbols ko shamil karne ke bohat se tariqe hain. In mein symbol ka entitiy naam (entity name), aashariya (decimal value), ya hexadecimal value shamil hai.

- **Copyright Symbol (©):** isko HTML me dikhane ke liye `©` likhein. Ye foter me boht istamal hota hai.
- **Dollar Symbol (\$):** isko dikhane ke liye `$` likhein. (Aam taur pe keyboard se bhi type kiya jaskta hai).
- **Ampersand Symbol (&):** isko dikhane ke liye `&` likhein. Ye lagana zaruri hai q k browser akele '&' ko samajhne me ghalti karta hai.
- **Greater than Symbol (>):** isko dikhane ke liye `>` likhein. Iska matlab hai "bada hai" (Greater Than).
- **Less than Symbol (<):** isko dikhane ke liye `<` likhein. Ye "chota hai" ko darshata hai. Ye is liye aham hai ta k browser isay kisi tag ka aghaz na samajh le.
- **Non-breaking Space:** Agar aapko do lafzon ke darmiyan extra faasla (space) chahiye ho to ` ` likhein. HTML warna sirf 1 hi space ginta hai chahe ap keyboard se 10 dafa space dabayen!
- **Euro Symbol (€):** isko dikhane ke liye `€` likhein.
- **Registered Trademark (®):** `®` likhein.
- **Trademark (™):** `™` likhein.

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <title> Code Help HTML Cheat Sheet </title>
  </head>
  <body>
    <p> Copyright Symbol: &copy; </p>
    <p> Dollar Symbol: &dollar; </p>
    <p> Ampersand Symbol: &amp; </p>
    <p> Greater than Symbol: &gt; </p>
    <p> Less than Symbol: &lt; </p>
    <p> Is se age &nbsp;&nbsp;&nbsp;&nbsp; 3 space hain! </p>
  </body>
</html>
```

Dua Aur Paigham

Bhai jaan! Umeed hai is asaan aur tafseeli andaz mein parhne ke baad, aap HTML ki har ek point ko mukammal taur par samajh gaye honge. Web Development ka safar aasan nahi magar ye bohat mazeed aur dilchasp hai. In tamam tags ki rozana practice karien. Yaad rakhye: Practice makes a man perfect! Happy Coding! 🍕🎉