

WHERE SHADING IS USED, THE BUILDING SHALL HAVE A PERMANENT FEATURE SUCH AS A VERANDA, BALCONY, FIXED CANOPY, EAVES OR SHADING HOOD WHICH EXTENDS HORIZONTALLY ON BOTH SIDES OF THE GLAZING FOR THE SAME PROJECTION DISTANCE OR PROVIDES THE EQUIVALENT SHADING WITH A REVEAL OR OTHER SHADING ELEMENT OR HAVE AN EXTERNAL SHADING DEVICE, SUCH AS A SHUTTER, BLIND, VERTICAL OR HORIZONTAL BUILDING SCREEN WITH BLADES, BATTENS OR SLATS, WHICH IS CAPABLE OF RESTRICTING AT LEAST 80 % OF SUMMER SOLAR RADIATION AND IF ADJUSTABLE, IS READILY OPERATED EITHER MANUALLY, MECHANICALLY OR ELECTRONICALLY BY THE BUILDING OCCUPANTS.

CARE SHOULD BE TAKEN TO ENSURE THAT THE ROOF VENTILATION OPENINGS DO NOT ALLOW RAIN PENETRATION. GAPS BETWEEN ROOF TILES WITH SARKING (OR REFLECTIVE INSULATION AT RAFTER LEVEL) AND METAL SHEET ROOFING ARE NOT ACCEPTABLE METHODS OF PROVIDING ROOF SPACE VENTILATION.

