ChatGPT

Part 7: Special Topics

AI/ML Engineering

Machine Learning Lifecycle: The ML lifecycle is an iterative pipeline spanning data preparation to model retraining. It begins with **data collection and preprocessing** – gathering relevant, high-quality data and cleaning it for use [1] [2]. Next is **feature engineering**, where raw data is transformed into informative features (e.g. scaling values, encoding categories) to improve model learning [3] [4]. With features ready, **model training and evaluation** occurs: different algorithms are experimented with, trained on historical data, and assessed via validation metrics (accuracy, precision, etc.) [5] [6]. After selecting the best model, it is **deployed** into production, often behind an API or service, so that predictions can integrate with applications [7] [8]. **Monitoring** then tracks the model's performance in real-time, watching for data drift or accuracy degradation; if the model's quality drops, a **retraining** cycle on fresh data is triggered [9] [10]. This end-to-end process (data → features → model → deploy → monitor → retrain) ensures ML systems remain accurate and reliable over time [11] [12].



Diagram of a typical machine learning lifecycle, illustrating stages from data ingestion to model retraining.

Deep Learning Frameworks: Modern AI development is dominated by TensorFlow and PyTorch. **TensorFlow** (by Google) pioneered a static graph approach – developers define a computation graph first, then execute it – enabling heavy optimizations for production and distributed training [13] [14]. It offers high-level APIs (Keras) for ease of use, plus tools like TensorBoard for visualization [15] [16]. **PyTorch** (by Meta/Facebook) took off with its dynamic graph (eager execution) that feels more "Pythonic" and intuitive for researchers [17] [18]. This flexibility lets you modify models on the fly, aiding experimentation and debugging. PyTorch is now favored in research and academia for rapid prototyping, while TensorFlow's ecosystem excels in large-scale deployments [19] [20]. In practice, both frameworks are widely used – PyTorch for its ease of use and growing community, and TensorFlow for its maturity in production (though

TensorFlow 2.x also adopted eager execution to bridge the gap). Many engineers learn both to stay versatile [20].

MLOps Pipelines: Bringing models to production reliably requires MLOps platforms. Open-source tools like **MLflow** focus on experiment tracking and model management – logging parameters, metrics, and packaging models for reproducibility [21]. **Kubeflow** runs on Kubernetes to orchestrate end-to-end ML workflows, allowing data prep, training, and deployment steps to be composed as pipelines on a cluster [22]. Cloud-managed services provide more integrated solutions: **AWS SageMaker** provides managed Jupyter notebooks, automated model tuning, one-click training and scalable hosting endpoints [23]. Similarly, **Google Vertex AI** offers a unified platform for data preparation, training (including AutoML), and deployment with minimal ops overhead [24]. These pipelines address the entire lifecycle – from data versioning to model registry – so that moving a model from a research notebook to a scalable service is streamlined [21] [25]. Teams often mix tools (for example, using MLflow with SageMaker) to leverage strengths of each.

Model Deployment and Serving: Deploying ML models requires balancing **latency vs. accuracy** for the target use-case. High-throughput web services might demand smaller or quantized models (e.g. using 8-bit integers via ONNX) to reduce latency at a modest cost to accuracy [26]. Common approaches for serving include specialized servers and lightweight web frameworks. **TorchServe** is a model server for PyTorch that supports loading models (including multiple versions) and provides APIs for inference with features like batch scheduling [27] [28]. It's less flexible in customization than a generic web framework, but convenient for PyTorch deployments. On the other hand, **FastAPI** (a high-performance Python web framework) is often used to wrap models behind REST endpoints – it's asynchronous and can handle many requests concurrently, allowing custom logic around model calls [29]. For cross-framework portability and optimization, engineers use **ONNX (Open Neural Network Exchange)** to convert models and run them on efficient runtimes or hardware accelerators. Best practices include containerizing the service (e.g. with Docker) and using orchestration like Kubernetes for scaling [30] [31]. In production, **monitoring** inference latency (e.g. p95 response time) and throughput is critical, and techniques like request batching can improve efficiency – though they introduce latency trade-offs [32] [26]. Teams experiment with hardware choices (CPU vs GPU inference) and model optimizations (TensorRT, ONNX Runtime, quantization) to meet strict latency requirements without sacrificing too much accuracy [33] [32].

Security in ML: Advanced ML systems face novel security risks. One is **model poisoning** – malicious actors compromise training data or the model update process to corrupt the model's behavior [34]. In a poisoning attack, an attacker might inject specially crafted data points during training so that the model learns incorrect or harmful outputs (for example, a "backdoor" trigger that causes a classifier to mislabel certain inputs) [35] [36]. Because ML models often retrain on new data (including user-provided data), they are susceptible to this data tampering which can degrade accuracy or embed hidden behaviors. Another concern is **inference-time attacks** that leak information from the model – for instance, *membership inference* allows an adversary to query a model and determine if a specific data record was in its training set [37]. These attacks exploit the fact that models often output with higher confidence on data they've seen, thus compromising privacy [38] [39]. Similarly, *model inversion* attacks can attempt to reconstruct sensitive features about inputs from model outputs. To mitigate these, practitioners employ measures like differential privacy during training, regularization to prevent overfitting (reducing memorization of training data), and careful user authentication and rate-limiting on model APIs. Awareness of security – from **model theft** (where attackers try to copy your model by repeated queries) to adversarial examples that trick

models – is increasingly important in ML engineering. Techniques like monitoring for abnormal inference patterns and robust training (e.g. adversarial training) help defend against these issues [40] [41].

Applications – Fraud Detection & Recommendations: AI/ML engineers often work on impactful real-world systems. In **fraud detection**, models (usually classification or anomaly detection models) help banks and e-commerce platforms flag suspicious transactions in real-time. For example, credit card companies train models on transaction histories to identify patterns associated with fraud (unusual spending patterns, geolocation mismatches, etc.) and can stop or alert on likely fraudulent charges. These models must be highly precise and fast, often using ensemble techniques and continuously retrained with new fraud examples. **Recommendation systems** are another ubiquitous example – companies like Netflix, Amazon, and Spotify deploy ML models to suggest content or products tailored to user preferences [42] [43]. These systems often combine collaborative filtering (finding similar users/items) with content-based methods, and operate on large-scale data (user ratings, browsing history). An ML engineer in this domain deals with feature engineering (e.g. encoding user behavior), model scalability, and balancing relevance vs. discovery. Notably, such systems are continuously evaluated via A/B testing in production to fine-tune algorithms for better user engagement [44] [43].

Career Path in ML: Roles in AI/ML span from data-focused to research-oriented. A typical progression might start as a **Data Scientist**, then move to **ML Engineer**, and for some, onto an **Applied Scientist** role. A **Data Scientist** usually emphasizes data analysis and modeling in notebooks – they clean and explore data, build initial models, and focus on extracting insights [45] [46]. They are often closer to business questions, using statistics and visualization to guide decisions. An **ML Engineer** takes those models into production: they need strong software engineering skills to integrate models with larger systems, build data pipelines, and ensure reliability at scale [47] [48]. ML Engineers set up training pipelines, deploy models to cloud services or edge devices, implement monitoring, and optimize for performance. They bridge the gap between prototype and product, often coding in languages like Python (for pipeline and model code) and using infrastructure tools (Kubernetes, CI/CD, etc.) [49] [50]. An **Applied Scientist** (sometimes called Research Scientist in industry) leans more toward innovative model development – they apply cutting-edge research to practical problems [51] [52]. Applied Scientists often have advanced degrees; they might design new algorithms, work on improving core model performance, or tackle problems requiring deep research (e.g. NLP or computer vision breakthroughs). In practice, these roles collaborate: Data Scientists define the problem and prototype solutions, ML Engineers productionize the solutions, and Applied Scientists push the boundaries of what models can do for the product. Mastery of both the theoretical and engineering aspects of ML is valuable for career growth – many senior roles expect one to drive a project end-to-end, from data preparation to deploying a novel model. Regardless of title, the ML field rewards continuous learning, given the rapid pace of new techniques and technologies.

Blockchain Development

Blockchain Fundamentals: Blockchains are decentralized ledgers composed of **blocks** of transactions cryptographically linked in sequence. Each block carries a unique **hash** (a fixed-size fingerprint of its data) and also includes the hash of the previous block's header [53] [54]. This chaining via hashes ensures tamper-resistance: if an attacker alters data in an earlier block, its hash changes and breaks the link, alerting the network of inconsistency [54] [55]. Blocks organize transactions and other metadata; for example, Bitcoin blocks bundle transactions and include a timestamp, a **nonce** for proof-of-work, and the hash of the prior block [56] [57]. A core data structure inside blocks is the **Merkle tree** (hash tree). Transactions are hashed and recursively combined into a single **Merkle root** [58]. This root hash (stored in the block header)

summarizes all transactions in the block [59] [58]. Merkle trees allow efficient proofs of inclusion: a node can prove a transaction exists in a block by revealing a small "hash path" rather than the entire block. Blockchains also rely on **public-key cryptography** for identity and security. Users have a **private key** (secret) and a corresponding **public key**. A private key can digitally **sign** transactions – for example, to transfer cryptocurrency, you sign the transaction with your private key, producing a signature that others can verify with your public key [60] [61]. This proves authenticity (only the holder of that private key could have made the transaction) without revealing the key itself. Public keys (or addresses derived from them) serve as user identifiers to receive funds [62] [63]. Thus, blocks + hashes ensure integrity, Merkle trees provide efficient verification, and public/private keys enable secure, pseudonymous transactions on the chain.

Consensus Algorithms (PoW, PoS, PBFT): Distributed blockchains need a **consensus mechanism** to agree on the next block without a central authority. **Proof of Work (PoW)**, first used in Bitcoin, requires miners to solve a difficult computational puzzle (finding a hash below a target difficulty) in order to propose a block [64]. This work is energy-intensive but secures the network: an attacker would need >50% of the total hashing power to consistently outpace others. PoW's downside is low throughput and high energy cost [65]. Newer networks use **Proof of Stake (PoS)**, where validators stake cryptocurrency to earn the right to produce blocks proportional to their stake [66]. Instead of burning energy, PoS's security comes from economic skin-in-the-game – if validators act dishonestly (e.g. sign two different block histories), they can be penalized (slashed) by losing their stake [67]. PoS is far more energy-efficient and can achieve faster finalization of blocks; Ethereum, for instance, transitioned to PoS to improve scalability and reduce energy use [68]. A different approach, often used in permissioned or consortium blockchains, is **Practical Byzantine Fault Tolerance (PBFT)**. PBFT is a classical consensus algorithm where a fixed (and often small) set of nodes collectively agree on each block through multiple rounds of voting, tolerating up to 1/3 of nodes being faulty or malicious [69]. In PBFT, one node may propose a block, and others must sign off in a series of prepared/commit phases, requiring a supermajority agreement (e.g. ≥67%) for the block to be finalized. This yields rapid finality and high transaction throughput in environments where nodes are authenticated (e.g. known organizations in a consortium) [70]. Hyperledger Fabric uses a PBFT-like protocol suitable for enterprise scenarios [71]. In summary, PoW emphasizes open security at the cost of speed, PoS trades energy use for capital at stake to secure the network (and enables more scalability), while PBFT-family algorithms excel in private networks where a set of validators can be managed for fast consensus.

Smart Contracts (Solidity, Rust, Vyper): Smart contracts are self-executing programs stored on blockchain platforms. **Solidity** is the dominant language for writing contracts on Ethereum and EVM-compatible chains. It's a high-level, statically-typed language with syntax similar to JavaScript/Java, designed for contract programming (e.g. support for addresses, fixed-point types, events) [72]. Solidity's popularity means a rich ecosystem of libraries (OpenZeppelin for secure ERC-20/ERC-721 contracts) and widespread developer knowledge. **Vyper** is another language targeting the EVM, built as a simpler and more secure alternative to Solidity. Vyper has a Python-like syntax and deliberately omits complex features (like class inheritance or certain opcodes) to reduce vulnerabilities and make auditing easier. Many Ethereum developers use Vyper for contracts where formal verification or simplicity is paramount (e.g. financial contracts) [72]. Outside the EVM, **Rust** has emerged as a smart contract language, notably for Solana and Polkadot's Substrate framework. Solana's smart contracts (called programs) are written in Rust, giving developers the benefits of Rust's safety and performance. Rust is low-level enough to manage memory and handle the concurrency model Solana uses, and frameworks like Anchor provide developer-friendly abstractions for Solana programs. In Polkadot's ecosystem, the Ink! library also uses Rust to write WebAssembly contracts for parachains [73] [74]. Overall, Solidity remains the go-to for Ethereum-based

contracts, but Rust is favored for high-performance chains like Solana, and Vyper is used when security and auditability are top concerns [75]. Each language comes with its own toolchain: e.g. Solidity has Truffle/Hardhat for testing and deployment, Rust contracts use Cargo and related tools, etc.

Platforms: Ethereum, Solana, Hyperledger: The blockchain landscape offers different platforms optimized for various needs. **Ethereum** is the most established smart contract platform – a public, permissionless blockchain supporting a wide range of decentralized applications (DApps) and tokens. It introduced the concept of the EVM (Ethereum Virtual Machine) and Solidity smart contracts, enabling ICOs, DeFi, NFTs and more [76] [77]. Ethereum recently moved to Proof of Stake, improving its energy efficiency, and is working on scalability (sharding, Layer-2 networks) to overcome its relatively lower throughput and higher gas fees compared to newer chains [78]. **Solana** is a high-performance Layer-1 blockchain designed for speed and low cost. It uses a unique Proof of History + PoS consensus, allowing it to process thousands of transactions per second with minimal fees [79]. Solana's architecture prioritizes scalability (often at the cost of higher hardware requirements for validators), making it attractive for DeFi and gaming DApps that need fast confirmation times. Smart contracts on Solana are typically written in Rust, and Solana can even support running compiled Solidity code through an EVM compatibility layer (e.g. Neon Labs) [80]. **Hyperledger** is not a single blockchain but an umbrella of open-source enterprise-focused blockchain frameworks hosted by the Linux Foundation [81] [82]. For example, Hyperledger Fabric is a permissioned blockchain where participants and their roles are defined by a central authority or consortium. It forgoes cryptocurrency and mining; instead, it uses a PBFT-style consensus among known nodes and allows smart contracts (called "chaincode") in general-purpose languages like Go or Java [82] [83]. Hyperledger is used in business contexts like supply chain tracking, trade finance, etc., where privacy and performance are crucial – it supports private channels and pluggable consensus modules. In summary, Ethereum is a general-purpose, global platform emphasizing decentralization and a broad developer ecosystem; Solana focuses on performance and throughput for next-gen decentralized apps; Hyperledger provides flexible toolkits for permissioned networks tailored to enterprises [84] [85].

Tooling (Truffle, Hardhat, MetaMask, Ganache): Blockchain developers rely on an array of tools to develop, test, and interact with smart contracts. **Truffle** is one of the oldest Ethereum development frameworks. It provides a project structure for contracts (written in Solidity/Vyper), scripts for migration (deployment), and integrates with testing frameworks (Mocha/Chai) to allow writing JavaScript tests for contracts [86] [87]. Truffle also includes an interactive console and supports network management, making it easier to deploy contracts to various networks (Ganache, testnets, mainnet). As part of Truffle Suite, **Ganache** is a personal blockchain for developers – essentially a local Ethereum simulator that spins up a blockchain on your machine [87]. Ganache provides default accounts with test Ether and instamines transactions instantly, enabling rapid testing without cost [88] [89]. (Ganache comes in both a CLI and a GUI flavor for convenience.) **Hardhat** is a newer Ethereum development environment that has become very popular. It offers a plugin-extensible framework and comes with **Hardhat Network**, a built-in local Ethereum node similar to Ganache [90] [91]. Hardhat emphasizes developer ergonomics – for example, it can automatically generate stack traces for failed Solidity transactions and simulate mining in step-by-step debug mode [92]. It also allows writing custom deployment scripts in JavaScript/TypeScript (giving more control than Truffle's migration scripts). Both Truffle and Hardhat facilitate compiling Solidity, running tests, and deploying contracts, but Hardhat's design (with its configuration and plugins like Ethers.js and Waffle) has led ConsenSys to endorse it moving forward (Truffle and Ganache were in fact sunset and handed over to the community in favor of Hardhat) [93]. On the user side, **MetaMask** is an essential tool: it's a browser extension wallet that lets users manage private keys and interact with DApps. When a DApp wants to access the blockchain (e.g. execute a smart contract function), MetaMask can prompt the user to approve the

transaction and sign it with their key. Developers test DApps by connecting MetaMask to local or test networks – for instance, connecting MetaMask to Ganache's RPC URL to simulate user transactions on a dev blockchain [94]. This enables end-to-end testing of how a user would invoke the contracts. In summary, Truffle/Hardhat streamline the contract development workflow, Ganache/Hardhat Network provide sandboxed blockchains for testing, and MetaMask serves as the bridge between real users (or testers) and the blockchain, enabling secure signing and transaction submission.

Deployment (Testnets, Gas Optimization, Audits): Before deploying to mainnet, developers use **testnets** extensively. Testnets are public blockchain networks (e.g. Ethereum's Sepolia or Goerli, or Solana's Devnet) that mimic the main network's behavior but use valueless tokens. They allow devs to find bugs or issues in contracts and deployment scripts without risking real funds. A typical flow is: write and test locally (with Ganache/Hardhat), then deploy to a testnet for more realistic testing (where other contracts and users exist), and finally deploy to mainnet. **Gas optimization** is a critical concern during deployment – on Ethereum, every operation has a gas cost, so writing efficient Solidity code can save users money and make your DApp more usable [95] [96]. Best practices for gas optimization include using smaller data types where possible, minimizing storage writes (since writing to blockchain storage is expensive gas-wise), avoiding unbounded loops or expensive computations on-chain, and leveraging bitwise operations or packed structs to save space [97] [98]. There are automated tools (like the Solidity compiler's optimizer, or gas profilers such as `hardhat-gas-reporter`) that help pinpoint gas bottlenecks. Gas optimization should *not* sacrifice clarity or security, but often there are win-win optimizations (e.g. caching repeated calculations, using `memory` instead of `storage` for temporary variables [98]). Prior to deployment, projects typically undergo **smart contract audits**. **Audit tools and services** help catch vulnerabilities like reentrancy, integer overflow, or logical bugs that could be catastrophic on immutable smart contracts. Static analysis tools like **Slither** (from Trail of Bits) scan Solidity code for common issues and even suggest optimizations [99]. **Mythril** (and its SaaS incarnation MythX) uses symbolic execution to find potential exploits in compiled bytecode [99]. These tools can detect things like reentrancy vulnerabilities, missing input validations, gas griefing attacks, etc. Additionally, teams often hire external **security auditors** to manually review the code and write custom tests – firms like OpenZeppelin, Trail of Bits, or Certik provide audit reports for DeFi protocols and NFTs. Auditors will scrutinize the contract logic, try to break invariants, and ensure compliance with best practices (like using checks-effects-interactions pattern to prevent reentrancy). Post-deployment, some projects run bug bounty programs to crowdsource security testing. In summary, deploying blockchain applications safely involves: testing on testnets, optimizing for gas costs, and rigorously auditing the contracts with both automated tools and human expertise to avoid costly vulnerabilities.

Real-World Examples (DeFi, NFTs, DAOs): Blockchain development has enabled entire new domains of applications. In **Decentralized Finance (DeFi)**, smart contracts recreate financial services without intermediaries [100]. For example, Uniswap is a smart contract on Ethereum that acts as an automated token exchange – users can swap tokens via a liquidity pool mechanism governed entirely by code [101]. Similarly, lending platforms like Aave or Compound allow users to deposit crypto and earn interest or borrow against collateral, with interest rates algorithmically adjusted by supply and demand. These DApps are composed of multiple contracts (for markets, oracles, governance tokens) and secure billions in value, demonstrating the need for robust engineering and audits. **NFTs** (Non-Fungible Tokens) have revolutionized digital ownership. An NFT is a unique token (often adhering to Ethereum's ERC-721 standard) that can represent ownership of a digital or physical asset – digital art, collectible profile pictures, virtual land, music rights, and more [102] [103]. NFTs exploded in popularity with examples like CryptoKitties (digital cats trading game) and artwork sales such as Beeple's piece auctioned for $69M in 2021 [103]. Blockchain developers in the NFT space work

on smart contracts that mint tokens and enforce rules (e.g. royalties for the original creator on secondary sales), and they often integrate with IPFS or other storage for the asset metadata. Finally, **DAOs (Decentralized Autonomous Organizations)** illustrate new ways of organization governance. A DAO is essentially a set of smart contracts (often with a token) that encode governance rules – members (token holders) can vote on proposals which, if passed, automatically execute certain actions (like releasing treasury funds or changing a protocol parameter). For instance, **MakerDAO** manages the Maker Protocol and its stablecoin DAI via token holder votes; the community decides on risk parameters and upgrades [104]. Another example is NounsDAO, which uses NFT-based membership to govern a community treasury. Blockchain engineers building DAOs focus on governance contract security (ensuring voting is fair and not exploitable) and often on upgradeability patterns, since governance contracts may need to evolve. They also interface with off-chain governance UIs and snapshot systems for vote signaling. These real-world examples show how blockchain development combines technical smart contract work with economic and game-theoretic design: DeFi requires careful incentive and risk design, NFTs blend tech with digital culture and legal considerations, and DAOs push the envelope in community-led software management. Each area continues to mature, presenting exciting challenges for developers to solve (scalability for DeFi, interoperability for NFTs, and security for DAOs, to name a few).

Career Path in Blockchain: Career roles in blockchain tech are evolving as the industry grows. A **Blockchain Developer** typically refers to someone building decentralized applications or smart contracts on existing platforms. They need skills in Solidity (for EVM chains) or Rust (for Solana/Substrate), familiarity with blockchain architecture, and also web development to build DApp frontends that interact with contracts [105] [106]. Blockchain developers often start by learning to write and deploy smart contracts and may work on teams launching DeFi protocols, NFT marketplaces, or Web3 games. As one gains experience, one could specialize or move to roles like **Smart Contract Auditor** or **Protocol Engineer**. A **Smart Contract Auditor** is a blockchain security expert – their job is to review others' contracts for vulnerabilities and verify correctness. Auditors need deep knowledge of common pitfalls (reentrancy, integer overflow, access control issues, etc.) and experience with the analysis tools mentioned earlier (Slither, Mythril, fuzzers like Echidna) to find subtle bugs. This role might appeal to those with a knack for security and an eye for detail; it's in high demand given the value locked in smart contracts and the frequency of hacks. A **Protocol Engineer** works on the blockchain platforms themselves – for example, contributing to Ethereum's core (clients like Geth or Prysm), developing Layer-2 scaling solutions, or building a new Layer-1 blockchain. This role requires strong systems programming skills (languages like Go, Rust, C++ are common for protocol development) and understanding of distributed systems and cryptography (consensus algorithms, networking, cryptographic primitives) [107]. Protocol engineers tackle problems of scalability (sharding, roll-ups), consensus improvements, and interoperability between chains. It's a path often taken by experienced developers or researchers, as it involves pushing the boundaries of blockchain performance and security. In summary, one might imagine starting as a DApp Developer writing smart contracts and UIs, then perhaps moving into auditing to deepen security expertise, and eventually becoming a Protocol Engineer to build the underlying blockchain tech. Other career paths exist too – **Blockchain Architect** (designing system architecture for enterprise use cases), **Product Manager** in blockchain, etc. But across all paths, a solid foundation in smart contracts, understanding of blockchain principles, and keeping abreast of new developments (like emerging standards, Layer-2 networks, and new languages) are keys to a successful blockchain engineering career.

---

[1] [2] [3] [4] [5] [6] [7] [8] [9] [10] [11] [12] Machine Learning Lifecycle - GeeksforGeeks
https://www.geeksforgeeks.org/machine-learning/machine-learning-lifecycle/

[13] [14] [15] [16] [17] [18] [19] [20] PyTorch vs TensorFlow: Comparative Guide of AI Frameworks 2025
https://opencv.org/blog/pytorch-vs-tensorflow/

[21] [22] [23] [24] [25] AI/ML Platforms: Pros and Cons - DEV Community
https://dev.to/polarsquad/aiml-platforms-pros-and-cons-28ka

[26] [32] [33] Inference.net | Serving Ml Models
https://inference.net/content/serving-ml-models

[27] [28] [29] [30] [31] Deployment Options - KodeKloud Notes
https://notes.kodekloud.com/docs/PyTorch/Model-Deployment-and-Inference/Deployment-Options

[34] [35] [36] What Is Data Poisoning? Attacks on Machine Learning Models
https://www.group-ib.com/resources/knowledge-hub/data-poisoning/

[37] [38] [39] [40] [41] Membership Inference Attacks: The New Privacy Threat to AI Models | by Vikaschoudhary16 | Techsutra
https://medium.com/techsutra/membership-inference-attacks-the-new-privacy-threat-to-ai-models-178d64e56088

[42] [43] [44] Machine Learning Lens - AWS Well-Architected Framework - Machine Learning Lens
https://docs.aws.amazon.com/wellarchitected/latest/machine-learning-lens/machine-learning-lens.html

[45] [46] [47] [48] [49] [50] [51] [52] Applied / Research Scientist, ML Engineer: What’s the Difference?
https://eugeneyan.com/writing/data-science-roles/

[53] [54] [55] Blocks, Chains, and Hashes. In the digital age, where information… | by Esthon Medeiros Jr | Medium
https://medium.com/@esthon/blocks-chains-and-hashes-b3bc323b978e

[56] [57] What Is a Block in the Crypto Blockchain, and How Does It Work?
https://www.investopedia.com/terms/b/block-bitcoin-block.asp

[58] [59] Understanding Merkle Trees: Enhancing Blockchain Efficiency and Security
https://www.investopedia.com/terms/m/merkle-tree.asp

[60] [61] [62] [63] Public & private keys explained
https://trezor.io/learn/basics/public-private-keys?srsltid=AfmBOopkOzpauxyU2_A80Qh-a_iZPqOVvtZU9Ke8WIiMuxXmuixs_IA0

[64] [65] [66] [67] [68] [69] [70] [71] Top Blockchain Consensus Mechanisms Explained | Cherry Servers
https://www.cherryservers.com/blog/consensus-mechanisms-in-blockchain

[72] [88] [89] How to use GANACHE Truffle Suite to Deploy a Smart Contract in Solidity (Blockchain)? - GeeksforGeeks
https://www.geeksforgeeks.org/solidity/how-to-use-ganache-truffle-suite-to-deploy-a-smart-contract-in-solidity-blockchain/

[73] [74] [75] Top 9 Smart Contract Programming Languages in 2026- Metana
https://metana.io/blog/top-9-smart-contract-programming-languages/

[76] [77] [78] [79] [80] [81] [82] [83] [84] [85] Difference Between Solana, Ethereum, Hyper ledger | by Diptendu Das | Block Magnates
https://blog.blockmagnates.com/difference-between-solana-ethereum-hyper-ledger-e91fd0a5bbd0?gi=c13866fce736

[86] [87] [90] [91] [92] [94] Hardhat Vs Truffle - Key Differences - 101 Blockchains
https://101blockchains.com/hardhat-vs-truffle/

[93] Consensys Announces the Sunset of Truffle and Ganache and New ...
https://consensys.io/blog/consensys-announces-the-sunset-of-truffle-and-ganache-and-new-hardhat

[95] [96] [97] [98] Gas Optimization in Ethereum Smart Contracts: Best Practices
https://www.vibraniumaudits.com/post/gas-optimization-in-ethereum-smart-contracts-10-best-practices

[99] The best smart contract analysis tools of 2025 - H-X Technologies
https://www.h-x.technology/blog/the-best-smart-contract-analysis-tools-2025

[100] [101] [102] [103] [104] DeFi, NFTs, DAOs, and Web 3.0 Understanding the Blockchain Revolution | by Alex Roupell | Medium
https://medium.com/@aroupell/defi-nfts-daos-and-web-3-0-understanding-the-blockchain-revolution-c9dd53ce6670

[105] Explain protocol engineering to me like I'm 5. : r/ethdev - Reddit
https://www.reddit.com/r/ethdev/comments/1hojr4h/explain_protocol_engineering_to_me_like_im_5/

[106] Blockchain Engineering Job Listing - cryptojobs.com
https://www.cryptojobs.com/blockchain-engineering

[107] Blockchain Protocol Engineers | Job Portal by OnHires
https://www.onhires.com/job-portal/blockchain-protocol-engineers