Feedback — Week 3 Quiz

Help

Thank you. Your submission for this quiz was received.

You submitted this quiz on **Sun 18 Jan 2015 12:14 PM COT**. You got a score of **1.00** out of **5.00**. You can attempt again, if you'd like.

Question 1

Take a look at the 'iris' dataset that comes with R. The data can be loaded with the code:

```
library(datasets)
data(iris)
```

A description of the dataset can be found by running

```
?iris
```

There will be an object called 'iris' in your workspace. In this dataset, what is the mean of 'Sepal.Length' for the species *virginica*? (Please only enter the numeric result and nothing else.)

You entered:

5.843333

Your Answer		Score	Explanation
5.843333	✖	0.00	
Total		0.00 / 1.00	

Question 2

Continuing with the 'iris' dataset from the previous Question, what R code returns a vector of the

means of the variables 'Sepal.Length', 'Sepal.Width', 'Petal.Length', and 'Petal.Width'?

Your Answer		Score	Explanation
apply(iris[, 1:4], 2, mean)			
apply(iris, 1, mean)			
apply(iris[, 1:4], 1, mean)	✖	0.00	this takes the row means of the dataset.
rowMeans(iris[, 1:4])			
Total		0.00 / 1.00	

Question 3

Load the 'mtcars' dataset in R with the following code

```
library(datasets)
data(mtcars)
```

There will be an object names 'mtcars' in your workspace. You can find some information about the dataset by running

```
?mtcars
```

How can one calculate the average miles per gallon (mpg) by number of cylinders in the car (cyl)?

Your Answer		Score	Explanation
split(mtcars, mtcars$cyl)	✖	0.00	this just splits the data frame by number of cylinders
sapply(mtcars, cyl, mean)			
lapply(mtcars, mean)			
with(mtcars, tapply(mpg, cyl, mean))			
Total		0.00 /	

1.00

Question 4

Continuing with the 'mtcars' dataset from the previous Question, what is the absolute difference between the average horsepower of 4-cylinder cars and the average horsepower of 8-cylinder cars?

You entered:

0.457895

Your Answer		Score	Explanation
0.457895	✖	0.00	
Total		0.00 / 1.00	

Question 5

If you run

```
debug(ls)
```

what happens when you next call the 'ls' function?

Your Answer		Score	Explanation
○ You will be prompted to specify at which line of the function you would like to suspend execution and enter the browser.			
◉ Execution of 'ls' will suspend at the beginning of the function and you will be in the browser.	✔	1.00	
○ The 'ls' function will return an error.			
○ Execution of the 'ls' function will suspend at the 4th line of			

the function and you will be in the browser.

Total	1.00 / 1.00