

This document was generated on 04/15/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>53261-0471</u>

Status: Active

Overview: PicoBlade™ Connector System

Description: 1.25mm Pitch PicoBlade™ Header, Surface Mount, Right Angle, Lead-Free, 4 Circuits

Documents:

3D Model Packaging Specification SPK-53261-002 (PDF)

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-51021-024 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series 53261

Application Signal, Wire-to-Board

MolexKits Yes

Overview <u>PicoBlade™ Connector System</u>

Product Name PicoBlade™ UPC 822348161072

Physical

Breakaway No
Circuits (Loaded) 4
Circuits (maximum) 4
Color - Resin Natural

Durability (mating cycles max) 30 First Mate / Last Break No Flammability 94V-0 **Glow-Wire Compliant** No Guide to Mating Part Yes Keying to Mating Part None Lock to Mating Part Yes Mated Height 3.40mm

Material - Metal Phosphor Bronze

Material - Plating Mating Tin Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 158.700/mg

Number of Rows


Orientation Right Angle
PCB Locator No
PCB Retention Yes

Packaging Type Embossed Tape on Reel

Pitch - Mating Interface 1.25mm
Plating min - Mating 1.016µm
Plating min - Termination 1.016µm
Polarized to PCB Yes
Shrouded Fully
Stackable No

Temperature Range - Operating -40°C to +85°C Termination Interface: Style Surface Mount

Electrical



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Contains SVHC: No
Low-Halogen Status
Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

<u>53261</u>Series

Mates With

<u>51021</u> PicoBlade[™] Wire-to-Wire and Wire-to-Board Housing

Current - Maximum per Contact 1A Voltage - Maximum 125V

Material Info

Reference - Drawing Numbers

Packaging Specification SPK-53261-002

Product Specification PS-51021-024, RPS-51021-036, RPS-51021-038,

RPS-51021-039, RPS-51021-040, RPS-51021-042, RPS-51021-043, RPS-51021-045, RPS-51021-046, RPS-51021-047, RPS-51021-051, RPS-51021-053,

RPS-51021-054, RPS-51021-057, RPS-51021-058,

RPS-51021-061, RPS-51021-062, RPS-51021-066,

RPS-51021-067, RPS-51021-068, RPS-51021-072, RPS-51021-073, RPS-51021-076, RPS-51021-079,

RPS-51021-080, RPS-51021-081, RPS-51021-084, RPS-51021-085, RPS-51021-086, RPS-51021-091,

RPS-51021-097, RPS-51021-099, RPS-51021-101, RPS-51021-102, RPS-51021-105, RPS-51021-107,

RPS-51021-108, RPS-51021-112, RPS-51021-114, RPS-51021-117, RPS-51021-122, RPS-53261-001,

RPS-53261-002

Sales Drawing SD-51021-002, SD-53261-023, SD-53261-024

This document was generated on 04/15/2014

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION