

`--deep` Considered Harmful

!

This thread has been locked by a moderator.



2.9k

Many of the trusted execution problems I see are caused by folks signing their product using the `--deep` option. While that can work in some circumstances, I generally recommend against it. There are two issues with `--deep`:

- It applies the same code signing options to every code item that it signs, something that’s not appropriate in general. For example, you might have an app containing a nested command-line tool, where the app and the tool need different entitlements. The `--deep` option will apply the same entitlements to both, which is a serious mistake.
- It only signs code that it can find, and it only finds code in nested code sites. If you put code in a place where the system is expecting to find data, `--deep` won’t sign it.

The first issue is fundamental to how `--deep` works, and is the main reason you should not use it. Indeed, on macOS it may cause the trusted execution system to block your program from running. For the details, see the *Check for Entitlements on Library Code* section of [Resolving Library Loading Problems](#).

The second issue is only a problem if you don’t follow the rules for nesting code and data within a bundle, as documented in [Placing Content in a Bundle](#). However, my experience is that the products that don’t follow those rules are exactly the same sort of products that try to use `--deep`.

The alternative to `--deep` is to sign each code item separately, from the inside out. If your product has lots of nested code, automate this using a script.

Note One exception to the prohibition on `--deep` is Automator apps. If you’re signing an Automator app, see [this DevForums post](#).

For detailed information on how to correctly sign and package Mac software, see [Creating Distribution-Signed Code for Mac](#) and [Packaging Mac Software for Distribution](#).

Share and Enjoy

—
Quinn “The Eskimo!” @ Developer Technical Support @ Apple
`let myEmail = "eskimo" + "1" + "@" + "apple.com"`

Revision history:

- **2022-06-14** Added a link to [Resolving Library Loading Problems](#). Replaced the link to *Signing a Mac Product For Distribution* with a link to [Creating Distribution-Signed Code for Mac](#). Made other minor editorial changes.
- **2021-10-21** Replaced the nested code reference with one to [Placing Content in a Bundle](#). Minor editorial changes.
- **2020-09-15** Adopted the correct terminology for Automator apps.
- **2020-03-09** First version.

Code Signing

Reply

Posted 2 years ago by eskimo

[Add a Comment](#)

This site contains user submitted content, comments and opinions and is for informational purposes only. Apple disclaims any and all liability for the acts, omissions and conduct of any third parties in connection with or related to your use of the site. All postings and use of the content on this site are subject to the [Apple Developer Forums Participation Agreement](#).

Apple

>

Developer

>

Forums

Platforms

iOS

iPadOS

macOS

tvOS

watchOS

Tools

Swift

SwiftUI

SF Symbols

Swift Playgrounds

TestFlight

Xcode

Xcode Cloud

Topics & Technologies

Accessibility

Accessories

App Extensions

App Store

Audio & Video

Augmented Reality

Business

Design

Distribution

Education

Fonts

Games

Health & Fitness

In-App Purchase

Localization

Maps & Location

Machine Learning

Security

Safari & Web

Resources

Documentation

Curriculum

Downloads

Forums

Videos

Support

Support Articles

Contact Us

Bug Reporting

System Status

Account

Apple Developer

App Store Connect

Certificates, IDs, & Profiles

Feedback Assistant

Programs

Apple Developer Program

Apple Developer Enterprise Program

App Store Small Business Program

MFi Program

News Partner Program

Video Partner Program

Security Bounty Program

Security Research Device Program

Events

App Accelerators

App Store Awards

Apple Design Awards

Apple Developer Academies

Entrepreneur Camp

Tech Talks

WWDC

To view the latest developer news, visit

[News and Updates](#)