

Calling BSD Sockets from Swift

!

This thread has been locked by a moderator.



56

I find myself using BSD Sockets a lot. Ironically this isn't because I'm doing networking. If I'm writing networking code on Apple platforms, I use one of Apple's preferred APIs, like `NSURLSession` or `Network` framework. For more on this see TN3151 [Choosing the right networking API](#)

No, I'm using BSD Sockets tangentially, not for my core networking code but for other, weirder stuff. For example, I might want to get a list of all the IP addresses on the system, and that requires calling `getifaddrs`, which returns its results as `struct sockaddr` values, which is the BSD Sockets address primitive.

Calling BSD Sockets correctly from Swift is a challenge [1]. Over the years I've come up with numerous wrappers to make this easier. I've found that tricky to do. If I were writing production code I would create a comprehensive wrapper that covers all the details. However, I don't write production code, I write test projects, snippets for posting to DevForums, and so on. Given that, I want my wrapper to be thin, so that the reader can understand the BSD Sockets concepts without getting lost of the wrapper.

Oh, and I don't really care about efficiency (-:

Recently I've used my understanding of these goals to create a BSD Sockets wrapper that I'm comfortable sharing. It's convenient, reasonably 'thin', and works well for test projects, snippets, and so on.

It can also be wildly inefficient but, as mentioned above, I don't care about that (-:

IMPORTANT [TN3151](#) discusses the circumstances under which it makes sense to use BSD Sockets for networking. Most of these involve calling BSD Sockets from a C-based language rather than Swift, and my wrapper is irrelevant in that case.

So, with that out of the way, meet QSocket2023! [2]

Well... actually... I'm going to put this in four separate posts:

- [QSocket: Addresses](#)
- [QSocket: DNS](#)
- [QSocket: Interfaces](#)
- [QSocket: System Additions](#)
- [QSocket: I/O](#)
- [QSocket: Socket Options](#)

If you have any questions or comments about this stuff, please start a new thread here on DevForums. Tag it with *Network* so that I see it.

Share and Enjoy

Quinn "The Eskimo!" @ Developer Technical Support @ Apple
`let myEmail = "eskimo" + "1" + "@" + "apple.com"`

[1] Rumour has it that, even in C, calling BSD Sockets without bumping into [undefined behaviour](#) is a challenge, but I'll let the C language lawyers litigate that (-:

[2] That's right, I've written so many BSD Sockets wrappers that I've started using the year to distinguish them!

Network

Reply

Posted 5 days ago by eskimo

Add a Comment

This site contains user submitted content, comments and opinions and is for informational purposes only. Apple disclaims any and all liability for the acts, omissions and conduct of any third parties in connection with or related to your use of the site. All postings and use of the content on this site are subject to the [Apple Developer Forums Participation Agreement](#).

Platforms

iOS

iPadOS

macOS

tvOS

watchOS

Tools

Swift

SwiftUI

SF Symbols

Swift Playgrounds

TestFlight

Xcode

Xcode Cloud

Topics & Technologies

Accessibility

Accessories

App Extensions

App Store

Audio & Video

Augmented Reality

Business

Design

Distribution

Education

Fonts

Games

Health & Fitness

In-App Purchase

Localization

Maps & Location

Machine Learning

Security

Safari & Web

Resources

Documentation

Curriculum

Downloads

Forums

Videos

Support

Support Articles

Contact Us

Bug Reporting

System Status

Account

Apple Developer

App Store Connect

Certificates, IDs, & Profiles

Feedback Assistant

Programs

Apple Developer Program

Apple Developer Enterprise Program

App Store Small Business Program

MFi Program

News Partner Program

Video Partner Program

Security Bounty Program

Security Research Device Program

Events

App Accelerators

App Store Awards

Apple Design Awards

Apple Developer Academies

Entrepreneur Camp

Tech Talks

WWDC