


# Running an HTTP Request over WWAN

 This thread has been locked by a moderator.



For important background information, read [Extra-ordinary Networking](#) before reading this.

Share and Enjoy

 29

Quinn “The Eskimo!” @ Developer Technical Support @ Apple  
`let myEmail = "eskimo" + "1" + "@" + "apple.com"`

## Running an HTTP Request over WWAN

`NSURLSessionConfiguration` has a property, `allowsCellularAccess`, that controls whether requests in that session are allowed to run over WWAN. However, there’s no opposite of that, a way to *force* requests to run over WWAN. Some apps need to do this.

**IMPORTANT** There are good and bad reasons to force a request to run over WWAN. I’ll explain a good reason below, but a bad reason is that you think that using WWAN is better aligned with your user’s networking preferences. Don’t go down that path. Rather, use the constraints mechanism described in [Network Interface Techniques](#) to align with the user’s preferences.

So what’s an example of a *good* reason for this? I once worked with a developer who’d cut a deal with a cellular carrier to offer special benefits to that carrier’s users. Rather than require that the user give the app access to their cellular account, they wanted to run an HTTP request over WWAN to a server that’s only available on the carrier’s network.

If you’re using Network framework, or even BSD Sockets, this isn’t a problem. For information about how to bind a connection to an interface, see [Network Interface Techniques](#). If you’re using `NSURLSession`, there’s no obvious way to achieve this goal, but there are two non-obvious approaches you can try:

- Implement your own HTTP protocol
- Fun with Multipath TCP!

Regarding the first approach, see the discussion in the [HTTP alternatives](#) section of TN3151 [Choosing the right networking API](#).

Regarding the second approach, the basic idea is to set up an HTTP server with Multipath TCP (MPTCP) support on the carrier’s network. If your app issues a request to that server while both Wi-Fi and WWAN are active, the system will try to connect over both interfaces. The Wi-Fi connection will fail but the WWAN connection will succeed, and thus the request runs over WWAN. Neat-o!

For information on how to enable MPTCP with `NSURLSession`, see [Supporting Multipath TCP](#).


Network

Reply

Posted 2 days ago by  eskimo 

[Add a Comment](#)

This site contains user submitted content, comments and opinions and is for informational purposes only. Apple disclaims any and all liability for the acts, omissions and conduct of any third parties in connection with or related to your use of the site. All postings and use of the content on this site are subject to the [Apple Developer Forums Participation Agreement](#).

 > Developer > Forums

### Platforms

iOS  
iPadOS  
macOS  
tvOS  
watchOS  
  
**Tools**  
Swift  
SwiftUI  
SF Symbols  
Swift Playgrounds  
TestFlight  
Xcode  
Xcode Cloud

### Topics & Technologies

Accessibility  
Accessories  
App Extensions  
App Store  
Audio & Video  
Augmented Reality  
Business  
Design  
Distribution  
Education  
Fonts  
Games  
Health & Fitness  
In-App Purchase  
Localization  
Maps & Location  
Machine Learning  
Security  
Safari & Web

### Resources

Documentation  
Curriculum  
Downloads  
Forums  
Videos

### Support

Support Articles  
Contact Us  
Bug Reporting  
System Status

### Account

Apple Developer  
App Store Connect  
Certificates, IDs, & Profiles  
Feedback Assistant

### Programs

Apple Developer Program  
Apple Developer Enterprise Program  
App Store Small Business Program  
MFi Program  
News Partner Program  
Video Partner Program  
Security Bounty Program  
Security Research Device Program

### Events

App Accelerators  
App Store Awards  
Apple Design Awards  
Apple Developer Academies  
Entrepreneur Camp  
Tech Talks  
WWDC

To view the latest developer news, visit

[News and Updates](#)