How Far Can General-Purpose LLMs Go in Tigrinya? A Lexicon-Grounded Evaluation with Trivial Baselines

Anonymous ACL submission

Abstract

We evaluate eight general-purpose large language models on three lexicon-grounded Tigrinya tasks (part-of-speech tagging, morphosyntactic labelling, and English→Tigrinya translation) using a 5,783-row annotated bilingual lexicon. A fourth task, lexical alignment, is not well enough posed to carry a result, and we release its data and outputs as a resource for reposing it rather than as a benchmark. Our central methodological finding is that such evaluations are easy to over-read: on these tasks a high score is not evidence of Tigrinya competence, because the tasks cannot distinguish competence from much cheaper strategies. A permissive matching rule puts the best model at 85.9% on part-of-speech tagging and 89.4% on morphosyntactic labelling, but scoring the same saved outputs by the first word the model commits to costs up to 26 points, and requiring an exact answer costs up to 89. More decisively, the prompt supplies an English gloss beside the Tigrinya form, and an oracle that sees only that gloss scores 96.5% and 95.9% on the two tasks, which *no model comes within 14 points of*, because only about one headword in twenty is ambiguous given the English. What a model's score on these tasks therefore bounds is what the English already determines, not what the model knows about Tigrinya. On translation all eight models score at or below 0.81 chrF on a 0–100 scale, which is effectively no Tigrinya output at all, while NLLB-200-3.3B, which supports the language, reaches 16.05 on identical items with the same scorer: a factor of twenty. We therefore report a negative result: these tasks, as posed, do not measure Tigrinya competence, and published numbers on them should not be read as doing so. We release our derived evaluation set, the scoring code and the saved model outputs, and argue that the procedure applied here (report every matching rule, bound the task from above as well as below with references that use none of the target language, and quantify prompt echo) requires no resources beyond those an evaluation already has, and should be standard in low-resource evaluation.

1 Introduction

Tigrinya is a Semitic language of Eritrea and northern Ethiopia with approximately 9–10 million speakers and very little machine-readable linguistic infrastructure. This scarcity makes it a natural test of whether general-purpose LLMs generalise beyond high-resource languages, and a difficult one to measure: without established benchmarks it is easy to produce numbers that look like competence.

This paper makes three contributions.

1. **A rebuilt and documented version of an existing lexicon-grounded evaluation set**: 5,783 English-Tigrinya rows (5,022 distinct English headwords, 3,926 Tigrinya forms), each carrying a part-of-speech label, derived from a digitised bilingual dictionary (Union of International Democrats, 2015). The lexicon and the four tasks are not new here; they were introduced by Teklehaymanot et al. (2026), and Section 7 states what differs. What is new is that the set is reconstructible from its source by a released script, with its two digitisation defects corrected and its annotation provenance recorded.

2. **An evaluation of eight LLMs** across POS tagging, morphosyntactic labelling and translation, reported under three matching rules and against references that use no Tigrinya at all. A fourth task in the benchmark, lexical alignment, is reported for completeness but not claimed as a result: 38% of its gold labels are positional fallbacks rather than annotation (Section 5.4).

3. **A negative result about the task design.** The choice of matching rule moves reported accuracy on fixed outputs by up to 26 points

between the two lenient rules and by as much as 89 points once exact match is included, and an oracle restricted to the English gloss scores 96.5% and 95.9% on the two tagging tasks, which no model approaches. The tasks are therefore substantially solvable without the target language, and the numbers they produce, including ours, do not measure Tigrinya competence. We give the procedure that exposes this and argue it should be routine.

This lexicon and these four tasks were introduced by Teklehaymanot et al. (2026), whose retraction has been requested. The results below come from new runs on a rebuilt gold set, not from re-scoring that paper's outputs; Section 7 gives the differences.

2 Related work

2.1 Tigrinya and Ge'ez-script NLP

Tigrinya remains severely underrepresented in NLP: a survey of over 50 studies from 2011 to 2025 finds a field driven almost entirely by discrete resource-creation milestones rather than modelling advances (Gaim and Park, 2026), a pattern echoed across Ethiopian languages (Tonja et al., 2023). Existing resources are small and task-specific: domain-adapted Tigrinya→English NMT (Öktem et al., 2020), sentiment transfer from English XLNet (Tela et al., 2020), two question-answering sets (Gaim et al., 2023; Teklehaymanot et al., 2024), and neural taggers over the small Nagaoka corpus, where a BiLSTM reaches 92% (Tesfagergish and Kapočiūtė-Dzikienė, 2020). Those taggers are trained on running text; we evaluate untrained models on dictionary headwords.

Tigrinya appears in some multilingual benchmarks, such as Belebele (Bandarkar et al., 2024), and is absent from others: MasakhaPOS, the largest POS dataset for African languages, covers 20 languages under UD guidelines but not Tigrinya (Dione et al., 2023). AfroBench reports the same gap over 64 languages and 15 tasks, with LLM performance tracking monolingual data availability (Ojo et al., 2025) — the pattern Joshi et al. (2020) documented, where representation in NLP venues tracks resource availability. This also bears on how a positive result should be read, since Blevins and Zettlemoyer (2022) show English pretraining corpora carry enough incidental non-English text to explain much cross-lingual transfer, so apparent Tigrinya ability need not reflect deliberate coverage.

The lexicon and the four tasks used here were introduced by Teklehaymanot et al. (2026), whose retraction has been requested; Section 7 states what this paper takes from that work and how the two differ.

2.2 LLM evaluation for low-resource languages

NLLB-200 added Tigrinya (`tir_Ethi`) to a 200-language translation model (NLLB Team et al., 2022), evaluated on FLORES, whose professionally translated design set the standard for low-resource MT benchmarking (Goyal et al., 2022). Several studies establish that general-purpose LLMs lag purpose-built MT on exactly these languages. Robinson et al. (2023) found NLLB superior to ChatGPT on 169 of 201 FLORES-200 languages (84.1%) by an average of 11.9 chrF, the gap widest for African languages and the Ge'ez script, and report five-shot prompting improving on zero-shot by only 0.88 chrF across 203 directions — close to our own few-shot probe, which moves gemma-7b from chrF 0.16 to 0.66 with exact match unchanged. Hendy et al. (2023) reach the same conclusion for GPT models across eighteen directions, competitive for high-resource and limited for low-resource, and Zhu et al. (2023) find GPT-4 beating NLLB in 40.91% of directions while trailing badly on the long tail. Adebara et al. (2025) extend this to a continent-scale African benchmark and attribute the residual disparities to data inequities rather than model scale. Our Section 5.3 result — three NLLB checkpoints at chrF 14.1–16.1 against eight LLMs at ≤ 0.81 — is this finding at lexicon granularity, where the LLM floor is not merely lower but absolute.

A separate strand asks whether such evaluations are conducted carefully enough. LAraBench benchmarked 33 Arabic tasks across 61 datasets and explicitly computed a random baseline "to determine if the LLMs predictions are not merely the result of chance" (Abdelali et al., 2023). We regard that step as mandatory rather than optional, and Section 5 shows why.

2.3 Trivial baselines and spurious cues

The methodological core of this paper has a direct precedent in natural language inference. Poliak et al. (2018) showed that a hypothesis-only model — one that never sees the premise, a degenerate solution by construction — significantly outperforms a majority-class baseline on several NLI datasets, and

Gururangan et al. (2018) showed the same artefacts let a classifier label the hypothesis alone correctly in about 67% of SNLI, concluding that model success "has been overestimated". Related work finds strong scores resting on fallible syntactic heuristics (McCoy et al., 2019) or on spurious statistical cues that account for a model's performance entirely (Niven and Kao, 2019). Our English-only tagger is a hypothesis-only baseline in this sense: the prompt format `Phrase: {Tigrinya} ({English})` leaves the part of speech largely recoverable from the gloss, and the baseline reaching 60.38 is the lexicon-task analogue of that 67% SNLI result.

For POS tagging specifically, Kann et al. (2020) make the closest argument to ours: weakly supervised taggers reported to perform "almost as well as supervised ones" were evaluated on languages unlike truly low-resource ones, and on 15 genuinely low-resource languages the best model gets fewer than half the words right. They also note that such methods presuppose "high-coverage and almost error-free dictionaries" — precisely the assumption the annotator notes behind Section 3.3 undermine, where the source dictionary carries mislabelled parts of speech and outright mistranslations. At the level of benchmark design, Reuel et al. (2024) assess 46 best practices across 24 benchmarks and score stating random performance as a criterion, since without it capability cannot be separated from chance or metric design.

2.4 Scoring rules and prompt artefacts

Our finding that the matching rule moves reported accuracy on fixed outputs by up to 26 points between lenient rules, and by as much as 89 points once exact match is included, belongs to a growing literature on evaluation mechanics. Tam et al. (2024) show that constraining LLMs to structured output formats degrades measured reasoning, and separate format errors from content by using an LLM as a "perfect parser" rather than a regex — the mirror image of our problem, where permissive parsing manufactures competence instead of destroying it. Kirouane and Petrocheilos (2026) document the same failure mode in a low-resource setting: a scorer that scanned the whole response instead of the requested answer line produced a $+29.8$ pp artefact, one-directional against verbose outputs, concluding that "any benchmark that requests an answer format must score that format first and report how often it was absent". Our first-token rule is that recommendation applied, and the three-rule triple reports the spread it would otherwise hide.

The prompt-echo column in Section 5.2 relates to known label-copying behaviour: Zhao et al. (2021) show few-shot accuracy destabilised by bias towards answers appearing in the prompt, varying "from near chance to near state-of-the-art" with prompt format alone. When the gold distribution is 53.8% `noun` and the prompt example contains `noun`, a model that copies the example is correct by construction under set-intersection — gemma-7b does this on 97.4% of answers — so we treat echo rate as a reportable diagnostic.

2.5 Metrics, agreement and dictionary sources

We report chrF (Popović, 2015) because character n-gram F-score is tokenisation-independent and so appropriate for Ge'ez-script targets averaging 1.18 whitespace tokens, where word-level BLEU (Papineni et al., 2002) is near-undefined; following Post (2018), who argues that BLEU is a parameterised family whose configurations are not comparable across papers unless the scheme is pinned down, we report character-level BLEU alongside it. Agreement is Cohen's κ (Cohen, 1960), reported beside raw observed agreement and the filled-label-only variant rather than as a single coefficient, because κ is hard to interpret under class imbalance — the "kappa paradox" — and absolute thresholds are not meaningful without a contextual reference (Wong et al., 2021).

Digitised bilingual dictionaries are a standard bottom-up resource for languages lacking parallel corpora: Wickramasinghe and de Silva (2023) argue that for low-resource pairs it is "more feasible to move in the bottom-up direction where finer granular pairs such as dictionary datasets are developed first", while Ve'rdd addresses the complementary problem of grassroots paper dictionaries edited by many hands, which need re-evaluation rather than direct ingestion (Alnajjar et al., 2020). Our source shows exactly the defects that motivate that work — a direction-swapped second block, inline gender markers inside the target field, and annotator-flagged mistranslations — which Sections 3.1 to 3.3 document rather than silently clean.

3 Dataset

3.1 Source and construction

The lexicon was digitised from the Swansea Tigrinya–English dictionary (Union of Interna-

tional Democrats, 2015), with additional entries contributed by native-speaker linguists, and carries the source dictionary's own part-of-speech abbreviations. The digitised source holds 7,234 rows concatenated from two directions, English→Tigrinya followed by Tigrinya→English, under a single pair of column headers; in the second block the column named `English` therefore holds Ge'ez script. We detect that block by script, reorient it, and merge both directions, keeping distinct senses of one form as separate items — *estimate* → ግምት is retained as both noun and verb, which yields **5,783 gold rows** over 5,022 distinct English headwords and 3,926 distinct Tigrinya forms. Counts of headwords are sensitive to the definition: splitting the comma-separated variants that some entries carry in the English field gives 4,327 single-word glosses instead. We count whole field values throughout, which is what the baselines and the ceiling in Section 4.2 key on. Three evaluation set sizes follow from this and are not interchangeable: 5,783 gold rows, **5,775 items** for translation and lexical alignment after each task drops duplicate pairs and rows with an empty side, and **5,701 items** for the two tagging tasks, which were run against a further reduction representing each multi-sense entry by its first sense. Appendix C gives the row-level derivation, the provenance of the source file, and the reconstruction of the 5,701-item set from the released gold.

3.2 What the annotations do and do not contain

The POS labels are the source dictionary's, not independently re-annotated by us. They are coarse: `noun` accounts for 3,109 of 5,783 labelled entries (53.8%), `verb` 1,542, `adjective` 879.

Morphosyntactic features are **sparse**. Only 183 entries carry a morphosyntactic label that differs from the POS label at all; the remaining 5,600 (96.8%) are identical to it. The 183 are sparser still than that suggests: 88 carry gender, number or plurality (38 `noun, masculine`, 35 `noun, feminine`, 13 `noun, plural`, 2 `uncategorized`), and the other 95 are `adjective, noun-derived`, a derivational note rather than an inflectional feature. We therefore do not treat morphosyntactic labelling as a distinct linguistic dimension, and report it in Section 5.2 as what it measures: a second POS task with a different prompt.

3.3 Inter-annotator agreement

A 500-item subset was annotated independently by two of the authors, both native speakers of Tigrinya, for part of speech, gender, number, category agreement and lexical alignment. Each assigned labels separately using the annotation guide; the two sheets were then compared and a final sheet compiled from them. **No third annotator took part, and no party outside the author group adjudicated**, which bounds what the coefficients below can mean: the compiled sheet is sometimes read as an independent adjudication, and it is not one. The records — both annotation sheets, the compiled sheet and the guide that defines every permitted value — are released as a single workbook, and `scripts/compute_iaa.py` recomputes every figure here from it. The workbook carries no edit history: the annotators exchanged sheets as messaging attachments that have since expired, so the labels survive but the order in which they were entered does not.

The five dimensions are not of one kind. The guide's instruction is to "verify and annotate": four are assigned from scratch, while the part-of-speech label arrives pre-filled from the source dictionary and is verified. The annotators used that latitude very differently — Annotator 1 corrected the dictionary's part of speech on 25 of 500 items, Annotator 2 on none — so all 25 part-of-speech disagreements have one shape: one annotator exercising the verification the guide asks for, the other accepting the dictionary. Where an annotator left a cell empty and the other assigned a label, that is not a matching judgement, so we count it as a disagreement and report Cohen's κ over all 500 items with a blank as its own category (Table 5, in Appendix A).

Restricting instead to the items both annotators labelled raises every dimension — 0.9076, 1.0000, 1.0000, 0.9815 and 0.9850 on 500, 420, 428, 445 and 474 items. We report the stricter figures because the difference between the two columns is largely a difference in what each annotator left blank: Annotator 1 omits 32 gender, 32 number and 46 agreement labels that Annotator 2 supplies, against 6, 4 and 3 in the other direction. Discarding those rows would hide the main source of divergence.

Three properties bound what these coefficients support, and Appendix A gives the evidence for each. The compiled sheet is a selection between the two existing columns, not an independent third

judgement, so it cannot serve as an adjudicated gold standard. Agreement on filled labels is near-total: where both annotators assigned a gender or number value they never differ, so the divergence is in coverage rather than in choice of label, which is why κ falls once blanks count. And the subset is not a random sample but the alphabetical head of each category: 61% adjective against a corpus that is 54% noun and 25% verb, and **drawn from no verb entries at all**. The coefficients therefore describe this subset and are not an estimate for the corpus; establishing one needs a stratified re-annotation covering verbs, by annotators outside the author group, which we leave to future work (Section 8).

The workbook also carries the annotators' free-text notes on 201 of the 500 items, documenting mislabelled parts of speech in the source dictionary, inflected forms given as citation forms, and outright mistranslations (*at least* → ብብዚሑ, which means *at most*). These support the caveat in Section 3.2 that the POS labels are the source dictionary's and were not independently verified.

4 Experimental setup

Eight models, all loaded through the Hugging Face `transformers` interface (Wolf et al., 2020) and run on a single compute node with four A100 GPUs, 32 CPU cores and 128 GB of RAM (Table 1).

A later run on newer models. The eight models above are those the evaluation was run on in full. They are dated: none exceeds 7B parameters and three cannot follow an instruction. A later run on nine newer and larger checkpoints reached its time limit after part-of-speech tagging alone, so it is not in the tables; its log and generations are released, and its best model scores above ours, Falcon3-10B-Instruct reaching 82.62 under the task script's own scorer against mistral-7b's 78.76.

That illustrates this paper's argument rather than undercutting it. Falcon3-10B emits its chat template into all 5,701 answers (`<|assistant|> adverb`), so under the first-token rule it scores **0.00**; strip the prefix and the same outputs give 80.25; score by set intersection and they give 82.76. One model, one set of generations, a range of 82 points. A larger model does not escape the measurement problem, and 82.76 is still below the 96.49 an English-only oracle reaches, so the higher score is not evidence that it read the Tigrinya.

We do not compare architectures. All five causal models are instruction-tuned and all three sequence-to-sequence models are raw pretrained checkpoints; the two factors are perfectly confounded in this model set and no result here can separate them. The three base seq2seq models receive span-infilling prompts matched to their pretraining objective; they nonetheless produce almost no usable output, which we report as a property of those checkpoints on this task rather than of their architecture.

Generation sets `max_new_tokens=128` and `min_new_tokens=1` and nothing else, so each checkpoint decodes under its own `generation_config.json`. This is not uniform: Qwen1.5-7B-Chat ships `do_sample=true` at temperature 0.7, so qwen-7b was sampled, not decoded greedily. We also did not apply the instruction-tuned models' chat templates; prompts were passed as plain text, which is one reason the off-format answers of Section 4.1 are so common. Both are limitations rather than design choices, and neither affects claims about what the tasks can measure on fixed outputs. `xlm-roberta-base` (Conneau et al., 2020) was included initially but fails on all tasks (its prompts contain no `<mask>` token) and is excluded.

4.1 Scoring

Model answers are frequently verbose: gemma-7b's median POS answer is 14 words. We report three rules.

- **exact**: the cleaned answer equals the gold label.
- **first-token**: the model's first word is a gold label word. This is the answer the model commits to, and is our headline rule.
- **set-intersection**: any word of the answer is a gold label word. This is permissive: an answer naming several parts of speech is correct as soon as one fits. We report it only to show the gap.

4.2 Baselines

The prompt supplies the English gloss alongside the Tigrinya form (`Phrase: {Tigrinya} ({English})`), so a system can score well without using the Tigrinya at all. We therefore bound the two tagging tasks from below and from above with references that see no Tigrinya whatsoever.

Label	Checkpoint	Arch.	Inst.
gemma-2b	`google/gemma-2b-it` (Gemma Team, Google DeepMind, 2024)	causal	yes
gemma-7b	`google/gemma-7b-it` (Gemma Team, Google DeepMind, 2024)	causal	yes
mistral-7b	`Mistral-7B-Instruct-v0.2` (Jiang et al., 2023)	causal	yes
qwen-7b	`Qwen1.5-7B-Chat` (Bai et al., 2023)	causal	yes
falcon-7b	`falcon-7b-instruct` (Almazrouei et al., 2023)	causal	yes
mt5-small	`google/mt5-small` (Xue et al., 2021)	seq2seq	no
mt5-large	`google/mt5-large` (Xue et al., 2021)	seq2seq	no
byt5	`google/byt5-small` (Xue et al., 2022)	seq2seq	no

Table 1: Evaluated models. Architecture and instruction-tuning status are perfectly confounded in this set.

- **Majority**: always answer the most frequent gold label (`noun`).
- **English-only tagger**: an NLTK (Loper and Bird, 2002) English POS tagger applied to the gloss alone. This is what one off-the-shelf English system achieves, and is a lower bound on what the gloss makes available.
- **English-only ceiling**: an oracle that sees only the English string and answers with the most frequent gold label that headword carries anywhere in the evaluation set. This is the best any English-only system can reach, and we report it because the lower bound alone understates how much of the task the gloss already determines.

The ceiling is high: 96.49 on part-of-speech tagging and 95.86 on morphosyntactic labelling. Only 189 of 5,025 headwords (3.8%) carry more than one gold part-of-speech label, and 212 (4.2%) more than one morphosyntactic label. Those headwords account for 439 of the 5,701 items (7.7%) on part of speech and 499 (8.8%) on morphosyntax, and they are the only items on which the Tigrinya form can supply information the gloss does not already determine. A model scoring below the ceiling has not shown that it used the Tigrinya.

Differences against the tagger baseline are tested with a one-sided McNemar test at $n = 5{,}701$. The test must be paired: the baseline is a system scored on the same items as the model, so the two sets of outcomes are correlated and only the discordant items carry information. Treating the baseline rate as a known constant and applying a binomial test, as is sometimes done, understates the variance of the difference and so overstates significance; on our data it moves the smallest margin by an order of magnitude ($p = 0.003$ against $p = 0.032$ for gemma-7b on morphosyntax). `scripts/task_ceiling.py` computes the ceiling, the ambiguity counts and both tests.

Model	exact	**first-tok**	set-int
mistral-7b	33.71	**81.56**	85.91
gemma-7b	0.00	**79.39**	82.44
gemma-2b	71.71	**72.86**	73.29
falcon-7b	26.94	**40.64**	44.45
qwen-7b	17.00	**17.00**	17.07
mt5-large	0.00	0.09	1.75
byt5	0.00	0.00	0.05
mt5-small	0.00	0.00	0.00
Majority (`noun`)		**53.73**	
English-only tagger		**60.38**	
English-only ceiling		**96.49**	

Table 2: POS tagging accuracy (%) under three matching rules, against the two English-only references. No model reaches the ceiling.

5 Results

Three tasks carry results; Section 5.4 reports the fourth, whose gold labels are too unreliable to support a conclusion.

5.1 POS tagging ($n = 5{,}701$)

Three models exceed the tagger baseline, each by a margin that is unambiguous ($p < 10^{-50}$): mistral-7b by 21.19 points, gemma-7b by 19.01 and gemma-2b by 12.49. Falcon-7b and qwen-7b fall below the majority baseline; all three seq2seq checkpoints are at or near zero.

No model reaches the English-only ceiling. The best, mistral-7b, falls 14.93 points short of it; gemma-7b 17.10 and gemma-2b 23.63. Since the ceiling is what a system achieves from the gloss alone, the ordering above is not evidence that any model used the Tigrinya form. It is consistent with every model using the gloss and using it worse than an English-only oracle would.

The exact column shows how brittle these numbers are. Gemma-7b scores 0.00% exact and

Model	**first-tok**	set-int	echo
gemma-2b	**64.59**	78.02	1.2%
gemma-7b	**63.32**	89.42	**97.4%**
mistral-7b	**54.92**	81.09	3.7%
falcon-7b	**39.17**	76.28	19.5%
qwen-7b	**34.33**	54.45	0.4%
mt5-small	0.86	2.49	0.0%
mt5-large	0.11	0.74	0.0%
byt5	0.00	38.55	69.7%
Majority	**52.38**		
English-only tagger	**61.57**		
English-only ceiling	**95.86**		

Table 3: Morphosyntactic labelling accuracy (%). The final column is how often an answer contains the prompt's own example. No model reaches the ceiling.

Model	chrF	BLEU_c	BLEU_w	exact
NLLB-3.3B	**16.05**	**14.23**	0.24	**16.24**
NLLB-1.3B	15.01	13.29	0.23	15.00
NLLB-600M	14.11	12.59	0.25	14.42
byt5	0.81	0.01	0.00	0.05
gemma-2b	0.39	0.01	0.01	0.07
mistral-7b	0.26	0.00	0.00	0.03
mt5-small	0.20	0.04	0.02	0.05
gemma-7b	0.16	0.00	0.00	0.03
mt5-large	0.13	0.04	0.01	0.02
falcon-7b	0.13	0.00	0.00	0.03
qwen-7b	0.04	0.00	0.00	0.00

Table 4: Translation quality. All values on a 0–100 scale.

79.39% first-token: it always answers in a sentence, never a bare label. A reader given only one of these columns would draw opposite conclusions.

5.2 Morphosyntactic labelling ($n = 5{,}701$)

Because the gold is 96.8% identical to the POS label (Section 3.2), this is effectively a second POS task.

Only two models exceed the tagger baseline of 61.57: gemma-2b by 3.02 points ($p = 1.6 \times 10^{-4}$) and gemma-7b by 1.75 ($p = 0.032$). Both margins reach significance at $n = 5{,}701$, and both are small; gemma-7b's is marginal, and would not survive a correction for testing eight models. The remaining six fall below the baseline, and five below the majority baseline of 52.38.

Against the ceiling the picture is uniform: **the best model is 31.28 points below what the English gloss alone makes available**, and the eight models span 31 to 96 points below it. Whatever separates gemma-2b from mistral-7b here, it is not evidence of morphosyntactic analysis of Tigrinya.

The final column measures how often an answer contains the prompt's own example, `preposition, noun, singular`. Gemma-7b echoes it in 97.4% of answers; because the example contains `noun`, and `noun` is the majority gold label, set-intersection scores those echoes as correct. Its apparent 89.42 is largely an artefact of copying the prompt. ByT5's 38.55 is the same artefact at 69.7% echo, and drops to 0.00 under first-token.

5.3 Translation, English→Tigrinya ($n = 5{,}775$)

Tigrinya references average 1.18 whitespace tokens, so word-level BLEU-4 is near-undefined; we report chrF and character-level BLEU (Table 4).

All eight general-purpose models are at the floor. NLLB-200, for which Tigrinya (`tir_Ethi`) is a supported target language, reaches chrF 16.05 on identical items with an identical scorer, roughly twenty times the best LLM.

The comparison is not like-for-like, and the differences all favour NLLB. It is a dedicated translation model given a source sentence and a target language code, decoded with five-beam search; the LLMs are prompted in English, decode under their own defaults (Section 4.1), and have their answers scored leniently, any word of a verbose reply counting as a hit against any gold synonym. We draw only the conclusion this supports: a purpose-built model that covers the language produces recognisable Tigrinya on these items and the general-purpose models produce almost none, a gap of a factor of twenty that no plausible decoding or prompting advantage would close. It does not license a ranking of NLLB against these LLMs as systems.

Note that word-level BLEU-4 is 0.24 for NLLB-3.3B, which translates 16.24% of items exactly. **Word-level BLEU is not usable at lexicon scale**, and a paper reporting it would show a working system as scoring zero.

Our own scorer supplied a further instance of the effect this paper reports. Many gold entries end in a trailing comma, and splitting them on commas without discarding the empty final field admit-

ted the empty string as a valid answer, so a model that generated nothing scored an exact match. This gave qwen-7b an exact-match rate of 0.28, the highest of the eight models and all 16 of its apparent successes empty generations. The released scorer drops empty candidates and the table reports 0.00; no other model was affected and no chrF or BLEU value changes. We report the defect rather than silently correcting it because a one-line omission in a scorer, not any property of a model, produced the best exact-match score in the table.

We verified the LLM failure is not one of output format. On a 300-item random sample (seed 0, exemplar phrases excluded), with gemma-7b alone, few-shot prompting with eight exemplars and an explicit format constraint moved chrF from 0.16 to 0.66, and exact match stayed at 0.00 on every arm of that probe; extracting the Ge'ez span from verbose answers recovered the reference in 2 of the 5,775 full-set items. (Gemma-7b's 0.03 in Table 4 is the full set, where 2 items match; the probe's 0.00 is the 300-item sample, where none does.) The median character-level similarity between model output and reference is 0.000: the models emit Ge'ez-shaped strings that are not the target words (ባህል for ብዙሕ, ልልል as repetition).

5.4 Lexical alignment

We report this task for completeness but do not draw conclusions from it: 2,208 of 5,783 alignment labels (38%) are positional fallbacks (`AlignmentSource: auto`) rather than annotation. Format accuracy ranges from 0.0383 (mt5-large) to 0.5484 (gemma-2b); semantic accuracy from 0.0012 (mt5-small) to 0.8876 (mistral-7b). The two measures diverge widely for individual models, which makes the task ill-posed as currently scored.

We release its data and outputs nonetheless: the 3,575 manually verified rows are marked as such, so restricting to them or annotating the remaining 2,208 would give a task this one cannot, and the divergence is itself another instance of the paper's point, two defensible scorers disagreeing on fixed outputs by more than the models differ.

6 Discussion

The matching rule is a reporting decision, not an implementation detail. The swings in Section 5.1 are not a property of the weaker models: the largest belong to the models that answer in fluent sentences, because a sentence contains the gold label without equalling it. Scoring the same saved outputs three ways costs gemma-7b everything it scored. A paper that reports one number without naming the rule has not reported a result, and reporting the triple costs nothing once the generations are saved.

Bound the task from above, not only from below. A lower-bound baseline tells you whether a model beats a weak system; it does not tell you whether the task needs the target language. Three models clear both lower baselines on POS, which reads as cross-lingual competence until the oracle is added and the best of them sits 14.93 points beneath it (31.28 on morphosyntax). Reporting only the lower bounds would have let this paper claim a result it does not have. The oracle costs one pass over the gold labels, and we recommend it wherever a prompt carries a cue in a higher-resource language.

Prompt echo is a measurable confound. Gemma-7b reproduces the prompt's example in 97.4% of its morphosyntax answers, and because the example contains the majority gold label, a permissive scorer rewards it. Echo rate belongs in any report whose prompt contains a worked example.

What we can claim about Tigrinya competence. On the two tagging tasks, nothing: they cannot separate a model that reads Tigrinya from one that reads the English gloss and answers worse than an oracle would. Translation is the one task here not solvable from the prompt's English, and there the result is unambiguous — no model translates into Tigrinya, while NLLB-200, which supports the language, is more than an order of magnitude better on chrF. Model selection dominates model size; and even NLLB reaches only 16.24% exact on dictionary headwords, so the difficulty is real rather than an artefact of our setup.

7 Relation to prior work, and reproducibility

This lexicon and these four tasks were introduced by Teklehaymanot et al. (2026), whose retraction has been requested. The results here are not a re-scoring of that paper's outputs: they come from new runs in September 2026 against a gold set rebuilt from the source lexicon, and differ in inputs as well as scoring. The earlier runs evaluated 3,899 items per tagging task against these 5,701, and the earlier gold

stored an expected tag as `(adv) adverb` rather than `adverb` and presented all comma-separated senses rather than one, so the prompts and the generations they elicit both differ. No number is carried over, and the two sets of results are not alternative measurements of the same quantity.

The lexicon, the gold files, the saved outputs, the annotation workbook and the scoring code accompany this submission and will be released publicly on acceptance; Appendix B gives the command that recomputes each reported table from them.

8 Limitations

- POS labels are the source dictionary's, verified but not independently re-annotated. The agreement coefficients in Section 3.3 describe a 500-item subset that is alphabetical and drawn from no verb entries, annotated by two of the authors rather than by annotators external to the work, and compiled without a third adjudicator. They are not an estimate for the corpus, and a stratified re-annotation covering verbs, by annotators outside the author group, would be needed for that.

- No edit history survives for the annotation. The annotators exchanged their sheets as messaging attachments, and those attachments have since expired, so the files that would carry a version history are no longer retrievable. The labels are intact in the released workbook; what cannot be evidenced is the order and timing in which they were entered.

- Morphosyntactic labels differ from the POS label on 183 of 5,783 gold rows, of which 88 carry gender, number or plurality.

- Lexical alignment gold is 38% positional fallback; Section 5.4 is not a result.

- Entries are dictionary headwords, not running text; performance here does not predict sentence-level performance.

- The model set cannot separate architecture from instruction-tuning. An instruction-tuned seq2seq model (`flan-t5`, `mt0`) would be needed. It is also dated: none of the eight exceeds 7B parameters, and three are span-denoising checkpoints that cannot follow an instruction at all. A later partial run on newer and larger models (Section 4.1) scores above our best model on POS, which we report rather than leave in the logs, though the ceiling result means a higher score on this task is not evidence of Tigrinya competence.

- Decoding was each checkpoint's own default rather than a uniform greedy setting, so qwen-7b was sampled at temperature 0.7, and no chat template was applied to the instruction-tuned models. Single run, no seed averaging.

- Both tagging tasks are substantially solvable without Tigrinya: an English-only oracle reaches 96.49 and 95.86, and under 5% of headwords are ambiguous given the gloss. This is a property of the task design, not of the models, and it bounds what any result on these tasks can mean. A task that withheld the gloss, or that drew its items from the ambiguous subset, would measure something the English does not already determine; we have not run that experiment.

- The ceiling is computed from the evaluation set itself, so it is an oracle rather than a system: it knows the label distribution of each headword. It bounds what the English makes available on these items, not what an English-only system would achieve on unseen data.

Ethics statement

The annotators are two of this paper's authors, both native speakers of Tigrinya, who annotated as part of their own research and received no separate compensation; no external or crowd workers were engaged, and no personal data was collected. The source material is a published bilingual dictionary and the evaluation items are dictionary headwords, which carry no information about individuals.

Each model was run once, with no seed averaging, under the decoding settings of Section 4.1. Evaluation used one node with four NVIDIA A100 80GB GPUs. The reported results come from two jobs: 66.3 hours wall clock for part-of-speech tagging, morphosyntax and lexical alignment over the eight models, and 13.9 hours for the translation rerun, about 321 GPU-hours together. The partial run on the newer roster (Section 4.1) consumed a further 288 GPU-hours before reaching its time limit. Every number in this paper is then recomputed from the saved outputs on CPU in under a minute, which is the point of releasing the generations.

chrF and character BLEU are computed with NLTK rather than sacreBLEU, so our chrF values are not directly comparable to sacreBLEU figures reported elsewhere; every comparison we draw is within this paper, between outputs scored by the same implementation, including the NLLB comparison. Package versions are listed in the released requirements file.

A risk specific to this work: a benchmark that reports high accuracy on a low-resource language can be cited as evidence that the language is served when it is not, which may divert effort from building the resources it actually needs. That is the failure this paper documents in its own earlier numbers, and it is why we report the task ceiling alongside every score.

References

Ahmed Abdelali et al. 2023. LAraBench: Benchmarking arabic AI with large language models. *arXiv preprint arXiv:2305.14982*.

Ife Adebara, Hawau Olamide Toyin, Nahom Tesfu Ghebremichael, AbdelRahim Elmadany, and Muhammad Abdul-Mageed. 2025. Where are we? evaluating LLM performance on african languages. *arXiv preprint arXiv:2502.19582*.

Ebtesam Almazrouei et al. 2023. The Falcon series of open language models. *arXiv preprint arXiv:2311.16867*.

Khalid Alnajjar, Mika Hämäläinen, Jack Rueter, and Niko Partanen. 2020. Ve'rdd. narrowing the gap between paper dictionaries, low-resource NLP and community involvement. *arXiv preprint arXiv:2012.02578*.

Jinze Bai et al. 2023. Qwen technical report. *arXiv preprint arXiv:2309.16609*.

Lucas Bandarkar et al. 2024. The Belebele benchmark: a parallel reading comprehension dataset in 122 language variants. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*.

Terra Blevins and Luke Zettlemoyer. 2022. Language contamination helps explain the cross-lingual capabilities of English pretrained models. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 3563–3574. Association for Computational Linguistics.

Jacob Cohen. 1960. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46.

Alexis Conneau et al. 2020. Unsupervised cross-lingual representation learning at scale. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*.

Cheikh M. Bamba Dione et al. 2023. MasakhaPOS: Part-of-speech tagging for typologically diverse african languages. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*.

Fitsum Gaim and Jong C. Park. 2026. Natural language processing for tigrinya: Current state and future directions. *arXiv preprint arXiv:2507.17974*.

Fitsum Gaim, Wonsuk Yang, Hancheol Park, and Jong C. Park. 2023. Question-answering in a low-resourced language: Benchmark dataset and models for Tigrinya. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11857–11870. Association for Computational Linguistics.

Gemma Team, Google DeepMind. 2024. Gemma: Open models based on Gemini research and technology. *arXiv preprint arXiv:2403.08295*.

Naman Goyal et al. 2022. The FLORES-101 evaluation benchmark for low-resource and multilingual machine translation. *Transactions of the Association for Computational Linguistics*, 10:522–538.

Suchin Gururangan et al. 2018. Annotation artifacts in natural language inference data. In *Proceedings of NAACL-HLT*.

Amr Hendy et al. 2023. How good are GPT models at machine translation? a comprehensive evaluation. *arXiv preprint arXiv:2302.09210*.

Albert Q. Jiang et al. 2023. Mistral 7B. *arXiv preprint arXiv:2310.06825*.

Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. 2020. The state and fate of linguistic diversity and inclusion in the NLP world. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6282–6293.

Katharina Kann, Ophelie Lacroix, and Anders Søgaard. 2020. Weakly supervised POS taggers perform poorly on truly low-resource languages. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Ayoub Kirouane and Christos Petrocheilos. 2026. Thinking in a low-resource language: What SFT builds, what RL fixes, what accuracy cannot see. *arXiv preprint arXiv:2608.17744*.

Edward Loper and Steven Bird. 2002. NLTK: The natural language toolkit. In *Proceedings of the ACL Workshop on Effective Tools and Methodologies for Teaching Natural Language Processing and Computational Linguistics*.

R. Thomas McCoy, Ellie Pavlick, and Tal Linzen. 2019. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*.

Timothy Niven and Hung-Yu Kao. 2019. Probing neural network comprehension of natural language arguments. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*.

NLLB Team et al. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.

Jessica Ojo, Odunayo Ogundepo, Akintunde Oladipo, Kelechi Ogueji, Jimmy Lin, Pontus Stenetorp, and David Ifeoluwa Adelani. 2025. AfroBench: How good are large language models on African languages? In *Findings of the Association for Computational Linguistics: ACL 2025*. Association for Computational Linguistics.

Alp Öktem, Mirko Plitt, and Grace Tang. 2020. Tigrinya neural machine translation with transfer learning for humanitarian response. In *AfricaNLP Workshop*.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318.

Adam Poliak, Jason Naradowsky, Aparajita Haldar, Rachel Rudinger, and Benjamin Van Durme. 2018. Hypothesis only baselines in natural language inference. In *Proceedings of the Seventh Joint Conference on Lexical and Computational Semantics*.

Maja Popović. 2015. chrF: character n-gram F-score for automatic MT evaluation. In *Proceedings of the Tenth Workshop on Statistical Machine Translation*, pages 392–395.

Matt Post. 2018. A call for clarity in reporting BLEU scores. In *Proceedings of the Third Conference on Machine Translation*, pages 186–191.

Anka Reuel et al. 2024. BetterBench: Assessing AI benchmarks, uncovering issues, and establishing best practices. *arXiv preprint arXiv:2411.12990*.

Nathaniel R. Robinson, Perez Ogayo, David R. Mortensen, and Graham Neubig. 2023. ChatGPT MT: Competitive for high- (but not low-) resource languages. *arXiv preprint arXiv:2309.07423*.

Zhi Rui Tam, Cheng-Kuang Wu, Yi-Lin Tsai, Chieh-Yen Lin, Hung-yi Lee, and Yun-Nung Chen. 2024. Let me speak freely? a study on the impact of format restrictions on performance of large language models. *arXiv preprint arXiv:2408.02442*.

Hailay Teklehaymanot, Dren Fazlija, Niloy Ganguly, Gourab K. Patro, and Wolfgang Nejdl. 2024. TiGQA: An expert-annotated question-answering dataset in tigrinya. *arXiv preprint arXiv:2404.17194*.

Hailay Kidu Teklehaymanot, Wolfgang Nejdl, and Gebrearegawi Gebremariam. 2026. LLM probe: Evaluating LLMs for low-resource languages. In *Proceedings of Shaping Multilingual, Multimodal AI for the Social Sciences and Humanities (LLMs4SSH) @ LREC 2026*, pages 224–234, Palma de Mallorca, Spain. ELRA Language Resources Association (ELRA).

Abrhalei Tela, Abraham Woubie, and Ville Hautamäki. 2020. Transferring monolingual model to low-resource language: The case of tigrinya. *arXiv preprint arXiv:2006.07698*.

Senait Gebremichael Tesfagergish and Jurgita Kapočiūtė-Dzikienė. 2020. Part-of-speech tagging via deep neural networks for Northern-Ethiopic languages. *Information Technology and Control*, 49(4):482–494.

Atnafu Lambebo Tonja et al. 2023. Natural language processing in ethiopian languages: Current state, challenges, and opportunities. *arXiv preprint arXiv:2303.14406*.

Union of International Democrats. 2015. Tigrinya–english dictionary. Digitised edition. `https://uidswansea.com/wp-content/uploads/2015/03/tigrinya-english-dictionary.pdf`.

Kasun Wickramasinghe and Nisansa de Silva. 2023. Sinhala-english parallel word dictionary dataset. In *Proceedings of the International Conference on Industrial and Information Systems (ICIIS)*.

Thomas Wolf et al. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of EMNLP: System Demonstrations*, pages 38–45.

Ka Wong, Praveen Paritosh, and Lora Aroyo. 2021. Cross-replication reliability — an empirical approach to interpreting inter-rater reliability. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics*.

Linting Xue et al. 2021. mT5: A massively multilingual pre-trained text-to-text transformer. In *Proceedings of NAACL-HLT*.

Linting Xue et al. 2022. ByT5: Towards a token-free future with pre-trained byte-to-byte models. *Transactions of the Association for Computational Linguistics*, 10:291–306.

Tony Z. Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. 2021. Calibrate before use: Improving few-shot performance of language models. In *Proceedings of the 38th International Conference on Machine Learning*, pages 12697–12706.

Wenhao Zhu et al. 2023. Multilingual machine translation with large language models: Empirical results and analysis. *arXiv preprint arXiv:2304.04675*.

A Annotation records in detail

What the released workbook does not carry is the history of how it was filled. The annotators exchanged their sheets as messaging attachments, and

Dimension	κ	Observed
Part of speech	0.9076	0.9500
Gender	0.8079	0.9240
Number	0.6762	0.9280
Category agreement	0.5912	0.9000
Lexical alignment	0.8487	0.9480

Table 5: Inter-annotator agreement on the 500-item subset, blanks counted as disagreements. All five dimensions are computed over all 500 items.

those attachments have since expired, so the files that would carry an edit history are no longer retrievable. The labels themselves are intact and are what the workbook contains; what is missing is the order and timing in which they were entered. We note this because the guide was applied unevenly in ways the figures below expose, and a record of the process would have shown whether that reflects a change of convention partway through.

The five dimensions are not of one kind, and the guide says so. Its instruction is to "verify and annotate" the dictionary entries: gender, number, category agreement and lexical alignment are assigned from scratch against the definitions the guide gives, while the part-of-speech label arrives prefilled from the source dictionary and is verified. The guide treats it as given material elsewhere too, defining category agreement as whether the Tigrinya entry matches "the English item and its POS label".

The two annotators used that latitude very differently. Annotator 1 corrected the dictionary's part of speech on 25 of 500 items; Annotator 2 corrected it on none, letting the source label stand everywhere. All 25 part-of-speech disagreements are therefore of one shape: one annotator exercising the verification the guide asks for, and the other accepting the dictionary.

Three properties of this subset bound what the coefficients support.

The compiled sheet is not an independent third judgement. This follows from how it was produced, and the records bear it out. The two annotators differ on 28 cells in total: 25 part of speech, one category agreement and two lexical alignment. On the 25 part-of-speech items the compiled sheet reproduces Annotator 2 on all 25 and Annotator 1 on none; on the other three it reproduces Annotator 1. **On none of the 28 does it record a label that neither annotator assigned.** Since Annotator 2's part-of-speech column is the source dictionary's throughout, the compilation rejected all 25 of Annotator 1's proposed corrections and deferred to the dictionary in every case. It selects between the two existing columns rather than adding a judgement of its own, so agreement with it is not evidence about either annotator, and it cannot serve as an adjudicated gold standard.

A third annotator would not repair this. The coefficients in Table 5 are computed between the two annotation columns and would be unchanged by a third. The divergence between those columns is in any case not a matter of conflicting labels: on gender and number the annotators never differ on an item both labelled, and what separates them is how often each left a cell empty. What the subset would need is a fresh annotation, stratified over the categories and including verbs, by annotators outside the author group; we report that as future work in Section 8 rather than adjudicating the present records after the fact.

Agreement on filled labels is near-total. Where both annotators assigned a gender or number value, they never differ — 0 disagreements across 420 and 428 items. The divergence between them is entirely in coverage, not in choice of label, which is why κ falls as far as it does once blanks count.

The subset is not a random sample. Tracing each item to its source sheet shows the 500 are the alphabetical head of each category: all 9 prepositions, all 10 pronouns and all 6 interjections, then 305 adjectives, 150 nouns and 20 adverbs from the tops of those sheets. The corpus is 54% noun and 25% verb; this subset is 61% adjective and **is drawn from no verb entries at all**. The only part-of-speech cells reading `Verb` anywhere in the records are seven of Annotator 1's corrections to noun headwords. The coefficients therefore describe agreement on this subset and are not an estimate for the corpus. Establishing one requires a stratified re-annotation covering verbs, which we leave to future work (Section 8).

B Reproducing each table

The supplementary material also contains the raw generation for every item, stored per task and per model, so any scoring rule other than the three reported here can be applied to the same outputs without re-running the models.

`$ROSTER` denotes the eight evaluated models,

Reported in	Command (in `scripts/`)	Artifact read
§3.1 counts	`build_merged_eval_set.py --dry-run --verify`	`Combined_POS_Lexicon.csv`
§3.1 5,701 set	`build_sense_split_eval_set.py --verify`	`*_sense_split.json`
§3.3 agreement	`compute_iaa.py`	`*_Annotated.xlsx`
§4.2 ceiling	`task_ceiling.py`	`*_sense_split.json`
§5.1, §5.2	`rescore_tasks.py --models $ROSTER`	`rescored_2026-09-28.json`
§5.3 LLMs	`compute_bleu.py`	`translation_fidelity_bleu.json`
§5.3 NLLB†	`probe_nllb_translation.py`	`nllb_probe_*.json`
§5.3 few-shot†	`probe_fewshot_translation.py`	`fewshot_probe_*.json`

Table 6: Each reported table, the command that regenerates it from the released artifacts, and the artifact it reads. Every row but the two marked † is computed from the saved generations and needs no model: those two run a model, NLLB-200 and gemma-7b respectively, and we release their outputs so the reported numbers can be checked without doing so.

which the scoring script takes as an explicit argument so that a reported table is reproduced over exactly that set; the task scripts default to the same roster, so a full re-run reproduces the published labels rather than the newer ones.

C Dataset derivation

This appendix records the row-level derivation summarised in Section 3.1. Every count is reproducible from the released code: `build_merged_eval_set.py --dry-run --verify` rebuilds the gold files from the source CSV and compares them against what is released, and `build_sense_split_eval_set.py --verify` does the same for the 5,701-item set.

Source and provenance. The digitised file `Combined_POS_Lexicon.csv` holds 7,234 rows: 3,587 English→Tigrinya entries followed by 3,647 Tigrinya→English entries. It is a flattening of the working annotation workbook, whose eleven part-of-speech sheets hold the same 7,234 rows with the same per-category counts (3,929 noun, 1,784 verb, 993 adjective, 194 adverb, and so on). The flattening lifts the inline gender and number markers that the workbook keeps inside the Tigrinya field `(nf)` ወካሲት, ከሳሲት out into the label column, which is the origin of the finer categories `(nm) noun masculine`, `(nf) noun feminine` and `(npl) noun plural`, which 107 export rows carry. Compared as multisets of (English, Tigrinya) pairs, the two files differ on 247 rows; stripping the parenthesised markers from both reconciles all but 12 of those, so the markers account for the difference without the 247 being the marked rows themselves. Twenty-four rows of the gold files still contain an inline marker, including translation references such as `(af)` ኣደናቒት: these are residual and should be stripped, and we note them rather than correct them silently so that the released gold matches the outputs the models were scored on. The direction swap is present in the workbook as well, in 3,635 of its 7,234 rows (50.2%), so it originates in digitisation rather than in the export.

7,234 counts rows, not independent annotations. Of the 3,646 unique reverse-direction pairs, 1,448 (39.7%) also occur in the forward block.

From 7,234 to 5,783. Merging the two directions deduplicates on the (English, Tigrinya, features) triple rather than on the pair alone, so that distinct senses of one form survive: *estimate* → ግምት is kept as both noun and verb, and *grocer* → በዓል ድኳን as both `noun` and `noun, masculine`. Expanding comma-separated senses gives 5,864 atomic pairs.

From 5,783 to 5,775. Each task script applies its own pair-level deduplication when loading the gold, dropping 7 duplicate (English, Tigrinya) pairs and 1 row with no English side.

From 5,775 to 5,701. The two tagging tasks were run against a gold file in which each multi-sense entry is represented by its first sense: (*a little*, ንእሽቶይ, ቁሩብ, ውሕድ) was evaluated as (*a little*, ንእሽቶይ). That intermediate file was not originally released, so the task scripts as published would evaluate 5,775 items rather than the 5,701 behind Sections 5.1 and 5.2. We reconstruct it from the released gold and verify the result row-for-row against the saved model outputs: 5,701 items, no row missing, none extra, and no label mismatch. The reconstructed file is released alongside the gold.