

# Class 14:

Hailey Heirigs (PID: A16962278)

## Table of contents

<b>Required packages</b>	<b>2</b>
<b>Data import</b>	<b>2</b>
<b>Remove zero count genes</b>	<b>3</b>
<b>Set up DESeq object for analysis</b>	<b>4</b>
<b>Run DESeq analysis</b>	<b>5</b>
<b>Extract the results</b>	<b>5</b>
<b>Add gene annotation</b>	<b>6</b>
<b>Save my results to a CSV file</b>	<b>7</b>
<b>Result visualization</b>	<b>7</b>
<b>Pathway analysis</b>	<b>9</b>
<b>Gene Ontology (GO)</b>	<b>13</b>
<b>Reactome Analysis</b>	<b>14</b>

Here we will perform a complete RNASeq analysis from counts to pathways and biological interpretation.

The data for hands-on session comes from GEO entry: GSE37704, which is associated with the following publication:

Trapnell C, Hendrickson DG, Sauvageau M, Goff L et al. "Differential analysis of gene regulation at transcript resolution with RNA-seq". Nat Biotechnol 2013 Jan;31(1):46-53. PMID:

23222703 The authors report on differential analysis of lung fibroblasts in response to loss of the developmental transcription factor HOXA1.

## Required packages

```
library(DESeq2)
library(AnnotationDbi)
library(org.Hs.eg.db)
library(pathview)
library(gage)
library(gageData)
```

## Data import

```
colData <- read.csv("GSE37704_metadata.csv", row.names = 1)
countData <- read.csv("GSE37704_featurecounts.csv", row.names = 1)
```

```
head(colData)
```

	condition
SRR493366	control_sirna
SRR493367	control_sirna
SRR493368	control_sirna
SRR493369	hoxa1_kd
SRR493370	hoxa1_kd
SRR493371	hoxa1_kd

```
head(countData)
```

	length	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370
ENSG00000186092	918	0	0	0	0	0
ENSG00000279928	718	0	0	0	0	0
ENSG00000279457	1982	23	28	29	29	28
ENSG00000278566	939	0	0	0	0	0
ENSG00000273547	939	0	0	0	0	0
ENSG00000187634	3214	124	123	205	207	212

	SRR493371
ENSG00000186092	0
ENSG00000279928	0
ENSG00000279457	46
ENSG00000278566	0
ENSG00000273547	0
ENSG00000187634	258

Check the correspondance of colData rows and countData columns.

```
rownames(colData)
```

```
[1] "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370" "SRR493371"
```

Remove the troublesome first column so we match the metadata

```
counts <- countData[, -1]
```

```
head(counts)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

```
all( rownames(colData) == colnames(counts) )
```

```
[1] TRUE
```

## Remove zero count genes

We will have rows in `counts` for genes that we can not say anything about because they have zero expression in the particular tissue we are looking at.

```
head(counts)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

If the `rowSums()` is zero, then give a gene (i.e. row) has no count data and we should exclude these genes from further consideration.

```
to.keep <- rowSums(counts) != 0  
cleancounts <- counts[to.keep,]
```

Q. How many genes do we have left?

```
nrow(cleancounts)
```

```
[1] 15975
```

## Set up DESeq object for analysis

```
dds <- DESeqDataSetFromMatrix(countData = cleancounts,  
                              colData = colData,  
                              design = ~condition)
```

Warning in `DESeqDataSet(se, design = design, ignoreRank)`: some variables in design formula are characters, converting to factors

## Run DESeq analysis

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

## Extract the results

```
res <- results(dds)
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj				
	<numeric>				
ENSG00000279457	6.86555e-01				
ENSG00000187634	5.15718e-03				

```
ENSG00000188976 1.76549e-35
ENSG00000187961 1.13413e-07
ENSG00000187583 9.19031e-01
ENSG00000187642 4.03379e-01
```

## Add gene annotation

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
res$symbol = mapIds(org.Hs.eg.db,
                     keys=rownames(res),
                     keytype="ENSEMBL",
                     column="SYMBOL",
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$name <- mapIds(x=org.Hs.eg.db,
                  keys=rownames(res),
                  keytype = "ENSEMBL",
                  column = "GENENAME")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez <- mapIds(x=org.Hs.eg.db,
                    keys=rownames(res),
                    keytype = "ENSEMBL",
                    column = "ENTREZID")
```

'select()' returned 1:many mapping between keys and columns

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj	symbol		name	entrez
	<numeric>	<character>		<character>	<character>
ENSG00000279457	6.86555e-01	NA		NA	NA
ENSG00000187634	5.15718e-03	SAMD11	sterile alpha motif ..		148398
ENSG00000188976	1.76549e-35	NOC2L	NOC2 like nucleolar ..		26155
ENSG00000187961	1.13413e-07	KLHL17	kelch like family me..		339451
ENSG00000187583	9.19031e-01	PLEKHN1	pleckstrin homology ..		84069
ENSG00000187642	4.03379e-01	PERM1	PPARGC1 and ESRR ind..		84808

## Save my results to a CSV file


```
write.csv(res, file="my_id_results.csv")
```

## Result visualization

```
mycols <- rep("grey", nrow(res))
mycols [ res$log2FoldChange <= -2 ] <- "blue"
mycols [ res$log2FoldChange >= +2 ] <- "blue"

mycols [ res$padj >= 0.05 ] <- "grey"
#mycols
plot(res$log2FoldChange, -log(res$padj), col=mycols)
```

```
abline(v=-2, col="red")
abline(v=+2, col="red")
abline(h=-log(0.005), col="red")
```




```
library(ggplot2)

ggplot(res) +
  aes(log2FoldChange, -log(padj)) +
  geom_point(col=mycols) +
  geom_vline(xintercept = c(-2, +2)) +
  geom_hline(yintercept = -log(0.05)) +
  theme_bw() +
  labs(x="Log2 Fold-Change",
       y="-log(Adjusted P-value)")
```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).





## Pathway analysis

```
library(gage)
library(gageData)
library(pathview)
```

```
data(kegg.sets.hs)
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways
head(kegg.sets.hs, 3)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
```

```

[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"

```

```
$`hsa00230 Purine metabolism`
```

```

[1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"
[9] "108" "10846" "109" "111" "11128" "11164" "112" "113"
[17] "114" "115" "122481" "122622" "124583" "132" "158" "159"
[25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"
[33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
[41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"
[49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"
[57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"
[65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"
[73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"
[81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"
[89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"
[97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"
[105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
[113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"
[121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"
[129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"
[137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"
[145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"
[153] "9061" "93034" "953" "9533" "954" "955" "956" "957"
[161] "9583" "9615"

```

```

foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)

```

```

      <NA>      148398      26155      339451      84069      84808
0.17925708 0.42645712 -0.69272046 0.72975561 0.04057653 0.54281049

```

```

# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)

```

```
attributes(keggres)
```

```
$names
```

```
[1] "greater" "less"    "stats"
```

```
# Look at the first few down (less) pathways
```

```
head(keggres$less)
```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013 RNA transport	1.246882e-03	-3.059466	1.246882e-03
hsa03440 Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03

	q.val	set.size	exp1
hsa04110 Cell cycle	0.001448312	121	8.995727e-06
hsa03030 DNA replication	0.007586381	36	9.424076e-05
hsa03013 RNA transport	0.066915974	144	1.246882e-03
hsa03440 Homologous recombination	0.121861535	28	3.066756e-03
hsa04114 Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14

Info: Writing image file hsa04110.pathview.png

```
# A different PDF based output of the same data
```

```
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

'select()' returned 1:1 mapping between keys and columns

Warning: reconcile groups sharing member nodes!

```
      [,1] [,2]
[1,] "9"  "300"
[2,] "9"  "306"
```

Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14

Info: Writing image file hsa04110.pathview.pdf

```
## Focus on top 5 upregulated pathways here for demo purposes only
keggrespathways <- rownames(keggres$greater)[1:5]

# Extract the 8 character long IDs part of each string
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
[1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14

Info: Writing image file hsa04640.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14

Info: Writing image file hsa04630.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14

Info: Writing image file hsa00140.pathview.png

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14
```

```
Info: Writing image file hsa04142.pathview.png
```

```
'select()' returned 1:1 mapping between keys and columns
```

```
Info: Working in directory /Users/haileyheirigs/Desktop/BIMM143.r-work/class14
```

```
Info: Writing image file hsa04330.pathview.png
```

## Gene Ontology (GO)

```
data(go.sets.hs)
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)

lapply(gobpres, head)
```

```
$greater
```

	p.geomean	stat.mean	p.val
GO:0007156 homophilic cell adhesion	8.519724e-05	3.824205	8.519724e-05
GO:0002009 morphogenesis of an epithelium	1.396681e-04	3.653886	1.396681e-04
GO:0048729 tissue morphogenesis	1.432451e-04	3.643242	1.432451e-04
GO:0007610 behavior	1.925222e-04	3.565432	1.925222e-04
GO:0060562 epithelial tube morphogenesis	5.932837e-04	3.261376	5.932837e-04
GO:0035295 tube development	5.953254e-04	3.253665	5.953254e-04

	q.val	set.size	exp1
GO:0007156 homophilic cell adhesion	0.1951953	113	8.519724e-05
GO:0002009 morphogenesis of an epithelium	0.1951953	339	1.396681e-04
GO:0048729 tissue morphogenesis	0.1951953	424	1.432451e-04
GO:0007610 behavior	0.1967577	426	1.925222e-04
GO:0060562 epithelial tube morphogenesis	0.3565320	257	5.932837e-04

G0:0035295	tube development	0.3565320	391	5.953254e-04
------------	------------------	-----------	-----	--------------

\$less

		p.geomean	stat.mean	p.val
G0:0048285	organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280	nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067	mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059	chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236	mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10

		q.val	set.size	expl
G0:0048285	organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280	nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067	mitosis	5.841698e-12	352	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059	chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236	mitotic prometaphase	1.178402e-07	84	1.729553e-10

\$stats

		stat.mean	expl
G0:0007156	homophilic cell adhesion	3.824205	3.824205
G0:0002009	morphogenesis of an epithelium	3.653886	3.653886
G0:0048729	tissue morphogenesis	3.643242	3.643242
G0:0007610	behavior	3.565432	3.565432
G0:0060562	epithelial tube morphogenesis	3.261376	3.261376
G0:0035295	tube development	3.253665	3.253665

## Reactome Analysis

We need to make a little file of our significant genes that we can upload to the reactome webpage:

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=
```

Then, to perform pathway analysis online go to the Reactome website (<https://reactome.org/PathwayBrowser/#>). Select “choose file” to upload your significant gene list. Then, select the parameters “Project to Humans”, then click “Analyze”.

