countries

code 🔑	int
name	varchar
continent_name	varchar

addresses

country_code	int
id 🔑	int
state	varchar
city	varchar
zipcode	int
street1	varchar
street2	varchar
phone_number	int
plus_code	varchar
(country_code, phone_number)	

phone_numbers

country_code 🔑	int
number 🔑	int
(country_code, number)	

users

id 🔑	int
full_name	varchar
email	varchar
created_at	datetime
billing_address	int
role	user_role E

orders

id 🔑	int
user_id	int NN
status	varchar
created_at	timestamp

order_items

order_id	int
product_id	int
quantity	int

stores

id 🔑	int
address 🔑	int
merchant_name	varchar
established_at	datetime
admin_id	int
(id, address)	

store_periods

id 🔑	int
store_id	int
address	int
start_date	datetime
end_date	datetime
(store_id, address)	

products

id 🔑	int
name	varchar
store_id	int NN
price	int NN
weight	int
size	int
restock_threshold	int
status	product_status E
created_at	datetime

product_tags

id 🔑	int
name	varchar

product_expiration

id 🔑	int
production_date	datetime
expiration_date	datetime

```
Enum user_role {
    standard
    business
}



Enum product_status {
    out_of_stock
    in_stock
    running_low [note: "less than products.restock_threshold"]
}



Enum order_status {
    initial
    in_process
    complete
    cancelled
}
```