

Regular Lossy Functions and Applications in Leakage-Resilient Cryptography

Yu Chen¹ Baodong Qin² Haiyang Xue¹

¹SKLOIS, IIE, Chinese Academy of Sciences

²Xi'an University of Posts and Telecommunication

CT-RSA 2018

April 20th, 2018

Outline

- 1 Backgrounds
- 2 Regular Lossy Functions
- 3 Constructions of ABO RLFs
 - Concrete Construction
 - Generic Construction
- 4 Applications of RLFs
 - Leakage-Resilient OWFs
 - Leakage-Resilient MAC
 - Leakage-Resilient CCA-secure KEM

Outline

- 1 Backgrounds
- 2 Regular Lossy Functions
- 3 Constructions of ABO RLFs
 - Concrete Construction
 - Generic Construction
- 4 Applications of RLFs
 - Leakage-Resilient OWFs
 - Leakage-Resilient MAC
 - Leakage-Resilient CCA-secure KEM


Lossy Trapdoor Functions



Lossy object *indistinguishable* from original


STOC 2008 Peikert and Waters: Lossy Trapdoor Functions and Their Applications

Lossy TDFs



Extension of LTFs: ABO LTFs

- $\text{Gen}(\lambda, b^*)$ has extra input: branch $b^* \in B$.




$$f_{ek, b}(\cdot) = \begin{cases} \text{lossy} & b = b^* \\ \text{injective and invertible} & b \neq b^* \end{cases}$$

LTFs \Leftrightarrow ABO LTFs


Constructions and Applications

(ABO)-LTF


Constructions and Applications




Constructions and Applications



Constructions and Applications



Constructions and Applications



Motivations

In all applications of LTF:

- normal mode: **injective+trapdoor** fulfill functionality
- lossy mode: establish security

Motivations

In all applications of LTF:

- normal mode: **injective+trapdoor** fulfill functionality
- lossy mode: establish security

However, the full power of LTF is

- expensive: large key size/high computation cost
- overkill: some applications (e.g., injective OWF, CRHF) do not require a trapdoor, but only **normal \approx_c lossy**

A central goal in cryptography is to base cryptosystems on primitives that are as weak as possible.

- Peikert and Waters conjectured “the weaker notion LF could be achieved more simply and efficiently than LTF”.
- They left the investigation of this question as an interesting problem.

A central goal in cryptography is to base cryptosystems on primitives that are as weak as possible.

- Peikert and Waters conjectured “the weaker notion LF could be achieved more simply and efficiently than LTF”.
- They left the investigation of this question as an interesting problem.

We are motivated to consider the following problems:

How to realize LF efficiently?

Are there any other applications of LF?

Can we further weaken the notion of LF?

Outline

- 1 Backgrounds
- 2 Regular Lossy Functions**
- 3 Constructions of ABO RLFs
 - Concrete Construction
 - Generic Construction
- 4 Applications of RLFs
 - Leakage-Resilient OWFs
 - Leakage-Resilient MAC
 - Leakage-Resilient CCA-secure KEM

A Simple But Important Observation

When trapdoor is not required for normal mode, the injective property may also be unnecessary.

A Simple But Important Observation

When trapdoor is not required for normal mode, the injective property may also be unnecessary.

This observation leads to our further relaxation of LFs

Regular Lossy Functions

A Simple But Important Observation

When trapdoor is not required for normal mode, the injective property may also be unnecessary.

This observation leads to our further relaxation of LFs

Regular Lossy Functions

Intuition: the output should preserves much *min-entropy* of input

- In RLFs, functions of normal mode could also be lossy, but has to lose in a regular manner.

A Simple But Important Observation

When trapdoor is not required for normal mode, the injective property may also be unnecessary.

This observation leads to our further relaxation of LFs

Regular Lossy Functions


Intuition: the output should preserves much *min-entropy* of input

- In RLFs, functions of normal mode could also be lossy, but has to lose in a regular manner.

Definition 1

f is v -to-1 (or v -regular) if $\max_y |f^{-1}(y)| \leq v$.

Regular Lossy Functions



- When $v = 1$, RLFs specialize to standard LFs

Remarks

Why we choose **regularity** but not **image size** to capture normal mode?

Remarks

Why we choose **regularity** but not **image size** to capture normal mode?

- **image size** is a *global* characterization, which only suffices to give the lower bound of $\tilde{H}_\infty(x|f(x))$ by the chain rule.

Remarks

Why we choose **regularity** but not **image size** to capture normal mode?

- **image size** is a *global* characterization, which only suffices to give the lower bound of $\tilde{H}_\infty(x|f(x))$ by the chain rule.
- In contrast, **regularity** is a *local* characterization, which suffices to give the lower bound of $H_\infty(f(x))$.

Remarks

Why we choose **regularity** but not **image size** to capture normal mode?

- **image size** is a *global* characterization, which only suffices to give the lower bound of $\tilde{H}_\infty(x|f(x))$ by the chain rule.
- In contrast, **regularity** is a *local* characterization, which suffices to give the lower bound of $H_\infty(f(x))$.

The following technical lemma establishes the relation between the min-entropy of x and $f(x)$:


Lemma 2

Let f be a v -to-1 function and x be a random variable over the domain:

$$H_\infty(f(x)) \geq H_\infty(x) - \log v$$

All-But-One Regular Lossy Functions

- $\text{Gen}(\lambda, b^*)$ has an extra input: branch $b^* \in B$.



$$f_{ek,b}(\cdot) = \begin{cases} \text{lossy} & b = b^* \\ \text{regular} & b \neq b^* \end{cases}$$

$$\text{RLF} \Leftrightarrow \text{ABO-RLF}$$

Outline

- 1 Backgrounds
- 2 Regular Lossy Functions
- 3 Constructions of ABO RLFs**
 - Concrete Construction
 - Generic Construction
- 4 Applications of RLFs
 - Leakage-Resilient OWFs
 - Leakage-Resilient MAC
 - Leakage-Resilient CCA-secure KEM

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$x \in \mathbb{Z}_2^n$$

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$x \in \mathbb{Z}_2^n$$

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}}$$

$$x \in \mathbb{Z}_2^n \quad \begin{pmatrix} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{pmatrix}$$

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}}$$

$$x \in \mathbb{Z}_2^n \quad \begin{pmatrix} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{pmatrix}$$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}}$$

$$x \in \mathbb{Z}_2^n \quad \begin{pmatrix} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{pmatrix} \xrightarrow{\downarrow} -b^*(\mathbf{e}_1, \dots, \mathbf{e}_m)$$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}}$$

$$x \in \mathbb{Z}_2^n \times \left(\begin{array}{cccc} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{array} \right) \xrightarrow{-b^*(\mathbf{e}_1, \dots, \mathbf{e}_m) + b(\mathbf{e}_1, \dots, \mathbf{e}_m)} y \in \mathbb{G}^m$$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

Concrete Construction from the DDH Assumption

Matrix approach for ABO-LTFs $f_{ek,b}(x) \rightarrow y$ due to Peikert and Waters

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}}$$

$$x \in \mathbb{Z}_2^n \times \left(\begin{array}{cccc} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{array} \right) \xrightarrow{\text{GenConceal}(n, m)} -b^*(\mathbf{e}_1, \dots, \mathbf{e}_m) + b(\mathbf{e}_1, \dots, \mathbf{e}_m) \rightarrow y \in \mathbb{G}^m$$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

To ensure invertible property

- input space is restricted to \mathbb{Z}_2^n (a.k.a. $\{0, 1\}^n$)
- column dimension $m = n + 1$

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}}$$

$$x \in \mathbb{Z}_p^n \times \left(\begin{array}{cccc} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{array} \right) \xrightarrow{-b^*(\mathbf{e}_1, \dots, \mathbf{e}_m) + b(\mathbf{e}_1, \dots, \mathbf{e}_m)} y \in \mathbb{G}^m$$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

(ABO)-RLFs do not require invertible or even injective

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}} \quad m \ll n$$

$$x \in \mathbb{Z}_p^n \times \left(\begin{array}{cccc} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{array} \right) - b^*(\mathbf{e}_1, \dots, \mathbf{e}_m) + b(\mathbf{e}_1, \dots, \mathbf{e}_m) \rightarrow y \in \mathbb{G}^m$$

$\gg \mathbb{Z}_2^n$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

(ABO)-RLFs do not require invertible or even injective

$$\text{Gen}(\lambda, b^*) \rightarrow ek$$

$$\text{GenConceal}(n, m) = g^{\mathbf{V}} \quad m \ll n$$

$$x \in \mathbb{Z}_p^n \times \left(\begin{array}{cccc} g^{r_1 s_1} & g^{r_1 s_2} & \dots & g^{r_1 s_m} \\ g^{r_2 s_1} & g^{r_2 s_2} & \dots & g^{r_2 s_m} \\ \vdots & \vdots & \vdots & \vdots \\ g^{r_n s_1} & g^{r_n s_2} & \dots & g^{r_n s_m} \end{array} \right) \xrightarrow{-b^*(\mathbf{e}_1, \dots, \mathbf{e}_m) + b(\mathbf{e}_1, \dots, \mathbf{e}_m)} y \in \mathbb{G}^m$$

$\gg \mathbb{Z}_2^n$

$$\text{DDH} \Rightarrow \approx_c U_{\mathbb{G}^{n \times m}}$$

Lemma 3

The above construction constitutes $(p^{n-m}, \log p)$ -ABO-RLF.

- $\forall b \neq b^*, \text{rank}(\mathbf{Y} + b\mathbf{I}') = m$ and $\#(\text{solution space})$ for every $y \in \mathbb{G}^m$ is p^{n-m} .
- $b = b^*, \text{rank}(\mathbf{Y} + b\mathbf{I}') = 1$ and thus the image size is at most p .
- Pseudorandomness of $\mathbf{C} = g^{\mathbf{V}} \Rightarrow$ hidden lossy branch

Summary and Comparison

Our DDH construction applies to extended DDH \leadsto generalize DDH, QR, DCR

- We have a more efficient and direct DCR-based construction

ABO-LTF/RLF	Assump.	Input	Lossiness	Key	Efficiency
ABO-LTF[PW08]	DDH	2^n	$n - \log p$	$nm \mathbb{G} $	nm Add
ABO-RLF	DDH	p^n	$(n - 1) \log p$	$nm \mathbb{G} $	nm (Exp+Add)
ABO-LTF[FGK ⁺ 13]	DCR	N^2	$\log N$	$ \mathbb{Z}_{N^3}^* $	1 Exp
ABO-LF	$N^2/4$	DCR	$\log N$	$ \mathbb{Z}_{N^2}^* $	1 Exp

Generic Construction from HPS

Wee (Eurocrypt 2012): dual HPS \Rightarrow LTF

- dual HPS: HPS satisfying strong property
- No efficient ABO construction is known

Generic Construction from HPS

Wee (Eurocrypt 2012): dual HPS \Rightarrow LTF

- dual HPS: HPS satisfying strong property
- No efficient ABO construction is known

We show HPS \Rightarrow ABO-RLF


- exploit algebra property of the underlying SMP

(Algebra) Subset Membership Problem

Task: distinguish

$$U_X \approx_c U_L$$

Solution: $\{0, 1\}$




(Algebra) Subset Membership Problem

Task: distinguish

$$U_X \approx_c U_L$$

Solution: $\{0, 1\}$



Algebra SMP (mild & natural)


- X forms an Abelian group, L forms a subgroup of X
- The quotient group $H = X/L$ is cyclic with order $p = |X|/|L|$

(Algebra) Subset Membership Problem

Task: distinguish

$$U_X \approx_c U_L$$

Solution: $\{0, 1\}$



Algebra SMP (mild & natural)


- X forms an Abelian group, L forms a subgroup of X
- The quotient group $H = X/L$ is cyclic with order $p = |X|/|L|$

Algebraic properties \Rightarrow two useful facts

- 1 Let $\bar{a} = aL$ for some $a \in X \setminus L$ be a generator of H , the co-sets $(aL, 2aL, \dots, (p-1)aL, paL = L)$ constitute a partition of X .
- 2 For each $x \in L$, $ia + x \notin L$ for $1 \leq i < p$


Hash Proof System

- $L \subset X$ — language defined by R_L where SMP holds.
- HPS equips $L \subset X$ with **Gen**, **Priv**, **Pub**.



Hash Proof System

- $L \subset X$ — language defined by R_L where SMP holds.
- HPS equips $L \subset X$ with **Gen**, **Priv**, **Pub**.



Projective: $\forall x \in L$, $\Lambda_{sk}(x)$ is uniquely determined by x and $pk \leftarrow \alpha(sk)$.

ABO-RLF from HPS for ASMP

Let aL be a generator for $H = X/L$, we build ABO-RLF from HPS for ASMP as below:

- $\text{Gen}(\lambda, b^*)$: $(x, w) \leftarrow \text{SampYes}(\lambda)$, output $ek = -b^*a + x$
- $f_{ek,b}(sk)$: output $\alpha(sk) || \Lambda_{sk}(ek + ba)$

ABO-RLF from HPS for ASMP

Let aL be a generator for $H = X/L$, we build ABO-RLF from HPS for ASMP as below:

- $\text{Gen}(\lambda, b^*)$: $(x, w) \leftarrow \text{SampYes}(\lambda)$, output $ek = -b^*a + x$
- $f_{ek,b}(sk)$: output $\alpha(sk) || \Lambda_{sk}(ek + ba)$

Lemma 4

Assume $g_x(sk) := \alpha(sk) || \Lambda_{sk}(x)$ is v -regular for any $x \notin L$. The above construction is $(v, \log |\text{Img}\alpha|)$ -ABO-RLF under ASMP.

ABO-RLF from HPS for ASMP

Let aL be a generator for $H = X/L$, we build ABO-RLF from HPS for ASMP as below:

- $\text{Gen}(\lambda, b^*)$: $(x, w) \leftarrow \text{SampYes}(\lambda)$, output $ek = -b^*a + x$
- $f_{ek,b}(sk)$: output $\alpha(sk) || \Lambda_{sk}(ek + ba)$

Lemma 4

Assume $g_x(sk) := \alpha(sk) || \Lambda_{sk}(x)$ is v -regular for any $x \notin L$. The above construction is $(v, \log |\text{Img}\alpha|)$ -ABO-RLF under ASMP.

- $ek + ba = x + (b - b^*)a \notin L$ if $b \neq b^* \Rightarrow v$ -regular
- $ek + ba = x + (b - b^*)a \in L$ if $b = b^* \Rightarrow$ lossy by the projective property
- ASMP \Rightarrow Hidden lossy branch. For any $b_0^*, b_1^* \in \mathbb{Z}_p$:


$$(-b_0^*a + x) \approx_c (b_0^*a + u) \equiv (b_1^*a + u) \approx_c (b_1^*a + x)$$

where $u \xleftarrow{R} X$.


Outline

- 1 Backgrounds
- 2 Regular Lossy Functions
- 3 Constructions of ABO RLFs
 - Concrete Construction
 - Generic Construction
- 4 Applications of RLFs
 - Leakage-Resilient OWFs
 - Leakage-Resilient MAC
 - Leakage-Resilient CCA-secure KEM


Leakage-Resilient Cryptography




Leakage-Resilient Cryptography



Leakage-Resilient Cryptography




Leakage-Resilient Cryptography




Leakage-Resilient Cryptography

leakage attacks (since 1996) invalidate this idealized assumption




Leakage-Resilient Cryptography

leakage attacks (since 1996) invalidate this idealized assumption




Leakage-Resilient Cryptography

leakage attacks (since 1996) invalidate this idealized assumption




Leakage-Resilient Cryptography

leakage attacks (since 1996) invalidate this idealized assumption




Leakage-Resilient Cryptography

leakage attacks (since 1996) invalidate this idealized assumption




Leakage-Resilient Cryptography

leakage attacks (since 1996) invalidate this idealized assumption



Bounded Leakage Model

In this work, we focus on a simple yet general leakage model called Bounded Leakage Model




$$\sum |g_i(sk)| \leq |sk|$$


Leakage-Resilient OWFs




Leakage-Resilient OWFs




Leakage-Resilient OWFs




Leakage-Resilient OWFs



Leakage-Resilient OWFs



Leakage-Resilient OWFs



Theorem 5

The normal mode of $(1, \tau)$ -RLFs (i.e., LFs) over domain $\{0, 1\}^n$ constitutes a family of ℓ -leakage-resilient injective OWFs, for any $\ell \leq n - \tau - \omega(\log \lambda)$.

Game 0: real game

- ① Setup: \mathcal{CH} generates $f \leftarrow \text{RLF.GenNormal}(\lambda)$, picks $x^* \xleftarrow{\text{R}} \{0, 1\}^n$ and sends $(f, y^* = f(x^*))$ to \mathcal{A} .
- ② Leakage queries: $\mathcal{A} \hookrightarrow g_i$, \mathcal{CH} responds with $g_i(x^*)$.
- ③ Invert: \mathcal{A} outputs x and wins if $x = x^*$.

$$\text{Adv}_{\mathcal{A}}(\lambda) = \Pr[S_0]$$

Game 1: same as Game 0 except that:

- ① Setup: \mathcal{CH} generates $f \leftarrow \text{RLF.GenLossy}(\lambda)$.

Security of RLFs $\Rightarrow |\Pr[S_1] - \Pr[S_0]| \leq \text{negl}(\lambda)$

In Game 1, $\tilde{H}_{\infty}(x^*|(y^*, \text{leak})) \geq n - \tau - \ell$.

- By the parameter choice, $\tilde{H}_{\infty}(x^*|(y^*, \text{leak})) \geq \omega(\log \lambda) \Rightarrow \Pr[S_1] \leq \text{negl}(\lambda)$ even w.r.t. unbounded adversary


Leakage-Resilient MAC




Leakage-Resilient MAC




Leakage-Resilient MAC




Leakage-Resilient MAC




Leakage-Resilient MAC




Leakage-Resilient MAC



Leakage-Resilient MAC




Leakage-Resilient MAC



Strong unforgeability can be relaxed in several ways:


Leakage-Resilient MAC



Strong unforgeability can be relaxed in several ways:

- One-time: \mathcal{A} only makes one tag query

Leakage-Resilient MAC



Strong unforgeability can be relaxed in several ways:

- One-time: \mathcal{A} only makes one tag query
- Selective: \mathcal{A} commits the target message before seeing pp

Construction

Ingredient
 (v, τ) -ABORLF

Construction


Ingredient
 (v, τ) -ABORLF

KeyGen




$ek \leftarrow \text{ABORLF.Gen}(\lambda, 0^d)$
 $k \xleftarrow{\mathcal{R}} \{0, 1\}^n$

Construction



Construction



Theorem 6

The above MAC is ℓ -leakage-resilient selectively one-time sUF for any $\ell \leq n - \tau - \log v - \omega(\log \lambda)$.

Game 0: (real game)

- ① Setup: $\mathcal{A} \looparrowright m^*$, \mathcal{CH} generates $ek \leftarrow \text{ABORLF.Gen}(\lambda, 0^d)$, picks $k \xleftarrow{\mathcal{R}} \{0, 1\}^n$, computes $t^* \leftarrow f_{ek, m^*}(k)$ and then sends (ek, t^*) to \mathcal{A} .
- ② Leakage queries: $\mathcal{A} \looparrowright g_i$, \mathcal{CH} responds with $g_i(k)$.
- ③ Forge: $\mathcal{A} \rightarrow (m, t)$ and wins if $m \neq m^* \wedge t = f_{ek, m}(k)$.

$$\text{Adv}_{\mathcal{A}}(\lambda) = \Pr[S_0]$$

Game 1: same as Game 0 except that

- 1 Setup: \mathcal{CH} generates $ek \leftarrow \text{ABORLF.Gen}(\lambda, m^*)$.

Hidden lossy branch $\Rightarrow |\Pr[S_1] - \Pr[S_0]| \leq \text{negl}(\lambda)$

In Game 1, \mathcal{A} 's view includes $(ek, leak, t^*)$. We have:

$$\begin{aligned}\tilde{H}_\infty(t|view) &= \tilde{H}_\infty(t|ek, leak, t^*) \\ &\geq \tilde{H}_\infty(t|ek) - \ell - \tau \\ &\geq \tilde{H}_\infty(k|ek) - \log v - \ell - \tau \\ &= n - \log v - \ell - \tau\end{aligned}$$

- By the parameter choice, $\tilde{H}_\infty(t|view) \geq \omega(\log \lambda) \Rightarrow \Pr[S_1] \leq \text{negl}(\lambda)$ even w.r.t. unbounded adversary.


Leakage-Resilient CCA-secure KEM




Leakage-Resilient CCA-secure KEM




Leakage-Resilient CCA-secure KEM




Leakage-Resilient CCA-secure KEM




Leakage-Resilient CCA-secure KEM




Leakage-Resilient CCA-secure KEM




Leakage-Resilient CCA-secure KEM



Leakage-Resilient CCA-secure KEM



Leakage-Resilient CCA-secure KEM



$$|\Pr[\beta' = \beta] - 1/2| \leq \text{negl}(\lambda)$$

Construction

Ingredients


HPS

ABORLF


strong extractor

Construction


Ingredients
HPS
ABORLF
strong extractor



Construction



Construction



Theorem 7

Suppose SMP for $L \subset \{0,1\}^m$ is hard, HPS is ϵ_1 -universal₁ and $n = \log(1/\epsilon_1)$, ABORLF is (v, τ) -regularly-lossy, ext is $(n - \tau - \ell, \kappa, \epsilon_2)$ -strong extractor, then the above KEM is ℓ -LR CCA secure for any $\ell \leq n - \tau - \log v - \omega(\log \lambda)$.

Game 0: (real game)

- ① Setup: \mathcal{CH} generates $(pk, sk) \leftarrow \text{HPS.Gen}(\lambda)$, $ek \leftarrow \text{ABORLF.Gen}(\lambda, 0^{m+d})$, sends (pk, ek) to \mathcal{A} .
- ② Leakage queries $\langle g_i \rangle$: \mathcal{CH} responds with $g_i(sk)$.
- ③ Challenge: \mathcal{CH} picks $\beta \in \{0, 1\}$, $s^* \leftarrow \{0, 1\}^d$, $(x^*, w^*) \leftarrow \text{SampYes}(\lambda)$, computes $\pi^* \leftarrow \text{Pub}(pk, x^*, w^*)$, $t^* \leftarrow f_{ek, x^* || s^*}(\pi^*)$, $k_0^* \leftarrow \text{ext}(\pi^*, s^*)$, picks $k_1^* \leftarrow \{0, 1\}^\kappa$, sends $c^* = (x^*, s^*, t^*)$ and k_β^* to \mathcal{A} .
- ④ Decaps queries $\langle c = (x, s, t) \neq c^* \rangle$: \mathcal{CH} computes $\pi \leftarrow \Lambda_{sk}(x)$, output $k \leftarrow \text{ext}(\pi, s)$ if $t = f_{ek, x || s}(\pi)$ and \perp otherwise.

$$\text{Adv}_{\mathcal{A}}(\lambda) = \Pr[S_0] - 1/2$$

Game 1: \mathcal{CH} samples (x^*, w^*) and s^* at Setup.

$$\Pr[S_0] = \Pr[S_1]$$

Game 1: \mathcal{CH} samples (x^*, w^*) and s^* at Setup.

$$\Pr[S_0] = \Pr[S_1]$$

Game 2: \mathcal{CH} generates $ek \leftarrow \text{ABORLF.Gen}(\lambda, \textcolor{red}{x}^* || \textcolor{red}{s}^*)$.

$$\text{Hidden lossy branch} \Rightarrow |\Pr[S_2] - \Pr[S_1]| \leq \text{negl}(\lambda)$$

Game 1: \mathcal{CH} samples (x^*, w^*) and s^* at Setup.

$$\Pr[S_0] = \Pr[S_1]$$

Game 2: \mathcal{CH} generates $ek \leftarrow \text{ABORLF.Gen}(\lambda, \textcolor{red}{x^*} || \textcolor{red}{s^*})$.

$$\text{Hidden lossy branch} \Rightarrow |\Pr[S_2] - \Pr[S_1]| \leq \text{negl}(\lambda)$$

Game 3: \mathcal{CH} computes $\pi^* \leftarrow \Lambda_{sk}(x^*)$ via $\text{Priv}(sk, x^*)$.

$$\text{Correctness of HPS} \Rightarrow \Pr[S_3] = \Pr[S_2].$$

Game 1: \mathcal{CH} samples (x^*, w^*) and s^* at Setup.

$$\Pr[S_0] = \Pr[S_1]$$

Game 2: \mathcal{CH} generates $ek \leftarrow \text{ABORLF.Gen}(\lambda, x^* || s^*)$.

$$\text{Hidden lossy branch} \Rightarrow |\Pr[S_2] - \Pr[S_1]| \leq \text{negl}(\lambda)$$

Game 3: \mathcal{CH} computes $\pi^* \leftarrow \Lambda_{sk}(x^*)$ via $\text{Priv}(sk, x^*)$.

$$\text{Correctness of HPS} \Rightarrow \Pr[S_3] = \Pr[S_2].$$

Game 4: \mathcal{CH} samples x^* via SampNo rather than SampYes .

$$\text{SMP} \Rightarrow |\Pr[S_4] - \Pr[S_3]| \leq \text{negl}(\lambda)$$

Game 1: \mathcal{CH} samples (x^*, w^*) and s^* at Setup.

$$\Pr[S_0] = \Pr[S_1]$$

Game 2: \mathcal{CH} generates $ek \leftarrow \text{ABORLF.Gen}(\lambda, x^* || s^*)$.

$$\text{Hidden lossy branch} \Rightarrow |\Pr[S_2] - \Pr[S_1]| \leq \text{negl}(\lambda)$$

Game 3: \mathcal{CH} computes $\pi^* \leftarrow \Lambda_{sk}(x^*)$ via $\text{Priv}(sk, x^*)$.

$$\text{Correctness of HPS} \Rightarrow \Pr[S_3] = \Pr[S_2].$$

Game 4: \mathcal{CH} samples x^* via SampNo rather than SampYes .

$$\text{SMP} \Rightarrow |\Pr[S_4] - \Pr[S_3]| \leq \text{negl}(\lambda)$$

Game 5: \mathcal{CH} directly rejects $\langle c = (x, s, t) \rangle$ if $x \notin L$. Define E : \mathcal{A} makes an invalid but well-formed decaps queries, i.e., $f_{ek, x||s}(\Lambda_{sk}(x)) = t$ and $x \in L \wedge (x, s, t) \neq (x^*, s^*, t^*)$.

$$|\Pr[S_5] - \Pr[S_4]| \leq \Pr[E]$$

To calculate $\Pr[E]$, it suffice to bound $\tilde{H}_\infty(t|view)$.

- $view: (pk, ek, leak, x^*, s^*, t^*, k_\beta^*)$
- $t = f_{ek, x||s}(\Lambda_{sk}(x))$

We bound $\tilde{H}_\infty(t|view)$ via $\tilde{H}_\infty(\Lambda_{sk}(x)|view)$ as below:

- (x^*, s^*) determines a lossy branch $\Rightarrow \tau$ only reveal partial info about $sk \Rightarrow \tilde{H}_\infty(\Lambda_{sk}(x)|view) \geq n - \ell - \tau - \kappa$
- We must have $(x, s) \neq (x^*, s^*)$, which determines a v -regular branch $\Rightarrow \tilde{H}_\infty(t|view) \geq \tilde{H}_\infty(\Lambda_{sk}(x)|view) - \log v$

By the parameter choice, $\tilde{H}_\infty(t|view) \geq \omega(\log \lambda)$, thus we have:

$$\Pr[E] \leq \text{negl}(\lambda)$$

Game 6: \mathcal{CH} samples $k_0^* \leftarrow \{0, 1\}^\kappa$ rather than $k_0^* \leftarrow \text{ext}(\Lambda_{sk}(x^*))$. Next, we analysis $\Delta[\text{view}_5, \text{view}_6]$.

- define $\text{view}' = (pk, ek, leak, x^*, s^*, t^*)$, chain rule $\Rightarrow \tilde{H}_\infty(\Lambda_{sk}(x^*)|\text{view}') \geq n - \ell - \tau$
- randomness extractor $\Rightarrow \Delta[(\text{view}', k_{5,0}^*), (\text{view}', k_{6,0}^*)] \leq \epsilon_2$.
- responses to all decaps queries in Game 5 and 6 are determined by the same function of $(\text{view}', k_{5,0}^*)$ and $(\text{view}', k_{6,0}^*)$ resp.

$$\Delta[\text{view}_5, \text{view}_6] \leq \epsilon_2/2 \leq \text{negl}(\lambda)$$

Putting all the above together, $\text{Adv}_{\mathcal{A}}(\lambda) = \text{negl}(\lambda)$.

Significance

$\text{Universal}_1 \text{ HPS} + \text{ABO-RLF} \Rightarrow \text{LR-CCA KEM}$

- proper parameter choice $\Rightarrow \ell/|sk| = 1 - o(1)$
- $\text{HPS} \Rightarrow \text{ABO-RLF}$

$\text{Universal}_1 \text{ HPS} + \text{ABO-RLF} \Rightarrow \text{LR-CCA KEM}$

- proper parameter choice $\Rightarrow \ell/|sk| = 1 - o(1)$
- $\text{HPS} \Rightarrow \text{ABO-RLF}$

CCA-secure KEM with optimal leakage rate based solely on universal_1 HPS

- go beyond **the upper bound** posed by Dodis et al. (Asiacrypt 2010)


leakage-rate only approaching $1/6$. Unfortunately, it seems that the hash proof system approach to building CCA encryption is inherently limited to leakage-rates below $1/2$: this is because the secret-key consists of two components (one for verifying that the ciphertext is well-formed and one for decrypting it) and the proofs break down if either of the components is individually leaked in its entirety.

- extend to identity-based setting as well


Conclusion

(ABO)-RLFs


Conclusion




Conclusion




Conclusion



Conclusion



Conclusion



Thanks for Your Attention!

Any Questions?

Reference

- [FGK⁺13] David Mandell Freeman, Oded Goldreich, Eike Kiltz, Alon Rosen, and Gil Segev. More constructions of lossy and correlation-secure trapdoor functions. *J. Cryptology*, 26(1):39–74, 2013.
- [PW08] Chris Peikert and Brent Waters. Lossy trapdoor functions and their applications. In *Proceedings of the 40th Annual ACM Symposium on Theory of Computing, STOC 2008*, pages 187–196. ACM, 2008.