



jobid: 25793660	uid: 35712	nprocs: 128	runtime: 15.4557 seconds

I/O performance *estimate* (at the MPI-IO layer): transferred 20480.0 MiB at 1340.23 MiB/s
I/O performance *estimate* (at the STDIO layer): transferred 0.0 MiB at 1.05 MiB/s










Most Common Access Sizes
(POSIX or MPI-IO)


	access size	count
POSIX	33554432	640
	544	4
	328	4
	600	3
MPI-IO ‡	33554432	640
	328	4
	544	4
	600	3


‡ NOTE: MPI-IO accesses are given in terms of aggregate datatype size.

File Count Summary
(estimated by POSIX I/O access offsets)

type	number of files	avg. size	max size
total opened	132	156MiB	21GiB
read-only files	1	270B	270B
write-only files	3	6.7GiB	21GiB
read/write files	0	0	0
created files	3	6.7GiB	21GiB








Average I/O per process (POSIX and STDIO)

	Cumulative time spent in I/O functions (seconds)	Amount of I/O (MiB)
Independent reads	0	0
Independent writes	0	0
Independent metadata	0.01849228125	N/A
Shared reads	8.3625e-05	0.000257492065429688
Shared writes	12.9764996484375	160.000083394349
Shared metadata	0.014518125	N/A

Data Transfer Per Filesystem (POSIX and STDIO)

File System	Write		Read	
	MiB	Ratio	MiB	Ratio
UNKNOWN	20480.01067	1.00000	0.03296	1.00000



sequential: An I/O op issued at an offset greater than where the previous I/O op ended.
consecutive: An I/O op issued at the offset immediately following the end of the previous I/O op.

Variance in Shared Files (POSIX and STDIO)

File Suffix	Processes	Fastest			Slowest			σ	
		Rank	Time	Bytes	Rank	Time	Bytes	Time	Bytes
...terleaved.h5	128	66	10.436861	160MiB	79	15.211516	160MiB	1.36	168
...ite_rep2.csv	128	15	0.000722	0	7	0.025869	0	0.008	26.9
.../h5bench.cfg	128	72	0.000107	270B	45	0.006883	270B	0.00141	0
...<STDOUT>	128	1	0.000000	0	0	0.000223	1.5KiB	0	130