Partie 3 : Exercice Git

1. Voir l'historique des commits :

   git log

2. Créer la branche "feature-xyz" à partir de main

   - git checkout -b feature-xyz main
   - git switch -c feature-xyz main

3. Fusionner "feature-xyz" dans "main"

   git checkout main

   git merge feature-xyz

4. Annuler les modifications locales avant commit

   git restore nom-du-fichier (un seul fichier)

   git restore (tous les fichiers)

5. Vérifier l'état du dépot :

   git status

Scanned with CamScanner

```
HP@Heju UCRT64 ~
$ git --version
git version 2.56.0.windows.1

HP@Heju UCRT64 ~
$ git config --global user.name "hajar"

HP@Heju UCRT64 ~
$ git --global user.email "dahbihajar213@gmail.com"
unknown option: --global
usage: git [-v | --version] [-h | --help] [-C <path>] [-c <name>=<value>]
           [--exec-path[=<path>]] [--html-path] [--man-path] [--info-path]
           [-p | --paginate | -P | --no-pager] [--no-replace-objects] [--no-lazy-fetch]
           [--no-optional-locks] [--no-advice] [--bare] [--git-dir=<path>]
           [--work-tree=<path>] [--namespace=<name>] [--config-env=<name>=<envvar>]
           <command> [<args>]

HP@Heju UCRT64 ~
$ mkdir depot_local

HP@Heju UCRT64 ~
$ cd depot_local

HP@Heju UCRT64 ~/depot_local
$ git init
Initialized empty Git repository in C:/Users/HP/depot_local/.git/

$ git remote add origin https://github.com/hajaardhb/depot_local.git

HP@Heju UCRT64 ~/depot_local (master)
$ git remote -v
origin  https://github.com/hajaardhb/depot_local.git (fetch)
origin  https://github.com/hajaardhb/depot_local.git (push)

HP@Heju UCRT64 ~/depot_local (master)
$ git config --global user.email "dahbihajar213@gmail.com"

HP@Heju UCRT64 ~/depot_local (master)
$ touch produit.html style.css script.js

HP@Heju UCRT64 ~/depot_local (master)
```

```
HP@Heju UCRT64 ~/depot_local (master)
$ touch produit.html style.css script.js

HP@Heju UCRT64 ~/depot_local (master)
$ git add produit.html style.css script.js

HP@Heju UCRT64 ~/depot_local (master)
$ git commit -m "Ajout des fichiers initiaux"
[master (root-commit) d335153] Ajout des fichiers initiaux
 3 files changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 produit.html
 create mode 100644 script.js
 create mode 100644 style.css

HP@Heju UCRT64 ~/depot_local (master)
$ git status
On branch master
nothing to commit, working tree clean

HP@Heju UCRT64 ~/depot_local (master)
$ git log --oneline
d335153 (HEAD -> master) Ajout des fichiers initiaux

HP@Heju UCRT64 ~/depot_local (master)
$ git checkout -b "Gestion produits"
fatal: 'Gestion produits' is not a valid branch name
hint: See 'git help check-ref-format'
hint: Disable this message with "git config set advice.refSyntax false"

HP@Heju UCRT64 ~/depot_local (master)
$ git checkout -b Gestion-produits
Switched to a new branch 'Gestion-produits'

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ git branch
* Gestion-produits
  master

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ echo "<h1>Produits</h1>" > produit.html

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ echo "body { margin: 0; }" > style.css

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ echo "console.log('ok');" > script.js
```

```
HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ echo "console.log('ok');" > script.js

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ git status
On branch Gestion-produits
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   produit.html
        modified:   script.js
        modified:   style.css

no changes added to commit (use "git add" and/or "git commit -a")

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ git add .
warning: in the working copy of 'produit.html', LF will be replaced by CRLF the next time Git touches it
warning: in the working copy of 'script.js', LF will be replaced by CRLF the next time Git touches it
warning: in the working copy of 'style.css', LF will be replaced by CRLF the next time Git touches it

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ git commit -m "Modification des fichiers"
[Gestion-produits caac108] Modification des fichiers
 3 files changed, 3 insertions(+)

HP@Heju UCRT64 ~/depot_local (Gestion-produits)
$ git checkout master
Switched to branch 'master'

HP@Heju UCRT64 ~/depot_local (master)
$ git merge Gestion-produits
Updating d335153..caac108
Fast-forward
 produit.html | 1 +
 script.js    | 1 +
 style.css    | 1 +
 3 files changed, 3 insertions(+)

HP@Heju UCRT64 ~/depot_local (master)
$ git log --oneline
caac108 (HEAD -> master, Gestion-produits) Modification des fichiers
d335153 Ajout des fichiers initiaux

HP@Heju UCRT64 ~/depot_local (master)
$ git remote show origin
* remote origin
```

```
caac108 (HEAD -> master, Gestion-produits) Modification des fichiers
d335153 Ajout des fichiers initiaux

HP@Heju UCRT64 ~/depot_local (master)
$ git remote show origin
* remote origin
  Fetch URL: https://github.com/hajaardhb/depot_local.git
  Push  URL: https://github.com/hajaardhb/depot_local.git
  HEAD branch: (unknown)

HP@Heju UCRT64 ~/depot_local (master)
$ git push -u origin master
Enumerating objects: 8, done.
Counting objects: 100% (8/8), done.
Delta compression using up to 8 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (8/8), 609 bytes | 304.00 KiB/s, done.
Total 8 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/hajaardhb/depot_local.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

HP@Heju UCRT64 ~/depot_local (master)
$ git log --oneline
caac108 (HEAD -> master, origin/master, Gestion-produits) Modification des fichiers
d335153 Ajout des fichiers initiaux

HP@Heju UCRT64 ~/depot_local (master)
$ git reset --hard d335153
HEAD is now at d335153 Ajout des fichiers initiaux

HP@Heju UCRT64 ~/depot_local (master)
$ git log --oneline
d335153 (HEAD -> master) Ajout des fichiers initiaux

HP@Heju UCRT64 ~/depot_local (master)
$ git status
On branch master
Your branch is behind 'origin/master' by 1 commit, and can be fast-forwarded.
  (use "git pull" to update your local branch)

nothing to commit, working tree clean

HP@Heju UCRT64 ~/depot_local (master)
$ git push --force origin master
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/hajaardhb/depot_local.git
 + caac108...d335153 master -> master (forced update)
```

```
nothing to commit, working tree clean

HP@Heju UCRT64 ~/depot_local (master)
$ git push --force origin master
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/hajaardhb/depot_local.git
 + caac108...d335153 master -> master (forced update)

HP@Heju UCRT64 ~/depot_local (master)
$ git status
On branch master
Your branch is up to date with 'origin/master'.

nothing to commit, working tree clean

HP@Heju UCRT64 ~/depot_local (master)
$ ^C

HP@Heju UCRT64 ~/depot_local (master)
$
```