

# Exploitation des symétries dynamiques pour la résolution des problèmes SAT

Thèse de doctorat de Sorbonne Université

Hakan METIN

## **Supervisors:**

SOUHEIB BAARIR  
FABRICE KORDON

Maître de conférences, Université Paris Nanterre  
Professeur, Sorbonne Université

## **Jury Members:**

PASCAL FONTAINE  
LAURE PETRUCCI  
JEAN-MICHEL COUVREUR  
EMANUELLE ENCRENAZ  
SOUHEIB BAARIR  
FABRICE KORDON

Maître de conférences, Université de Lorraine  
Professeur, Université Paris 13  
Professeur, Université d'Orléans  
Maître de conférences, Sorbonne Université  
Maître de conférences, Université Paris Nanterre  
Professeur, Sorbonne Université



# Motivation

SAT is widely used in different domains:

- Artificial intelligence (planning, games, ...)
- Bioinformatics (haplotype inference, ...)
- Security (cryptanalysis, inversion attack on hash function)
- Computationally hard problems (graph coloring, ...)
- Formal Methods (hardware model checking, ...)

# Outline

## ① SAT overview

- SAT basics

- SAT and symmetries

## ② Existing approaches

- Static symmetry breaking


- Dynamic symmetry breaking

## ③ Contribution and results


- CDCL [Sym]

- Combination of different approaches


# SAT an example



1



2



3



A




B



C

Is it possible to attribute each group to a classroom ?


# SAT an example



1  
↑




A



2  
↑



B



3  
↑







C

Is it possible to attribute each group to a classroom ?

YES!

# SAT an example



A



B




C


Is it possible to attribute each group to a classroom ?

YES! Many solutions

# SAT




# SAT



$$\underbrace{(x_1 \vee x_2 \vee \neg x_3)}$$
  
Clause with literals  $x_1, x_2, \neg x_3$



# SAT



$$\overbrace{(x_1 \vee x_2 \vee \neg x_3) \wedge (\neg x_1 \vee \neg x_2) \wedge (x_2 \vee \neg x_4)}^{\text{Formula (CNF)}}$$

$\underbrace{(x_1 \vee x_2 \vee \neg x_3)}_{\text{Clause}}$

# Computing symmetries of a SAT problem

*CNF formula*

$$\begin{aligned} & (x_1 \vee x_2 \vee x_3) \wedge (x_4 \vee x_5 \vee x_6) \wedge (x_7 \vee x_8 \vee x_9) \\ & \wedge (\neg x_1 \vee \neg x_4) \wedge (\neg x_1 \vee \neg x_7) \wedge (\neg x_4 \vee \neg x_7) \\ & \wedge (\neg x_2 \vee \neg x_5) \wedge (\neg x_2 \vee \neg x_8) \wedge (\neg x_5 \vee \neg x_8) \\ & \wedge (\neg x_3 \vee \neg x_6) \wedge (\neg x_3 \vee \neg x_9) \wedge (\neg x_6 \vee \neg x_9) \end{aligned}$$

---

<sup>1</sup><http://www.tcs.hut.fi/Software/bliss/>

<sup>2</sup><http://vlsicad.eecs.umich.edu/BK/SAUCY/>


# Computing symmetries of a SAT problem

CNF formula

$$\begin{aligned} & (x_1 \vee x_2 \vee x_3) \wedge (x_4 \vee x_5 \vee x_6) \wedge (x_7 \vee x_8 \vee x_9) \\ & \wedge (\neg x_1 \vee \neg x_4) \wedge (\neg x_1 \vee \neg x_7) \wedge (\neg x_4 \vee \neg x_7) \\ & \wedge (\neg x_2 \vee \neg x_5) \wedge (\neg x_2 \vee \neg x_8) \wedge (\neg x_5 \vee \neg x_8) \\ & \wedge (\neg x_3 \vee \neg x_6) \wedge (\neg x_3 \vee \neg x_9) \wedge (\neg x_6 \vee \neg x_9) \end{aligned}$$



colored graph




# Computing symmetries of a SAT problem

CNF formula

$$\begin{aligned} & (x_1 \vee x_2 \vee x_3) \wedge (x_4 \vee x_5 \vee x_6) \wedge (x_7 \vee x_8 \vee x_9) \\ & \wedge (\neg x_1 \vee \neg x_4) \wedge (\neg x_1 \vee \neg x_7) \wedge (\neg x_4 \vee \neg x_7) \\ & \wedge (\neg x_2 \vee \neg x_5) \wedge (\neg x_2 \vee \neg x_8) \wedge (\neg x_5 \vee \neg x_8) \\ & \wedge (\neg x_3 \vee \neg x_6) \wedge (\neg x_3 \vee \neg x_9) \wedge (\neg x_6 \vee \neg x_9) \end{aligned}$$



colored graph



graph automorphism



(bliss<sup>1</sup> or saucy<sup>2</sup>)

<sup>1</sup><http://www.tcs.hut.fi/Software/bliss/>

<sup>2</sup><http://vlsicad.eecs.umich.edu/BK/SAUCY/>


# Computing symmetries of a SAT problem

CNF formula

$$\begin{aligned} &(x_1 \vee x_2 \vee x_3) \wedge (x_4 \vee x_5 \vee x_6) \wedge (x_7 \vee x_8 \vee x_9) \\ &\wedge (\neg x_1 \vee \neg x_4) \wedge (\neg x_1 \vee \neg x_7) \wedge (\neg x_4 \vee \neg x_7) \\ &\wedge (\neg x_2 \vee \neg x_5) \wedge (\neg x_2 \vee \neg x_8) \wedge (\neg x_5 \vee \neg x_8) \\ &\wedge (\neg x_3 \vee \neg x_6) \wedge (\neg x_3 \vee \neg x_9) \wedge (\neg x_6 \vee \neg x_9) \end{aligned}$$



colored graph



⇓  
graph automorphism

⇓  
set of symmetries

⇓  
(bliss<sup>1</sup> or saucy<sup>2</sup>)

⇓

$$\begin{aligned} g_1 &= (x_2 \ x_3)(x_5 \ x_6)(x_8 \ x_9) \\ g_2 &= (x_4 \ x_7)(x_5 \ x_8)(x_6 \ x_9) \\ g_3 &= (x_1 \ x_2)(x_4 \ x_5)(x_7 \ x_8) \\ g_4 &= (x_1 \ x_4)(x_2 \ x_5)(x_3 \ x_6) \end{aligned}$$


<sup>1</sup><http://www.tcs.hut.fi/Software/bliss/>

<sup>2</sup><http://vlsicad.eecs.umich.edu/BK/SAUCY/>


# SAT

example solving arbre

# Conflict Driven Clause Learning Algorithm (CDCL)




# Tree






## SAT an example 2



1



2



A




B



C


Attribute each group to a class room

## SAT an example 2




Attribute each group to a class room

## SAT an example 2




Attribute each group to a class room

## SAT an example 2




Attribute each group to a class room

## SAT an example 2




Attribute each group to a class room

## SAT an example 2



Attribute each group to a class room

## SAT an example 2



Attribute each group to a class room

