




sartorius stedim
biotech

Sterisart® NF

Meet our family for sterility testing –
reliable, economical, compatible



turning science into solutions

Sterisart® NF. Versatile and highly compatible

International pharmacopoeias require the complete sterility of pharmaceutical products that are injected into the blood stream or that otherwise enter the body below the skin surface. As a manufacturer of such products, you are required to supply proof of the sterility of final product batch.

The preferred method for sterility testing is the membrane filter method – any microorganisms present are concentrated on the membrane filter surfaces in the sample containers, then nutrient media are added to these containers, and the containers are incubated under the conditions specified.

The convincing solution for safe handling.

The Sterisart® NF system, order number 16466, is equipped with a dual-needle metal spike, which has been specially designed for closed sample containers. The two needles are made of metal, allowing the spike to be briefly flamed. This feature enables you to change sample containers, while considerably minimizing the risk of contamination. Unlike plastic needles, metal needles do not snap off when tilted under pressure. This benefit together with the large protective plate on the spike not only makes it easy to pierce stoppers. The plate construction also helps prevent injury to fingers by ruling out breakage or slippage. The lengths of the dual-needles allow the same spike to be used for various types of closures.



The second Sterisart® NF adapter type with the order number 16467 has been specially designed for use with open containers, such as ampoules or collapsible plastic bags that do not require venting when samples are removed. The thickness and length of the individual needle enable samples to be drawn even from exceptionally small ampoules with narrow openings. In addition, the length of the needle makes it easy to remove samples from plastic bags without piercing the bag itself. Last but not least, this needle can also be briefly flamed, which minimizes the risk of contamination when you change sample containers.

Both Sterisart® NF types are also available as special isolator versions with the model suffix "gamma," which is indicated by the last letters of the order number: GBD.

The gamma version features a gastight packaging that reliably retains gas, such as H₂O₂, used for routine sterilization inside isolators. This feature simplifies validation of Sterisart systems, helping prevent false negative results that might be caused by H₂O₂ seeping into the inside of sterility test units.

Sterisart® NF systems can be used with the Sterisart® Universal Pumps 16419 and 16420 that Sartorius Stedim Biotech recently designed. Versatile and flexible, they offer considerable benefits, and are ideal for use in clean rooms and clean benches or isolators when installed in the working surface.

Intelligent, closed system design.

Compact Sterisart® NF systems feature a closed design for sterility testing, which means they maintain a closed system during transfer and distribution of the sample into two sample containers, filtration, rinsing, the addition of nutrient media, incubation and evaluation. Therefore, this design reliably prevents secondary contamination. They are ideal for routine or sporadic sterility testing in the pharmaceutical industry. The procedure is mostly independent of the sample volume because sufficiently large total volumes of sample can be filtered through the membranes in the two sample containers.

A membrane you can benefit from.

The Sartochem® membrane has been specifically developed to meet the requirements of sterility testing, in particular for extremely low adsorption characteristics and for appropriate chemical compatibility. The special clamping technology used to seal the outer edges of the disk membranes to the sample containers not only holds up very well to pressure. It also enhances the membrane's low adsorption by not retaining inhibitors in such a way that could affect microbiological growth. This is very important with regard to the reliability of the test.



Specifications

Pore size of the Sartochem® membrane filter	0.45 µm, tested with <i>Serratia marcescens</i>
Filter area	15.7 cm ² in each Sterisart® container
Flow rate (for water)	500 ml/min at 1 bar (approx. 15 psi)
Pore size of the air filters	0.2 µm PTFE, validated acc. to HIMA for the retention of <i>B. diminuta</i>
Sample container capacity	120 ml (graduation marks at 50, 75 and 100 ml)
Max. operating pressure	3 bar (approx. 44 psi) at 20°C
Max. operating temperature	50°C
Sterilization	ETO (ethylene oxide gas) or gamma irradiation

Specifications subject to change without notice.

Chemical compatibility of the components (24-hour contact at 20°C)

	Sartochem® membrane	Tubing	Sterisart® containers
Aqueous solutions	C	C	C
Alcohols	C	C	C
Aliphatic hydrocarbons	C	C	C
Oils	C	C	C
Salt solutions	C	C	C
Ether	C	C	C
Weak acids	C	C	LC
Weak bases	LC	C	LC
Aromatic hydrocarbons	C	N	N
Esters	C	N	LC
Halogenated hydrocarbons	C	N	N

C = compatible, LC = limited compatibility, N = not compatible

Ordering information

Name	Description	Quantity	Order number
Sterisart® NF alpha	Dual-needle metal spike for closed containers (sterilized with ETO; single-packed)	Box of 10	16466 ACD
Sterisart® NF alpha	6-cm metal needle for open containers (sterilized with ETO; single-packed)	Box of 10	16467 ACD
Sterisart® NF gamma	Dual-needle metal spike for closed containers (gamma sterilized, double-packed, optimal for use in isolators)	Box of 10	16466 GBD
Sterisart® NF gamma	6-cm metal needle for open containers (gamma sterilized, double-packed, optimal for use in isolators)	Box of 10	16467 GBD
Sterisart® Universal pump	basic version	1	16419
Sterisart® Universal pump	upgraded version with display user software	1	16420

Further Sterisart units and accessories (e.g. adapters for use of Sterisart® Systems in available competitor pumps) are available on request.

Comprehensive validation support literature is available on request.

Publ. No. SL-4507-e05061, Order No. 85030-522-85

Sales and Service Contacts

For further contacts, visit www.sartorius-stedim.com

Europe

Germany

Sartorius Stedim Biotech GmbH
August-Spindler-Strasse 11
37079 Goettingen

Phone +49.551.308.0
Fax +49.551.308.3289

www.sartorius-stedim.com

Sartorius Stedim Systems GmbH
Schwarzenberger Weg 73-79
34212 Melsungen

Phone +49.5661.71.3400
Fax +49.5661.71.3702

www.sartorius-stedim.com

France

Sartorius Stedim Biotech S.A.
ZI Les Paluds
Avenue de Jouques – BP 1051
13781 Aubagne Cedex

Phone +33.442.845600
Fax +33.442.845619

Sartorius Stedim France SAS
ZI Les Paluds
Avenue de Jouques – CS 71058
13781 Aubagne Cedex

Phone +33.442.845600
Fax +33.442.846545

Austria

Sartorius Stedim Austria GmbH
Franzosengraben 12
A-1030 Vienna

Phone +43.1.7965763.18
Fax +43.1.796576344

Belgium

Sartorius Stedim Belgium N.V.
Leuvensesteenweg, 248/B
1800 Vilvoorde

Phone +32.2.756.06.80
Fax +32.2.756.06.81

Denmark

Sartorius Stedim Nordic A/S
Hoerskaetten 6D, 1.
DK-2630 Taastrup

Phone +45.7023.4400
Fax +45.4630.4030

Italy

Sartorius Stedim Italy S.p.A.
Via dell'Antella, 76/A
50012 Antella-Bagno a Ripoli (FI)

Phone +39.055.63.40.41
Fax +39.055.63.40.526

Netherlands

Sartorius Stedim Netherlands B.V.
Edisonbaan 24
3439 MN Nieuwegein

Phone +31.30.6025080
Fax +31.30.6025099

Spain

Sartorius Stedim Spain SA
C/Isabel Colbrand 10-12,
Planta 4, Oficina 121
Polígono Industrial de Fuencarral
28050 Madrid

Phone +34.91.3586102
Fax +34.91.3588804

Switzerland

Sartorius Stedim Switzerland GmbH
Lerzenstrasse 21
8953 Dietikon

Phone +41.44.741.05.00
Fax +41.44.741.05.09

U.K.

Sartorius Stedim UK Limited
Longmead Business Park
Blenheim Road, Epsom
Surrey KT19 9 QQ

Phone +44.1372.737159
Fax +44.1372.726171

America

USA

Sartorius Stedim North America Inc.
5 Orville Drive
Bohemia, NY 11716

Toll-Free +1.800.368.7178
Fax +1.631.254.4253

Sartorius Stedim SUS Inc.
1910 Mark Court
Concord, CA 94520

Phone +1.925.689.6650
Toll Free +1.800.914.6644
Fax +1.925.689.6988

Sartorius Stedim Systems Inc.
201 South Ingram Mill Road
Springfield, MO 65802

Phone +1.417.873.9636
Fax +1.417.873.9275

Argentina

Sartorius Argentina S.A.
Int. A. Avalos 4251
B1605ECS Munro
Buenos Aires

Phone +54.11.4721.0505
Fax +54.11.4762.2333

Brazil

Sartorius do Brasil Ltda
Av. Dom Pedro I, 241
Bairro Vila Pires
Santo André
São Paulo
Cep 09110-001

Phone +55.11.4451.6226
Fax +55.11.4451.4369

Mexico

Sartorius de México S.A. de C.V.
Circuito Circunvalación Poniente No. 149
Ciudad Satélite
53100 Naucalpan, Estado de México

Phone +52.5555.62.1102
Fax +52.5555.62.2942

Asia | Pacific

China

Sartorius Stedim Beijing
Representative Office
No. 33, Yu'an Road,
Airport Industrial Zone B, Shunyi District
Beijing 101300

Phone +86.10.80426516
Fax +86.10.80426580

Sartorius Stedim Shanghai
Representative Office
Room 618, Tower 1, German Centre,
Shanghai, PRC., 201203

Phone +86.21.28986393
Fax +86.21.28986392.11

Sartorius Stedim Guangzhou Office
Room 704, Broadway Plaza,
No. 233-234 Dong Feng West Road
Guangzhou 510180

Phone +86.20.8351.7921
Fax +86.20.8351.7931

India

Sartorius Stedim India Pvt. Ltd.
10, 6th Main, 3rd Phase Peenya
KIADB Industrial Area
Bangalore – 560 058

Phone +91.80.2839.1963|0461
Fax +91.80.2839.8262

Japan

Sartorius Stedim Japan K.K.
KY Building, 8-11
Kita Shinagawa 1-chome
Shinagawa-ku
Tokyo 140-0001

Phone +81.3.3740.5407
Fax +81.3.3740.5406

Malaysia

Sartorius Stedim Malaysia Sdn. Bhd.
Lot L3-E-3B, Enterprise 4
Technology Park Malaysia
Bukit Jalil
57000 Kuala Lumpur

Phone +60.3.8996.0622
Fax +60.3.8996.0755

Singapore

Sartorius Stedim Singapore Pte. Ltd.
10, Science Park Road, The Alpha
#02-25, Singapore Science Park 2
Singapore 117684

Phone +65.6872.3966
Fax +65.6778.2494

Australia

Sartorius Stedim Australia Pty. Ltd.
Unit 5, 7-11 Rodeo Drive
Dandenong South Vic 3175

Phone +61.3.8762.1800
Fax +61.3.8762.1828