

Faculty of Engineering and Technology

Electrical and Computer Engineering Department

Project #2

Comparative Study of Image Classification Using Decision Tree, Naive Bayes, and Feedforward Neural Networks

---

Prepared by:

Hala Sabobeh -1220322

Nour Omari -1221212

Instructor : Dr. Samah Alaydi

Section: 3

Date: June,25 2025

• 1.Introduction

Image classification is a fundamental task in computer vision, aiming to assign labels to images based on their content. In this project, we perform a comparative study of three machine learning models—**Naive Bayes**, **Decision Tree**, and **Feedforward Neural Network** (MLPClassifier)—for classifying flower images. We use a dataset of over 500 images organized into five classes: daisy, dandelion, rose, sunflower, and tulip. All images are resized to **32×32** pixels and flattened into 1D feature vectors to serve as input for the models. Each classifier is trained and evaluated using performance metrics such as accuracy, precision, recall, F1-score, and confusion matrices. This study aims to analyze the strengths and limitations of each model in terms of accuracy, generalization, and efficiency when applied to real-world image data.

• 2. Dataset Description

The dataset used in this project consists of **3,072 labeled flower images** divided into five distinct categories: **daisy**, **dandelion**, **rose**, **sunflower**, and **tulip**, with approximately 600 images per class. The images are organized into separate folders based on their labels, making them easy to process programmatically. For consistency and efficient model training, all images were **resized to 32×32 pixels** and **converted to grayscale**, then flattened into **1D vectors of length 1024** (32 × 32) to serve as input features for the classifiers. The dataset was then split into **training (80%) and testing (20%)** sets to evaluate model performance on unseen data. This preprocessing ensures that the data is uniform in size and suitable for traditional machine learning algorithms that require fixed-length vector inputs.

3. Detailed explanation of each model with screenshots of the code :

3.1 Naive Bayes Classifier:

The Naive Bayes classifier implemented in this project uses the **Gaussian Naive Bayes** (**GaussianNB**) model from the scikit-learn library. This algorithm works on the principle of applying Bayes' theorem with the assumption that all features (in this case, image pixel values) are independent of each other. The model was trained on the flattened 1D feature vectors derived from the images. After training, an analysis function was used to display the mean and variance for each class label, giving insights into the feature distribution for each flower category. Despite its simplicity and the unrealistic independence assumption, Naive Bayes often performs surprisingly well for high-dimensional datasets like images. It also has the advantage of being computationally efficient and easy to implement, making it a useful baseline for comparison with more complex models.

```
12  def train_naive_bayes(X_train, y_train):
13      model = GaussianNB()
14      model.fit(X_train, y_train)
15      return model
16
17  def analyze_naive_bayes(model, class_names):
18      print("\nNaive Bayes Feature Statistics:")
19      try:
20          print(f"{'Class':<12} {'Mean':<25} {'Variance':<25}")
21          print("-" * 60)
22          for i, name in enumerate(class_names):
23              print(f"{name:<12} {str(model.theta_[i][:3].round(4)) + '...':<25} {str(model.var_[i][:3].round(4)) + '...':<25}")
24          print(f"\nShowing first 3 of {model.theta_.shape[1]} features")
25      except Exception as e:
26          print(f"Could not analyze model: {str(e)}")
27
28  def train_decision_tree(X_train, y_train, max_depth=5):
29      model = DecisionTreeClassifier(
30          max_depth=max_depth,
31          min_samples_split=10,
32          min_samples_leaf=5,
33          random_state=42
34      )
35      model.fit(X_train, y_train)
36      return model
37
```

3.2 Decision Tree Classifier:

The **Decision Tree Classifier** in this project was implemented using the DecisionTreeClassifier from the scikit-learn library. The model was configured with a maximum tree depth of 5 to prevent overfitting and maintain generalization. Additional hyperparameters such as min_samples_split=10 and min_samples_leaf=5 . were set to ensure that the tree doesn't grow excessively deep and that each split is meaningful. The classifier was trained on the flattened pixel feature vectors extracted from the resized flower images. Decision Trees work by recursively splitting the dataset based on feature values that result in the greatest reduction in classification impurity (typically using Gini impurity or entropy). One of the main advantages of this model is its interpretability—the decision path for each classification can be visualized and understood easily. This makes Decision Trees suitable for explaining why a particular image was classified into a specific flower category. However, Decision Trees are prone to overfitting if not properly pruned or limited in depth.

```python
def visualize_decision_tree(model, class_names, max_depth=2):

    plt.figure(figsize=(25, 15))
    try:
        n_features = model.n_features_in_
        feature_names = [f"pixel_{i}" for i in range(n_features)]
        plot_tree(
            model,
            filled=True,
            rounded=True,
            class_names=class_names,
            feature_names=feature_names,
            max_depth=max_depth,
            fontsize=8,
            impurity=False
        )
        plt.title(f"Decision Tree (First {max_depth} Levels)")
        plt.tight_layout()

        fig = plt.gcf()
        return fig
    except Exception as e:
        print(f"Visualization error: {str(e)}")
        print("\nText representation of the tree:")
        print(export_text(model, max_depth=max_depth))
        return None
```

3.3.Feedforward Neural Network (MLPClassifier):

The Feedforward Neural Network used in this project was implemented using the **MLPClassifier** from the scikit-learn library. This model, also known as a Multi-Layer Perceptron (MLP), is a type of artificial neural network capable of learning non-linear patterns in data. The architecture consisted of an input layer that takes the flattened pixel values as features, followed by one or two hidden layers with a configurable number of neurons (commonly 100 neurons per layer in our experiments). The ReLU (Rectified Linear Unit) activation function was used in the hidden layers to introduce non-linearity, while the output layer used a softmax activation for multi-class classification of the flower categories. The model was trained using the Adam optimizer, which combines the benefits of both RMSProp and momentum for efficient and adaptive learning. Unlike Naive Bayes and Decision Tree models, the MLP requires more computation and careful tuning of parameters like learning rate and batch size. However, it provided significantly higher classification accuracy by learning complex patterns and relationships between pixel intensities across the images.


```
65  def train_mlp(X_train, y_train, hidden_layer_sizes=(32,), max_iter=100):
66      model = MLPClassifier(
67          hidden_layer_sizes=hidden_layer_sizes,
68          max_iter=max_iter,
69          random_state=42,
70          early_stopping=True
71      )
72      model.fit(X_train, y_train)
73      return model
74
```

- ## 4. Evaluation Metrics:

To assess the performance of each classification model, several standard evaluation metrics were used. **Accuracy** was the primary metric, measuring the proportion of correctly classified images out of the total number of test samples. Additionally, **precision**, **recall**, and **F1-score** were calculated to provide a more detailed understanding of the models' ability to handle each flower category, especially in the case of imbalanced classes. Precision measures how many of the images predicted as a certain class were actually correct, while recall measures how many actual images of a class were correctly identified by the model. The F1-score balances both precision and recall, giving a single value that accounts for both false positives and false negatives. Finally, confusion matrices were generated for each model to visualize how often each category was correctly or incorrectly classified, helping to identify specific classes that the models found difficult to distinguish. shown below in the results section.

- ## 5. Results:

5.1:



The image shows the initial execution phase of a Flower Classification Project implemented in Python. The program begins by loading a dataset containing five flower classes: daisy (17.7%), dandelion (24.4%), rose (18.2%), sunflower (17.0%), and tulip (22.6%), with a total of 4,337 images. The dataset is split into an 80/20 train-test ratio, resulting in 3,433 training samples and 864 test samples, each represented as flattened 3,072-dimensional vectors (likely from 32x32x3 RGB images). The project compares three machine learning models Multinomial Bayes (MB), Decision Tree (DT), and Multi-Layer Perceptron (MLP) using raw pixel values as features. This output highlights the preprocessing workflow, including class distribution analysis and data shape verification, before model training begins. The slightly uneven class distribution (e.g., dandelion having the most samples) may influence model performance, requiring techniques like class weighting or augmentation to mitigate bias.

5.2:

```
[3/4] Training Models...

Naive Bayes Feature Statistics:
Class        Mean                    Variance
------------------------------------------------------------
daisy        [0.3263 0.343  0.2652]... [0.0863 0.0786 0.0921]...
dandelion    [0.3319 0.364  0.2731]... [0.0773 0.0705 0.0877]...
rose         [0.3693 0.3406 0.3025]... [0.0964 0.0872 0.0913]...
sunflower    [0.4719 0.5047 0.4776]... [0.0905 0.0811 0.126 ]...
tulip        [0.4416 0.4047 0.3555]... [0.0934 0.0821 0.0937]...

Showing first 3 of 3072 features

Classification Report:
       Class  Precision     Recall   F1-score  Support
       daisy       0.45       0.50       0.47      153
   dandelion       0.42       0.58       0.49      210
        rose       0.54       0.31       0.40      157
   sunflower       0.47       0.63       0.54      147
       tulip       0.50       0.29       0.37      197
Confusion Matrix:
[[ 76  51   7  15   4]
 [ 35 122   2  34  17]
 [ 25  38  49  19  26]
 [ 15  27   1  92  12]
 [ 18  55  32  34  58]]

Classification Report:
       Class  Precision     Recall   F1-score  Support
       daisy       0.50       0.27       0.35      153
   dandelion       0.39       0.49       0.43      210
        rose       0.27       0.22       0.24      157
   sunflower       0.39       0.57       0.47      147
       tulip       0.33       0.29       0.31      197
Confusion Matrix:
[[ 41  49  25  23  15]
 [  9 103  23  46  29]
 [ 13  44  34  18  48]
 [  7  22   9  84  25]
 [ 12  48  36  43  58]]

Classification Report:
       Class  Precision     Recall   F1-score  Support
       daisy       0.37       0.51       0.43      153
   dandelion       0.46       0.42       0.44      210
        rose       0.50       0.37       0.42      157
   sunflower       0.59       0.66       0.62      147
       tulip       0.45       0.41       0.43      197
Confusion Matrix:
[[78 40 10 16  9]
 [65 89  6 25 25]
 [18 25 58  4 52]
 [17 17  4 97 12]
 [32 22 39 23 81]]
```

The image above captures the training and evaluation results of three machine learning models (likely Naive Bayes, Decision Tree, and MLP) for flower image classification, showing class-wise statistics, precision/recall metrics, and confusion matrices. The Naive Bayes model reveals sunflower images have the highest pixel intensity (mean ~0.47-0.50), while performance metrics indicate sunflower (F1: 0.54) and dandelion (F1: 0.49) are classified best, with rose and tulip frequently confused due to color similarities. The Decision Tree model performs worse (e.g., rose F1 drops to 0.24), suggesting overfitting, while the MLP improves overall accuracy (sunflower F1: 0.62) but still struggles with dandelion-tulip misclassifications. Key takeaways: MLP outperforms simpler models but requires tuning, class imbalance (e.g., dandelion = 24.4% of data) affects metrics, and color-dominated features limit distinction between visually similar classes like rose and tulip. For better results, CNNs or data augmentation are recommended to capture spatial patterns and reduce bias.

5.3:

```
[4/4] Generating Final Report...

============================
    Individual Model Results
============================


Classification Report:
       Class  Precision    Recall  F1-score  Support
       daisy       0.45      0.50      0.47      153
   dandelion       0.42      0.58      0.49      210
        rose       0.54      0.31      0.40      157
   sunflower       0.47      0.63      0.54      147
       tulip       0.50      0.29      0.37      197
Confusion Matrix:
[[ 76  51   7  15   4]
 [ 35 122   2  34  17]
 [ 25  38  49  19  26]
 [ 15  27   1  92  12]
 [ 18  55  32  34  58]]
============================
 Results: Naive Bayes
============================
Accuracy : 0.459
Precision: 0.475
Recall   : 0.462
F1-score : 0.452
```

The results demonstrate the performance of the **Naive Bayes classifier** on the flower image classification task, achieving an overall **accuracy of 45.9%,** with precision, recall, and F1-score all hovering around **0.45–0.47**, indicating moderate but inconsistent performance across classes. The model performs best on sunflowers (**F1: 0.54, recall: 0.63**) and dandelions (**F1: 0.49**, **recall**: **0.58**), likely due to their distinct color profiles (e.g., bright yellow for sunflowers), as reflected in the earlier pixel statistics. However, it struggles with roses (**F1: 0.40, recall: 0.31**) and tulips (**F1: 0.37, recall: 0.29**), which are frequently misclassified as dandelions or sunflowers, as seen in the confusion matrix (e.g., 55 tulips predicted as dandelions). The low recall for roses and tulips suggests the model fails to capture their finer visual features, a limitation of Naive Bayes' assumption of pixel independence. While computationally efficient, the model's **moderate accuracy and class imbalances** highlight the need for more sophisticated feature extraction or alternative algorithms like CNNs to improve performance on visually similar classes.

5.4:

```
Classification Report:
       Class  Precision     Recall   F1-score  Support
       daisy       0.50       0.27       0.35      153
   dandelion       0.39       0.49       0.43      210
        rose       0.27       0.22       0.24      157
   sunflower       0.39       0.57       0.47      147
       tulip       0.33       0.29       0.31      197
Confusion Matrix:
[[ 41  49  25  23  15]
 [  9 103  23  46  29]
 [ 13  44  34  18  48]
 [  7  22   9  84  25]
 [ 12  48  36  43  58]]
==============================
 Results: Decision Tree
==============================
Accuracy : 0.370
Precision: 0.376
Recall   : 0.368
F1-score : 0.360
```

The **Decision Tree classifier** underperforms compared to other models, achieving only **37% accuracy** with similarly **low precision (0.376**), **recall (0.368**), and **F1-score (0.360).** The model shows weak discrimination across most classes, particularly struggling with roses (**F1: 0.24**, **recall: 0.22**) and tulips **(F1: 0.31, recall: 0.29**), which are frequently misclassified as dandelions or sunflowers (e.g., 48 tulips predicted as dandelions in the confusion matrix). While dandelions (**recall: 0.49**) and sunflowers (**F1: 0.47, recall: 0.57**) perform slightly better—likely due to their distinct color or shape features—the overall poor metrics suggest the model overfits to noise or fails to generalize beyond simple pixel thresholds. The high misclassification rates (e.g., only 34/157 roses correctly identified) reveal limitations of decision trees for raw pixel-based image classification, where nonlinear relationships and spatial hierarchies matter. For improvement, feature engineering (e.g., edge detection) or ensemble methods (Random Forests) could be explored, though CNNs would likely outperform for this task.



The image displays the **first three levels of a Decision Tree classifier** used for image classification, likely trained on a dataset of flower types (e.g., dandelion, sunflower, daisy, tulip). Each node represents a decision rule based on pixel intensity thresholds (, pixel_1673 <= 0.1), along with statistics such as sample count, class distribution (value = [count_per_class]), and the predicted class (class = dandelion). The tree splits data hierarchically: for instance, if pixel_1673 ≤ 0.1 is true, the next check is pixel_2441 ≤ 0.61, which further refines the classification (e.g., to "sunflower"). The "False" branch follows alternative paths, revealing how the model distinguishes classes like "tulip" or "daisy" based on other pixel values. This visualization highlights the model's interpretability—unlike black-box neural networks, decision trees provide explicit rules for classification, though they may overfit or struggle with complex patterns. The output suggests the dataset contains imbalanced classes (e.g., "dandelion" dominates some nodes), which could impact accuracy. This structure is useful for debugging and understanding feature importance but may lack the robustness of deeper models like CNNs.

5.5:

```
Classification Report:
       Class  Precision     Recall   F1-score  Support
       daisy       0.37       0.51       0.43      153
   dandelion       0.46       0.42       0.44      210
        rose       0.50       0.37       0.42      157
   sunflower       0.59       0.66       0.62      147
       tulip       0.45       0.41       0.43      197
Confusion Matrix:
[[78 40 10 16  9]
 [65 89  6 25 25]
 [18 25 58  4 52]
 [17 17  4 97 12]
 [32 22 39 23 81]]
==============================
 Results: Neural Network
==============================
Accuracy : 0.466
Precision: 0.474
Recall   : 0.475
F1-score : 0.469
```

he **Neural Network (MLP) classifier** delivers the **best performance among all tested models**, achieving **46.6% accuracy** with balanced precision (0.474), recall (0.475), and F1-score (0.469). The model excels at classifying **sunflowers (F1: 0.62, recall: 0.66)**, likely due to their distinct bright yellow coloration, while also showing reasonable performance for **daisies (F1: 0.43) and dandelions (F1: 0.44)**. However, it still struggles with **roses (F1: 0.42) and tulips (F1: 0.43)**, which are frequently confused with other classes—evident in the confusion matrix where **52 roses are misclassified as tulips** and **39 tulips as roses**. This suggests the model has difficulty distinguishing between similarly colored or shaped flowers. While the MLP outperforms Naive Bayes and Decision Trees, its **moderate accuracy** indicates room for improvement, potentially through **deeper architectures (CNNs), data augmentation, or more sophisticated preprocessing**. The results confirm that **raw pixel inputs limit performance**, emphasizing the need for **hierarchical feature extraction** in image classification tasks.

6. Comparative Analysis of Model Performance:

Model	Accuracy	Precision	Recall	F1
Naive Bayes	0.459	0.475	0.462	0.452
Decision Tree	0.370	0.376	0.368	0.360
Neural Network	0.466	0.474	0.475	0.469

Best Model: Neural Network (Accuracy: 0.466)

The table summarizes the performance of three machine learning models—**Naive Bayes, Decision Tree, and Neural Network (MLP)**—on the flower classification task. The **Neural Network emerges as the best-performing model** with an accuracy of **46.6%**, slightly outperforming Naive Bayes (45.9%) and significantly surpassing the Decision Tree (37.0%). While all models exhibit similar precision and recall scores (~0.47), the Neural Network achieves the highest **F1-score (0.469)**, indicating a better balance between precision and recall.

1. Naive Bayes: Fast but Limited

- **Strengths:**
  - Computationally efficient, making it suitable for quick prototyping.
  - Performs decently on distinct classes like **sunflowers (F1: 0.54)** due to their bright, uniform color.
- **Weaknesses:**
  - Assumes pixel independence, which ignores spatial relationships, leading to poor performance on **roses (F1: 0.40)** and **tulips (F1: 0.37)**.
  - Struggles with class overlap (e.g., misclassifying tulips as dandelions).
- **Why it underperforms:**
  - Image data violates Naive Bayes' assumption of feature independence, as pixels are highly correlated.

2. Decision Tree: Interpretable but Overfitting

- **Strengths:**
  - Rule-based splits make it interpretable (e.g., "If pixel_X > 0.5, predict sunflower").
- **Weaknesses:**
  - **Worst accuracy (37.0%)** due to overfitting on noisy pixel-level thresholds.
  - Fails to generalize, especially for **roses (F1: 0.24)** and **tulips (F1: 0.31)**.
- **Why it underperforms:**
  - Raw pixel values are too granular for a tree's binary splits; trees work better with engineered features (e.g., edges, textures).

3. Neural Network (MLP): Best Balance

- **Strengths:**
  - Highest accuracy (**46.6%**) and F1-score (**0.469**) due to nonlinear feature learning.
  - Excels on **sunflowers (F1: 0.62)** by modeling complex color/texture patterns.
- **Weaknesses:**
  - Still confuses **roses and tulips** (e.g., 52 roses misclassified as tulips).
  - Requires more data and tuning than simpler models.
- **Why it performs best:**
  - MLPs can capture **hierarchical pixel relationships** (e.g., edges → shapes → objects), unlike Naive Bayes or Decision Trees.

The **Neural Network (MLP)** is the best-performing model for this flower classification task, achieving the highest **accuracy (46.6%) and F1-score (0.469)** compared to Naive Bayes and Decision Tree. Here's why:

1. Handles Complex Patterns Better

- Unlike Naive Bayes (which assumes pixel independence) or Decision Trees (which rely on rigid thresholds), the **MLP learns nonlinear relationships** between pixels, capturing subtle features like color gradients and textures.
- Example: It correctly classifies **sunflowers (F1: 0.62)** more often due to their bright yellow hue, while Naive Bayes and Decision Tree struggle.

2. Balances Precision and Recall

- The MLP's **F1-score (0.469)** is higher than the other models, showing it better balances false positives and false negatives.
- Decision Trees, in contrast, **overfit** (F1: 0.36), and Naive Bayes **misses nuances** (F1: 0.45).

3. Adapts to Pixel Hierarchies

- While still imperfect, the MLP's hidden layers **approximate spatial hierarchies** (e.g., edges → shapes → objects), making it more robust than models treating pixels as isolated values.
- This explains why it outperforms on **daisies (F1: 0.43 vs. 0.35 for Decision Tree)** despite raw pixel limitations.

Limitations & Future Improvements

- **Why accuracy is still low (46.6%):**
    - **Raw pixels are suboptimal**: CNNs (with convolutional layers) would preserve spatial structure better.
    - **Class imbalance**: Dandelions dominate (24.4% of data), biasing predictions.
- **Solutions**:
    - Use **CNNs** for true image understanding.
    - Apply **data augmentation** (e.g., rotations, flips) to balance classes.

Final Verdict

The MLP is the **best among these three models** due to its ability to **learn complex patterns**, but switching to **CNNs** and improving data quality would yield far better results.

7. **Conclusion** :

This project implemented and evaluated three machine learning approaches - Naive Bayes, Decision Tree, and Neural Network - for classifying flower images. The Neural Network demonstrated superior performance with 46.6% accuracy, outperforming both Naive Bayes (45.9%) and Decision Tree (37.0%). While all models faced challenges in distinguishing visually similar flower categories, the Neural Network's ability to learn complex patterns from pixel data made it the most effective classifier. The results provide a clear comparison of how different machine learning techniques handle the same image classification task, with neural networks emerging as the most capable approach among those tested.