



STM32CubeMX LabHomework2.ioc: STM32F103C8Tx

File Window Help myST

Home > STM32F103C8Tx > LabHomework2.ioc - Pinout & Configuration > GENERATE CODE

Pinout & Configuration Clock Configuration Project Manager Tools

Software Packs Pinout

Pinout view System view

Categories A-Z

System Core >

Analog >

Timers >

RTC
TIM1
TIM2
TIM3
TIM4

Connectivity >

CAN
I2C1
I2C2
SPI1
SPI2
USART1
USART2
USART3
USB

Mode

Slave Mode Disable

Trigger Source Disable

☒ Internal Clock

Channel1 Disable

Channel2 Disable

Channel3 Disable

Channel4 Disable

Combined Channels Disable

Configuration

Reset Configuration

☒ NVIC Settings ☒ DMA Settings

☒ Parameter Settings ☒ User Constants

Configure the below parameters :

Search (Ctrl+F)

Counter Settings

Prescaler (PSC - 16 bits ... 7999

Counter Mode Up

Counter Period (AutoRelo. ... 499

Internal Clock Division (C ... No Division

STM32F103C8Tx LQFP48

VBAT
PC13
PC14
PC15
P00
NRST
VSSA
VDDA
MOTOR
B1
B2
PA0
PA1
PA2
PA3
PA4
PA5
PA6
PA7
PA8
PA9
PA10
PA11
PA12
PA13
PA14
PA15
RCC_OSC_IN
RCC_OSC_OUT
R02_S01

03:50 2025/07/01 17:09

اكتب هنا للبحث