

Address Translation Introduction

Hammurabi Mendes Fall 18

 Both virtual and physical address spaces are divided in "buckets"

- Both virtual and physical address spaces are divided in "buckets"
 - In the virtual space, they're called pages

- Both virtual and physical address spaces are divided in "buckets"
 - In the virtual space, they're called pages
 - In the physical space, they're called frames

- Both virtual and physical address spaces are divided in "buckets"
 - In the virtual space, they're called pages
 - In the physical space, they're called frames


Pages and frames have the same, fixed size

- Both virtual and physical address spaces are divided in "buckets"
 - In the virtual space, they're called pages
 - In the physical space, they're called frames

- Pages and frames have the same, fixed size
 - A power of 2: say $2^{12} = 4096$ B

- Both virtual and physical address spaces are divided in "buckets"
 - In the virtual space, they're called pages
 - In the physical space, they're called frames

- Pages and frames have the same, fixed size
 - A power of 2: say $2^{12} = 4096$ B
 - This prevents external fragmentation!



x86-64 gives you a 48-bit virtual address space:

Virtual

Address

Page # Offset

x86-64 gives you a 48-bit virtual address space:

Virtual

Address

Page # Offset

12 bits

x86-64 gives you a 48-bit virtual address space:

Virtual

Address

Page # Offset

12 bits

Page size: $2^{12} = 4096 \text{ B}$

x86-64 gives you a 48-bit virtual address space:

Virtual

Address

Page # Offset

36 bits 12 bits

Page size: $2^{12} = 4096 \text{ B}$

x86-64 gives you a 48-bit virtual address space:

Virtual

Address

Page # Offset

36 bits 12 bits

Page size: $2^{12} = 4096 \text{ B}$

Maximum process image: $2^{48} = 281474976710655 B = 256 TB$

Advantages over Segmentation

- Advantages over Segmentation
 - No external fragmentation
 - Only internal fragmentation: last page is not fully used

- Advantages over Segmentation
 - No external fragmentation
 - Only internal fragmentation: last page is not fully used
 - Can load code/data on demand as the process executes

- Advantages over Segmentation
 - No external fragmentation
 - Only internal fragmentation: last page is not fully used
 - Can load code/data on demand as the process executes
 - When the program references a non-mapped virtual address, the hardware generates a page fault (interrupt)

- Advantages over Segmentation
 - No external fragmentation
 - Only internal fragmentation: last page is not fully used
 - Can load code/data on demand as the process executes
 - When the program references a non-mapped virtual address, the hardware generates a page fault (interrupt)
 - The OS loads the page and resumes the program

- Advantages over Segmentation
 - No external fragmentation
 - Only internal fragmentation: last page is not fully used
 - Can load code/data on demand as the process executes
 - When the program references a non-mapped virtual address, the hardware generates a page fault (interrupt)
 - The OS loads the page and resumes the program
 - Out of memory? Store unused pages in the disk!

Drawbacks:


- Drawbacks:
 - Requires more space to translate address

- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!


- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space

- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space
 - Keeping track of free/used physical frames


- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space
 - Keeping track of free/used physical frames
 - Simplistically, a bitmap solves the problem




- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space
 - Keeping track of free/used physical frames
 - Simplistically, a bitmap solves the problem




- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space
 - Keeping track of free/used physical frames
 - Simplistically, a bitmap solves the problem



- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space
 - Keeping track of free/used physical frames
 - Simplistically, a bitmap solves the problem



- Drawbacks:
 - Requires more space to translate address
 - Naively, we need an entry for every page!
 - That's 262144 entries for a 1GB space
 - Keeping track of free/used physical frames
 - Simplistically, a bitmap solves the problem



Of course

we will use better data structures to tackle both problems

Multilevel Paging

Multilevel Paging


Never heard of a program using 256TB of memory


Multilevel Paging


- Never heard of a program using 256TB of memory
 - Page table is a sparse data structure


- Never heard of a program using 256TB of memory
 - Page table is a sparse data structure
 - Should be divided, with pieces allocated on demand!


- Never heard of a program using 256TB of memory
 - Page table is a sparse data structure
 - Should be divided, with pieces allocated on demand!


















































Each process has its own page-table structure

- Each process has its own page-table structure
- It's a tree, not a chain

- Each process has its own page-table structure
- It's a tree, not a chain
 - May have looked like a chain in the previous slides...

- Each process has its own page-table structure
- It's a tree, not a chain
 - May have looked like a chain in the previous slides...
 - But it's not! As your memory footprint increases, the more the structure looks like a tree

- Each process has its own page-table structure
- It's a tree, not a chain
 - May have looked like a chain in the previous slides...
 - But it's not! As your memory footprint increases, the more the structure looks like a tree
- On context-switch, change it completely


- Each process has its own page-table structure
- It's a tree, not a chain
 - May have looked like a chain in the previous slides...
 - But it's not! As your memory footprint increases, the more the structure looks like a tree
- On context-switch, change it completely
 - On x86-64, that means reassigning the CR3 register

- Each process has its own page-table structure
- It's a tree, not a chain
 - May have looked like a chain in the previous slides...
 - But it's not! As your memory footprint increases, the more the structure looks like a tree
- On context-switch, change it completely
 - On x86-64, that means reassigning the CR3 register
 - One-shot change

Alternative

(less important)

Paged Segmentation



Fim

*all images belong to their copyright owners, including the Computer History Museum, Wikipedia/Youtube users, or Recursive Books