Six maps between three definitions of system: Klir, Bunge and Mobus

Shingai Thornton

Working note, 15 October 2026

Orientation

Klir, Bunge and Mobus each define *system* formally. For three definitions there are six ordered pairs, and for each pair we ask: is there a map from the systems of one kind to the systems of the other, and does it lose information? This note answers all six under one reading of Klir, and sketches what changes under the other.

Two readings of Klir. Klir's Eq. (1.1) [6] defines $S = (T, R)$ with T "a set of things" and R "a relation (or, possibly, a set of relations) defined on T." His own examples in Chapter 2 use this in two incompatible senses (§1). We fix the *relational reading* ($R \subseteq T \times T$) for §§2–5 and return to the *product reading* ($R \subseteq \prod_i X_i$) in §7.

Method and purpose. The note compares the definitions as mathematical objects. Two of the three authors say their definitions are not mathematics for its own sake, and §8 records what each says the definition is for. Whether a map loses information is relative to what that purpose requires it to keep (Proposition 26).

Status tags. Every result carries one: [Lean] names a theorem in the Lean library [9]; [proof here] means the proof is given in this note and is not yet in Lean; [open] means no proof exists.

The answer in one paragraph. The three downward maps (Mobus → Bunge → Klir, and Mobus → Klir) exist, commute, and are not injective. More strongly, *no* map that keeps the things a system is made of can be injective (Theorem 20). The three upward directions exist only on exactly characterized subclasses (Propositions 14–17): Klir → Bunge needs a bond, Klir → Mobus needs irreflexivity, Bunge → Mobus needs four conditions. Where they exist they are sections: projecting back recovers the original exactly.

1 The two readings of Klir's definition

Klir's Chapter 2 examples split as follows.

Example (Klir 2001, Ch. 2)	T	R
Students, §2.2	the students	$R \subseteq T \times T$
Rectangle, Fig. 2.1	$\{A_x, A_y\}$, two intervals	$R \subseteq A_x \times A_y$
Random variable	$\{V, [0,1]\}$	$R \subseteq V \times [0,1]$
Finite-state machine	$\{X, Y, Z\}$, state sets	$R \subseteq X \times Z \times Y \times Z$

Only the students example is a relation *on* T. In the other three, T is a family of sets and R is a subset of the product of its members. That second form is the definition of Mesarović, as stated by Joslyn [5, Def. 5]: given sets $X_1, \ldots, X_n$, a system is any nonempty $S \subseteq \prod_i X_i$.

Example 1 (Two things)**.** Let $T = \{A, B\}$ where A and B are sets of states.

- Product reading: $R \subseteq A \times B$, a constraint on joint states. There are $2^{|A|\cdot|B|}$ of these.
- Relational reading: $R \subseteq T \times T = \{\langle A, A\rangle, \langle A, B\rangle, \langle B, A\rangle, \langle B, B\rangle\}$. There are $2^4 = 16$ of these, whatever A and B are.

With $|T| = 1$, $T = \{A\}$, the relational reading allows only $R = \varnothing$ or $R = \{\langle A, A\rangle\}$, while the product reading allows any $R \subseteq A$.

Example 2 (Three things)**.** Let $U = \{O, D, M\}$. The relational reading relates the three things: $R \subseteq U \times U$, a directed graph on U; an undirected graph is a set of 2-subsets, $G \subseteq \binom{U}{2} \subseteq 2^U$. The product reading constrains their states: $R \subseteq O \times D \times M$. For a single thing, $U = \{M\}$, the set $U \times U = \{\langle M, M\rangle\}$ is not $M \times M$.

The rest of the note keeps the two apart. $\mathbf{K}$ denotes the relational reading and $\mathbf{K}_\Pi$ the product reading.

2 Definitions

Fix a set α of things and a relation $\triangleright \subseteq \alpha \times \alpha$, read "acts on."

Definition 3 (Bond; Bunge 1979, §1.2)**.** Things a, b are *bonded*, Bonded(a, b), iff $a \triangleright b$ or $b \triangleright a$.

The relation $\triangleright$ is primitive here, as in Lean (`ActsOn`). Bunge gives it content in [3, Def. 5.31]: the action of x on y is the difference between y's history when acted on by x and its free history. That reading is not formalized.

Definition 4 (Klir, relational reading)**.** $\mathbf{K}$ is the set of pairs (T, R) with $T \subseteq \alpha$ and $R \subseteq T \times T$, ordered by $(T_1, R_1) \leq (T_2, R_2)$ iff $T_1 \subseteq T_2$ and $R_1 \subseteq R_2$. We write $\mathbf{K}^+ \supseteq \mathbf{K}$ for pairs with $R \subseteq \alpha \times \alpha$ unconstrained.

Lean: $\mathbf{K}$ is `Kernel` (the constraint is `dep_on`); $\mathbf{K}^+$ is `KlirSystem`.

Definition 5 (Bunge; 1979, Def. 1.1–1.2)**.** $\mathbf{B}$ is the set of triples $\sigma = \langle C, E, S\rangle$ with $C, E \subseteq \alpha$, $C \cap E = \varnothing$, $S \subseteq (C \cup E)^2$, and distinct $a, b \in C$ with Bonded(a, b). The order is the subsystem order: $\sigma_1 \leq \sigma_2$ iff $C_1 \subseteq C_2$, $E_2 \subseteq E_1$ and $S_1 \subseteq S_2$.

Lean: `ConcreteSystem`, `Subsystem`, preorder `instPreorderConcreteSystem`. The bonded pair need not lie in S.

Definition 6 (Mobus; 2022, revised 2025)**.** Fix types $\kappa, \mu, \pi, \tau, \eta, \delta$ (capacities, milieu, boundary properties, transforms, history, time scale). A *flow network* on α is a set of nodes and a set of edges $(s, t, k) \in \alpha \times \alpha \times \kappa$ between nodes, with $s \neq t$ for every edge. $\mathbf{M}$ is the set of tuples $\langle C, N, E, G, B, T, H, \Delta t\rangle$ with

- $C \subseteq \alpha$; N a flow network with node set C;
- $E = \langle O, m\rangle$ with $O \subseteq \alpha$, $O \cap C = \varnothing$, $m \in \mu$;
- $B = \langle p, I\rangle$ with $p \in \pi$, $I \subseteq C$;
- G a flow network whose nodes lie in $O \cup I$ and whose every edge runs between O and I (either way), with every $i \in I$ on some edge of G;

- $T \in \tau$, $H \in \eta$, $\Delta t \in \delta$.

Write $\rho(N) \subseteq \alpha^2$ for the pairs underlying N's edges, and $\rho(S) = \rho(N) \cup \rho(G)$ for the *total relation*. The order: $S_1 \leq S_2$ iff $C_1 \subseteq C_2$, $O_2 \subseteq O_1$, $\rho(S_1) \subseteq \rho(S_2)$.

The book's Eq. 4.1 is a 7-tuple without E; the environment $E = \langle O, M \rangle$ is added in Mobus's revisions manuscript. Lean: `MobusSystem`, `FlowNetwork.no_self_loops`, `IsBipartiteFlow`, `InterfacesCarryFlow`, `MobusSystem.totalRelation`, `MobusSubsystem`.

All three orders are preorders, so each kind of system forms a thin category; a monotone map is a functor. On $\mathbf{M}$ the order is not antisymmetric: systems differing only in $\mu, \pi, \tau, \eta, \delta$ or capacities are $\leq$ each other.


3 The three downward maps

Definition 7. $\pi_{BK} : \mathbf{B} \to \mathbf{K}^+$, $\langle C, E, S \rangle \mapsto (C, S)$. $\pi_{MK} : \mathbf{M} \to \mathbf{K}^+$, $S \mapsto (C, \rho(S))$. $\pi_{MB} : \mathbf{M}^\circ \to \mathbf{B}$, $S \mapsto \langle C, O, \rho(S) \rangle$, where $\mathbf{M}^\circ \subseteq \mathbf{M}$ is the set of systems with N nonempty and $s \triangleright t$ for every edge (s, t, k) of N.

Lean: `ConcreteSystem.toKlir`, `MobusSystem.toKlir`, `MobusSystem.toBunge` (hypotheses `FlowInducesAction`, nonempty edges).

Remark 8. π_{BK} and π_{MK} land in $\mathbf{K}^+$, not $\mathbf{K}$: S may contain pairs with an endpoint in E, and $\rho(G)$ always has an endpoint in O. They land in $\mathbf{K}$ exactly when $S \subseteq C^2$ (resp. when G has no edges). This is a defect of the current encoding, not of the three authors: the Klir side of the triangle should be $(C \cup E, S)$, or the internal part $(C, S \cap C^2)$. Every non-injectivity result below holds for all three choices.

Proposition 9 (The triangle)**.** *On* $\mathbf{M}^\circ$, $\pi_{BK} \circ \pi_{MB} = \pi_{MK}$. *[Lean: `triangle_commutes, by rfl`]*



Proposition 10 (Mobus → Bunge)**.**

(a) π_{MB} *is monotone.* *[Lean: `toBunge_preserves_subsystem`]*

(b) $\pi_{MB}(S)$ *depends only on* $(C, O, \rho(S))$. *[Lean: `toBunge_eq_of_structural_eq`]*

(c) If any of $\mu, \pi, \tau, \eta, \delta$ *has two elements,* π_{MB} *is not injective.* *[proof here]*

(d) If $\kappa, \mu, \pi, \tau, \eta, \delta$ *are singletons,* π_{MB} *is injective on systems whose* G *has no node outside the endpoints of its edges.* *[proof here]*

Proof. (c) Take $S \in \mathbf{M}^\circ$ and change only the milieu m (or p, T, H, Δt) to a different element. Both are in $\mathbf{M}^\circ$ and have the same $(C, O, \rho(S))$, so by (b) the same image.

(d) Let $\pi_{MB}(S) = \langle C, E, R \rangle$. Then C and $O = E$ are given. Every pair in $\rho(G)$ has an endpoint in O, and $O \cap C = \varnothing$, so $\rho(N) = R \cap C^2$ and $\rho(G) = R \setminus C^2$. With κ a singleton, an edge set is determined by its pairs, so N and the edges of G are determined; the nodes of N are C, and the nodes of G are its endpoints by assumption. By bipartiteness every edge of G has an endpoint in I, and every element of I lies on an edge, so $I = C \cap \{\text{endpoints of } G\}$. The remaining coordinates are the unique elements of singleton types. □

Remark 11. Proposition 10(d) says what Mobus → Bunge loses: exactly the parametric slots (milieu, boundary properties, transforms, history, time scale, capacities), plus the bookkeeping of isolated nodes of G. The split of S into internal and external flows, and the interfaces, are recoverable.

Proposition 12 (Bunge → Klir)**.**
(a) π_{BK} *is monotone.* *[proof here]*
(b) $\pi_{BK}(\sigma)$ *depends only on* (C, S). *[Lean: `toKlir_eq_of_composition_structure_eq`]*
(c) If some $\sigma = \langle C, E, S\rangle$ *has* $\alpha \setminus (C \cup E) \neq \varnothing$, π_{BK} *is not injective.* *[proof here]*

Proof. (a) $\sigma_1 \leq \sigma_2$ gives $C_1 \subseteq C_2$ and $S_1 \subseteq S_2$. (c) Pick $e \in \alpha \setminus (C \cup E)$. Then $\langle C, E \cup \{e\}, S\rangle \in \mathbf{B}$ (disjointness holds, $S \subseteq (C \cup E)^2 \subseteq (C \cup E \cup \{e\})^2$, the bonded pair is unchanged) and has the same image as σ. □

Proposition 13 (Mobus → Klir)**.** π_{MK} *is monotone and depends only on* $(C, \rho(S))$. *If some* $S \in \mathbf{M}$ *has* $\alpha \setminus (C \cup O) \neq \varnothing$, *or any parametric type has two elements,* π_{MK} *is not injective.* *[proof here]*

Proof. Monotone: by definition of the order. Adding an environment object $o \notin C \cup O$ that no flow touches, or changing a parametric coordinate, gives a different system with the same $(C, \rho(S))$. □

4 The three upward directions

An upward translation should be a *section*: a richer system that projects back to the given one. The question for each pair is exactly when one exists.

Proposition 14 (Klir → Bunge)**.** *For* $(T, R) \in \mathbf{K}$ *there is* $\sigma \in \mathbf{B}$ *with* $\pi_{BK}(\sigma) = (T, R)$ *iff* T *contains distinct* a, b *with* Bonded(a, b). *[proof here]*

Proof. ($\Leftarrow$) $\sigma = \langle T, \varnothing, R\rangle$: disjointness is trivial, $R \subseteq T^2 = (T \cup \varnothing)^2$, and a, b give the bond. ($\Rightarrow$) $\pi_{BK}(\sigma) = (T, R)$ forces $C = T$, and the bond condition of $\mathbf{B}$ gives distinct bonded $a, b \in T$. □

Remark 15. Lean proves ($\Leftarrow$) under a stronger hypothesis, that the bonded pair lies in R (`Kernel.HasBond`, `Kernel.toBunge`), together with $\pi_{BK} \circ s = \mathrm{id}$ (`Kernel.toBunge_toKlir`) and injectivity of s (`Kernel.toBunge_injective`). The section $s(T, R) = \langle T, \varnothing, R\rangle$ is monotone and is the least section: any other adds environment.

Proposition 16 (Klir → Mobus)**.** *Suppose* $\kappa, \mu, \pi, \tau, \eta, \delta$ *are inhabited. For* $(T, R) \in \mathbf{K}$ *there is* $S \in \mathbf{M}$ *with* $\pi_{MK}(S) = (T, R)$ *iff* R *is irreflexive.* *[⇐ Lean; ⇒ proof here]*

Proof. ($\Rightarrow$) $\rho(S) = \rho(N) \cup \rho(G)$, and N and G are both flow networks, so neither contains a pair (t, t). ($\Leftarrow$) Take $C = T$, N the edges of R with any capacity, $O = \varnothing$, G and I empty, any parametric values. Lean builds this for singleton parameter types: `Kernel.toMobus`, with `Kernel.toMobus_toKlir` and `Kernel.toMobus_injective`. □

Proposition 17 (Bunge → Mobus)**.** *Suppose the parametric types and* κ *are inhabited. For* $\sigma = \langle C, E, S\rangle \in \mathbf{B}$ *there is* $S' \in \mathbf{M}^\circ$ *with* $\pi_{MB}(S') = \sigma$ *iff*
(i) S *is irreflexive;*
(ii) no pair of S *has both endpoints in* E*;*

(iii) $a \triangleright b$ *for every* $(a, b) \in S \cap C^2$*;*
(iv) $S \cap C^2 \neq \varnothing$*.*

[proof here]

Proof. ($\Rightarrow$) $S = \rho(N) \cup \rho(G)$. Flow networks have no self-loops, giving (i). Pairs of $\rho(N)$ lie in C^2; pairs of $\rho(G)$ join $O = E$ to $I \subseteq C$; so none lies in E^2, giving (ii), and $\rho(N) = S \cap C^2$. Membership in $\mathbf{M}^\circ$ gives (iii) and (iv). ($\Leftarrow$) Let N have node set C and one edge per pair of $S \cap C^2$; it has no self-loops by (i). Let G have one edge per pair of $S \setminus C^2$; by (ii) and $S \subseteq (C \cup E)^2$ each joins E and C; its nodes are its endpoints. Let I be the endpoints of G in C, and $O = E$. All Mobus conditions hold, $\rho(N) \cup \rho(G) = S$, and (iii)–(iv) put the system in $\mathbf{M}^\circ$. □

Remark 18. Each condition marks a real difference. (i): Bunge allows self-action (his coupling matrices have a diagonal, 1979 §2.1); Mobus forbids it (Eq. 4.4, $k \neq o$). (ii): Bunge's structure may relate two environment things; Mobus's flows always touch the system. (iii): Bunge's structure may contain mere, non-bonding relations; an internal Mobus flow, read into Bunge, is an action. (iv): Bunge requires a bond, which in Mobus must be a flow.

5 No lossless translation

"Lossless" must be defined with care. Between bare sets of the same size there are always bijections, so "no injective map exists" is false in general. The right requirement is that a translation keep what the system is made of.

Definition 19. A map Φ from $\mathbf{B}$ (resp. $\mathbf{M}$) to $\mathbf{K}$ or $\mathbf{K}^+$ is *thing-preserving* if the T of $\Phi(\sigma)$ is the C of σ. A map $\mathbf{B} \to \mathbf{M}$ or $\mathbf{M} \to \mathbf{B}$ is thing-preserving if it keeps C.

All of $\pi_{BK}, \pi_{MK}, \pi_{MB}$ are thing-preserving.

Theorem 20 (No lossless thing-preserving map into Klir)**.** *Suppose* $|\alpha| \geq 7$*, and for (b) that* $\mu, \pi, \tau, \eta, \delta$ *are inhabited.*
(a) If α *contains a bonded pair* $a \neq b$*, no thing-preserving* $\Phi : \mathbf{B} \to \mathbf{K}$ *is injective.*
(b) No thing-preserving $\Phi : \mathbf{M} \to \mathbf{K}$ *is injective.*

[proof here]

Proof. Fix $T = \{a, b\}$. Elements of $\mathbf{K}$ with this T are the subsets of T^2, so there are $2^4 = 16$. (a) For every $E \subseteq \alpha \setminus T$, $\langle T, E, \varnothing \rangle \in \mathbf{B}$ (the bond does not need to lie in S). These are $2^{|\alpha|-2} \geq 32$ distinct systems, all sent to one of 16 elements. (b) For every $O \subseteq \alpha \setminus T$, the Mobus system with $C = T$, environment objects O, and N, G, I empty is in $\mathbf{M}$; again $2^{|\alpha|-2} > 16$. □

Remark 21. The theorem needs the relational reading $R \subseteq T \times T$, and it fails for the unconstrained $\mathbf{K}^+$ used in Lean: there the fibre over T has $2^{|\alpha|^2}$ elements, enough room to encode the environment in extra pairs. So the encoding Klir is given decides whether "Mobus cannot be translated losslessly into Klir" is provable. For $\mathbf{K}^+$ and $\mathbf{M}$, the same count works with the milieu once $|\mu| > 2^{|\alpha|^2}$.

Theorem 22 (Mobus $\to$ Bunge)**.** *If* $|\mu| > 2^{|\alpha|} \cdot 2^{|\alpha|^2}$*, no thing-preserving* $\mathbf{M} \to \mathbf{B}$ *is injective. If the parametric types and* κ *are singletons,* π_{MB} *is injective on systems with tight* G *(Proposition 10(d)).* *[proof here]*

Proof. For fixed C, Bunge systems are determined by $E \subseteq \alpha$ and $S \subseteq \alpha^2$, so there are at most $2^{|\alpha|} \cdot 2^{|\alpha|^2}$. Varying the milieu gives $|\mu|$ distinct Mobus systems with the same C. □

So the loss from Mobus to Bunge is exactly the parametric content, while the loss from Bunge or Mobus to relational Klir is forced by structure alone.

6 Summary of the six

Direction	Result	Status
Mobus → Bunge	π_{MB} on $\mathbf{M}^\circ$, monotone; loses exactly the parametric slots (Prop. 10, Thm. 22)	(a),(b) Lean; rest proof here
Bunge → Klir	π_{BK}, monotone, not injective; no thing-preserving map into $\mathbf{K}$ is injective (Prop. 12, Thm. 20)	(b) Lean; rest proof here
Mobus → Klir	$\pi_{MK} = \pi_{BK} \circ \pi_{MB}$; no thing-preserving map into $\mathbf{K}$ is injective (Prop. 13, Thm. 20)	triangle Lean; rest proof here
Klir → Bunge	section iff T has a bonded pair (Prop. 14)	⇐ Lean (stronger hypothesis); iff proof here
Klir → Mobus	section iff R irreflexive (Prop. 16)	⇐ Lean; ⇒ proof here
Bunge → Mobus	section iff (i)–(iv) (Prop. 17)	proof here

For every upward direction, section followed by projection is the identity, while projection followed by the least section is not (it empties the environment, the boundary and the parametric slots).

7 The product reading

Definition 23 (Klir, product reading; Mesarović, Joslyn 1995 Def. 5)**.** $\mathbf{K}_\Pi$ is the set of pairs (X, R) where $X = (X_i)_{i \in I}$ is a family of sets and $\varnothing \neq R \subseteq \prod_{i \in I} X_i$. The *constraint* is $\prod_i X_i \setminus R$.

A natural map to the relational reading sends a constraint to its pairwise dependency graph:

$$\gamma : \mathbf{K}_\Pi \to \mathbf{K}, \qquad (X, R) \mapsto \big(I,\ \{(i,j) : i \neq j,\ R_{ij} \neq R_i \times R_j\}\big),$$

where R_i and R_{ij} are the projections of R to X_i and to $X_i \times X_j$.

Proposition 24. *γ is not injective, and it does not detect all constraint: there is $R \neq \prod_i X_i$ with $\gamma(X, R)$ having no pairs.* *[proof here]*

Proof. Let $I = \{1, 2, 3\}$, $X_i = \{0, 1\}$, and $R = \{x : x_1 \oplus x_2 \oplus x_3 = 0\}$, four of the eight states. Each pairwise projection R_{ij} is all of $\{0, 1\}^2$, since for any values of two coordinates the third can be chosen. So $\gamma(X, R) = (I, \varnothing) = \gamma(X, \prod_i X_i)$, while $R \neq \prod_i X_i$. □

So a three-way constraint can be invisible to every relation among things. This is the precise sense in which the two readings of Klir differ.

Open. [open]

- The six maps under the product reading. Bunge's state-space representation (1979, §2.2) is a $\mathbf{K}_\Pi$ object: properties F_i with values in V_i, and a lawful state space properly inside $\prod_i V_i$ because "the components of $\mathbb{F}$ are lawfully interrelated." A map $\mathbf{B} \to \mathbf{K}_\Pi$ therefore needs Bunge's state functions, which $\mathbf{B}$ as encoded does not carry.
- Whether Bunge's state-space criterion for an aggregate (`IsProductAggregate`) is the statement that the lawful state set is the product of its one-coordinate projections, i.e. carries no constraint in Joslyn's sense.
- A Lean encoding of $\mathbf{K}_\Pi$, and of the propositions marked [proof here].

8 What each definition is for

The results so far compare the three definitions as mathematical objects. That is the method of this note, not the authors' account of their definitions, and two of them say so explicitly. This section records what each author says the definition is for, and restates the losslessness results relative to those purposes. Section numbers are the authors'.

8.1 Stated purposes

Klir. A system is a construct: "Every system is a construction based upon some world of experiences, and these, in turn, are expressed in terms of purposeful distinctions made either in the real world or in the world of ideas" [6, §2.3]. The stance is about knowledge and is neutral about what exists: constructivism "is not an ontological view (concerned with the existence and ultimate nature of reality), but an epistemological view" (§2.3). Eq. (1.1) itself "is weak because it is too general and, consequently, of little pragmatic value. It is strong because it encompasses all other, more specific definitions of systems" (Ch. 1). What the abstraction buys is method: "the abstraction from thinghood properties is useful. It leads to the development of methods that have broad, cross-disciplinary applicability" (§5.1). Klir separates this from mathematics: "the primacy of problems in systems methodology is in sharp contrast with the primacy of methods in applied mathematics" (§6.1). Theorems belong to "the various mathematical systems theories, each applicable to some class of systems" (§7.1).

Mesarović and Takahara. The mathematical program in the strict sense: "The interest in the present volume is strictly in the mathematical aspects of the theory" [7, Preface], and its aim is to establish "the minimal set of assumptions needed in order that a given property or relationship holds" (Ch. 1). This is the product reading of §7. Klir treats it as the same definition as his own: "a system is a family of sets and a relation defined on the sets" [6, §3.3].

Bunge. Ontology is assigned "the task of constructing the most general theories concerning such and only such [concrete] objects" [3, Intro. §2]. It is meant to be exact, its theories having "a definite mathematical structure" (Preface), and it proves theorems about the general scheme, such as [4, Thm. 1.1]: "(i) There are concrete systems. (ii) Every thing is a component of at least one system." Mathematics is a tool: "not the world but some of our ideas about the world are mathematical" [3, Ch. 3 §1.3]. His criterion for a lossless representation is strict, and he says it is never met: a representation is *accurate* iff it is bijective and every representing statement is true [1, Def. 3.3], and "As a matter of fact there are no accurate theoretical representations of real systems: every theory misses some possible states, or it includes some impossible states, or

the formulas of it are only approximately true" (Ch. 3). What he rejects is identifying a thing with a structure, not representing it by one: "things can only be represented (or misrepresented), and occasionally also manipulated. But the mistake is harmless if we are aware of it" (Ch. 3 §1.4). Accordingly $\langle C, E, S\rangle$ "is (or represents) a system" [4, §1.1], and is its "minimal model", which "will not suffice for quantitative purposes" (§1.2).

Mobus. "We will not be doing math, in the sense of proving theorems or the like" [8, §1.3.5]. The definition "will be used to guide analysis of systems, since the definition tells us what we should be looking for, and to build models of systems at various levels of abstraction" (§4.3), and it is the schema of a knowledgebase (§8.1). He names the difference from Klir and Wymore as one of purpose: "Both of their works were, however, devoted to a purely mathematical approach to defining system and then using the definition and the math to explore the mathematical implications. However, the approach taken in this book is quite different in purpose" (§4.3.3). Proof by others is not excluded: treating his principles "as true axioms is not precluded (indeed it is expected)" (§3.2, n. 13).

	A system is	The definition is for	A faithful map keeps
Klir	a construct of an investigator	methods that apply whatever the things are	systemhood, up to isomorphism (§2.4)
Mesarović	a mathematical object	theorems from minimal assumptions	what the theorem uses
Bunge	a concrete thing, which the triple represents	the most general theory of concrete things	C, E and S (the minimal model)
Mobus	a physical thing, whose description the tuple holds	analysis, models, a knowledgebase	what the model's purpose needs (§10.1)

Mobus states the last entry directly: "if our major interest is in predicting some future state of the system, any model that captures the main variables and transition functions may serve. But, at the same time, if our intent is to deeply understand how these transitions and behaviors are accomplished, then it might be necessary to include more details than are necessary for mere prediction" [8, §10.1].

All three keep the formal object apart from the concrete one. Klir: "the homomorphism cannot be defined mathematically since reality, or any aspect of it, is not a mathematical object" [6, §5.3]. Bunge: "a real system is not a mathematical object" [2, Ch. 6 §1]. Mobus: "The model is not the system" [8, §8.4]. Every map in this note is therefore a map between representations.

8.2 Lossless relative to an invariant

Definition 25. Let X, Y be classes of systems and $\iota : X \to V$ any function, the *invariant*. A map $\Phi : X \to Y$ is *lossless for* ι if $\iota = \iota' \circ \Phi$ for some $\iota' : Y \to V$; equivalently, $\Phi(x) = \Phi(x')$ implies $\iota(x) = \iota(x')$. Injectivity is losslessness for the identity.

Each purpose in the table names an invariant: on $\mathbf{K}$ and $\mathbf{K}^+$, the isomorphism class $[T, R]$ (Klir's general system, §2.4); on $\mathbf{B}$ and $\mathbf{M}$, the identity, since the minimal model is already minimal; on $\mathbf{K}_\Pi$, the constraint $c(X, R) = \prod_i X_i \setminus R$.

Proposition 26 (Losslessness depends on the purpose)**.** *(a) For $\sigma \in \mathbf{M}^\circ$, Klir's invariant is the same computed directly or through Bunge: $[\pi_{MK}(\sigma)] = [\pi_{BK}(\pi_{MB}(\sigma))]$.*

(b) Under the hypotheses of Theorems 20 and 22, no thing-preserving map $\mathbf{B} \to \mathbf{K}$ or $\mathbf{M} \to \mathbf{K}$, and no thing-preserving map $\mathbf{M} \to \mathbf{B}$, is lossless for the identity on its source.

(c) No map out of $\mathbf{K}_\Pi$ that factors through γ is lossless for c.

[(a) Lean; (b), (c) proof here]

Proof. (a) is the commuting triangle (Proposition 9). (b) restates the two theorems. (c) If $\Phi = \Psi \circ \gamma$, take R the parity relation of Proposition 24: $\Phi(X, R) = \Phi(X, \prod_i X_i)$, while $c(X, \prod_i X_i) = \varnothing \neq c(X, R)$. □

Read with the table: (b) says the realist's content does not survive the passage to a relation on things; (c) says the constraint the product reading is built to study does not survive the passage to relations among things, which is how Bunge's structure and Mobus's flows are encoded here. Neither direction is lossless outright. "Which definition is more general" has an answer only once a purpose fixes the invariant.

Remark 27. Klir's own vocabulary has the shape of §§3–4: "The isomorphic transformation from an interpreted system into the corresponding general system, which may be called an abstraction, is always possible. The inverse transformation, which may be called an interpretation, is not guaranteed and must be properly justified in each case" [6, §2.4]. The projections are always defined; the sections exist only on the subclasses characterized in Propositions 14–17.

Remark 28. Part (c) depends on the binary encodings. Bunge's S is "a nonempty set of relations on the union of C and E" [4, §1.1], which admits relations of any arity, and his state-space representation (§2.2) carries the lawful state set directly. An encoding of $\mathbf{B}$ with either would not factor through γ. [open]

Notation

Symbol	Meaning	Lean
α	the set of things	α (type)
$a \triangleright b$	a acts on b (primitive)	`ActsOn`
Bonded(a, b)	$a \triangleright b$ or $b \triangleright a$	`Bonded`
$\mathbf{K}$	Klir, relational reading: (T, R), $R \subseteq T^2$	`Kernel`
$\mathbf{K}^+$	as $\mathbf{K}$ with $R \subseteq \alpha^2$ unconstrained	`KlirSystem`
$\mathbf{K}_\Pi$	Klir, product reading: $\varnothing \neq R \subseteq \prod_i X_i$	none
$\mathbf{B}$	Bunge systems $\langle C, E, S \rangle$	`ConcreteSystem`
$\mathbf{M}$	Mobus systems $\langle C, N, E, G, B, T, H, \Delta t \rangle$	`MobusSystem`
$\mathbf{M}^\circ$	Mobus systems with nonempty N whose flows are actions	hypotheses of `toBunge`
C, E, S	composition, environment, structure	
N, G	internal and external flow networks	`internalNetwork`, `externalFlows`
O, m	environment objects, milieu	`environment`
p, I	boundary properties, interfaces	`boundary`
$\kappa, \mu, \pi, \tau, \eta, \delta$	types of capacities, milieu, boundary properties, transforms, history, time scale	type parameters
$\rho(S)$	total relation $\rho(N) \cup \rho(G)$	`totalRelation`
$\pi_{BK}, \pi_{MK}, \pi_{MB}$	the three projections	`toKlir`, `toBunge`
γ	pairwise dependency graph of a product-reading system	none
$\leq$	subsystem order on each kind	`Subsystem`, `MobusSubsystem`

References

[1] M. Bunge, *Semantics I: Sense and Reference*, Treatise on Basic Philosophy Vol. 1, Reidel, 1974.

[2] M. Bunge, *Semantics II: Interpretation and Truth*, Treatise on Basic Philosophy Vol. 2, Reidel, 1974.

[3] M. Bunge, *Ontology I: The Furniture of the World*, Treatise on Basic Philosophy Vol. 3, Reidel, 1977.

[4] M. Bunge, *Ontology II: A World of Systems*, Treatise on Basic Philosophy Vol. 4, Reidel, 1979.

[5] C. Joslyn, Semantic control systems, *World Futures* 45 (1995) 87–123.

[6] G. J. Klir, *Facets of Systems Science*, 2nd ed., Kluwer/Plenum, 2001.

[7] M. D. Mesarović and Y. Takahara, *General Systems Theory: Mathematical Foundations*, Academic Press, 1975.

[8] G. E. Mobus, *Systems Science: Theory, Analysis, Modeling, and Design*, Springer, 2022; revisions manuscript 2025.

[9] `systems-science-foundations`, Lean 4 library, commit `6ab7aba` (2026-10-10).