Topic/Title: Adding JavaScr	ript to Websites
Keywords/Questions:	Notes:
Inline Javascript	Inline JavaScript:-
<body onload=""></body>	-you put your JavaScript code inside the quotes in <body onload=""> <body onload="alert('Hello');"></body></body>
<style type="text/javascript"></td><td>-Don't make both quotes double quotes the inside one should a single quote. Otherwise, it won't work.</td></tr><tr><td>-When the code is loaded up, we see an alert that says Hello.</td></tr><tr><td rowspan=2>Internal Javascript</td><td>-Inline JavaScript has a lot of the downsides of inline CSS. It's not very modular, it's difficult to debug, and it's also not good practice as well, so try to avoid that it</td></tr><tr><td>you can.</td></tr><tr><td><style src="index.js" charset="utf-8"></td><td>Internal JavaScript:- we can include it by using a <script type="text/plain"> </script> tag inside the body. <h1>Hello</h1></td></tr><tr><td>External Javascript</td><td><pre> <script type="text/javascript"> alert("Hello"); </script> </body> </pre></td></tr><tr><td rowspan=2>styles.css</td><td>HTML code is executed line by line. We place our <i>sylesheet code inside the title</i> while we</td></tr><tr><td>place our <i>script</i> code at the end of the body. If we put our stylesheet at the end of the</td></tr><tr><td>ment.querySelector("h1").innerHTML="Hi";</td><td>the styling will be applied after all the code inside the body is executed. For example, the color of an h1 code might change at the end.</td></tr><tr><td>Summary: Inline JavaScript</td><td>t:- added in the body tag.</td></tr><tr><td></td><td>/ onload="alert('Hello');"> -The inside quotes should be ' '.</td></tr><tr><td>Internal JavaScr</td><td>ipt:- added in the body part and we enclose our code within the <script type="text/javascript"</td></tr><tr><td></script> tag.</td><td><pre><script type="text/javascript"> alert("Hello"); </script></pre></td></tr><tr><td>External JavaScr</td><td>ript:- add <script src="index.js" charset="utf-8"></script> to the end of the <body> part.</td></tr><tr><td><body> <h1>Hell <script </body></td><td>lo</h1> src="index.js" charset="utf-8"></script></td></tr></tbody></table></style>	

 $document.query Selector ("h1").inner HTML = "Good Bye"; :-write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h1 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ to \ Good \ Bye = "Good Bye"; -write it in index. js. It changes the \ h2 \ Hello \ t$

External JavaScript:-

- -Add <script src="index.js" charset="utf-8"></script> to the end of the <body> part.
- -We create a file outside called "index.js"

```
<body>
    <h1>Hello</h1>
    <script src="index.js" charset="utf-8"></script>
</body>
```

```
document.querySelector("h1").innerHTML = "Good Bye";
```

-This code right above changes the "Hello" h1 text to a Good Bye. It is written in the "index.js" file.