



# Python Plus



- Functions
- Modules & Packages
- Working with Files
- Errors & Exceptions Handling



# Acquaintance with Functions



# Table of Contents



- ▶ Introduction
- ▶ Calling a Function
- ▶ Built-in Functions



1

## Introduction to Functions

# What do you know about functions in Python?


Type at least 3 things...



Students, write your response!

Pear Deck Interactive Slide  
Do not remove this bar


## ► Introduction





# Introduction (review)


- Functions free us from chaos.



7



# Introduction (review)



8

8



## 2 Calling a Function

### Calling a Function Means Using It(review)

- ▶ Reading a function is very easy in Python.

```
multiply(2, 5)
```

**name** of  
the function

**arguments** of  
the function

# Calling a Function Means Using It(review)

- ▶ Calling a function :



```
1 a = 3
2 b = 5
3
4 multiply(3, 5)
```

# Calling a Function Means Using It(review)

- ▶ Calling a function :



```
1 a = 3
2 b = 5
3
4 multiply(3, 5)
```

```
1 15
```

## Calling a Function Means Using It(review) »

- ▶ Calling a function .



```
1 a = 3
2 b = 5
3
4 multiply(a, b)
```

## Calling a Function Means Using It(review) »



```
1 a = 3
2 b = 5
3
4 multiply(a, b)
```

```
1 15
```

# ▶ Calling `print()` Function (review)



- ▶ Calling `print()` function :

```
print("Say : I love you!")
```

**name** of  
the function

**argument** of  
the function

# ▶ Calling `print()` Function (review)



- ▶ Take a look at this pre-class example 🖱️

```
1 print('Say: I love you!')
2 print()
3 print('me too', 2019)
```



# Calling `print()` Function (review)



- Take a look at the example 

```
1 print('Say: I love you!')
2 print()
3 print('me too', 2019)
```

```
1 Say: I love you!
2
3 me too 2019
```



## 3 Built-in Functions

# Built-in Functions (review)

- ▶ The number of built-in functions :

In the latest version  
Python 3.9.1



69

# Built-in Functions (review)

- ▶ So far we have learned 

```
print(), int(), list(), input(), range()
```

- ▶ Some of them return bool type 

```
all(iterable), any(iterable), callable(object)
```

## Built-in Functions (review)

- Some of them help you convert data types 

```
bool(), float(), int(), str()
```

- For creating and processing the collection types. 

```
dict(), list(), tuple(), set(), len(), zip(),  
filter(function, iterable), enumerate(iterable)
```

## Built-in Functions (review)

- Some others tackle numbers. 

```
max(), min(), sum(), round()
```

- The others are built for special purposes. 

```
map(function, iterable, ...), eval(expression[,  
globals[, locals]]), sorted(iterable), open(),  
dir([object]), help([object])
```

As mentioned in the pre-class content, I took a look at the *built-in functions* in the official Python docs.




Students choose an option

Pear Deck Interactive Slide  
Do not remove this bar

## ► Built-in Functions



- Leaking snow water in your ear.





# Built-in Functions

## ► `all()` function.

```
1 names = ["susan", "tom", "False"]
2 mood = ["happy", "sad", 0]
3 empty = {}
4
5 print(all(names), all(mood), all(empty), sep="\n")
6
```

What is the output? Try to figure out in your mind...



Students, write your response!

Pear Deck Interactive Slide  
Do not remove this bar

25



# Built-in Functions

## ► `all()` function.

`all()` method returns:

Truth table for `all()`

When	Return Value
All values are true	True
All values are false	False
One value is true (others are false)	False
One value is false (others are true)	False
Empty Iterable	True

# Built-in Functions

## ► `all()` function.

`all()` method returns:

- **True** - If all elements in an iterable are true
- **False** - If any element in an iterable is false

```
1 names = ["susan", "tom", "False"]
2 mood = ["happy", "sad", 0]
3 empty = {}
4
5 print(all(names), all(mood), all(empty), sep="\n")
6
```

### Output

```
True
False
True
```

# Built-in Functions

## ► `any()` function.

```
1 listA = ["susan", "tom", False]
2 listB = [None, (), 0]
3 empty = {}
4
5 print(any(listA), any(listB), any(empty), sep="\n")
6
```

What is the output? Try to figure out in your mind...

# Built-in Functions



## any() function

The `any()` function returns a boolean value:

Condition	Return Value
All values are true	True
All values are false	False
One value is true (others are false)	True
One value is false (others are true)	True
Empty Iterable	False

True  
False  
False

# Built-in Functions



## any() function.

The `any()` function returns a boolean value:

- `True` if at least one element of an iterable is true
- `False` if all elements are false or if an iterable is empty

```
1 listA = ["susan", "tom", False]
2 listB = [None, (), 0]
3 empty = {}
4
5 print(any(listA), any(listB), any(empty), sep="\n")
6
```

Output

True  
False  
False



# Built-in Functions

## ► `filter(function, iterable).`

### `filter()` Parameters

`filter()` method takes two parameters:

- **function** - function that tests if elements of an iterable return true or false  
If None, the function defaults to Identity function - which returns false if any elements are false
- **iterable** - iterable which is to be filtered, could be `sets`, `lists`, `tuples`, or containers of any iterators



# Built-in Functions

## ► `filter(function, iterable).`

```
1 listA = ["susan", "tom", False, 0, "0"]
2
3 filtered_list = filter(None, listA)
4
5 print("The filtered elements are : ")
6 for i in filtered_list:
7     print(i)
8
```

What is the output? Try to figure out in your mind...



# Built-in Functions

## ► `filter(function, iterable)`.

```
1 listA = ["susan", "tom", False, 0, "0"]
2
3 filtered_list = filter(None, listA)
4
5 print("The filtered elements are : ")
6 for i in filtered_list:
7     print(i)
8
```

With `filter()` function as `None`, the function defaults to Identity function, and each element in `listA` is checked if it's `True`.

### Output

```
The filtered elements are :
susan
tom
0
```

WAY TO REINVENT YOURSELF

33

# Built-in Functions

## ► `enumerate(iterable, start=0)`.

### `enumerate()` Parameters

`enumerate()` method takes two parameters:

- **iterable** - a sequence, an iterator, or objects that supports iteration
- **start** (optional) - `enumerate()` starts counting from this number. If `start` is omitted, `0` is taken as `start`.

What is the output? Try to figure out in your mind...



# Built-in Functions

## ▶ `enumerate(iterable, start=0)`.

```
1 grocery = ['bread', 'water', 'olive']
2 enum_grocery = enumerate(grocery)
3
4 print(type(enum_grocery))
5
6 print(list(enum_grocery))
7
8 enum_grocery = enumerate(grocery, 10)
9 print(list(enum_grocery))
10
```

What is the output? Try to figure out in your mind...



# Built-in Functions

## ▶ `enumerate(iterable, start=0)`.

```
1 grocery = ['bread', 'water', 'olive']
2 enum_grocery = enumerate(grocery)
3
4 print(type(enum_grocery))
5
6 print(list(enum_grocery))
7
8 enum_grocery = enumerate(grocery, 10)
9 print(list(enum_grocery))
```

### Output

```
<class 'enumerate'>
[(0, 'bread'), (1, 'water'), (2, 'olive')]
[(10, 'bread'), (11, 'water'), (12, 'olive')]
```



# Built-in Functions

## ► `max(iterable)`, `min(iterable)`.

```
1 number = [-222, 0, 16, 5, 10, 6]
2 largest_number = max(number)
3 smallest_number = min(number)
4
5 print("The largest number is:", largest_number)
6 print("The smallest number is:", smallest_number)
7
```

What is the output? Try to figure out in your mind...



Students, write your response!

Pear Deck Interactive Slide  
Do not remove this bar

37

# Built-in Functions

## ► `max(iterable)`, `min(iterable)`.

```
1 number = [-222, 0, 16, 5, 10, 6]
2 largest_number = max(number)
3 smallest_number = min(number)
4
5 print("The largest number is:", largest_number)
6 print("The smallest number is:", smallest_number)
7
```

### Output

```
The largest number is: 16
The smallest number is: -222
```





# Built-in Functions

## ► `sum(iterable, start)`.

```
1 numbers = [2.5, 30, 4, -15]
2
3 numbers_sum = sum(numbers)
4 print(numbers_sum)
5
6 numbers_sum = sum(numbers, 20)
7 print(numbers_sum)
8
```

What is the output? Try to figure out in your mind...

### `sum()` Parameters

- **iterable** - iterable (list, tuple, dict, etc). The items of the iterable should be numbers.
- **start** (optional) - this value is added to the sum of items of the iterable. The default value of `start` is 0 (if omitted)

WAY TO REINVENT YOURSELF

39



# Built-in Functions

## ► `sum(iterable)`.

```
1 numbers = [2.5, 30, 4, -15]
2
3 numbers_sum = sum(numbers)
4 print(numbers_sum)
5
6 numbers_sum = sum(numbers, 20)
7 print(numbers_sum)
8
```

### Output

```
21.5
41.5
```



# Built-in Functions

## ► `round(numbers, ndigits)`.

```
1 print(round(12))
2 print(round(10.8))
3 print(round(3.665, 2))
4 print(round(3.675, 2))
5
```

What is the output? Try to figure out in your mind...

### `round()` Parameters

The `round()` function takes two parameters:

- **number** - the number to be rounded
- **ndigits (optional)** - number up to which the given number is rounded; defaults to 0

REINVENT YOURSELF

do not remove this bar

41



# Built-in Functions

## ► `round(numbers, ndigits)`.

```
1 print(round(12))
2 print(round(10.8))
3 print(round(3.665, 2))
4 print(round(3.675, 2))
5
```

### Output

```
12
11
3.67
3.67
```

42

# Built-in Functions

## ► `round(numbers, ndigits).`

```
1 print(round(12))
2 print(round(10.8))
3 print(round(3.665, 2))
4 print(round(3.675, 2))
5
```

Homework



3.67499999999999982236431605997495353221893310546875

12  
11  
3.67  
3.67



# THANKS!

## End of the Lesson

(Acquaintance with Func)

next Lesson

Defining a Function

click above

