Supplementary Material 5

The Open Software Stack Behind SWAFL Desktop

Languages and libraries and code and techniques and tools used to build the software and its documents

Naziru Halilu[1,2,*]

[1] Agricultural University of Athens, Athens, Greece

[2] Public University of Navarre, Pamplona, Spain

ORCID: 0009-0006-2324-9599

[*] Correspondence: halilunaziru73@gmail.com

Contents

S1 Purpose and scope . . . 2

S2 The software at a glance . . . 2

S3 Languages . . . 3

S4 Runtime stack . . . 4

S5 Libraries carried inside the program . . . 4

S6 Online services (optional) . . . 5

S7 Techniques used in the code . . . 5

S7.1 Structure of the program . . . 5

S7.2 Methods of the models . . . 6

S8 How the software is built . . . 7

S9 How the documents are built . . . 7

S10 Tools used to test and check . . . 8

S11 Licences and credit . . . 8

S12 Where to find it . . . 8

S1. Purpose and scope

This supplement stands alone. It belongs to the four articles of the series but is not tied to one of them: it records what SWAFL Desktop 1.1.0 is made of, in which languages it is written, which libraries and programs it carries, which techniques its parts use, and which tools were used to build, test and document it. Every figure below was counted on the source of version 1.1.0 or read from its `package.json`; where a number is approximate the text says so. Nothing in the stack is proprietary and nothing needs an account: all parts are open source or are the model and data that the series publishes.

S2. The software at a glance

SWAFL Desktop is one program with four layers, from the outside in.

1. **The desktop shell.** An Electron application (`main.js`, `preload.js`, `daisy-runner.js`, `serve.js`) that opens the window, saves and opens files, starts Daisy and opens the manual.
2. **The workbench.** About 90 JavaScript files in `app/js` (layers, properties, toolbox, dashboard, field on the map, sketch, the Daisy tabs, scientific figures, reports).
3. **The simulation engine.** A single page (`engine.html`, 1.5 MB, 7 225 lines) with the scripts of `app/engine` (crops, weather, the layers of the seasons, deterministic phenotyping). It runs in an inline frame and is joined to the workbench by a bridge.
4. **The Daisy model.** Daisy 7.1.14 for Windows with its library, packed unchanged beside the program and started as a separate process.

The same workbench and engine run in a web browser from a small local server (`npm run web`, or the `START_SWAFL_WEB` files) and online from the project page, so one code base serves the desktop, the browser and the web.

S3. Languages

Table S1: Languages and formats of the 1.1.0 source (the Daisy program and the manual PDF are not counted).

Language or format	Files	Lines (about)	Used for
JavaScript (ECMAScript)	90	14 100	workbench and engine scripts and desktop shell; every equation of the layers and designs
HTML and inline script	2	7 200	the window (`index.html`) and the simulation engine (`engine.html`)
CSS	4	630	the classic grey and navy look and the dashboard
Python 3.13	20	2 500	build tools of the data and of the manual (indexes and annotated screenshots and the equation table)
JSON	4	20 500	libraries and indexes read by the program (for example the manual index)
Markdown	47	31 000	the chapters of the manual
LaTeX	about 100	–	the four articles and their supplements (XeLaTeX with BibTeX)
Batch and shell scripts	7	80	start and build files for Windows and macOS and Linux
Daisy set-up language (`.dai`)	library	–	the model description that Daisy reads; written by the workbench and by the user

The model of Daisy itself is written in C++ and is used here as a compiled program; SWAFL does not change its source. No framework (React or Vue or Angular) and no bundler is used: the pages are plain JavaScript loaded in order, so that the program can be read and changed with a text editor.

S4. Runtime stack

Table S2: What runs when SWAFL.exe is opened.

Part	Version	Role
Electron	31 (range `^31.0.0`)	window and Chromium and Node.js in one package; the portable build is made with it
Chromium and Node.js	those of Electron 31	draw the canvases and run the JavaScript; Node gives file and process access to the shell only
Daisy	7.1.14	soil and plant and atmosphere process model (University of Copenhagen); its Windows folder carries the program, a Python 3.13 runtime for its Python functions and the C++ libraries it needs

The shell and the page talk through a small bridge (`preload.js`, `contextBridge`) with about 20 named handlers (save a file, open a file, open the manual, find Daisy, run a Daisy job, read a log, list the runs, fetch an address, and a few window commands). The page itself has no direct access to the disk.

S5. Libraries carried inside the program

Table S3: Third party code that is copied into the program (all under open licences; the licence text sits beside each file).

Library	Version	Licence	Use in SWAFL
Leaflet	1.9.4	BSD 2-Clause	the map of the field (satellite and street layers; outlining the field)
GeoTIFF.js	bundled	MIT	reading the Sentinel-2 bands of the field from cloud-optimised GeoTIFF files in the browser
SheetJS (xlsx)	0.18.5	Apache 2.0	importing weather from Excel and CSV and writing result tables
Daisy 7.1.14 with Boost and SuiteSparse and the GCC runtime	as shipped	GPL and LGPL families (see the Daisy folder)	the process model and its numerical libraries; started as a separate program, not linked into SWAFL

Everything else, including the figures, the report writer, the equations of the layers and the pipe hydraulics, is code written for this program.

S6. Online services (optional)

Table S4: Services the program can call. All are optional; without a connection every other number is computed on the computer.

Service	Used for
Open-Meteo (forecast and archive and geocoding and elevation)	weather of any place (measured archive and forecast); place names; elevation
Esri World Imagery and OpenStreetMap tiles	the satellite picture and the street map under the field
Microsoft Planetary Computer and Element 84 Earth Search (STAC)	Sentinel-2 L2A scenes for the vegetation and water indices
SoilGrids (ISRIC)	soil of the field and its retention curves
ESA WorldCover and Overpass (OpenStreetMap)	land cover and roads and water sources near the field
Nominatim and Photon	finding a place by name

S7. Techniques used in the code

S7.1 Structure of the program

- **Two halves joined by a bridge.** The workbench (shell page) and the engine (inline frame) share state through one object that the bridge sends to the engine and reads back; a setting changed in Properties is applied to every layer, the dashboard, the report and the designs, so they cannot disagree.
- **Canvas drawing.** Every picture (the field and the layers and the designs and the scientific figures) is drawn on a 2D canvas by code, so a figure can be exported as a picture or as numbers from the same data.
- **Lazy loading and guards.** Heavy scripts load when a tab is first opened; a guard module stops a failed script from freezing the window; long runs are cut into steps so the window stays responsive.
- **Provenance by construction.** Every number that is shown carries a label that leads to a numbered equation of the manual; the table of equations is generated from one file (`eqs.json`).
- **The rule of the Daisy layers.** A Daisy layer shows a result only from a Daisy run: results are read back from the log files of the run, never typed in.

- **Seeded randomness.** Projected seasons reuse the simulated seasons in a fixed random order from a seeded generator, so a projection is exactly repeatable.

S7.2 Methods of the models

- Soil hydraulics from texture with the Saxton and Rawls pedotransfer functions; the van Genuchten and Mualem retention and conductivity; the Richards equation solved in the soil column tab of the workbench.
- Surface irrigation: Kostiakov and Green and Ampt intake, Manning flow in the furrow, advance and recession by volume balance (Walker and Skogerboe).
- Pressurised irrigation: Hazen and Williams friction (C of 140 and 150), speed limits, pump head with lift and friction and working head, emitter and sprinkler layouts.
- Crop water: the FAO paper 56 daily balance with the crop coefficient method and the yield response of FAO paper 33; the FAO Penman and Monteith evapotranspiration.
- Satellite chain: scene search by STAC, band reading by range requests, cloud mask from the scene classification, vegetation and water indices per pixel, zonal statistics inside the outlined field.
- Experiment planning for Daisy: a catalogue of the factors Daisy can vary, a check of every design against it, an exact run budget, and a summary of the effect of every input from the logs.
- Verification by independent references: worked examples and held-out simulations and stored Daisy output, with the defect found in the denitrification function reported in the articles.

S8. How the software is built

Table S5: The build of the program.

Step	What happens
Start from source	`START_SWAFL.bat` (or `.command`) starts the program from the folder; it finds Node.js or fetches a portable copy of about 30 to 40 MB into `tools/node`
Install the build tools	`npm install` fetches Electron and electron-builder (24.13.3) listed in `package.json`
Build	`npm run get-app` runs electron-builder for Windows and writes `SWAFL.exe`
Targets	`portable` (one file and no installation) and `nsis` (an installer); a macOS `dmg` target is also defined
Packed into the file	the files of the shell and `app/**/*` and the icon; as extra resources the manual PDF and the `daisy` folder
Web build	none needed: `npm run web` serves the same `app` folder with `serve.js`

The program is not code-signed, so Windows may show a SmartScreen notice, which is cleared with More info and then Run anyway.

S9. How the documents are built

- **The manual.** The chapters are Markdown files. A Python tool (`build_single.py`) joins them, adds the icons of the layers and the equation table, and `pandoc` 3.1.3 with the XeLaTeX engine (TeX Live 2023) makes one PDF with DejaVu Serif and DejaVu Sans Mono. Other tools write the index of sections that the program uses to open the manual at the page in use, and `PyMuPDF` reduces the size of the pictures so that the PDF opens from GitHub on any device.
- **The screenshots of the manual.** Taken from the running program with Playwright and headless Chromium, then annotated by Python scripts (`annot.py`, `new_capture.py`).
- **The articles and supplements.** LaTeX with XeLaTeX and BibTeX (`build.sh`); the tables and the numbers are written into the source from the data files by scripts, so that the text, the tables and the figures use the same numbers.
- **The figures of the series.** Python with matplotlib and numpy and pandas and scipy and statsmodels and scikit-learn and openpyxl and Pillow, in the scripts of the repository.

S10. Tools used to test and check

- Playwright with headless Chromium drives the real program: every layer is opened and run, the dashboard and the figures are read back, and page errors in the console are counted (the target is none).
- Node.js scripts run the equations of the designs outside the page and compare them with worked examples.
- Python scripts compare results with the stored Daisy output (`compare_results.py`, `audit_numbers.py`) and check the data against a table of checksums (`CHECKSUMS.sha256`).
- A local static server (`python -m http.server`) serves the program for these tests so that the same files are tested as are shipped.

S11. Licences and credit

The code of SWAFL and the articles are by Naziru Halilu and are released under the MIT licence of the repository. Leaflet and GeoTIFF.js and SheetJS keep their own licences and notices in the folders `app/vendor` and `app/engine/vendor`. Daisy keeps its licence in its own folder and is credited to the Daisy project of the University of Copenhagen (Hansen et al., 2012). The online services keep the terms of their owners and are credited where their data appear.

S12. Where to find it

All parts are in the repository *Coupled Water Fluxes, Pore-Scale Dynamics, Precision Irrigation, Mulching Feedback Loops*: the program in `Software/v1.1.0/SWAFL_Desktop`, the manual in `Software/v1.1.0/Manual`, the articles and supplements in `Manuscripts/pdf`, and the data in `Data` and `Results`. The way to rebuild the program is given in the install chapter of the manual.

References

Søren Hansen, Per Abrahamsen, Christian T. Petersen, and Merete Styczen. Daisy: model use, calibration, and validation. *Transactions of the ASABE*, 55:1317–1335, 2012. doi: 10.13031/2013.42244.