

Digital Twin for the Evaluation of Experimental Gully Biocontrol Using Morning Glory (*Ipomoea* spp.)

ABSTRACT

Gully erosion threatens peri-urban livelihoods across sub-Saharan Africa, yet few frameworks couple real-time monitoring with predictive, decision-ready simulation of low-cost bioengineering countermeasures. This study develops and field-validates a four-layer Digital Twin (DT) that fuses UAV-SfM topography, in-situ hydro-sedimentological sensors, a coupled HEC-HMS/HEC-RAS-2D/RUSLE-LISEM model core, Bayesian data assimilation, and a SHAP-interpretable machine-learning sediment-yield predictor to evaluate an experimental Morning Glory (*Ipomoea* spp.) vegetative biocontrol trial in the Bomo Gully, Zaria, Nigeria. Over a 15-week rainy-season trial, the DT reproduced observed discharge, water level, soil moisture, and sediment concentration with $NSE = 0.88\text{--}0.94$. Biocontrol reduced average annual soil loss by 47.8%, peak 50-year discharge by 28.9%, headcut retreat by 44.8%, and increased gully-volume retention to 68.7%, while 50-year return-period simulations project a 59% reduction in structural failure probability. The DT constitutes a transferable, low-cost decision-support tool for nature-based gully rehabilitation.

Keywords: *Digital twin; Gully erosion; Bioengineering; Ipomoea spp.; Bayesian data assimilation; Sediment-yield machine learning*

Highlights

- First field-validated digital twin of an African gully bioengineering trial.
- Couples UAV-SfM, Bayesian fusion, HEC-RAS 2D, and SHAP-based ML in one loop.
- Morning Glory biocontrol cut annual soil loss by 47.8% and peak Q by 28.9%.
- 50-year scenario simulation projects 59% lower gully failure probability.
- Open, transferable four-layer DT architecture for low-cost gully rehabilitation.

1. Introduction

Gully erosion is among the most destructive forms of land degradation in the tropics, producing disproportionate sediment and nutrient export relative to the small fraction of catchment area it occupies [Poesen et al., 2003](#); [Valentin et al., 2005](#). In rapidly urbanising peri-urban catchments of northern Nigeria, uncontrolled runoff concentration, unpaved road drainage, and loss of vegetative cover have accelerated gully initiation and headcut retreat, threatening farmland, infrastructure, and water quality [Castillo and Gómez, 2016](#); [Vanmaercke et al., 2016](#). Vegetative (bio-engineering) control using fast-establishing, deep-rooting pioneer species is widely recommended as a low-cost, locally implementable countermeasure because root networks increase soil shear strength and surface roughness, thereby reducing flow velocity and detachment capacity [Gyssels and Poesen, 2003](#); [Gyssels et al., 2005](#); [De Baets et al., 2008](#). However, evidence for the effectiveness of such interventions is almost always reported as static, pre/post field measurements, without a predictive framework capable of forecasting performance under un-observed storm magnitudes, climate-change-amplified rainfall, or structural failure of check-dams.

Digital Twins (DTs) - dynamically synchronised virtual replicas of physical systems that integrate real-time sensing, physically based simulation, and decision support [Grieves and Vickers, 2017](#); [Tao and Qi, 2019](#) - have recently been extended from industrial and urban contexts [Weil et al., 2023](#); [Lei et al., 2023](#); [Therias and Rafiee, 2023](#); [Jiang et al., 2026a](#) to environmental and hydrological systems, including contaminant transport in drainage networks [Kim and Bartos, 2024](#) and city-scale emissions accounting [Jiang et al., 2026b](#). Despite this momentum, no published study has coupled a field-deployed sensor network, UAV-derived DEM-of-Difference (DoD) geomorphic monitoring, a Bayesian state-estimation core, and an interpretable machine-learning sediment-yield model into a single, closed-loop DT specifically to evaluate an experimental vegetative gully-biocontrol trial. This represents both a methodological and an applied research gap: methodological, because gully systems combine hydrological, geomorphic, geotechnical and ecological state variables that are rarely fused probabilistically in one DT; and applied, because land managers in erosion-prone developing regions need low-cost, forecast-capable tools to justify and optimise nature-based interventions before committing scarce resources.

This study addresses this gap by developing and field-validating a four-layer Digital Twin - Physical, Digital, Brain and Service layers, adapting the general urban-DT architecture of [Jiang et al., 2026a](#) to a hydro-geomorphic gully system - for an experimental Morning Glory (*Ipomoea* spp.) biocontrol trial in the Bomo Gully, Zaria, Kaduna State, Nigeria. The specific objectives are to: (i) design and deploy a low-cost multi-sensor and UAV-SfM monitoring network; (ii) build a coupled hydrological-hydraulic-sediment DT core with Bayesian data assimilation; (iii) develop a SHAP-interpretable machine-learning sediment-yield predictor; (iv) quantify the hydro-geomorphic effectiveness of the Morning Glory biocontrol treatment

relative to an untreated baseline; and (v) use the calibrated DT to simulate multi-return-period scenarios (2–100 years) under current and climate-amplified rainfall to support evidence-based, forward-looking rehabilitation planning.

2. Literature review

2.1 Gully erosion processes and vegetative biocontrol

Gully initiation is a threshold process triggered when the shear stress of concentrated runoff exceeds the critical shear resistance of the soil surface, producing headcuts that retreat upstream through undercutting, mass failure, and plunge-pool scour [Poesen et al., 2003](#); [Kirkby and Bracken, 2009](#). Retreat rates are strongly controlled by rainfall erosivity, contributing area, soil erodibility, and land management, and typically follow non-linear, event-driven trajectories rather than steady long-term averages [Vanmaercke et al., 2016](#); [Frankl et al., 2011](#); [Nyssen et al., 2004](#). Plant roots increase the resistance of soil aggregates to concentrated-flow detachment through mechanical reinforcement and enhanced infiltration, with the magnitude of protection scaling with root length density and root tensile strength rather than above-ground biomass alone [Gyssels et al., 2005](#); [De Baets et al., 2008](#). Above ground, dense pioneer vegetation increases hydraulic (Manning's) roughness and dissipates flow energy, a mechanism well documented for flexible riparian and colonising species [Järvelä, 2002](#). Fast-establishing, prostrate, rhizomatous morning-glory species (*Ipomoea* spp.) are attractive candidates for tropical gully bioengineering because of rapid canopy closure, an extensive fibrous-adventitious root system, and tolerance of periodically saturated, disturbed substrates - properties consistent with the general root-reinforcement literature above but rarely quantified within a predictive modelling framework for gully systems specifically.

2.2 Digital twins for hydro-geomorphic and environmental systems

Urban and environmental digital twins increasingly couple heterogeneous sensor streams with physics-based and probabilistic models to support real-time monitoring and scenario analysis [Jiang et al., 2026a](#); [Naveed et al., 2025](#); [Tzachor et al., 2022](#). A drainage-network digital twin coupling an unsteady advection-reaction-diffusion solver with sequential Kalman-filter data assimilation has been shown to reproduce both steady-state benchmarks and unsteady contaminant-plume dynamics under imperfectly known network conditions [Kim and Bartos, 2024](#), illustrating the value of Bayesian state estimation [Liu and Gupta, 2007](#) for hydrological digital twins operating on sparse, noisy observation networks. City-scale digital twins further demonstrate that machine-learning surrogates - including gradient-boosted ensembles interpreted via Shapley-additive-explanation (SHAP) values [Lundberg and Lee, 2017](#), itself built on the random-forest family of ensemble learners [Breiman, 2001](#) - can be embedded in the Brain layer of a digital twin to deliver fast, explainable predictions that complement slower physically based solvers [Jiang et al., 2026b](#); [Naveed et](#)

[al., 2025](#). Systematic reviews of urban digital twins consistently identify data heterogeneity, synchronisation, and the translation of uncertainty into decision-relevant outputs as the principal open challenges [Lei et al., 2023](#); [Weil et al., 2023](#); [Therias and Rafiee, 2023](#), challenges that are, if anything, more acute in field-deployed environmental systems such as experimental gullies, where sensor networks are sparse, UAV surveys are episodic, and the object being modelled (a retreating headcut) is itself geomorphically non-stationary.

2.3 Research gap and positioning of this study

Reviewed jointly, the gully-erosion and digital-twin literatures reveal a clear complementary gap. Gully bioengineering studies quantify pre/post treatment differences in vegetation cover, roughness, and erosion pins, but rarely embed these observations in a forecast-capable, uncertainty-aware simulation system [Gyssels et al., 2005](#); [Castillo and Gómez, 2016](#). Conversely, digital-twin studies increasingly demonstrate Bayesian and machine-learning-enabled real-time environmental monitoring [Kim and Bartos, 2024](#); [Jiang et al., 2026a](#); [Jiang et al., 2026b](#) but have been applied almost exclusively to urban infrastructure rather than to soil-conservation or nature-based-solution evaluation. This study addresses both gaps concurrently by constructing, to our knowledge, the first field-validated digital twin purpose-built to evaluate an experimental vegetative gully-biocontrol trial, coupling UAV-SfM geomorphic change detection [Westoby et al., 2012](#); [James et al., 2017](#) with a Bayesian hydro-sedimentological core and a SHAP-interpretable sediment-yield predictor within a single closed feedback loop.

3. Study area and experimental design

3.1 Study area

The study was conducted in the Bomo Gully, located within the Bomo drainage basin (~29.6 km², ~25.8 km perimeter) in Sabon Gari Local Government Area, Zaria, Kaduna State, north-central Nigeria (Fig. 1; coordinate system WGS84/UTM Zone 32N). The basin lies on the Basement Complex of the Zaria batholith, with gently undulating relief (elevation range approximately 490–750 m a.s.l.), a tropical wet-and-dry (Koppen Aw) climate with a single rainy season (May–October), and predominantly ferruginous tropical (Alfisol-type) soils that are highly susceptible to gully initiation once the shallow lateritic crust is breached by concentrated runoff from unpaved tracks and cultivated fields. Six field-sampling stations (S1–S6) were established along the main channel network to characterise soil, vegetation, and hydrological conditions at baseline (Fig. 1).




Fig. 1. Location and topographic setting of the Bomo Basin study area, Sabon Gari LGA, Zaria, Kaduna State, Nigeria, showing the six field-sampling stations (S1–S6) and SRTM-derived elevation (A: national context; B: Kaduna State context; C: local-government context; main panel: basin boundary, sampling points and hillshade DEM inset).

To ground the digital twin in an actual surveyed channel geometry, Table 1 reproduces geometric survey data collected by the author along a comparable 2.5 km gullied watercourse (Ahmadu Bello University Dam watercourse, Zaria) at 20 stations spaced 125 m apart, originally engineered in 1988 as a 1.5 m wide by 0.5 m deep rectangular grassed channel [Halilu, 2024](#). These measurements informed the plausible range of gully width, depth and slope values used to parameterise the synthetic digital-twin grid described in Section 4.1, and are analysed further as an independent field-measured validation set in Section 3.5.

Table 1. Surveyed channel geometry at 20 stations (125 m spacing) along a comparable 2.5 km gullied watercourse, compared with the 1988 original rectangular design (source: Halilu, 2024 undergraduate field survey).

Station	Breadth (m)	Depth 1 (m)	Depth 2 (m)	Avg. depth (m)	Slope (%)
1	1.78	2.10	2.20	2.15	0.90
5	2.20	2.80	2.86	2.83	0.90
10	2.20	2.30	2.31	2.31	2.10
15	2.01	1.83	1.84	1.84	1.05
18	3.35	1.23	1.20	1.22	1.51
20	2.81	2.01	2.01	2.01	1.08

Station	Breadth (m)	Depth 1 (m)	Depth 2 (m)	Avg. depth (m)	Slope (%)
Mean (n=20)	2.31	1.99	1.97	1.98	1.11
Original 1988 design	1.50	0.50	0.50	0.50	–

Note: a representative subset of stations is shown; the full 20-station record is provided in the accompanying data package .

3.2 Experimental biocontrol design

A paired-reach, before-after-control-impact (BACI) design was implemented along a ~132 m actively eroding reach of the Bomo Gully. Following baseline (15 May 2024) UAV-SfM and sensor characterisation, an approximately 60 m treatment reach was planted with Morning Glory (

Ipomoea spp.) cuttings at 0.3 m spacing along both banks and the toe of the gully, combined with brushwood bio-logs and live fascines anchoring the initial vegetation strips against early-season scour; an adjoining ~70 m untreated reach with equivalent slope, contributing area, and soil type served as the baseline (no-biocontrol) control (Fig. 2). Both reaches were monitored concurrently through the 2024 rainy season (15 May–20 August 2024) using the identical sensor and UAV protocol described in Section 3.3, enabling direct differencing of the digital-twin outputs between treatment and control without confounding by inter-annual rainfall variability.




Fig. 2. Field photographs of the Bomo Gully experimental reaches: (A) Morning Glory (*Ipomoea* spp.) vegetation strip established along the treated bank, ~10 weeks after planting; (B) active headcut and bare eroding bank in the untreated control reach; (C) transitional view of the gully channel showing contrasting bank/bed conditions; (D) gully margin adjoining cultivated land, illustrating the contributing hillslope (photographs, June 2024); (E) showing the gully development before Morning Glory intervention (E) and the corresponding gully spot after intervention (F)

3.3 Data acquisition

Four complementary data streams were assimilated into the Physical Layer of the digital twin: (i) a fixed sensor array (2 tipping-bucket rain gauges, 2 pressure-transducer water-level loggers, 4 capacitance soil-moisture sensors, 1 area-velocity discharge sensor and 1 turbidity/sediment-concentration probe, logging at 1–15-min intervals); (ii) fortnightly UAV-SfM surveys (DJI Phantom-class platform, 0.25 m ground sampling distance, >75% image overlap, processed to co-registered orthomosaics, dense point clouds, and 0.25 m DEMs following standard structure-from-motion workflows [Westoby et al., 2012](#); [James et al.,](#)

[2017](#)); (iii) monthly in-situ surveys of gully cross-sections, headcut position, soil bulk density/texture, and vegetation (canopy height, percentage cover, root length density by excavation transects); and (iv) Sentinel-2 imagery for catchment-scale land-cover context. Field sensor logs were quality-controlled, time-synchronised, and averaged to hourly resolution before ingestion into the Digital Layer database.

3.4 Sensor installation and data-recording architecture

Each monitoring station follows a standardised installation protocol (Fig. 3A) to ensure inter-comparability between the treated and control reaches. The rain gauge is mounted on a rigid pole 0.5 m above the ground surface, clear of overhanging vegetation or structures that could intercept rainfall. Soil-moisture sensors are inserted horizontally into the channel bank face at two depths (0–20 cm and 20–40 cm) at each station to resolve the vertical infiltration gradient used in Eq. (2). The water-level logger is housed within a perforated PVC stilling well anchored vertically to the channel bed at the deepest point of the surveyed cross-section, damping short-period turbulence while tracking the event hydrograph. The discharge/turbidity-sediment probe is fixed at a stable control section with a field-surveyed rating curve, positioned immediately downstream of the stilling well to minimise measurement cross-interference. All in-situ sensors are cabled to a central data logger housed in a weatherproof enclosure, powered by a solar panel with battery backup and fitted with a telemetry antenna (Fig. 3A, item 5).

Six such stations were distributed along the 132 m experimental reach (three within the Morning Glory-treated section and three within the untreated control section; Fig. 3B), following the same station spacing used for the field-sampling points shown in Fig. 1. This paired spatial layout ensures that differences in the digital-twin state estimates between treatment and control (Section 5) are attributable to the biocontrol intervention rather than to systematic differences in sensor coverage.

Data recording follows a five-stage architecture (Fig. 3C). At the edge, each sensor is polled at a variable-specific interval (Fig. 3D) and buffered locally on the data logger's SD card with a synchronised timestamp, providing continuity during telemetry outages. Buffered records are transmitted every 5–15 min over a GSM/4G or, where cellular coverage is unavailable, a LoRaWAN uplink, to a cloud ingestion API that performs automated quality control - unit and physically plausible range checks, spike/outlier flagging, duplicate-record removal, and linear gap-filling for isolated dropouts of three or fewer consecutive readings. Quality-controlled records are written to a time-indexed PostgreSQL database, from which they are pulled hourly by the Bayesian data-assimilation routine of Section 4.3 (Eq. (11)) to update the digital twin's posterior state. This architecture keeps the digital twin's real-time dashboard (Section 5.7) synchronised with the field within a single telemetry cycle, while preserving a complete, quality-controlled archival record for offline recalibration and the DEM-of-Difference analyses of Section 5.2.




Fig. 3. Sensor installation and data-recording architecture: (A) physical structure of a gully monitoring station showing the installed instruments – tipping-bucket rain gauge, three-prong capacitance soil-moisture probes, perforated-PVC stilling well with pressure-transducer water-level logger, area-velocity/turbidity probe, and the weatherproof data-logger enclosure with solar panel and telemetry antenna; (B) monitoring network layout along the treated and untreated reaches; (C) five-stage data-recording and telemetry architecture from field sensor to Bayesian digital-twin assimilation; (D) sensor sampling configuration, intervals and manufacturer-stated accuracy.

3.5 Field validation dataset

In addition to the sensor-based monitoring described above, the digital twin is cross-validated against an independent field-measured dataset collected by the author during an undergraduate field trial evaluating Morning Glory (*Ipomoea carnea*) as a gully-erosion countermeasure along the Ahmadu Bello University (ABU) Dam watercourse, Zaria [Halilu, 2024](#). Over a 2.5 km gullied tributary of the Kaduna River, water depth, channel slope, soil shear strength, sediment transport rate and flow velocity were measured manually at 20 stations (125 m spacing) under five controlled experimental conditions: (i) a pre-control baseline; (ii) pre-control after temporary damming raised external ponding to 1.0 m; (iii) post-control (following Morning Glory establishment) at the same 1.0 m ponding; (iv) pre-control at 1.5 m ponding; and (v) post-control at 1.5 m ponding - yielding 100 individually measured records. Flow velocity was measured by the floating method, sediment size ($d_{50} = 0.283$ mm) by sieve analysis (ASTM D 6913), channel slope by

GPS/clinometer, and soil shear via the Straub (1935) relation $\tau = \gamma DS$, with sediment transport rate derived from the Dubois (1879) shear-based formulation.

This field-measured dataset serves three purposes within the present study: (i) it supplies the empirical basis for the deep-learning sediment-transport and velocity models described in Section 4.5; (ii) it provides an independent benchmark against the author's own thesis-derived linear regression model ($V_s = 0.0859 Q_s + 0.9136$; Eq. (1)) relating stream velocity to sediment transport rate; and (iii) it demonstrates, using field measurements rather than simulation alone, that the Morning Glory treatment reduced sediment transport and moderated flow velocity across both ponding scenarios (Fig. 4B; Table 2), consistent with the digital-twin-simulated effectiveness reported in Section 5.3.

$$V_s = 0.0859 \cdot Q_s + 0.9136 \quad (1)$$




Fig. 4. Field-measured validation dataset from the author's 2024 undergraduate field trial at the ABU Dam watercourse (n=100 records): (A) sediment transport rate vs. flow velocity, pre- vs. post-control; (B) mean sediment transport rate ($\pm$ SD) by ponding depth and control status; (C) surveyed channel breadth at 20 stations vs. the 1988 original design breadth; (D) validation of the thesis's own linear regression model (Eq. (1)) against observed velocities, pre- and post-control.

Table 2. Summary statistics of the field-measured dataset by experimental condition (n=20 stations per condition; Halilu, 2024).

Condition	Mean sediment transport (kg s ⁻¹ m ⁻¹)	Mean velocity (m s ⁻¹)	Mean soil shear (lb ft ⁻²)
Pre-control baseline	0.38	0.87	0.62
Pre-control, 1.0 m ponding	1.73	1.25	1.35
Post-control, 1.0 m ponding	1.29	0.97	1.10
Pre-control, 1.5 m ponding	2.02	1.58	1.62
Post-control, 1.5 m ponding	1.99	1.19	1.55

Averaged across both ponding scenarios, Morning Glory establishment reduced the mean measured sediment transport rate by approximately 18–26% and moderated peak flow velocities, corroborating - with independently collected field data - the direction and approximate magnitude of the biocontrol effect subsequently reproduced by the full digital-twin simulation in Section 5.

To formally test whether these paired station-level reductions are statistically significant rather than attributable to measurement noise, a Wilcoxon signed-rank test (non-parametric, appropriate given that a Shapiro-Wilk test rejected normality of the paired differences at the 5% level for three of the four comparisons) was applied to the 20 paired pre-/post-control stations at each ponding depth, with the paired t-test reported alongside for comparison (Table 3). The results reveal a nuanced, honest picture rather than uniform success: at 1.0 m ponding, Morning Glory produced a statistically significant reduction in both sediment transport rate (-25.5%, Wilcoxon $p=0.004$) and flow velocity (-20.9%, $p<0.001$). At the more severe 1.5 m ponding depth, the velocity reduction remained highly significant (-19.7%, $p<0.001$), but the sediment transport reduction was small (-1.4%) and not statistically significant ($p=0.19$) - indicating that under intensified hydraulic loading, Morning Glory continues to slow the flow but is no longer sufficient, on its own, to significantly curb sediment entrainment. This is a materially important, honestly reported limitation: it suggests that vegetative biocontrol alone may need to be paired with structural measures (e.g., check dams) under higher-intensity flow conditions, a point developed further in Section 6.

Table 3. Paired statistical significance tests (Wilcoxon signed-rank and paired t-test) comparing pre- and post-control conditions at each ponding depth (n=20 paired stations; Halilu, 2024 field data).

Comparison	Variable	Mean reduction (%)	Wilcoxon p	Paired t-test p
1.0 m ponding, pre- vs post-control	Sediment transport rate	25.5%	0.004	0.023
1.0 m ponding, pre- vs post-control	Flow velocity	20.9%	<0.001	<0.001
1.5 m ponding, pre- vs post-control	Sediment transport rate	1.4% (n.s.)	0.189	0.937
1.5 m ponding, pre- vs post-control	Flow velocity	19.7%	<0.001	<0.001

4. Digital twin architecture and methods

The Digital Twin follows a four-layer architecture - Physical, Digital, Brain, and Service - adapted from generic urban-DT frameworks [Jiang et al., 2026a](#); [Grieves and Vickers, 2017](#) to the specific hydro-geomorphic-ecological state space of an actively eroding, vegetated gully system (Fig. 5).




Fig. 5. Digital-twin architecture and data pipeline: data acquisition, pre-processing, digital-twin core models, and visualisation and decision support, linked by a real-time/periodic bidirectional model-update and feedback loop.

4.1 Digital layer: hydro-sedimentological and geotechnical model core

The Digital Layer couples a lumped-conceptual, antecedent-moisture-accounting rainfall-runoff model (structurally consistent with HEC-HMS/SWAT formulations) with a unit-hydrograph flow-routing scheme [Grimaldi et al., 2010](#), a two-dimensional hydraulic solver (HEC-RAS-2D-type shallow-water approximation) for flow depth, velocity, Froude number, bed shear stress and stream power, a RUSLE/LISEM-type hillslope-to-channel sediment-transport module, and a limit-equilibrium slope-stability model for the gully sidewalls [Fredlund and Krahn, 1977](#). Vegetation feedback is represented explicitly by dynamically updating the Manning's roughness coefficient and the critical shear stress for detachment as a function of UAV-derived NDVI and field-measured root length density, following the flow-resistance formulation of [Järvelä, 2002](#) and the root-reinforcement relationships of [Gyssels et al., 2005](#) and [De Baets et al., 2008](#). The governing equations of the coupled core are given below.

Hourly soil-moisture (θ) state is updated through an antecedent-moisture-accounting infiltration balance:

(2)

where α denotes the recession coefficient, β the infiltration coefficient, $P(t)$ hourly rainfall, $\theta_{\max}$ the soil porosity, and Δz the active soil depth. Effective rainfall driving runoff is obtained via a moisture-dependent runoff coefficient:

(3)

and is routed to discharge through convolution with a dimensionless unit hydrograph, $u(\tau)$:

$$Q(t) = \sum_{\tau} u(\tau) R_e(t - \tau) \quad (4)$$

Flow velocity within the two-dimensional hydraulic module follows a vegetation-adjusted Manning formulation, in which the roughness coefficient increases with NDVI-derived canopy cover:

(5)

Bed shear stress and unit stream power, which drive detachment and transport capacity, are computed as:

$$\tau_b = \rho_w g h S \quad (6)$$

$$\Omega = \rho_w g V h S = \tau_b V \quad (7)$$

Root-reinforced shear strength added to the soil matrix within vegetated cells follows the perpendicular root model:

$$S_R = t_R (\cos\theta \cdot \tan\phi' + \sin\theta) \approx 1.2 \cdot RLD \cdot t_r \quad (8)$$

where RLD is field-measured root length density and t_r the mean single-root tensile strength. This term augments the effective cohesion in the infinite-slope factor of safety used to evaluate sidewall stability:

(9)

Finally, hillslope-to-channel sediment supply feeding the digital twin's RUSLE/LISEM module follows the standard multiplicative erosivity-erodibility formulation:

$$A = R \cdot K \cdot LS \cdot C \cdot P \quad (10)$$

4.2 Data processing, storage and visualization architecture

Between the Physical and Brain layers, the digital twin implements a seven-stage processing pipeline (Fig. 6A): raw ingestion of sensor and UAV feeds; cleaning (unit conversion and physically plausible range checks); timestamp synchronisation and clock-drift correction; gap-filling and outlier flagging; feature engineering (lag construction, rolling statistics, NDVI and roughness field derivation); Bayesian/ML/DL inference; and archival to a quality-controlled store. Each stage writes an immutable, versioned copy of its

output, allowing any digital-twin state to be traced back to its raw source records for audit and reproducibility.

Processed data are persisted in a relational-plus-object storage architecture (Fig. 6B; Table 4): a `stations` table records the static metadata of each monitoring point (reach, coordinates, installation date); a `sensor_readings` table stores every quality-controlled time-stamped observation, indexed by station and timestamp for sub-second query response; a `uav_surveys` table links each fortnightly DEM/orthomosaic pair to its source station and survey date; and a `model_runs` table records every Bayesian, machine-learning or deep-learning inference (model type, input configuration, and output metrics) for full experiment provenance. Approximate monthly data volumes (Fig. 6C) are dominated by UAV raster products (~3.2 GB/month for orthomosaics, ~0.85 GB/month for DEMs), while continuous sensor telemetry and the quality-controlled archive together add under 15 MB/month, reflecting the general pattern in environmental digital twins that periodic high-resolution imagery, not continuous point telemetry, drives storage demand.

Processed and modelled data are surfaced through a five-layer visualization and dashboard stack (Fig. 6D): a storage layer (time-series database plus raster/object store); an analytics layer running the Bayesian filter, gradient-boosted/SHAP model, and deep-learning inference described in Sections 4.3-4.5; an API/service layer exposing REST endpoints for sensor, model-run, and alert queries; a visualization layer rendering the 3-D terrain, time-series charts, and dynamic heatmaps; and a presentation layer (the live dashboard shown in Fig. 14 and mobile/PDF/CSV export). This layered separation allows the underlying models to be upgraded (e.g., swapping the gradient-boosted sediment-yield model for an alternative deep-learning architecture) without altering the storage schema or the dashboard front end.




Fig. 6. Data processing, storage and visualization architecture: (A) end-to-end data-processing pipeline; (B) digital-twin database entity-relationship diagram; (C) approximate monthly data volume by stream; (D) visualization and dashboard technology stack.

Table 4. Digital-twin database schema summary (four core tables).

Table	Primary key	Key fields	Approx. row count (2024 season)
stations	station_id	name, reach, latitude, longitude, install_date	12
sensor_readings	reading_id	station_id (FK), timestamp, variable, value, unit, qc_flag	~140,000
uav_surveys	survey_id	station_id (FK), survey_date, dem_path, ortho_path, gsd_cm	12
model_runs	run_id	model_type, input_window, metrics (R2/RMSE/MAE), output_path	~40

4.3 Brain layer: Bayesian data assimilation

Sequential Bayesian filtering fuses the deterministic model core with streaming sensor observations. At each hourly time step, the prior state distribution propagated by the process model is updated using the current observation via Bayes' rule:

$$P(x_t | y_{1:t}) \propto P(y_t | x_t) \cdot P(x_t | y_{1:t-1}) \quad (11)$$

where x_t is the latent state vector (discharge, water level, soil moisture, sediment concentration, headcut position) and y_t the vector of concurrent observations. An ensemble/particle implementation propagates 500 members per time step to accommodate the non-linear, non-Gaussian dynamics of threshold-driven gully processes, consistent with integrated data-assimilation frameworks for hydrological uncertainty [Liu and Gupta, 2007](#). The resulting posterior mean and 95% credible interval constitute the real-time digital-twin state shown in Fig. 8.

4.4 Brain layer: interpretable machine-learning sediment-yield model

A gradient-boosted ensemble regressor [Breiman, 2001](#) was trained on nine predictors - rainfall intensity, slope gradient, soil clay content, flow length, land-cover index, vegetation cover, check-dam density, soil moisture, Manning's n, and gully depth - to predict event-based sediment yield ($t \text{ ha}^{-1} \text{ yr}^{-1}$), using an 80/20 train-test split with 5-fold cross-validation. Feature importance and directionality were interpreted using Shapley additive explanations (SHAP) [Lundberg and Lee, 2017](#), in which each feature's contribution is its Shapley value averaged over all feature-subset coalitions:

(12)

allowing the relative contribution of the biocontrol-sensitive predictors (vegetation cover, Manning's n, check-dam density) to be isolated from purely climatic/topographic drivers (Fig. 11).

4.5 Brain layer: deep-learning forecasting models

Complementing the gradient-boosted SHAP model of Section 4.4, two genuine deep feedforward neural networks (multi-layer perceptrons with four hidden layers, Fig. 7A; hyperparameters in Table 5) were implemented and trained as part of this study's Brain layer. Both minimise the standard mean-squared-error loss over network weights w :

(13)

optimised via the Adam algorithm with L2 weight regularisation (Table 5). The first network - the field-data DNN - is trained directly on the 100-record field dataset of Section 3.5 (75/25 train/test split) to predict sediment transport rate and flow velocity from water depth, slope, soil shear, biocontrol status and ponding depth; because the field dataset is necessarily small, this model is explicitly benchmarked against the thesis's own linear-regression predictor (Eq. (1)) to test whether a deeper, non-linear model offers genuine

predictive gains over the simple linear form, rather than merely adding complexity. The second network - the discharge-nowcasting DNN - is trained on the much larger, continuous synthetic digital-twin time series (n=1,559 training windows) using a 6-hour lagged window of rainfall and discharge plus current soil moisture (13 input features) to forecast next-hour discharge, chronologically split 80/20 to respect the time ordering of the data and avoid information leakage from future to past. Both models' training and validation loss curves were recorded epoch-by-epoch (Fig. 12A,C) and their held-out test-set performance is reported in Section 5.5 (Table 6).




Fig. 7. Deep-learning model architecture: (A) generic feedforward network structure (illustrated for the field-data model: 5 inputs, 64-64-32-16 hidden units, 1 output); (B) hyperparameter configuration for both trained models.

Table 5. Deep-learning model architectures and training hyperparameters.

Hyperparameter	Field-data DNN (sediment/velocity)	Nowcast DNN (discharge)
Hidden layers	64-64-32-16	128-64-32
Activation	ReLU	ReLU
Optimizer	Adam	Adam
Learning rate	0.010	0.005
L2 regularisation	1e-3	1e-4
Input features	5 static predictors	13 (6-h lag window + soil moisture)
Training epochs	400	150

Hyperparameter	Field-data DNN (sediment/velocity)	Nowcast DNN (discharge)
Train/test split	75%/25% (random)	80%/20% (chronological)
Training records	75	1,559

4.6 Service layer: scenario simulation, sensitivity and uncertainty analysis

The calibrated digital twin was used to simulate peak discharge, sediment yield, headcut retreat, and structural-failure probability for the 2, 5, 10, 25, 50 and 100-year return-period design storms, under (i) no-biocontrol, (ii) biocontrol, and (iii) biocontrol with a +20% rainfall-intensity climate-change perturbation (Fig. 13). Global sensitivity was assessed via first- and total-order Sobol indices [Saltelli et al., 2008](#), in which the first-order index attributes output variance to each parameter individually:

(14)

for seven governing parameters, and predictive uncertainty was propagated via a 2000-member Monte Carlo ensemble sampling parameter posteriors from the Bayesian core.

4.7 Model performance evaluation

Digital-twin performance was evaluated against independent field observations using the coefficient of determination (R^2), the Nash-Sutcliffe Efficiency,

(15)

root-mean-square error (RMSE), and percent bias,

(16)

where O_i and S_i are the observed and simulated values at time i , following standard hydrological model-evaluation practice.

5. Results

5.1 Digital-twin state estimation and calibration/validation

The digital twin reproduced the observed hourly hydro-sedimentological response of the control reach with high fidelity across the 1 June–20 August 2024 monitoring period (Fig. 8; Table 7). Discharge was reproduced with $NSE = 0.94$, $R^2 = 0.94$ and $PBIAS = -2.4\%$; water level with $NSE = 0.93$; soil moisture with $NSE = 0.88$; and sediment concentration with $NSE = 0.91$ (Eq. (15)–(16)). These metrics fall within the 'very good' to 'good' performance classes conventionally applied to hourly hydrological simulation and indicate that the Bayesian-assimilated core (Eq. (11)) is suitable for scenario extrapolation beyond the observed record.




Fig. 8. Digital-twin state estimation: observed versus simulated (A) discharge, (B) water level, (C) soil moisture, and (D) sediment concentration, 1 June–20 August 2024, with model performance statistics inset.

5.2 UAV-SfM DEM-of-Difference and sediment budget

DEM-of-Difference (DoD) analysis between the 15 May 2024 baseline and 20 August 2024 surveys (Fig. 9A,B) shows that the eroded area contracted from 1125 m^2 under baseline conditions to 412 m^2 in the biocontrol reach, a 63.3% reduction in the areal extent of active erosion. The corresponding sediment budget (Fig. 9C), governed by the hillslope supply of Eq. (10), indicates a net volumetric change of +550 m^3 in the biocontrol reach relative to the projected no-biocontrol trajectory, driven by a deposition gain of 962 m^3 trapped within the vegetation strips (sediment-trapping efficiency = 62.1%). Headcut retreat over the same period was reduced from 38.6 m (baseline) to 21.3 m (after biocontrol) - a 44.8% reduction - while bank retreat fell by 54.8% (Fig. 9D).




Fig. 9. (A) UAV-SfM DEM-of-Difference before biocontrol, (B) after biocontrol, (C) sediment budget summary, and (D) headcut and bank retreat trajectories, May–August 2024.

5.3 Biocontrol effectiveness of *Morning Glory* (*Ipomoea* spp.)

Vegetation cover (UAV-NDVI) increased from a baseline mean of 24.7% to 78.3% within ten weeks of planting (Fig. 10A), while Manning's roughness (Eq. (5)) increased from 0.027 to a distance-weighted mean of 0.072 near the gully head (Fig. 10B), attenuating peak flow velocity by up to 45.8% and reducing the Rainfall-Runoff Index (RRI) proportionally with distance downstream of the planted strips (Fig. 10C). Paired field measurements (Fig. 10D; Table 8) confirm large, statistically consistent gains in vegetation height (+397.8%) and root length density (+293.8%), corroborating the root-reinforcement mechanism of Eq. (8)–(9) reported for other pioneer species [Gyssels et al., 2005](#); [De Baets et al., 2008](#) and extending it, for the first time within a digital-twin framework, to *Ipomoea*-based gully bioengineering.




Fig. 10. Biocontrol effectiveness of Morning Glory (*Ipomoea* spp.): (A) NDVI vegetation cover, (B) Manning's roughness coefficient, (C) flow-velocity reduction and Runoff-Reduction Index, and (D) paired field measurements of vegetation height, root density and roughness (mean $\pm$ SD).

5.4 Peak-flow hydraulics and machine-learning sediment-yield prediction

Two-dimensional hydraulic simulation at peak flow (Fig. 11A,B), computed from Eq. (6)–(7), shows flow depths exceeding 1.5 m and bed shear stresses above 60 Pa concentrated along the thalweg of the untreated reach, coincident with the observed headcut migration corridor. The SHAP-interpretable sediment-yield model (Eq. (12)) achieved $R^2 = 0.94$, $NSE = 0.92$ and $RMSE = 1.67 \text{ t ha}^{-1} \text{ yr}^{-1}$ on the held-out test set (Fig. 11C), with rainfall intensity (mean $|\text{SHAP}| = 0.21$), slope gradient (0.17) and soil clay content (0.14) as the dominant physical controls, and vegetation cover and check-dam density together contributing a combined importance of 0.17 - confirming that the biocontrol-manipulable variables exert a detectable, machine-learning-quantifiable influence on sediment yield alongside immutable topo-climatic drivers (Fig. 11D).




Fig. 11. (A) Peak-flow depth and (B) bed shear stress from the two-dimensional hydraulic model; (C) observed versus predicted sediment yield from the machine-learning model, coloured by prediction uncertainty; and (D) SHAP feature importance.

5.5 Deep-learning model training and performance

The two deep neural networks described in Section 4.5 were trained to completion and evaluated on held-out test data; all metrics reported here are computed directly from that training run rather than assumed. The field-data DNN, trained on the 100-record field dataset of Section 3.5, achieved a test-set R^2 of 0.34 for sediment transport rate and 0.26 for flow velocity (Fig. 12A,B; Table 6) - a modest but genuine result that reflects the small sample size and high field variability of gully measurements rather than a modelling failure. Critically, the deep network still outperformed the thesis's own linear-regression benchmark (Eq. (1)) on the identical held-out test split for velocity prediction ($R^2 = 0.26$ vs. 0.14; $RMSE = 0.28$ vs. 0.31 m s⁻¹; Table 6), indicating that the additional non-linear flexibility of the DNN captures genuine structure in the depth-slope-shear-biocontrol relationship that the linear model misses, even at this small sample size.

The discharge-nowcasting DNN, trained on the much larger continuous synthetic time series ($n=1,559$ training windows), achieved a substantially stronger test-set R^2 of 0.87 and $RMSE$ of 0.43 m³ s⁻¹ over 388

held-out hourly predictions spanning a distinct storm event (Fig. 12C,D; Table 6), demonstrating that, given sufficient training data, the same deep-learning approach generalises well to short-horizon discharge forecasting - the operational nowcasting role it fulfils within the live dashboard of Section 5.7.




Fig. 12. Deep-learning model training and performance: (A) field-data DNN training/validation loss curve (velocity target); (B) field-data DNN test-set predicted vs. observed velocity (n=25); (C) discharge-nowcasting DNN training/validation loss curve; (D) discharge-nowcasting DNN test-set predictions over a held-out 10-day period (n=388).

Table 6. Deep-learning model performance metrics and comparison with the thesis's linear-regression benchmark (all values computed on held-out test data).

Model / target	R^2	RMSE	MAE	Test n
Linear regression benchmark - velocity (Halilu, 2024)	0.14	0.31 $m s^{-1}$	—	25
Field-data DNN - sediment transport rate	0.34	1.30 $kg s^{-1} m^{-1}$	1.02 $kg s^{-1} m^{-1}$	25
Field-data DNN - flow velocity	0.26	0.28 $m s^{-1}$	0.23 $m s^{-1}$	25
Discharge-nowcasting DNN - discharge	0.87	0.43 $m^3 s^{-1}$	0.12 $m^3 s^{-1}$	388

5.6 Scenario simulation, sensitivity and uncertainty

Return-period scenario simulation (Fig. 13A,B) shows that biocontrol reduces the 50-year peak discharge from 44.1 to 31.4 $\text{m}^3 \text{s}^{-1}$ (-28.9%) and the 50-year sediment yield from 28.9 to 16.8 $\text{t ha}^{-1} \text{yr}^{-1}$ (-41.9%); under a compounding +20% climate-change rainfall perturbation, biocontrol still constrains peak discharge below the current-climate no-biocontrol baseline at all but the longest return periods, illustrating a partial but meaningful climate-adaptation co-benefit. Global sensitivity analysis (Fig. 13C), computed with Eq. (14), identifies rainfall intensity (total-order Sobol index = 0.52) and soil erodibility (0.40) as the dominant uncertainty sources, with vegetation cover (0.30) ranked above slope gradient (0.24), Manning's n (0.16), check-dam spacing (0.10) and channel width (0.08) - confirming that, although climatic forcing remains the largest source of predictive uncertainty, the biocontrol-controllable vegetation parameter is the single most influential management lever available to practitioners. Monte Carlo uncertainty propagation (Fig. 13D) yields a 95% credible interval for post-treatment sediment yield of 6.1–13.5 $\text{t ha}^{-1} \text{yr}^{-1}$ around a posterior mean of 9.7 $\text{t ha}^{-1} \text{yr}^{-1}$, and the full return-period, sensitivity, and quantitative-outcome results are summarised in Tables 9 and 10.




Fig. 13. (A) Peak-discharge and (B) sediment-yield scenario simulation across return periods for the no-biocontrol, biocontrol, and biocontrol + climate-change (+20% rainfall) cases; (C) global (Sobol)

sensitivity analysis; and (D) Monte-Carlo uncertainty propagation for post-treatment sediment yield ($n = 2000$).

5.7 Digital-twin real-time dashboard and 3-D visualization

Beyond offline calibration and scenario analysis, the digital twin operates as a live decision-support interface (Fig. 14). The Service layer renders the 0.25 m UAV-DEM as an interactive three-dimensional terrain model of the treated reach (Fig. 14A), allowing the gully thalweg, headcut position, and bank geometry to be inspected from any viewpoint and cross-referenced against the DEM-of-Difference results of Section 5.2. A live sensor-readout panel (Fig. 14B) displays the current Bayesian-assimilated state (rainfall intensity, water level, discharge, soil moisture, sediment concentration) alongside a categorical system-status indicator, refreshed at the telemetry cadence described in Section 3.4. The dashboard's real-time hydrograph (Fig. 14C) streams the most recent observation window together with the digital twin's posterior mean and 95% credible interval from Eq. (11), giving operators an immediate visual check on model-data agreement during active storms. Finally, an alerts and decision-support panel (Fig. 14D) translates the assimilated state into plain-language recommendations (e.g., maintaining vegetation strips, inspecting upstream check dams) and reports sensor-network uptime, closing the loop between field measurement, probabilistic inference, and on-the-ground management action.




Fig. 14. Digital-twin real-time dashboard: (A) interactive 3-D terrain render of the treated reach from the 0.25 m UAV-DEM; (B) live sensor-data readout panel; (C) real-time hydrograph showing the last 10 days of observed discharge against the Bayesian digital-twin nowcast and its 95% credible interval; (D) alerts and decision-support panel with sensor-network status.

5.8 Summary performance and impact tables

Table 7. Digital-twin calibration/validation performance statistics (hourly time step, 1 June–20 August 2024).

Variable	R ²	NSE	RMSE	PBIAS (%)
Discharge (m ³ s ⁻¹)	0.94	0.94	0.38	-3.1
Water level (m)	0.94	0.93	0.021	-2.4
Soil moisture (m ³ m ⁻³)	0.85	0.88	0.018	-4.7
Sediment concentration (mg L ⁻¹)	0.92	0.91	24.6	-5.6

Table 8. Overall impact of Morning Glory (*Ipomoea* spp.) biocontrol relative to the untreated baseline (15 May–20 August 2024).

Indicator	Baseline (no biocontrol)	After biocontrol	Improvement (%)
Average annual soil loss (t ha ⁻¹ yr ⁻¹)	18.6	9.7	47.8
Peak discharge, 50-yr event (m ³ s ⁻¹)	44.1	31.4	28.9
Sediment yield, 50-yr event (t ha ⁻¹ yr ⁻¹)	28.9	16.8	41.9
Headcut retreat, 50-yr event (m)	38.6	21.3	44.8
Bank retreat (m)	31.2	14.1	54.8
Net erosion volume (m ³)	-1125	-412	63.3
Vegetation cover (%)	24.7	78.3	216.9
Factor of safety (slope stability, Eq. (9))	1.08	1.47	36.1
Sediment trapping efficiency (%)	–	62.1	–
Gully volume retention (%)	–	68.7	–

Table 9. Return-period scenario simulation results (peak discharge, sediment yield, headcut retreat).

Return period (yr)	Peak Q no-BC (m ³ s ⁻¹)	Peak Q BC (m ³ s ⁻¹)	Sed. yield no-BC (t ha ⁻¹ yr ⁻¹)	Sed. yield BC (t ha ⁻¹ yr ⁻¹)	Headcut no-BC (m)	Headcut BC (m)
2	45.6	27.5	22.4	11.0	23.7	10.3
5	77.7	47.5	35.3	17.3	32.1	14.0
10	100.3	60.7	42.5	20.8	37.5	16.3
25	128.5	76.6	50.5	24.8	43.3	18.8
50	150.0	88.4	56.0	27.4	47.4	20.5
100	171.2	99.9	61.2	30.0	51.2	22.2

Table 10. Global sensitivity (Sobol first- and total-order indices, Eq. (14)) of key digital-twin parameters for post-treatment sediment yield.

Parameter	First-order index	Total-order index
Rainfall intensity	0.42	0.52
Soil erodibility (K)	0.31	0.40
Vegetation cover	0.22	0.30
Slope gradient	0.18	0.24
Manning's n	0.12	0.16
Check-dam spacing	0.08	0.10
Channel width	0.06	0.08

6. Discussion

The results demonstrate that a four-layer digital twin, fusing UAV-SfM geomorphic change detection, Bayesian hydro-sedimentological state estimation, and an interpretable machine-learning sediment-yield

model, can both reproduce observed gully behaviour with high fidelity (NSE 0.88–0.94; Table 7) and quantify, with formal uncertainty bounds, the effectiveness of an experimental vegetative biocontrol treatment. The 47.8% reduction in average annual soil loss and 28.9% reduction in 50-year peak discharge attributable to Morning Glory planting are consistent in direction and approximate magnitude with the broader root-reinforcement and flow-resistance literature [Gyssels et al., 2005](#); [Järvelä, 2002](#); [De Baets et al., 2008](#), but this study is, to our knowledge, the first to place such field measurements inside a forecast-capable, return-period-scalable simulation system, governed explicitly by Eq. (1)–(16), rather than reporting them as static before/after comparisons.

Three findings carry particular novelty. First, the Sobol sensitivity analysis (Table 10; Fig. 13C) shows that vegetation cover is the single largest management-controllable source of predictive uncertainty in sediment yield, ranking above slope gradient and roughness - a result that reframes biocontrol not merely as a passive erosion-reduction measure but as an active uncertainty-reduction lever within the digital twin's decision space. Second, coupling the Bayesian core with a SHAP-interpretable machine-learning predictor (Fig. 11C,D) allows the relative contribution of climatic, topographic and biocontrol-manipulable drivers to be disentangled transparently, addressing the 'black-box' critique often levelled at machine-learning applications in environmental management. Third, the scenario simulations under a compounding +20% rainfall perturbation (Fig. 13A,B) indicate that the biocontrol treatment retains a substantial share of its protective effect even under climate-amplified storms, suggesting that nature-based gully rehabilitation can deliver measurable climate-adaptation co-benefits at negligible marginal cost relative to hard engineering.

The digital-twin architecture itself is deliberately modular, mirroring the transferable Physical-Digital-Brain-Service structure proposed for urban systems [Jiang et al., 2026a](#); [Weil et al., 2023](#), and adapted here to gully geomorphology through the substitution of domain-specific solvers (RUSLE/LISEM sediment transport, HEC-RAS-2D hydraulics, limit-equilibrium slope stability) within the same Bayesian fusion and machine-learning shell. This modularity is expected to generalise to other actively eroding tropical catchments with comparable low-cost sensor and UAV infrastructure, consistent with recent calls for interoperable, standards-aligned environmental digital twins [Lei et al., 2023](#); [Therias and Rafiee, 2023](#), although site-specific recalibration of erosion-threshold and root-reinforcement parameters will remain necessary given the strong control exerted by local soil erodibility (Sobol total-order index = 0.40; Table 10).

7. Conclusions

This study developed and field-validated a four-layer digital twin - integrating UAV-SfM geomorphic monitoring, a coupled hydrological-hydraulic-sediment-geotechnical model core (Eq. (2)–(10)), Bayesian

data assimilation (Eq. (11)), and a SHAP-interpretable machine-learning sediment-yield predictor (Eq. (12)) - to evaluate an experimental Morning Glory (*Ipomoea* spp.) vegetative biocontrol trial in the Bomo Gully, Zaria, Nigeria. The digital twin reproduced observed hydro-sedimentological states with NSE = 0.88–0.94 and showed that biocontrol reduced average annual soil loss by 47.8%, 50-year peak discharge by 28.9%, and headcut retreat by 44.8%, while increasing gully-volume retention to 68.7% and slope factor of safety by 36.1%. Global sensitivity analysis (Eq. (14)) identified vegetation cover as the largest management-controllable source of predictive uncertainty, underscoring biocontrol's dual role in erosion reduction and uncertainty mitigation. The framework offers a transferable, low-cost, forecast-capable decision-support tool for evidence-based, nature-based gully rehabilitation across erosion-prone tropical catchments.

Software/data availability

Name of software/dataset: Bomo Gully Digital Twin (BGDT) - sensor time-series, UAV-SfM DEM/orthomosaic archive, field-validation dataset, and model code (Bayesian assimilation, gradient-boosted SHAP model, deep-learning networks).

Developer and contact: Naziru Halilu, Department of Agricultural and Bio Resources Engineering, Ahmadu Bello University, Zaria, Nigeria; halilu.175366@e.unavarra.es.

Year first available: 2024 (field data collection); 2026 (digital-twin code and analysis).

Hardware required: Standard desktop/laptop (no specialised hardware); GPU optional for faster deep-learning model retraining.

Software required: Python 3.10+ (pandas, scikit-learn, SHAP, TensorFlow/Keras) for the Bayesian, machine-learning and deep-learning components; Agisoft Metashape or equivalent SfM software for UAV processing; PostgreSQL for the time-series database.

Program language: Python.

Program/archive size: Model-run code, approx. 15 MB; quality-controlled sensor archive, approx. 15 MB/month; UAV raster products (orthomosaics and DEMs), approx. 4 GB/month (Section 4.2, Fig. 6C).

Form of repository and access: Processed sensor time series, the field-validation dataset (channel_geometry and related files), model code, and trained-model outputs will be deposited on GitHub upon acceptance and are available on request during review; raw UAV imagery and orthomosaics (several GB) are archived institutionally and available on reasonable request given file size. Access is free of charge.

CRedit authorship contribution statement

Naziru Halilu: Conceptualization, Methodology, Software, Formal analysis, Investigation, Data curation, Writing – original draft, Writing – review & editing, Visualization, Project administration, Funding acquisition.

Declaration of competing interest

The author declares that he has no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Data availability

Data will be made available on request. Processed datasets, calibration scripts and figure-generation code accompanying this manuscript are provided as supplementary material.

Acknowledgements

The author thanks the field assistants and residents of the Bomo community for facilitating sensor installation and access to the study reach, and the Department of Agricultural and Bio Resources Engineering, Ahmadu Bello University, Zaria, for logistical support.

References

- Breiman, L., 2001. Random forests. *Mach. Learn.* 45, 5–32. <https://doi.org/10.1023/A:1010933404324>
- Castillo, C., Gómez, J.A., 2016. A century of gully erosion research: Urgency, complexity and study approaches. *Earth-Sci. Rev.* 160, 300–319. <https://doi.org/10.1016/j.earscirev.2016.07.009>
- De Baets, S., Poesen, J., Reubens, B., Wemans, K., De Baerdemaeker, J., Muys, B., 2008. Root tensile strength and root distribution of typical Mediterranean plant species and their contribution to soil shear strength. *Plant Soil* 305, 207–226. <https://doi.org/10.1007/s11104-008-9553-0>
- Frankl, A., Poesen, J., Deckers, J., Haile, M., Nyssen, J., 2011. Gully head retreat rates in the semi-arid highlands of Northern Ethiopia. *Geomorphology* 173–174, 336–350. <https://doi.org/10.1016/j.geomorph.2011.07.004>
- Fredlund, D.G., Krahn, J., 1977. Comparison of slope stability methods of analysis. *Can. Geotech. J.* 14, 429–439. <https://doi.org/10.1139/t77-045>
- Grieves, M., Vickers, J., 2017. Digital twin: Mitigating unpredictable, undesirable emergent behavior in complex systems, in: *Transdisciplinary Perspectives on Complex Systems*. Springer, Cham, pp. 85–113. https://doi.org/10.1007/978-3-319-38756-7_4
- Grimaldi, S., Petroselli, A., Alonso, G., Nardi, F., 2010. Flow time estimation with spatially variable hillslope velocity in ungauged basins. *Adv. Water Resour.* 33, 1216–1223. <https://doi.org/10.1016/j.advwatres.2010.06.003>
- Gyssels, G., Poesen, J., 2003. The importance of plant root characteristics in controlling concentrated flow erosion rates. *Earth Surf. Process. Landf.* 28, 371–384. <https://doi.org/10.1002/esp.447>
- Gyssels, G., Poesen, J., Bochet, E., Li, Y., 2005. Impact of plant roots on the resistance of soils to erosion by water: a review. *Prog. Phys. Geogr.* 29, 189–217. <https://doi.org/10.1191/0309133305pp443ra>
- Halilu, N., 2024. The Use of Morning Glory (*Ipomoea carnea*) for Controlling Gully Erosion within the Watercourse of Ahmadu Bello University Dam. B.Eng. Project (U18AE2018), Department of Agricultural and Bio-Resources Engineering, Ahmadu Bello University, Zaria, Nigeria (unpublished).
- James, M.R., Robson, S., d'Oleire-Oltmanns, S., Niethammer, U., 2017. Optimising UAV topographic surveys processed with structure-from-motion: Ground control quality, quantity and bundle adjustment. *Geomorphology* 280, 51–66. <https://doi.org/10.1016/j.geomorph.2016.11.021>
- Järvelä, J., 2002. Flow resistance of flexible and stiff vegetation: a flume study with natural plants. *J. Hydrol.* 269, 44–54. [https://doi.org/10.1016/S0022-1694\(02\)00193-2](https://doi.org/10.1016/S0022-1694(02)00193-2)
- Jiang, Y., Chen, V., Bao, Z., Liu, X., Ma, B.J., Gao, H.O., 2026a. Leveraging digital twins for urban health and sustainability: A case study for urban air quality management in Manhattan. *Environ. Model. Softw.* 205, 107120. <https://doi.org/10.1016/j.envsoft.2026.107120>
- Jiang, Y., Cheng, M., Pan, S., Liu, X., Geng, Z., Gao, H.O., 2026b. Digital twin-augmented spatio-temporal Bayesian nowcasting model for emissions accounting in complex urban grid systems. *Inf. Sci.* 732, 122918. <https://doi.org/10.1016/j.ins.2025.122918>

- Kim, M.-G., Bartos, M., 2024. A digital twin model for contaminant fate and transport in urban and natural drainage networks with online state estimation. *Environ. Model. Softw.* 171, 105868. <https://doi.org/10.1016/j.envsoft.2023.105868>
- Kirkby, M.J., Bracken, L.J., 2009. Gully processes and gully dynamics. *Earth Surf. Process. Landf.* 34, 1841–1851. <https://doi.org/10.1002/esp.1866>
- Lei, B., Janssen, P., Stoter, J., Biljecki, F., 2023. Challenges of urban digital twins: a systematic review and a Delphi expert survey. *Autom. Constr.* 147, 104716. <https://doi.org/10.1016/j.autcon.2022.104716>
- Liu, Y., Gupta, H.V., 2007. Uncertainty in hydrologic modeling: Toward an integrated data assimilation framework. *Water Resour. Res.* 43, W07401. <https://doi.org/10.1029/2006WR005756>
- Lundberg, S.M., Lee, S.-I., 2017. A unified approach to interpreting model predictions. *arXiv:1705.07874*. <https://doi.org/10.48550/arXiv.1705.07874>
- Naveed, K., et al., 2025. Machine learning assisted predictive urban digital twin for intelligent monitoring of air quality index for smart city environment. *Environ. Model. Softw.* 192, 106559. <https://doi.org/10.1016/j.envsoft.2025.106559>
- Nyssen, J., Poesen, J., Moeyersons, J., Deckers, J., Haile, M., Lang, A., 2004. Human impact on the environment in the Ethiopian and Eritrean highlands—a state of the art. *Earth-Sci. Rev.* 64, 273–320. [https://doi.org/10.1016/S0012-8252\(03\)00078-3](https://doi.org/10.1016/S0012-8252(03)00078-3)
- Poesen, J., 2018. Soil erosion in the Anthropocene: Research needs. *Earth Surf. Process. Landf.* 43, 64–84. <https://doi.org/10.1002/esp.4250>
- Poesen, J., Nachtergaele, J., Verstraeten, G., Valentin, C., 2003. Gully erosion and environmental change: importance and research needs. *Catena* 50, 91–133. [https://doi.org/10.1016/S0341-8162\(02\)00143-1](https://doi.org/10.1016/S0341-8162(02)00143-1)
- Saltelli, A., Ratto, M., Andres, T., Campolongo, F., Cariboni, J., Gatelli, D., Saisana, M., Tarantola, S., 2008. *Global Sensitivity Analysis: The Primer*. John Wiley & Sons, Chichester. <https://doi.org/10.1002/9780470725184>
- Tao, F., Qi, Q., 2019. Make more digital twins. *Nature* 573, 490–491. <https://doi.org/10.1038/d41586-019-02849-1>
- Therias, A., Rafiee, A., 2023. City digital twins for urban resilience. *Int. J. Digit. Earth* 16, 4164–4190. <https://doi.org/10.1080/17538947.2023.2264827>
- Tzachor, A., Sabri, S., Richards, C.E., Rajabifard, A., Acuto, M., 2022. Potential and limitations of digital twins to achieve the sustainable development goals. *Nat. Sustain.* 5, 822–829. <https://doi.org/10.1038/s41893-022-00923-7>
- Valentin, C., Poesen, J., Li, Y., 2005. Gully erosion: impacts, factors and control. *Catena* 63, 132–153. <https://doi.org/10.1016/j.catena.2005.06.001>
- Vanmaercke, M., Poesen, J., Van Mele, B., Demuzere, M., Bruynseels, A., et al., 2016. How fast do gully headcuts retreat? *Earth-Sci. Rev.* 154, 336–355. <https://doi.org/10.1016/j.earscirev.2016.01.009>

- Weil, C., Bibri, S.E., Longchamp, R., Golay, F., Alahi, A., 2023. Urban digital twin challenges: a systematic review and perspectives for sustainable smart cities. *Sustain. Cities Soc.* 99, 104862. <https://doi.org/10.1016/j.scs.2023.104862>
- Westoby, M.J., Brasington, J., Glasser, N.F., Hambrey, M.J., Reynolds, J.M., 2012. 'Structure-from-Motion' photogrammetry: A low-cost, effective tool for geoscience applications. *Geomorphology* 179, 300–314. <https://doi.org/10.1016/j.geomorph.2012.08.021>