

▼ Copyright 2019 The TensorFlow Authors.

## Licensed under the Apache License, Version 2.0 (the "License");

```
import os

from tensorflow.keras import layers
from tensorflow.keras import Model
!wget --no-check-certificate \
    https://storage.googleapis.com/mledu-datasets/inception_v3_weights_tf_dim_ordering_tf_kernels
    -O /tmp/inception_v3_weights_tf_dim_ordering_tf_kernels_notop.h5

from tensorflow.keras.applications.inception_v3 import InceptionV3

local_weights_file = '/tmp/inception_v3_weights_tf_dim_ordering_tf_kernels_notop.h5'

pre_trained_model = InceptionV3(input_shape = (150, 150, 3),
                                include_top = False,
                                weights = None)

pre_trained_model.load_weights(local_weights_file)

for layer in pre_trained_model.layers:
    layer.trainable = False

# pre_trained_model.summary()

last_layer = pre_trained_model.get_layer('mixed7')
print('last layer output shape: ', last_layer.output_shape)
last_output = last_layer.output

from tensorflow.keras.optimizers import RMSprop

# Flatten the output layer to 1 dimension
x = layers.Flatten()(last_output)
# Add a fully connected layer with 1,024 hidden units and ReLU activation
x = layers.Dense(1024, activation='relu')(x)
# Add a dropout rate of 0.2
x = layers.Dropout(0.2)(x)
# Add a final sigmoid layer for classification
x = layers.Dense(1, activation='sigmoid')(x)

model = Model(pre_trained_model.input, x)

model.compile(optimizer = RMSprop(lr=0.0001),
              loss = 'binary_crossentropy',
              metrics = ['accuracy'])
```

```
!wget --no-check-certificate \
```

```

https://storage.googleapis.com/mledu-datasets/cats_and_dogs_filtered.zip \
-0 /tmp/cats_and_dogs_filtered.zip

```

```

from tensorflow.keras.preprocessing.image import ImageDataGenerator

import os
import zipfile

local_zip = '../tmp/cats_and_dogs_filtered.zip'

zip_ref = zipfile.ZipFile(local_zip, 'r')

zip_ref.extractall('/tmp')
zip_ref.close()

# Define our example directories and files
base_dir = '../tmp/cats_and_dogs_filtered'

train_dir = os.path.join( base_dir, 'train')
validation_dir = os.path.join( base_dir, 'validation')

train_cats_dir = os.path.join(train_dir, 'cats') # Directory with our training cat pictures
train_dogs_dir = os.path.join(train_dir, 'dogs') # Directory with our training dog pictures
validation_cats_dir = os.path.join(validation_dir, 'cats') # Directory with our validation cat pictures
validation_dogs_dir = os.path.join(validation_dir, 'dogs') # Directory with our validation dog pictures

train_cat_fnames = os.listdir(train_cats_dir)
train_dog_fnames = os.listdir(train_dogs_dir)

# Add our data-augmentation parameters to ImageDataGenerator
train_datagen = ImageDataGenerator(rescale = 1./255.,
                                   rotation_range = 40,
                                   width_shift_range = 0.2,
                                   height_shift_range = 0.2,
                                   shear_range = 0.2,
                                   zoom_range = 0.2,
                                   horizontal_flip = True)

# Note that the validation data should not be augmented!
test_datagen = ImageDataGenerator( rescale = 1.0/255. )

# Flow training images in batches of 20 using train_datagen generator
train_generator = train_datagen.flow_from_directory(train_dir,

# Flow validation images in batches of 20 using test_datagen generator
validation_generator = test_datagen.flow_from_directory( validation_dir,

```

```
history = model.fit(
    train_generator,
    validation_data = validation_generator,
    steps_per_epoch = 100,
    epochs = 20,
    validation_steps = 50,
    verbose = 2)
```

```
import matplotlib.pyplot as plt
acc = history.history['accuracy']
val_acc = history.history['val_accuracy']
loss = history.history['loss']
val_loss = history.history['val_loss']
```

```
epochs = range(len(acc))
```

```
plt.plot(epochs, acc, 'r', label='Training accuracy')
plt.plot(epochs, val_acc, 'b', label='Validation accuracy')
plt.title('Training and validation accuracy')
plt.legend(loc=0)
plt.figure()
```

```
plt.show()
```