

```

#@title Licensed under the Apache License, Version 2.0 (the "License";
# you may not use this file except in compliance with the License
# You may obtain a copy of the License at https://www.apache.org/licenses/LICENSE-2.0
#
# Unless required by applicable law or agreed to in writing, software
# distributed under the License is distributed on an "AS IS" BASIS
# WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
# See the License for the specific language governing permissions
# limitations under the License.

import tensorflow as tf

from tensorflow.keras.preprocessing.sequence import pad_sequences
from tensorflow.keras.layers import Embedding, LSTM, Dense, Bidirectional
from tensorflow.keras.preprocessing.text import Tokenizer
from tensorflow.keras.models import Sequential
from tensorflow.keras.optimizers import Adam
import numpy as np

tokenizer = Tokenizer()

data="In the town of Athy one Jeremy Lanigan \n Battered away til he hadnt a pound.

corpus = data.lower().split("\n")

tokenizer.fit_on_texts(corpus)
total_words = len(tokenizer.word_index) + 1

print(tokenizer.word_index)
print(total_words)

input_sequences = []
for line in corpus:
    token_list = tokenizer.texts_to_sequences([line])[0]
    for i in range(1, len(token_list)):
        n_gram_sequence = token_list[:i+1]
        input_sequences.append(n_gram_sequence)

# pad sequences
max_sequence_len = max([len(x) for x in input_sequences])
input_sequences = np.array(pad_sequences(input_sequences, maxlen=max_sequence_len, padding='pre

# create predictors and label
xs, labels = input_sequences[:, :-1], input_sequences[:, -1]

ys = tf.keras.utils.to_categorical(labels, num_classes=total_words)

print(tokenizer.word_index['in'])

```

```

print(tokenizer.word_index[' the' ])
print(tokenizer.word_index[' town' ])
print(tokenizer.word_index[' of' ])
print(tokenizer.word_index[' athy' ])
print(tokenizer.word_index[' one' ])
print(tokenizer.word_index[' jeremy' ])
print(tokenizer.word_index[' lanigan' ])

```

```
print(xs[6])
```

```
print(ys[6])
```

```
print(xs[5])
```

```
print(ys[5])
```

```
print(tokenizer.word_index)
```

```

model = Sequential()
model.add(Embedding(total_words, 64, input_length=max_sequence_len-1))
model.add(Bidirectional(LSTM(20)))
model.add(Dense(total_words, activation='softmax'))
model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])
history = model.fit(xs, ys, epochs=500, verbose=1)

```

```
import matplotlib.pyplot as plt
```

```

def plot_graphs(history, string):
    plt.plot(history.history[string])
    plt.xlabel("Epochs")
    plt.ylabel(string)
    plt.show()

```

```
plot_graphs(history, 'accuracy')
```

```

seed_text = "Laurence went to dublin"
next_words = 100

```

```

for _ in range(next_words):
    token_list = tokenizer.texts_to_sequences([seed_text])[0]
    token_list = pad_sequences([token_list], maxlen=max_sequence_len-1, padding='pre')
    predicted = model.predict_classes(token_list, verbose=0)
    output_word = ""
    for word, index in tokenizer.word_index.items():
        if index == predicted:
            output_word = word
            break
    seed_text += " " + output_word

```

```
seed_text =  
print(seed_text)
```