

#@title Licensed under the Apache License, Version 2.0 (the "License");
 # you may not use this file except in compliance with the License.
 # You may obtain a copy of the License at <https://www.apache.org/licenses/LICENSE-2.0>
 #
 # Unless required by applicable law or agreed to in writing, software
 # distributed under the License is distributed on an "AS IS" BASIS
 # WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
 # See the License for the specific language governing permissions and
 # limitations under the License.

 Open in Colab

```
try:
    # %tensorflow_version only exists in Colab.
    %tensorflow_version 2.x
except Exception:
    pass

import tensorflow as tf
import numpy as np
import matplotlib.pyplot as plt
print(tf.__version__)

def plot_series(time, series, format="-", start=0, end=None):
    plt.plot(time[start:end], series[start:end], format)
    plt.xlabel("Time")
    plt.ylabel("Value")
    plt.grid(True)

def trend(time, slope=0):
    return slope * time

def seasonal_pattern(season_time):
    """Just an arbitrary pattern, you can change it if you wish"""
    return np.where(season_time < 0.4,
                    np.cos(season_time * 2 * np.pi),
                    1 / np.exp(3 * season_time))

def seasonality(time, period, amplitude=1, phase=0):
    """Repeats the same pattern at each period"""
    season_time = ((time + phase) % period) / period
    return amplitude * seasonal_pattern(season_time)

def noise(time, noise_level=1, seed=None):
    rnd = np.random.RandomState(seed)
    return rnd.randn(len(time)) * noise_level
```

```
time = np.arange(4 * 365 + 1, dtype="float32")
```

https://colab.research.google.com/drive/1vH2g_LFSuuZOKJ_b13vSqsNyOaToP-r_

```

time = np.arange(1 + 365 * 4, dtype='float32')
baseline = 10
series = trend(time, 0.1)
baseline = 10
amplitude = 40
slope = 0.05
noise_level = 5

# Create the series
series = baseline + trend(time, slope) + seasonality(time, period=365, amplitude=amplitude)
# Update with noise
series += noise(time, noise_level, seed=42)

split_time = 1000
time_train = time[:split_time]
x_train = series[:split_time]
time_valid = time[split_time:]
x_valid = series[split_time:]

window_size = 20
batch_size = 32
shuffle_buffer_size = 1000

def windowed_dataset(series, window_size, batch_size, shuffle_buffer):
    series = tf.expand_dims(series, axis=-1)
    ds = tf.data.Dataset.from_tensor_slices(series)
    ds = ds.window(window_size + 1, shift=1, drop_remainder=True)
    ds = ds.flat_map(lambda w: w.batch(window_size + 1))
    ds = ds.shuffle(shuffle_buffer)
    ds = ds.map(lambda w: (w[:-1], w[1:]))
    return ds.batch(batch_size).prefetch(1)

def model_forecast(model, series, window_size):
    ds = tf.data.Dataset.from_tensor_slices(series)
    ds = ds.window(window_size, shift=1, drop_remainder=True)
    ds = ds.flat_map(lambda w: w.batch(window_size))
    ds = ds.batch(32).prefetch(1)
    forecast = model.predict(ds)
    return forecast

tf.keras.backend.clear_session()
tf.random.set_seed(51)
np.random.seed(51)

window_size = 30
train_set = windowed_dataset(x_train, window_size, batch_size=128, shuffle_buffer=shuffle_buffer)

model = tf.keras.models.Sequential([
    tf.keras.layers.Conv1D(filters=32, kernel_size=5,
                           strides=1, padding="causal",
                           activation="relu",
                           input_shape=[None, 1]),
    tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(32, return_sequences=True)),
    tf.keras.layers.Bidirectional(tf.keras.layers.LSTM(32, return_sequences=True))
])

```

```

tf.keras.layers.Dense(1),
tf.keras.layers.Lambda(lambda x: x * 200)
])

lr_schedule = tf.keras.callbacks.LearningRateScheduler(
    lambda epoch: 1e-8 * 10**(epoch / 20))
optimizer = tf.keras.optimizers.SGD(lr=1e-8, momentum=0.9)
model.compile(loss=tf.keras.losses.Huber(),
              optimizer=optimizer,
              metrics=["mae"])
history = model.fit(train_set, epochs=100, callbacks=[lr_schedule])

plt.semilogx(history.history["lr"], history.history["loss"])
plt.axis([1e-8, 1e-4, 0, 30])

tf.keras.backend.clear_session()
tf.random.set_seed(51)
np.random.seed(51)
#batch_size = 16
dataset = windowed_dataset(x_train, window_size, batch_size, shuffle_buffer_size)

model = tf.keras.models.Sequential([
    tf.keras.layers.Conv1D(filters=32, kernel_size=3,
                           strides=1, padding="causal",
                           activation="relu",
                           input_shape=[None, 1]),
    tf.keras.layers.LSTM(32, return_sequences=True),
    tf.keras.layers.LSTM(32, return_sequences=True),
    tf.keras.layers.Dense(1),
    tf.keras.layers.Lambda(lambda x: x * 200)
])

optimizer = tf.keras.optimizers.SGD(lr=1e-5, momentum=0.9)
model.compile(loss=tf.keras.losses.Huber(),
              optimizer=optimizer,
              metrics=["mae"])
history = model.fit(dataset, epochs=500)

rnn_forecast = model_forecast(model, series[..., np.newaxis], window_size)
rnn_forecast = rnn_forecast[split_time - window_size:-1, -1, 0]

plt.figure(figsize=(10, 6))
plot_series(time_valid, x_valid)
plot_series(time_valid, rnn_forecast)

tf.keras.metrics.mean_absolute_error(x_valid, rnn_forecast).numpy()

import matplotlib.image as mpimg
import matplotlib.pyplot as plt

#-----
# Retrieve a list of list results on training and test data

```

```
# retrieve a list of list results on training and test data
# sets for each training epoch
#-----
mae=history.history['mae']
loss=history.history['loss']

epochs=range(len(loss)) # Get number of epochs

#-----
# Plot MAE and Loss
#-----
plt.plot(epochs, mae, 'r')
plt.plot(epochs, loss, 'b')
plt.title('MAE and Loss')
plt.xlabel("Epochs")
plt.ylabel("Accuracy")
plt.legend(["MAE", "Loss"])

plt.figure()

epochs_zoom = epochs[200:]
mae_zoom = mae[200:]
loss_zoom = loss[200:]

#-----
# Plot Zoomed MAE and Loss
#-----
plt.plot(epochs_zoom, mae_zoom, 'r')
plt.plot(epochs_zoom, loss_zoom, 'b')
plt.title('MAE and Loss')
plt.xlabel("Epochs")
plt.ylabel("Accuracy")
plt.legend(["MAE", "Loss"])

plt.figure()
```

