

cis112

Version Control Systems (Git)

BBBF

Yeditepe University

V2025-02-17

Agenda

- Why use Version (Source) Control Systems?
- What are Git and GitHub?
- Basic Git Commands

Motivation

Motivation for the Single Programmer

Why version control?

■ Scenario 1:

- ☐ Your program is working
- ☐ You change “just one thing”
- ☐ Your program breaks
- ☐ You change it back
- ☐ Your program is still broken—*why?*

■ Has this ever happened to you?



Why version control? (part 2)

- Your program worked well enough yesterday
- You made a lot of improvements last night. . .
 - ...but you haven't gotten them to work yet
 - You need to turn in your program *now*
- Has this ever happened to you?




Motivation for a Team of Programmers

Version control for teams

■ Scenario:

- ☐ You change one part of a program—it works
- ☐ Your co-worker changes another part—it works
- ☐ You put them together—it doesn't work
- ☐ Some change in one part must have broken something in the other part
- ☐ What were all the changes?




Teams (part 2)

■ Scenario:

- ☐ You make a number of improvements to a class
- ☐ Your co-worker makes a number of *different* improvements to the *same* class

■ How can you merge these changes?



Version Control Systems

Version control systems

- A **version control system** (often called a **source code control system**) does these things:
 - Keeps multiple versions (older and newer) of everything (not just source code)
 - Requests **comments** regarding every change
 - Allows “**check in**” and “**check out**” of files so you know which files someone else is working on
 - Displays **differences** between versions

Benefits of version control

■ For working **by yourself**:

- ☐ Gives you a “time machine” for going back to earlier versions
- ☐ Gives you great support for different versions (standalone, web app, etc.) of the same basic project

■ For working **with others**:

- ☐ Greatly simplifies concurrent work, merging changes

Git and GitHub

What are Git and GitHub?

- Git is a **free** and **open source**, **distributed** **version control system** designed to handle everything from small to very large projects with speed and efficiency.
- **GitHub** is a **web-based** Git repository **hosting service**, which offers all of the distributed revision control and **source code management (SCM)** functionality of Git as well as adding its own features. GitHub is also free (as in free beer).

GitHub

- <https://github.com/>
- When looking for a software developer position, host substantial projects you have developed on GitHub and give a link in your resume.

About Git


- Created by **Linus Torvalds**, who is the creator of **Linux kernel**, in 2005
 - Came out of Linux development community
 - Designed to do version control on Linux kernel
- Goals of Git:
 - **Speed**
 - Support for **non-linear development** (thousands of parallel branches)
 - Fully **distributed**
 - Able to handle large projects efficiently

(A “git” is a cranky old man. Linus meant himself.)




Centralized VCS

- In **Subversion**, **CVS**, **Perforce**, etc., a central server repository (repo) holds the “official copy” of the code
 - the server maintains the sole version history of the repo
- You make “checkouts” of it to your local copy
 - you make local modifications
 - your changes are not versioned
- When you’re done, you “check in” back to the server
 - your checkin increments the repo’s version



Distributed VCS (Git)


- In **git**, **mercurial**, etc., you don't "checkout" from a central repo
 - you "**clone**" it and "**pull**" changes from it
- Your local repo is a **complete copy** of everything on the remote server
 - yours is "just as good" as theirs
- Many operations are local:
 - **check in/out** from local repo
 - **commit** changes to local repo
 - local repo keeps version history
- When you're ready, you can "**push**" changes back to server



Git


Git snapshots

- Centralized VCS like Subversion track version data on each **individual file**.
- Git keeps “snapshots” of the **entire state** of the project.
 - Each check-in version of the overall code has a copy of each file in it.
 - Some files change on a given check-in, some do not.
 - More redundancy, but faster.




Local git areas

- In your local copy on git, files can be:
 - In your local repo
 - committed
 - Checked out and modified, but not yet committed
 - working copy
 - Or, in-between, in a “staging” area
 - “Staged” files are ready to be committed.
 - A commit saves a snapshot of all staged state.



Basic Git workflow

- **Modify** files in your working directory.
- **Stage** files, adding snapshots of them to your staging area.
- **Commit**, which takes the files in the staging area and stores that snapshot permanently to your Git directory.



Git commit checksums

- In **Subversion** each modification to the central repo increments the version # of the overall repo.
- In **Git**, each user has their own copy of the repo, and commits changes to their local copy of the repo before pushing to the central server.
 - So Git generates a unique **SHA-1 hash** (40-character hex digits) for every commit, **commit hash**
 - Refers to commits by this **ID** rather than a version number.
 - Often we only see the first 7 characters:
 - 1677b2d Edited first line of readme
 - 258efa7 Added line to readme
 - 0e52da7 Initial commit

Git Repository

Initial Git Configuration

- Set the name and email for Git to use when you commit:

- ☐ `git config --global user.name "Bugs Bunny"`
- ☐ `git config --global user.email bugs@gmail.com`
- ☐ You can call `git config --list` to verify these are set.

- Set the editor that is used for writing commit messages:

- ☐ `git config --global core.editor nano`
 - (it is vim editor by default)

The Repository

- Your top-level **working directory** contains everything about your project
 - The working directory probably contains many subdirectories—source code, binaries, documentation, data files, etc.
 - One of these subdirectories, named **.git**, is your repository
- At any time, you can take a “snapshot” of everything (or selected things) in your project directory, and put it in your repository
 - This “snapshot” is called a **commit object**
 - The commit object contains (1) a set of files, (2) references to the “parents” of the commit object, and (3) a unique “SHA1” name
 - Commit objects do *not* require huge amounts of memory
- You can work as much as you like in your working directory, but the repository isn’t updated until you **commit** something

init and the .git repository

- When you said `git init` in your project directory, or when you cloned an existing project, you create a repository
 - The repository is a subdirectory named `.git` containing various files
 - The `dot` indicates a “hidden” directory
 - You **do not** work directly with the contents of `.git`; various git commands do that for you

Creating a Git repo

- To create a new **local Git repo** in your current directory:

- `git init`

- This will create a `.git` directory in your current directory.

- Then you can commit files in that directory into the repo.

- `git add filename`

- `git commit -m "commit message"`

- To **clone a remote repo** to your current directory:

- `git clone url localDirectoryName`

- This will create the given local directory, containing a working copy of the files from the repo, and a `.git` directory (used to hold the staging area and your actual local repo)

Git commands

command	description
<code>git clone url [dir]</code>	copy a Git repository so you can add to it
<code>git add file</code>	adds file contents to the staging area
<code>git commit</code>	records a snapshot of the staging area
<code>git status</code>	view the status of your files in the working directory and staging area
<code>git diff</code>	shows diff of what is staged and what is modified but unstaged
<code>git help [command]</code>	get help info about a particular command
<code>git pull</code>	fetch from a remote repo and try to merge into the current branch
<code>git push</code>	push your new branches and data to a remote repository
others: <code>init</code> , <code>reset</code> , <code>branch</code> , <code>checkout</code> , <code>merge</code> , <code>log</code> , <code>tag</code>	

Local Git Repository

Add and commit a file

- The first time we ask a file to be tracked, and every time before we commit a file, we must add it to the staging area:
 - `git add Hello.java Goodbye.java`
 - Takes a snapshot of these files, adds them to the staging area.
 - In older VCS, “add” means “start tracking this file.” In Git, “add” means “add to staging area” so it will be part of the next commit.
- To move staged changes into the repo, we commit:
 - `git commit -m "Fixing bug #22"`
- To undo changes on a file before you have committed it:
 - `git reset HEAD -- filename` (Unstages the file)
 - `git checkout -- filename` (Undoes your changes)
- All these commands are acting on your local version of repo.

Making Commits

- You do your work in your project directory, as usual
- If you create new files and/or folders, they are *not tracked* by Git unless you ask it to do so

- ☐ `git add newFile1 newFolder1 newFolder2 newFile2`

- Committing makes a “snapshot” of everything being tracked into your repository

- ☐ A message telling what you have done is required
- ☐ `git commit -m "Uncrevulated the conundrum bar"`
- ☐ `git commit`

- This version opens an editor for you to enter the message
 - To finish, save and quit the editor

- Format of the commit message

- ☐ One line containing the complete summary
- ☐ If more than one line, the second line must be blank

Commits and graphs

- A **commit** is when you tell git that a change (or addition) you have made is ready to be included in the project
- When you commit your change to git, it creates a **commit object**
 - A commit object represents the complete state of the project, including all the files in the project
 - The *very first* commit object has no “parents”
 - Usually, you take some commit object, make some changes, and create a new commit object; the original commit object is the parent of the new commit object
 - Hence, most commit objects have a single parent
 - You can also **merge** two commit objects to form a new one
 - The new commit object has two parents
- Hence, commit objects form a **directed acyclic graph (DAG)**
 - Git is all about using and manipulating this graph

Commit messages

- In git, “commits are cheap.” Do them often.
- When you commit, you must provide a one-line message communicating what you have done (to team members or your future self):
 - ☐ Terrible message: “Fixed a bunch of things”
 - ☐ Better message: “Corrected the calculation of median scores”
- You can't say much in one line, so commit often

Typical workflow


■ `git status`

- ☐ See what Git thinks is going on
- ☐ Use this frequently!

■ Work on your files

■ `git add yourEditedFiles`

■ `git commit -m "What did"`



Viewing/undoing changes

- To view status of files in working directory and staging area:

- ☐ `git status` or
- ☐ `git status -s` (short version)

- To see what is modified but unstaged:

- ☐ `git diff`

- To see a list of staged changes:

- ☐ `git diff --cached`

- To see a log of all changes in your local repo:

- ☐ `git log` or `git log --oneline` (shorter version)
 - 1677b2d Edited first line of readme
 - 258efa7 Added line to readme
 - 0e52da7 Initial commit
- ☐ `git log -5` (to show only the 5 most recent updates), etc.

An example workflow

```
$ git init
$ vi sample.txt
$ git status
$ git status -s
  ?? sample.txt
$ git add sample.txt
$ git status -s
  A  sample.txt
```

```
(update sample.txt in editor)
$ git diff
diff --git a/sample.txt b/sample.txt
index 6231f5a..3e32a85 100644
--- a/sample.txt
+++ b/sample.txt
@@ -1,3 +1,3 @@
 12345
 67890
-
+abcde
$ git status -s
AM sample.txt
$ git log
```


Using GitHub with Eclipse

- Open an account on GitHub
- And also create a new repository.
- Also create a token (<https://github.com/settings/tokens>). You will use this token to access your repository on GitHub.
- On the Eclipse side:
 - Click on your project (in Package Explorer)
 - On the menu choose *Team -> Share Project* which creates a *local* git repository for you.
- Then, again from the menu *Team -> Commit*
- Click on the ++ icon to commit staged files (also enter a commit message)
- As the third and final step, “push” committed changes to the repository you created in GitHub account.

Branch in Git

What is a Branch in Git?


- Branch in Git is a way to keep developing and coding a new feature or modification to the software and still not affecting the main part of the project.




- ***The primary or default branch in Git is the master branch (similar to a trunk of the tree).*** As soon as the repository creates, so does the master branch (*or the default branch*).

Branching in Git

- You have been working on a project with the client being happy until this point.




- After that, you decide to develop a feature and create a new branch called feature for the same purpose and start working on it.




Branching in Git

- In the meantime, you decide to develop another feature and wait for the client's approval.



- Now, since you were following the branched strategy, you need to remove the branch, and all the remaining code remains as it is.
- The new feature can be easily added to the master branch to achieve the following.



Branching and Merging

Git uses branching heavily to switch between multiple tasks.

- To create a new local branch:
 - `git branch name`
- To list all local branches: (* = current branch)
 - `git branch`
- To switch to a given local branch:
 - `git checkout branchname`
- To merge changes from a branch into the local master:
 - `git checkout master`
 - `git merge branchname`

Resources

Installing/learning Git

- Git website: <http://git-scm.com/>
 - Free on-line book: <http://git-scm.com/book>
 - Git for Computer Scientists:
 - <http://eagain.net/articles/git-for-computer-scientists/>
- At command line: (where verb = config, add, commit, etc.)
 - `git help verb`