Detectors and alerts

A flag is a reason to look, not a finding.

How our alerts work, and why they're fixed rules rather than a model.



HalvorAI

An analyst never sees a bare score.

Our detectors are deterministic rules with documented thresholds, not a model. Every alert comes with a plain-language explanation.

✕ Alert loop

agt_07 paid Example Market Data $0.01 forty times in 6 minutes at a steady interval. This looks like a retry loop.

Illustrative example

Source: docs.halvorai.com/monitoring/detectors

Behaviour rules

loop

Five or more payments to the same payee for the same amount within ten minutes, at a steady interval.

velocity_spike

Payments in the last hour exceed three times the usual peak, or the usual maximum plus five.

scope_drift

A category or rail the agent has not used in 30 days, three or more times in a day.

Thresholds as documented. Baselines use each agent's last 30 days.

Payee and amount

new_payee

The agent pays someone it has never paid. High when the payee is new to the whole organization and the amount is large.

amount_outlier

An amount far above the agent's usual range and over $50.

sanctions_hit

A payee matched a sanctions list.

Mandates, proofs and combinations

mandate_breach

A payment fell outside the owner's mandate, or a closed mandate's values differ from the event.

evidence_invalid

A cryptographic check on the payment's evidence failed.

composite

Two medium findings from different detectors on one agent within an hour raise one high alert. A hijacked agent usually shows as a combination.

Source: docs.halvorai.com/monitoring/detectors

Where fixed rules fall short.

We put the limits in the pack itself:

- An agent with fewer than 20 events is still learning. Only the rule-based detectors fire for it.
- Newly created agents receive fewer flags.
- A change to a payee's bank details under the same name and payee id is not detected.
- The pack does not prove that the agent's owner authorized a payment.

Source: docs.halvorai.com; limits stated in our synthetic sample evidence pack, halvorai.com/sample

Then a person decides.

- Dismissing an alert takes a reason: expected behaviour, test traffic, duplicate or other.
- So the overview can show a false-positive rate for each detector.
- Every action is recorded with who did it and when.
- Review, and any decision to file a report, belong to the operator and its bank.

HalvorAI reports. It never blocks a payment.

Source: docs.halvorai.com/monitoring/detectors; halvorai.com/sample

Read the thresholds

Every rule is written down.

If a bank reviewer asks why an alert fired, the answer should fit in a sentence. Check ours against the docs and tell us what's missing.

docs.halvorai.com/monitoring/detectors

Developer preview.



HalvorAI