

API Trading Registration & Daily Login Guide

This document explains how to register for API trading and complete the daily login flow to obtain an access token.

1) Registration

1. Go to the registration portal: <https://lemonn-pro.lemonn.co.in/dashboards> (Click **Create App.**)
2. Fill the form:
 - IP address you will use for API trading
 - Callback URL (redirect URL)
3. Submit the form.
4. You will receive:
 - API Key
 - Secret Key

Important: Secret key is shown only once. Store it securely.

2) Daily Login Flow

Step 1: Open login URL

`https://lemonn-pro.lemonn.co.in/login?api_key=<your api key>`

Step 2: Login with phone number

Step 3: Validate OTP

Step 4: Validate PIN

Step 5: Receive request token

After successful login, you will be redirected to your callback URL with a request token.

Notes:

- Request token is single-use
 - Valid for 5 minutes
-

3) Generate Signature

Use your API Key, Secret Key, and Request Token to generate a signature.

```
from cryptography.hazmat.primitives.asymmetric import ed25519
import time

def generate_signature():
    request_token = 'here' # Replace with your request token
    api_key = 'here' # Replace with your API key
    private_key_hex = 'here' # Replace with your secret key (hex)
    epoch_time = str(int(time.time() * 1000))

    signature_msg = request_token + api_key

    # Convert private key from hex
```

```
private_key_bytes = bytes.fromhex(private_key_hex)
private_key = ed25519.Ed25519PrivateKey.from_private_bytes(private_key_bytes)

# Sign the message
signature_bytes = private_key.sign(signature_msg.encode('utf-8'))
signature = signature_bytes.hex()

return epoch_time, signature

if __name__ == "__main__":
    epoch_time, signature = generate_signature()
    print("Epoch Time:", epoch_time)
    print("Signature :", signature)
```

4) Generate Access Token

Call the generate session token API:

```
curl --location --request POST
'https://cs-prod.lemonn.co.in/api-trading/api/v1/generate_session_token' \
--header 'Content-Type: application/json' \
--header 'x-api-key: <your api key>' \
--header 'x-request-token: <request token>' \
--header 'x-signature: <signature>'
```

Response will contain an access token.

5) Use Access Token

- The access token must be used for all subsequent API calls.
 - If the IP address does not match the one registered, the request will fail.
-

Summary Checklist

- Register app and collect API Key + Secret Key
- Daily login to get Request Token
- Generate Signature
- Call Generate Session Token API
- Use Access Token for API calls