

Inspection Report Template

MVTec AD Industrial Defect Inspection - RAG Knowledge Base Document

Synthetic QA/SOP document for AI defect detection, root-cause assistance, and automated inspection report generation.

Document ID	IRT-MVTec-RAG-005
Version	1.0
Prepared For	AI Defect Detection and Root-Cause Assistant
Dataset Context	MVTec AD categories: bottle, cable, screw, transistor, tile, toothbrush, zipper, metal_nut
Document Type	Inspection report structure, field definitions, output format, and RAG guide
Status	Synthetic training and demonstration document
Generated On	2026-05-19

Important note: This document is created for a student/prototype AI inspection system. It is not an official factory compliance standard and must be validated by a qualified quality engineer before use in real production.

1. Purpose of This Template

This document defines the standard inspection report format for the AI Defect Detection and Root-Cause Assistant. The report template is designed to capture the visual model output, retrieved QA/SOP evidence, possible root-cause notes, operator actions, and human review decisions in one consistent structure.

The template is also prepared for RAG ingestion. Each section uses clear headings, repeated keywords, and structured field names so that a retrieval system can find the correct report rules when the AI assistant is asked how to write, complete, validate, or explain an inspection report.

The template supports the following selected MVTec AD categories: bottle, cable, screw, transistor, tile, toothbrush, zipper, and metal_nut.

The final generated inspection report should not be only a free-text paragraph. It should be a structured quality record that can be reviewed, stored, searched, and compared across inspection runs.

2. Scope and Intended Users

User	How the template helps
Quality inspector	Provides a clear record of product condition, AI findings, severity, and required action.
Line operator	Shows immediate action such as accept, rework, reject, quarantine, retake image, or escalate.
Supervisor	Supports review of major/critical findings and uncertain AI decisions.
AI system developer	Defines required backend fields, frontend display sections, PDF report layout, and database schema.
RAG assistant	Retrieves report rules, field definitions, evidence requirements, and report writing instructions.

3. Report Generation Principles

- 1 Every report must include product category, image filename, inspection timestamp, defect status, severity, action, and review decision.
- 2 Every AI explanation must be grounded in the vision model result and retrieved QA/SOP evidence when available.
- 3 The system must not claim a guaranteed root cause from an image alone. It must use wording such as possible cause, likely checkpoint, or recommended investigation area.
- 4 If confidence is low, image quality is poor, or RAG evidence is missing, the report must clearly mark human review required.
- 5 The generated report must separate model output, retrieved evidence, and final recommendation so users can understand where each conclusion came from.
- 6 The report must be understandable by non-technical users, but it should still preserve important technical metadata for audit and debugging.

4. Standard Report Header

Every generated report must start with a standard header. The header identifies the inspection record and connects the uploaded image with product category, operator, model version, and timestamp.

Field	Required	Description	Example
Inspection ID	Yes	Unique ID for the inspection record. Should be generated automatically by the backend.	INS-2026-000124
Report Type	Yes	Type of report generated by the system.	AI Defect Inspection Report
Date and Time	Yes	Local timestamp when inspection was executed.	2026-05-19 09:45:12

Field	Required	Description	Example
Product Category	Yes	MVTec AD category or selected product type.	bottle / cable / screw / transistor / tile / toothbrush / zipper / metal_nut
Image Filename	Yes	Original uploaded image or frame name.	bottle_test_015.png
Operator ID	Optional	Human user who submitted the inspection.	OP-014
Inspection Station	Optional	Factory line, bench, or camera station.	Line-A Camera-02
Model Version	Yes	Vision model version used for prediction.	anomaly_model_v1.2
RAG Knowledge Base Version	Yes	Document index or knowledge base version used.	rag_kb_2026_05_v1

5. Executive Summary Section

The executive summary is the first section shown to the user. It should provide a short and simple answer before detailed evidence is displayed.

Summary Field	Rule
Overall Decision	Use one of: ACCEPT, REWORK, REJECT, QUARANTINE, RETAKE_IMAGE, HUMAN_REVIEW, ESCALATE_PROCESS.
Defect Status	Use one of: Normal, Defective, Suspected Defect, Unclear Image, Unknown.
Severity	Use one of: Normal, Minor, Major, Critical, Human Review Required.
Confidence	Show model confidence as percentage or score. If unavailable, write Not available.
Short Explanation	One to three sentences written in simple English.
Recommended Action	State what the operator should do next.

Example executive summary:

The uploaded image is classified as defective with high confidence. The system detected a visible anomaly on the bottle surface. Based on the QA inspection guide, visible cracks, contamination, or structural deformation should not be accepted without review. Recommended action: reject the item or send it for supervisor review depending on final severity confirmation.

6. Image and Input Quality Section

The report must include an image quality result before the defect conclusion. A poor image can cause false positive or false negative model outputs. If the image quality check fails, the report should not present a strong final decision.

Input Check	Pass Condition	Fail Condition	Report Action
Image clarity	Product edges and defect region are visible.	Blur, motion shake, heavy noise.	Mark RETAKE_IMAGE or HUMAN_REVIEW.
Lighting	Image is neither too dark nor overexposed.	Very dark, glare, strong reflection.	Ask user for better lighting.
Product visibility	Main product is fully visible.	Product partly cut off or blocked.	Request full product image.
Resolution	Sufficient detail for model inference.	Very low resolution or compressed image.	Request higher-quality image.
Correct category	Image matches selected product category.	Wrong product type uploaded.	Ask user to select correct category.

7. Visual Model Output Section

This section records the direct output of the computer vision module. It should not be rewritten as if it were human-confirmed truth. It is a model prediction and must be labelled as such.

Field	Required	Description
Predicted status	Yes	Normal, abnormal, suspected anomaly, or model unable to decide.
Predicted category	Yes	The product category used by the model.
Anomaly score	Yes if available	Numerical anomaly score from the model.
Confidence score	Yes if available	Probability or confidence returned by the classifier/detector.
Detected region	Optional	Bounding box, mask, heatmap, or textual location.
Region description	Optional	Example: upper edge, lower-left area, connector side, thread region.
Model notes	Optional	Any technical warning such as out-of-distribution or low image quality.

For anomaly models using MVTec AD, the report may show an anomaly heatmap or mask when available. If no heatmap is produced, the report must clearly state that localization is unavailable.

8. Category-Specific Report Notes

The product category must control the language used in the final report. The same word defective is not enough because a defect in a bottle, cable, screw, transistor, tile, toothbrush, zipper, or metal nut has different quality meaning and action.

Category	Main inspection focus	Common report language	Critical report trigger
Bottle	Surface integrity, shape, contamination, deformation, visible cracks	The bottle image shows a suspected surface or structural anomaly.	Crack, hole, deformation that may affect containment or sealing.
Cable	Outer insulation, connector region, cuts, bends, missing segments	The cable image shows a suspected insulation or connector anomaly.	Exposed conductor, severe cut, connector damage, safety risk.
Screw	Thread quality, head condition, deformation, contamination	The screw image shows a suspected thread, head, or surface anomaly.	Damaged thread, broken head, deformation affecting assembly.
Transistor	Pins/leads, body damage, placement, contamination	The transistor image shows a suspected component body or pin anomaly.	Broken/missing pin, severe body damage, electrical assembly risk.
Tile	Surface cracks, chips, stains, texture discontinuity	The tile image shows a suspected surface or edge anomaly.	Large crack, broken edge, deep chip, structural issue.
Toothbrush	Bristles, handle, head, contamination	The toothbrush image shows a suspected bristle or handle anomaly.	Missing bristles, broken head/handle, hygiene or safety risk.
Zipper	Teeth alignment, slider, tape, missing/broken teeth	The zipper image shows a suspected tooth, slider, or alignment anomaly.	Broken/missing teeth, slider failure, closure failure.
Metal nut	Thread, edge, surface, corrosion, deformation	The metal nut image shows a suspected thread, surface, or shape anomaly.	Damaged thread, crack, deformation affecting fastening.

9. Severity and Decision Section

The report must map the detected issue to a severity level and an operator action. The AI assistant may suggest a severity, but the report must show whether the decision is automatic or requires human review.

Severity	Meaning	Typical action	Report wording
Normal	No visible defect or anomaly is detected with acceptable confidence.	ACCEPT	No defect was detected. Product may continue if all checks pass.
Minor	Small cosmetic or low-impact anomaly that may not affect function.	REWORK or ACCEPT_WITH_NOTE	Minor anomaly detected. Rework or monitor based on SOP.
Major	Clear defect that may affect product function, fit, finish, reliability, or customer acceptance.	REJECT or REWORK	Major defect detected. Remove from normal flow and follow SOP.
Critical	Defect may create safety, functional, sealing, electrical, assembly, hygiene, or structural risk.	REJECT and ESCALATE	Critical defect suspected. Reject item and notify supervisor.
Human Review Required	AI result is uncertain, image quality is poor, or evidence is insufficient.	HUMAN_REVIEW	AI cannot make a reliable final decision. Manual inspection required.

10. RAG Evidence Section

The report must include a section that lists the documents used by the RAG system. This is important because the final recommendation should be grounded in QA/SOP evidence rather than unsupported model memory.

Evidence Field	Description	Example
Source document	Name of retrieved manual, guide, SOP, or policy.	Defect_Severity_Guide.pdf
Section title	Heading or subsection retrieved by RAG.	Bottle Severity Rules

Evidence Field	Description	Example
Evidence snippet	Short supporting text from the retrieved chunk.	Visible structural cracks are treated as major or critical defects.
Relevance score	Vector search similarity score if available.	0.82
Used in final answer	Yes or No. Only evidence used should be cited in final explanation.	Yes

If no relevant evidence is found, the report must say: No matching SOP evidence was retrieved. Human review is required before final action.

11. Possible Root-Cause Section

The inspection report may include possible root causes, but it must never claim a guaranteed cause from image data alone. Root cause should be written as a hypothesis and connected to recommended inspection checkpoints.

Root-cause wording	Allowed?	Reason
This defect may be related to poor handling or impact damage.	Allowed	Uses possible language and does not overclaim.
The likely checkpoint is machine alignment, tool wear, or material contamination.	Allowed	Lists investigation areas.
This defect was definitely caused by overheating.	Not allowed	Image-only evidence cannot prove this.
The operator must investigate molding pressure, alignment, or contamination based on SOP evidence.	Allowed	Suggests action rather than making a final cause claim.

12. Operator Action Section

The final report must include a clear action code. The action code is important because it can be stored in the database, filtered in dashboards, and used to trigger follow-up tasks.

Action Code	When to use	Report sentence
ACCEPT	Normal result with acceptable confidence and no review trigger.	Product may continue to the next process step.
REWORK	Minor or repairable anomaly based on SOP.	Send item for rework and inspect again after correction.
REJECT	Major or critical defect affecting quality, fit, function, safety, or customer acceptance.	Remove item from normal production flow and mark as rejected.
QUARANTINE	Batch-level concern, repeated defect pattern, or uncertain safety issue.	Hold the item or batch until supervisor review is completed.
RETAKE_IMAGE	Poor image quality or product not fully visible.	Upload a clearer image before final decision.
HUMAN_REVIEW	Low confidence, missing RAG evidence, conflicting results, or critical case.	Manual inspection is required before final disposition.
ESCALATE_PROCESS	Repeated defects or possible process fault.	Notify process engineer or supervisor to investigate equipment/process condition.

13. Complete Report Layout

A generated PDF inspection report should follow this layout order:

- 1 Report header: inspection ID, timestamp, product category, operator, model version, knowledge base version.
- 2 Executive summary: overall decision, defect status, severity, recommended action.
- 3 Uploaded image preview and optional annotated image or heatmap.
- 4 Image quality check results.
- 5 Computer vision model output: prediction, confidence, anomaly score, region.
- 6 OCR results if printed text is detected.
- 7 Retrieved RAG evidence: source document, section, snippet, relevance score.
- 8 Possible root-cause hypotheses and recommended checkpoints.
- 9 Operator action and escalation requirement.
- 10 Human review status and reviewer signature if needed.
- 11 System metadata and audit log summary.

14. Report Field Dictionary

The following dictionary can be used by the backend, frontend, database, and PDF generator. It helps keep the generated reports consistent.

Field Name	Type	Required	Description
inspection_id	string	Yes	Unique inspection record ID.
created_at	datetime	Yes	Date and time of report generation.
product_category	string	Yes	MVTec AD category selected for the image.
image_filename	string	Yes	Original uploaded image filename.
image_quality_status	string	Yes	Pass, fail, warning, or not checked.
defect_status	string	Yes	Normal, defective, suspected defect, unclear, or unknown.
predicted_label	string	Yes	Model predicted label or anomaly type.
confidence_score	float	Optional	Model confidence score when available.
anomaly_score	float	Optional	Anomaly score when using anomaly detection.
severity_level	string	Yes	Normal, Minor, Major, Critical, Human Review Required.
action_code	string	Yes	ACCEPT, REWORK, REJECT, QUARANTINE, RETAKE_IMAGE, HUMAN_REVIEW, ESCALATE_PROCESS.
detected_region	string/object	Optional	Text location, bounding box, segmentation mask path, or heatmap path.
ocr_text	string	Optional	Text extracted from label, serial number, batch code, or product marking.
rag_sources	list	Yes	Retrieved documents and evidence snippets used in answer.
possible_root_causes	list	Optional	Possible causes or checkpoints. Must not be written as certain facts.
recommended_action	string	Yes	Plain-English operator action.
human_review_required	boolean	Yes	True if manual inspection is needed.
review_reason	string	Optional	Reason why human review is required.
model_version	string	Yes	Version of computer vision model.
kb_version	string	Yes	RAG knowledge base version.

15. Recommended JSON Output Schema

The AI backend should first create a structured JSON object, then generate the PDF from that JSON. This prevents missing report fields and makes the report easier to test.

```
{ "inspection_id": "INS-2026-000124", "created_at": "2026-05-19T09:45:12+05:30", "product_category": "bottle", "image_filename": "bottle_test_015.png", "image_quality_status": "pass", "vision_result": { "defect_status": "defective", "predicted_label": "surface anomaly", "confidence_score": 0.92, "anomaly_score": 0.81, "detected_region": "upper-right body area" }, "severity_level": "Major", "action_code": "REJECT", "rag_sources": [ { "document": "QA_Inspection_Manual_MVTec_AD.pdf", "section": "Bottle Inspection SOP", "snippet": "Visible cracks or structural deformation require rejection or review." }, { "document": "QA_Inspection_Manual_MVTec_AD.pdf", "section": "Molding or cooling variation", "snippet": "Molding or cooling variation requires review." } ], "possible_root_causes": [ "handling damage", "molding or cooling variation" ], "recommended_action": "Remove the item from normal flow and send for supervisor confirmation.", "human_review_required": true, "review_reason": "Major defect detected and root cause cannot be confirmed from image alone." }
```

16. Printable Report Template

The following template can be used as the main PDF layout generated by the application. Placeholders in square brackets should be replaced by backend values.

A. Report Header

- Inspection ID: [inspection_id]
- Date and Time: [created_at]
- Product Category: [product_category]
- Image Filename: [image_filename]
- Operator ID: [operator_id]
- Inspection Station: [inspection_station]
- Model Version: [model_version]
- Knowledge Base Version: [kb_version]

B. Executive Summary

- Overall Decision: [action_code]
- Defect Status: [defect_status]
- Severity Level: [severity_level]
- Confidence Score: [confidence_score]
- Human Review Required: [yes/no]
- Summary: [short_explanation]

C. Image Quality Result

- Image Quality Status: [pass/warning/fail]
- Quality Notes: [image_quality_notes]
- Retake Required: [yes/no]

D. Vision Model Result

- Predicted Label: [predicted_label]
- Anomaly Score: [anomaly_score]
- Detected Region: [detected_region]
- Annotated Image or Heatmap: [image_path]

E. RAG Evidence

- Source Document 1: [document_name]
- Section: [section_title]
- Evidence Snippet: [snippet]
- Relevance Score: [score]

F. Possible Root Cause and Checkpoints

- Possible Root Cause(s): [possible_root_causes]

- Recommended Checkpoints: [machine/process/material/operator checkpoints]
- Caution: Root cause is a hypothesis and must be confirmed by human/process evidence.

G. Recommended Operator Action

- Action Code: [action_code]
- Recommended Action: [recommended_action]
- Escalation Needed: [yes/no]
- Supervisor Review Required: [yes/no]

H. Review and Sign-off

- Reviewer Name: _____
- Reviewer Decision: Accept / Rework / Reject / Quarantine / Retake Image
- Reviewer Comment: _____
- Signature: _____
- Date: _____

17. Category-Specific Example Report Sentences

These example sentences can be used by the LLM when generating short, consistent report explanations. They must be adapted to the actual prediction and retrieved evidence.

Category	Normal example	Defective example
Bottle	No visible bottle anomaly was detected. The item may continue if all station checks pass.	A visible bottle surface or shape anomaly was detected. Review sealing and structural integrity before release.
Cable	The cable insulation and visible connector area appear acceptable in the uploaded image.	A suspected cable insulation or connector anomaly was detected. The item should be held for safety and continuity review.
Screw	The screw head and thread region appear acceptable in the uploaded image.	A suspected screw thread or head anomaly was detected. Check assembly fit and remove from use if fastening reliability is affected.
Transistor	The transistor body and visible pins appear acceptable in the uploaded image.	A suspected pin, lead, or body anomaly was detected. Send for electronic component review before assembly.
Tile	The tile surface appears normal with no visible crack or major surface issue.	A suspected tile crack, chip, stain, or texture anomaly was detected. Review structural and appearance requirements.
Toothbrush	The toothbrush head, bristles, and handle appear acceptable in the uploaded image.	A suspected bristle, handle, or contamination anomaly was detected. Hold item due to hygiene or user safety concern.
Zipper	The zipper teeth, slider, and tape appear acceptable in the uploaded image.	A suspected zipper tooth, slider, or alignment anomaly was detected. Check closure function before acceptance.
Metal nut	The metal nut thread and surface appear acceptable in the uploaded image.	A suspected metal nut thread, surface, or shape anomaly was detected. Review fastening reliability before use.

18. Confidence and Review Logic

Condition	Report decision behavior
Confidence $\geq$ 90% and severity normal	Allow ACCEPT if image quality passed and no other warnings exist.
Confidence $\geq$ 85% and severity minor	Allow REWORK or ACCEPT_WITH_NOTE based on SOP evidence.
Confidence $\geq$ 80% and severity major	Recommend REJECT or REWORK and mark supervisor review if required.
Critical severity at any confidence	Recommend REJECT/QUARANTINE and require human review.
Confidence between 60% and 79%	Mark HUMAN_REVIEW unless strong evidence and safe action rules exist.
Confidence $<$ 60%	Do not make final defect decision. Mark HUMAN_REVIEW or RETAKE_IMAGE.
Image quality fail	Do not issue final product decision. Mark RETAKE_IMAGE.
No RAG evidence retrieved	Allow visual summary, but mark evidence missing and request human review for action.

19. Audit Log and Traceability Section

The report should include enough metadata to reproduce or debug the result later. This is especially important for AI systems because model versions, prompt versions, and RAG index versions may change over time.

Audit Item	Required?	Description
Model version	Yes	Exact trained model or checkpoint used.
Prompt version	Yes if LLM used	Prompt template version for explanation/report writing.
RAG index version	Yes if RAG used	Vector database collection or index version.
Source document list	Yes if RAG used	Files used as supporting evidence.
Image preprocessing settings	Optional	Resize, normalization, crop, threshold, or augmentation settings.
Runtime warnings	Yes if present	Low confidence, poor image, missing OCR, no evidence retrieved, etc.
Human override	Yes if used	Any manual change to severity, action, or report decision.

20. Report Validation Checklist

Before saving or downloading the report, the system should validate that key fields are present.

Check	Pass condition
Report ID exists	inspection_id is not empty.
Category selected	product_category is one of bottle, cable, screw, transistor, tile, toothbrush, zipper, metal_nut.
Image attached	image_filename or stored image path exists.
Image quality result	image_quality_status is pass, warning, fail, or not checked.
Prediction result	defect_status and predicted_label are present.
Decision present	severity_level and action_code are present.
RAG evidence handling	Either sources are listed or missing-evidence warning is shown.
Human review logic	human_review_required is true when confidence/image/evidence conditions require it.
Root-cause safety	Root-cause section uses possible/likely/checkpoint wording, not guaranteed wording.

21. RAG Retrieval Keywords

The following keywords and phrases should be included in this document to help the retriever find relevant report-writing rules.

Topic	Recommended retrieval keywords
Report header	inspection ID, timestamp, product category, image filename, model version, operator ID
Executive summary	overall decision, defect status, severity level, recommended action, short explanation
Evidence	RAG evidence, source document, evidence snippet, relevance score, retrieved section
Human review	human review required, low confidence, missing evidence, poor image quality, manual inspection
Root cause	possible root cause, likely checkpoint, investigation area, do not overclaim
Action code	ACCEPT, REWORK, REJECT, QUARANTINE, RETAKE_IMAGE, HUMAN_REVIEW, ESCALATE_PROCESS
Audit	model version, prompt version, RAG index version, traceability, system metadata

22. RAG Chunking Guidance

For best retrieval results, chunk this document by headings. Keep each chunk with its title, section number, and product category where applicable. Do not merge unrelated sections such as report header fields and root-cause safety rules into one large chunk.

- Recommended chunk size: 500 to 900 tokens per chunk.
- Recommended overlap: 80 to 120 tokens.
- Preserve table titles and first column names during chunking.
- Use metadata fields such as `document_name`, `section_title`, `category`, and `document_type`.
- Mark this file with `document_type = inspection_report_template`.

23. Sample Filled Report - Bottle

This sample is provided for testing the report generator and RAG retrieval. It is not a real inspection record.

Field	Sample value
Inspection ID	INS-SAMPLE-0001
Product Category	bottle
Image Filename	bottle_test_sample_01.png
Image Quality	Pass
Defect Status	Defective
Predicted Label	surface anomaly
Confidence Score	0.92
Detected Region	upper-right bottle body area
Severity	Major
Action Code	REJECT
RAG Evidence	QA manual section: visible cracks, contamination, or deformation require rejection or supervisor review.
Possible Root Cause	Possible handling damage, molding variation, or contamination checkpoint.
Recommended Action	Remove item from normal flow, mark rejected, and notify supervisor if repeated defects are observed.
Human Review Required	Yes

Sample executive summary:

The bottle image is classified as defective with high confidence. A visible surface anomaly was found in the upper-right body area. Based on the QA inspection guidance, visible structural anomalies should be rejected or reviewed before release. Recommended action: reject the item and check whether similar defects are appearing in the same batch.

24. Sample Filled Report - Cable

Field	Sample value
Inspection ID	INS-SAMPLE-0002
Product Category	cable
Image Filename	cable_test_sample_04.png
Image Quality	Warning - glare near connector
Defect Status	Suspected Defect
Predicted Label	connector/insulation anomaly
Confidence Score	0.76
Detected Region	connector end
Severity	Human Review Required
Action Code	HUMAN_REVIEW
RAG Evidence	Operator SOP section: cable insulation and connector anomalies must be reviewed before release.
Possible Root Cause	Possible handling, connector crimping, or insulation process checkpoint.
Recommended Action	Do not release item automatically. Send to human inspector and retake image if glare prevents clear decision.
Human Review Required	Yes

25. Sample Filled Report - Metal Nut

Field	Sample value
Inspection ID	INS-SAMPLE-0003
Product Category	metal_nut
Image Filename	metal_nut_test_sample_07.png
Image Quality	Pass
Defect Status	Defective
Predicted Label	thread/surface anomaly
Confidence Score	0.88
Detected Region	inner thread region
Severity	Major
Action Code	REJECT
RAG Evidence	Severity guide section: damaged thread or deformation affecting fastening reliability is major or critical.
Possible Root Cause	Possible tool wear, machining misalignment, or material contamination checkpoint.
Recommended Action	Reject item, inspect tooling condition, and review nearby production samples if repeated.
Human Review Required	Yes

26. Questions This Document Should Answer in RAG

Use these questions as retrieval tests after indexing the document into the vector database.

- 1 What fields must be included in an AI inspection report?
- 2 How should the report show RAG evidence?
- 3 What should the report say if no SOP evidence is retrieved?
- 4 How should possible root causes be written safely?
- 5 What action codes can appear in the inspection report?
- 6 When should human review be marked in the report?
- 7 What should be included in the executive summary?
- 8 What should a bottle defect report include?
- 9 How should a cable defect report handle low confidence?
- 10 What JSON schema should the backend produce before generating the PDF?

27. Final Rule for the AI Assistant

When generating an inspection report, the AI assistant must be clear, grounded, and cautious. It should combine model output, image quality status, RAG evidence, and safe action rules. It must not invent evidence, must not overclaim root cause, and must mark human review when confidence or evidence is insufficient.

28. Document Control

Version	Date	Change summary	Prepared by
1.0	2026-05-19	Initial synthetic inspection report template for MVTec AD RAG document set.	AI assistant