

Note to other teachers and users of these slides: We would be delighted if you found this our material useful in giving your own lectures. Feel free to use these slides verbatim, or to modify them to fit your own needs. If you make use of a significant portion of these slides in your own lecture, please include this message, or a link to our web site: <http://www.mmds.org>

Mining Data Streams (Part 1)

Mining of Massive Datasets

Jure Leskovec, Anand Rajaraman, Jeff Ullman

Stanford University

<http://www.mmds.org>




Data Streams

- In many data mining situations, we do not know the entire data set in advance
- **Stream Management** is important when the input rate is controlled **externally**:
 - Google queries
 - Twitter or Facebook status updates
- We can think of the **data** as **infinite** and **non-stationary** (the distribution changes over time)

The Stream Model

- Input **elements** enter at a rapid rate, at one or more input ports (i.e., **streams**)
 - **We call elements of the stream tuples**
- **The system cannot store the entire stream accessibly**
- **Q: How do you make critical calculations about the stream using a limited amount of (secondary) memory?**

General Stream Processing Model



Problems on Data Streams

- **Types of queries one wants on answer on a data stream:**
 - **Sampling data from a stream**
 - Construct a random sample
 - **Queries over sliding windows**
 - Number of items of type x in the last k elements of the stream

Problems on Data Streams

- **Types of queries one wants on answer on a data stream:**
 - **Filtering a data stream**
 - Select elements with property x from the stream
 - **Counting distinct elements**
 - Number of distinct elements in the last k elements of the stream
 - **Estimating moments**
 - Estimate avg./std. dev. of last k elements
 - **Finding frequent elements**

Applications (1)

- **Mining query streams**
 - Google wants to know what queries are more frequent today than yesterday
- **Mining click streams**
 - Yahoo wants to know which of its pages are getting an unusual number of hits in the past hour
- **Mining social network news feeds**
 - E.g., look for trending topics on Twitter, Facebook

Applications (2)

- **Sensor Networks**

- Many sensors feeding into a central controller

- **Telephone call records**

- Data feeds into customer bills as well as settlements between telephone companies

- **IP packets monitored at a switch**

- Gather information for optimal routing
- Detect denial-of-service attacks

Sampling from a Data Stream: Sampling a fixed proportion

As the stream grows the sample
also gets bigger

Sampling from a Data Stream

- Since **we can not store the entire stream**, one obvious approach is to store a **sample**
- **Two different problems:**
 - (1) Sample a **fixed proportion** of elements in the stream (say 1 in 10)
 - (2) Maintain a **random sample of fixed size** over a potentially infinite stream
 - At any “time” k we would like a random sample of s elements
 - **What is the property of the sample we want to maintain?**
For all time steps k , each of k elements seen so far has equal prob. of being sampled

Sampling a Fixed Proportion

- **Problem 1: Sampling fixed proportion**
- **Scenario:** Search engine query stream
 - **Stream of tuples:** (user, query, time)
 - **Answer questions such as:** How often did a user run the same query in a single days
 - Have space to store $1/10^{\text{th}}$ of query stream
- **Naïve solution:**
 - Generate a random integer in $[0..9]$ for each query
 - Store the query if the integer is **0**, otherwise discard

Problem with Naïve Approach

- **Simple question:** What fraction of queries by an average search engine user are duplicates?
 - Suppose each user issues x queries once and d queries twice (total of $x+2d$ queries)
 - **Correct answer:** $d/(x+d)$
 - **Proposed solution:** We keep 10% of the queries
 - Sample will contain $x/10$ of the singleton queries and $2d/10$ of the duplicate queries at least once
 - But only $d/100$ pairs of duplicates
 - $d/100 = 1/10 \cdot 1/10 \cdot d$
 - Of d “duplicates” $18d/100$ appear exactly once
 - $18d/100 = ((1/10 \cdot 9/10) + (9/10 \cdot 1/10)) \cdot d$
 - **So the sample-based answer is**
$$\frac{\frac{x}{10} + \frac{\frac{d}{100}}{100} + \frac{18d}{100}}{\frac{x}{10} + \frac{d}{100} + \frac{18d}{100}} = \frac{d}{10x + 19d}$$

Solution: Sample Users

Solution:

- Pick $1/10^{\text{th}}$ of **users** and take all their searches in the sample
- Use a hash function that hashes the user name or user id uniformly into 10 buckets

Generalized Solution

- **Stream of tuples with keys:**
 - Key is some subset of each tuple's components
 - e.g., tuple is (user, search, time); key is **user**
 - Choice of key depends on application
- **To get a sample of a/b fraction of the stream:**
 - Hash each tuple's key uniformly into **b** buckets
 - Pick the tuple if its hash value is at most **a**



Hash table with **b** buckets, pick the tuple if its hash value is at most **a** .

How to generate a 30% sample?

Hash into $b=10$ buckets, take the tuple if it hashes to one of the first 3 buckets

Queries over a (long) Sliding Window

Sliding Windows

- A useful model of stream processing is that queries are about a **window** of length N – the N most recent elements received
- **Interesting case:** N is so large that the data cannot be stored in memory, or even on disk
 - Or, there are so many streams that windows for all cannot be stored
- **Amazon example:**
 - For every product X we keep 0/1 stream of whether that product was sold in the n -th transaction
 - We want answer queries, how many times have we sold X in the last k sales

Sliding Window: 1 Stream

■ Sliding window on a single stream:

N = 6

q w e r t y u i o p a s d f g h j k l z x c v b n m

q w e r t y u i o p a s d f g h j k l z x c v b n m

q w e r t y u i o p a s d f g h j k l z x c v b n m

q w e r t y u i o p a s d f g h j k l z x c v b n m

← Past

Future →

Counting Bits (1)


■ Problem:

- Given a stream of **0s** and **1s**
- Be prepared to answer queries of the form
How many 1s are in the last k bits? where $k \leq N$

■ Obvious solution:

Store the most recent N bits

- When new bit comes in, discard the $N+1^{\text{st}}$ bit



Suppose $N=6$


Counting Bits (2)

- You can not get an exact answer without storing the entire window

- **Real Problem:**

What if we cannot afford to store N bits?


- E.g., we're processing 1 billion streams and
 $N = 1$ billion



- **But we are happy with an approximate answer**

An attempt: Simple solution

- Q: How many 1s are in the last N bits?
- A simple solution that does not really solve our problem: **Uniformity assumption**



- **Maintain 2 counters:**
 - S : number of 1s from the beginning of the stream
 - Z : number of 0s from the beginning of the stream
- How many 1s are in the last N bits? $N \cdot \frac{S}{S+Z}$
- **But, what if stream is non-uniform?**
 - What if distribution changes over time?


DGIM Method

- DGIM solution that does not assume uniformity
- We store $O(\log^2 N)$ bits per stream
- Solution gives approximate answer, never off by more than 50%
 - Error factor can be reduced to any fraction > 0 , with more complicated algorithm and proportionally more stored bits

Idea: Exponential Windows

- **Solution that doesn't (quite) work:**
 - Summarize **exponentially increasing** regions of the stream, looking backward
 - Drop small regions if they begin at the same point as a larger region

Window of
width 16
has 6 1s




We can reconstruct the count of the last N bits, except we are not sure how many of the last **6 1s** are included in the N

What's Good?

- Stores only $O(\log^2 N)$ bits
 - $O(\log N)$ counts of $\log_2 N$ bits each
- Easy update as more bits enter
- Error in count no greater than the number of **1s** in the “**unknown**” area


What's Not So Good?

- As long as the **1s** are fairly evenly distributed, the error due to the unknown region is small
 - **no more than 50%**
- But it could be that all the **1s** are in the unknown area at the end
- In that case, **the error is unbounded!**



Fixup: DGIM method

- **Idea:** Instead of summarizing fixed-length blocks, summarize blocks with specific number of **1s**:
 - Let the block *sizes* (number of **1s**) increase exponentially
- When there are few 1s in the window, block sizes stay small, so errors are small




DGIM: Timestamps

- Each bit in the stream has a *timestamp*, starting **1, 2, ...**
- Record timestamps modulo N (**the window size**), so we can represent any **relevant** timestamp in $O(\log_2 N)$ bits

DGIM: Buckets


- A **bucket** in the DGIM method is a record consisting of:
 - (A) The timestamp of its end [$O(\log N)$ bits]
 - (B) The number of 1s between its beginning and end [$O(\log \log N)$ bits]
- **Constraint on buckets:**
Number of **1s** must be a power of 2
 - That explains the $O(\log \log N)$ in (B) above



Representing a Stream by Buckets

- Either **one** or **two** buckets with the same **power-of-2 number of 1s**
- **Buckets do not overlap in timestamps**
- **Buckets are sorted by size**
 - Earlier buckets are not smaller than later buckets
- Buckets disappear when their end-time is $> N$ time units in the past

Example: Bucketized Stream



Three properties of buckets that are maintained:

- Either **one** or **two** buckets with the same **power-of-2** number of **1s**
- Buckets do not overlap in timestamps
- Buckets are sorted by size

Updating Buckets (1)

- When a new bit comes in, drop the last (oldest) bucket if its end-time is prior to N time units before the current time
- **2 cases:** Current bit is **0** or **1**
- **If the current bit is 0:**
no other changes are needed

Updating Buckets (2)

- **If the current bit is 1:**
 - (1) Create a new bucket of size **1**, for just this bit
 - End timestamp = current time
 - (2) If there are now **three buckets of size 1**,
combine the oldest two into a bucket of size 2
 - (3) If there are now **three buckets of size 2**,
combine the oldest two into a bucket of size 4
 - (4) And so on ...

Example: Updating Buckets

Current state of the stream:

10010101100010110 101010101010110 1010101010101110 1010101110101000 10110010

Bit of value 1 arrives

0010101100010110 101010101010110 1010101010101110 1010101110101000 10110010101

Two orange buckets get merged into a yellow bucket

0010101100010110 101010101010110 1010101010101110 1010101110101000 101100101

Next bit 1 arrives, new orange bucket is created, then 0 comes, then 1:

0101100010110 101010101010110 1010101010101110 1010101110101000 101100101101

Buckets get merged...

0101100010110 101010101010110 1010101010101110 1010101110101000 101100101101


State of the buckets after merging

0101100010110 1010101010101101010101010101110 1010101110101000 101100101101

How to Query?


- To estimate the number of 1s in the most recent N bits:
 1. Sum the sizes of all buckets but the last
(note “size” means the number of 1s in the bucket)
 2. Add half the size of the last bucket
- **Remember:** We do not know how many 1s of the last bucket are still within the wanted window

Example: Bucketized Stream



Error Bound: Proof

- **Why is error 50%? Let's prove it!**
- Suppose the last bucket has size 2^r
- Then by assuming 2^{r-1} (i.e., half) of its **1s** are still within the window, we make an error of at most 2^{r-1}
- Since there is at least one bucket of each of the sizes less than 2^r , the true sum is at least $1 + 2 + 4 + \dots + 2^{r-1} = 2^r - 1$
- Thus, error at most 50%




Further Reducing the Error

- Instead of maintaining **1** or **2** of each size bucket, we allow either **$r-1$** or **r** buckets (**$r > 2$**)
 - Except for the largest size buckets; we can have any number between **1** and **r** of those
- **Error is at most $O(1/r)$**
- By picking **r** appropriately, we can tradeoff between number of bits we store and the error

Extensions


- Can we use the same trick to answer queries
How many 1's in the last k ? where $k < N$?
 - **A:** Find earliest bucket **B** that at overlaps with k .
Number of **1s** is the **sum of sizes of more recent buckets + $\frac{1}{2}$ size of B**



- Can we handle the case where the stream is not bits, but integers, and we want the sum of the last k elements?

Extensions

- **Stream of positive integers**
- **We want the sum of the last k elements**
 - Amazon: Avg. price of last k sales
- **Solution:**
 - **(1) If you know all have at most m bits**
 - Treat m bits of each integer as a separate stream
 - Use DGIM to count **1s** in each integer c_i ...estimated count for **i -th bit**
 - The sum is $= \sum_{i=0}^{m-1} c_i 2^i$
 - **(2) Use buckets to keep partial sums**
 - **Sum of elements in size b bucket is at most 2^b**



Idea: Sum in each bucket is at most 2^b (unless bucket has only 1 integer)
Bucket sizes:

16 8 4 2 1

Summary

- **Sampling a fixed proportion of a stream**
 - Sample size grows as the stream grows
- **Counting the number of 1s in the last N elements**
 - Exponentially increasing windows
 - Extensions:
 - Number of 1s in any last k ($k < N$) elements
 - Sums of integers in the last N elements