

Daubert Nox-Rust 502 DLS

INGREDIENTS	CAS NO	%	8HR OEL
naphthenic distillate, heavy, hydrotreated (severe)	64742-52-5.	10-20	5 mg/m3
Stoddard Solvent	8052-41-3.	32-42	790 mg/m3
(C15-30)alkylbenzenesulfonic acid, sodium salts	78330-12-8	6-11	-
zinc petrolatum (oxidised) sulfonate	68918-69-4	20-30	-



UN No: 1993
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to skin.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep out of reach of children.
 Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

Environment:

Harmful to aquatic organisms.

PROPERTIES



Liquid.Flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Emesis generally unnecessary. Debride for subcutaneous injection.
 Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Eliminate ignition sources.
 Consider evacuation.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x — Must not be stored together