

PPG PR 1422 B 1/2 Part A

INGREDIENTS	CAS NO	%	8HR OEL
N,N-dimethylacetamide	127-19-5	15-40	36 mg/m3
calcium dichromate	14307-33-6	10-30	0.05 mg/m3
kaolin	1332-58-7	3-7	10 mg/m3
carbon black	1333-86-4	0.1-1	3 mg/m3



UN No: **3082**
 Hazchem Code: •**3Z**
 DG Class: **9**
 Subsidiary Risk: **None**
 Packing Group: **III**
 Poisons Schedule: **S6**



NFPA Rating:

- ▶ **0:** Minimum
- ▶ **1:** Low
- ▶ **2:** Moderate
- ▶ **3:** High
- ▶ **4:** Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Harmful in contact with skin.
 Harmful if swallowed.
 Irritating to respiratory system.
 Risk of serious damage to eyes.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 May cause harm to the unborn child.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.SARANEX-23 2.NATURALRUBBER

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES

2

Does not burn.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Advice To Doctor:

Ipecac emesis. Chrome ulcers respond to CaNa2EDTA.

Fire Fighting:

Keep containers cool. Keep surrounding area cool. Water spray/fog.

Spills and Disposal:

Spilled liquid has low boiling temperature and evaporates quickly. Pollutant. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive

x

x

x — Must not be stored together