

Sigma-Aldrich Chromium Standard For AAS

INGREDIENTS	CAS NO	%	8HR OEL
NITRIC ACID	7697-37-2	1-<3	5.2 mg/m3
ammonium dichromate	7789-09-5	0.3-<1	0.05 mg/m3



UN No: **3264**
 Hazchem Code: **2X**
 DG Class: **8**
 Subsidiary Risk: **None**
 Packing Group: **III**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ **0:** Minimum
- ▶ **1:** Low
- ▶ **2:** Moderate
- ▶ **3:** High
- ▶ **4:** Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Causes burns.
 Risk of serious damage to eyes.
 May cause SENSITISATION by inhalation.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

May cause CANCER.
 May cause heritable genetic damage.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 May impair fertility.
 May cause harm to the unborn child.

* – limited evidence

PROPERTIES



Liquid. Mixes with water. Corrosive. Acid. Does not burn.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Flood body with water. Remove contaminated clothing. Wash with water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.

Fire Fighting:

Keep surrounding area cool. Water spray/fog.

Spills and Disposal:

Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.BUTYL 2.HYPALON 3.NEOPRENE

Respirator:

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive

x

x

x — Must not be stored together