

Schlumberger Corrosion Inhibitor A262

INGREDIENTS	CAS NO	%	8HR OEL
propargyl alcohol	107-19-7	5-10	2.3 mg/m3
formamide	75-12-7	10-30	18 mg/m3
methanol	67-56-1	10-30	262 mg/m3
isopropanol	67-63-0	10-30	983 mg/m3



UN No: **3286**
 Hazchem Code: ***3WE**
 DG Class: **3**
 Subsidiary Risk: **6.1**
 Packing Group: **II**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Liquid.
 Mixes with water.
 Corrosive. Highly flammable.
 May form explosive peroxides.

EMERGENCY



FIRST AID

Swallowed:	If more than 15 mins from Doctor, INDUCE VOMITING (if conscious). Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Severe exposure indicated by respiratory distress/hypotension Managements is essentially supportive. Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Keep containers cool. Water spray/ fog. Foam - alcohol type.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x x x x x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Toxic by inhalation.
 Toxic in contact with skin.
 Toxic if swallowed.
 Causes burns.
 Toxic: Danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
 Risk of serious damage to eyes.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

May cause harm to the unborn child.
 * — limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.NITRILE+PVC 2.PVDC/PE/PVDC

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report.
 Take precautionary measures against static discharges.
 Dispose of this material and its container at hazardous or special waste collection point.
 Keep locked up.
 Keep out of reach of children.
 Keep away from living quarters.
 Keep container in a well ventilated place.
 Keep away from food, drink and animal feeding stuffs.
 Keep away from sources of ignition. No smoking.
 Handle and open container with care.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Toxic smoke/fumes in a fire.
 Take precautionary measures against static discharges.
 Dispose of this material and its container at hazardous or special waste collection point.
 In case of fire and/or explosion, DO NOT BREATHE FUMES.