

## **Dow Ucarsol GT-10 Antifoam**

INGREDIENTS	CAS NO	%	8HR OEL
TRITON X-100	9036-19-5	0.25-<0.5	-
Phosphate Standard Solution 500 mg/l as PO4	7732-18-5	<20	-
FUSEROIL 8836	63148-62-9	3-<5	-

UN No: Not Applicable

Hazchem Code: Not Applicable

DG Class: None Subsidiary Risk: None Packing Group: None

Poisons Schedule: Not Applicable



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

# **HEALTH HAZARD INFORMATION**

#### PRECAUTIONS FOR USE











	U	
Appropriate	 	

Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	1.BUTYL 2.NEOPRENE 3.VITON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.
Environment:	Toxic to bees.Use appropriate container to avoid environmental contamination.  Avoid release to the environment. Refer to special

instructions/Safety data sheets.

### **PROPERTIES**



Liquid.Combustible.

### **EMERGENCY**







FIRST AID	
Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Pollutant. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Must not be stored together