

Akzo Nobel Interseal 1052 Mio Red Oxide Part A

INGREDIENTS	CAS NO	%	8HR OEL
XYLENE	1330-20-7	2.5-<10	350 mg/m3
bisphenol A/ diglycidyl ether resin, liquid	25068-38-6	10-<25	-
bisphenol A/ bisphenol A diglycidyl ether polymer	25036-25-3	1-<2.5	-
n-butanol	71-36-3	1-<2.5	-



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **None**
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.
 Irritating to skin.
 May cause SENSITISATION by skin contact.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of impaired fertility.
 Possible risk of harm to the unborn child.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)


Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Handle and open container with care.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid. Does not mix with water. Sinks in water.R10R19

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x — Must not be stored together