

Saudi Muitchem SM-0990

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	30-40	350 mg/m3
1,2,4-trimethyl benzene	95-63-6	NotSpec	-
solvent naphtha petroleum, heavy aromatic	64742-94-5	NotSpec	-
residues, petroleum, catalytic reformer fractionator	64741-67-9	1-5	-



UN No: 1986 Hazchem Code: •3W DG Class: 3 Subsidiary Risk: 6.1 Packing Group: III Poisons Schedule: S6

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES







Does not mix with water. Floats on water.Flammable.

EMERGENCY









Acute	Health
	Effects:

Harmful by inhalation and in contact with skin.

Irritating to eyes and skin.

Chronic **Health Effects:** May cause CANCER.

* - limited evidence

PRECAUTIONS FOR USE

HEALTH HAZARD INFORMATION





Environment:













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

Harmful to aquatic organisms.

FIRST AID

Give water (if conscious). Seek medical advice.

Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Advice To Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

> Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

Absorb with dry agent.

Stop leak if safe to do so.

Spills and Use only in well ventilated areas. Disposal:

Dispose of this material and its container at hazardous or special waste collection point.

This material and its container must be disposed of

in a safe way.

To clean the floor and all objects contaminated by

this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive

Toxic

Radioactive Oxidizing Х

х х - Must not be stored together