

## International Paint Thinner-Eqpt Cleaner

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	2.5-<10	350 mg/m3
ethylbenzene	100-41-4	1-<2.5	434 mg/m3
naphtha petroleum, light aromatic solvent	64742-95-6.	25-<50	-
n-butanol	71-36-3	25-<50	N/A



UN No: 1263  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **S6 NZS3**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation and if swallowed.  
 Irritating to respiratory system and skin.  
 Risk of serious damage to eyes.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 \* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.TEFLON 2.PVA

## Storage and Transportation:

Store in cool, dry, protected area.  
 Restrictions on Storage apply. Refer to Full Report.

## Fire/Explosion Hazard:

Flammable.  
 Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.

## Environment:

Toxic to aquatic organisms.  
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.  
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

## PROPERTIES



Liquid.  
 Does not mix with water.  
 Floats on water. Flammable.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice.  
 Do NOT give milk or oil.  
 Do NOT give alcohol.

## Eye:

Wash with running water (15 mins). Medical attention.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

## Fire Fighting:

Foam.

## Spills and Disposal:

Eliminate ignition sources.  
 Prevent from entering drains.  
 Contain spillage by any means.  
 Absorb with dry agent.  
 Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together