

Rust-Oleum Strust Hp 6Pk Gloss White

INGREDIENTS	CAS NO	%	8HR OEL
C14-20 aliphatics (<=2% aromatics)	64742-47-8.	25-50	5 mg/m3
Stoddard Solvent	8052-41-3.	0.1-1	790 mg/m3
naphtha, petroleum, hydrodesulfurised heavy	64742-88-7.	10-25	790 mg/m3
titanium dioxide	13463-67-7	10-25	10 mg/m3



UN No: 1263
 Hazchem Code: 3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic Health Effects: May cause CANCER. May cause heritable genetic damage. Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Liquid. Does not mix with water. Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

Eye: Wash with running water.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Treat symptomatically.

Fire Fighting: Foam.

Spills and Disposal: Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x — Must not be stored together

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: PVC chemical resistant type.

Respirator: Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard: Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.