

Sulzer MetcoMETCO: 4010, 4017, 4018, 4020, XPT-W310, XPT-W317, XPT-W318, XPTW320, SMJ-150TS, SMJ-250TILOP

INGREDIENTS CAS NO 8HR OEL titanium 7440-32-6 >90 2 mg/m3



UN No: 3089 Hazchem Code: 4Y DG Class: 4.1

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE









Glasses:	Consider chemical goggles.
Gloves:	Leather Gloves.
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE.

PROPERTIES



Highly flammable.

EMERGENCY





Eye:





Wash with running water.

FIRST AID

Swallowed: Rinse mouth with water.

Wash with soap

For burns: Apply cold water. Do NOT remove Skin:

clothes from area. Cover wound. NO OINTMENTS.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Treat symptomatically. **Advice To** Supportive care. "metal fume fever". Remove from

Doctor: exposure. Treatment is supportive.

Water iets. Fire Fighting:

Do NOT fight fire with BCF extinguisher.

Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







Х



Radioactive Oxidizing

x x - Must not be stored together