


MULTICORE SOLDER

INGREDIENTS	CAS NO	%	8HR OEL
stibine	7803-52-3	-	0.51 mg/m ³
lead fumes	7439-92-1.	-	0.15 mg/m ³
lead	7439-92-1	NotSpec.	0.15 mg/m ³
antimony	7440-36-0	NotSpec.	0.5 mg/m ³

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Mechanical exhaust recommended
Glasses:	Consider chemical goggles.
Gloves:	Leather Gloves.
Respirator:	Type B Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.

PROPERTIES



Does not mix with water. Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water. For burns: Immerse in cold running water (15 mins). Bandage lightly. MEDICAL ATTENTION.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Diazepam is anti-convulsant of choice. BAL may be an effective antidote.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Sweep shovel to safe place.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together