

## PPG CA 8000/B50459 Base Component

INGREDIENTS	CAS NO	%	8HR OEL
amyl methyl ketone	110-43-0	10-<30	233 mg/m3
XYLENE	1330-20-7	1-<10	350 mg/m3
methyl propyl ketone	107-87-9	1-<10	705 mg/m3



UN No: 1263  
 Hazchem Code: •3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful if swallowed.  
 HARMFUL-May cause lung damage if swallowed.

## Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

## Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

## Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point.

## Environment:

Harmful to aquatic organisms.

## PROPERTIES



Liquid.Flammable.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm.

## Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

## Fire Fighting:

Foam.

## Spills and Disposal:

Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x — Must not be stored together