

# **Devcon Wear Resistant Putty Resin**

INGREDIENTS	CAS NO	%	8HR OEL
bisphenol A/ diglycidyl ether resin, liquid	25085-99-8	30-60	-

UN No: Not Applicable

Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable

Poisons Schedule: S5

#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### **HEALTH HAZARD INFORMATION**







**Acute Health** Effects: Irritating to eyes and skin.

May cause SENSITISATION by skin contact.

#### PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Environment:	Toxic to aquatic organisms.  May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.  Avoid release to the environment. Refer to special

instructions/Safety data sheets.

#### **PROPERTIES**





Does not mix with water. Sinks in water. Does not burn.

#### **EMERGENCY**









# **FIRST AID**

Swallowed:	Give milk or water. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).
Eye:	Wash with running water.

Remove contaminated clothing. Wash with soap &

Skin: water.

Fresh air. Rest, keep warm. If breathing shallow,

give oxygen. Medical attention.

Advice To Treat symptomatically. Doctor:

Fire Fighting: Keep surrounding area cool. Water spray/fog.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS





Inhaled:



Explosive Radioactive Oxidizing

x x

- Must not be stored together