

## Hempel Hempatex HI-BUILD 46330

| INGREDIENTS                                 | CAS NO     | %     | 8HR OEL   |
|---|------------|-------|-----------|
| solvent naphtha petroleum, medium aliphatic | 64742-88-7 | 1-3   | 790 mg/m3 |
| xylene                                      | 1330-20-7  | 10-20 | 350 mg/m3 |
| n-butyl acetate                             | 123-86-4   | 3-5   | 713 mg/m3 |
| ethylbenzene                                | 100-41-4   | 1-3   | 434 mg/m3 |



UN No: 1263  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Harmful by inhalation.  
 Harmful in contact with skin.  
 Irritating to eyes.  
 Irritating to skin.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 May cause harm to breastfed babies.  
 Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PROPERTIES



Liquid. Mixes with water. Flammable.

## EMERGENCY



## FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

**Eye:** Wash with running water.

**Skin:** Remove contaminated clothing. Wash with soap & water.

**Inhaled:** Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

**Advice To Doctor:** Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

**Fire Fighting:** Water spray/ fog.

**Spills and Disposal:** Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.VITON/CHLOROBUTYL 2.PVA 3.PE

## Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

## Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together