

Meghmani Petromate Red13 (S.Red 164)

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	25-<40	350 mg/m3
C.I. Solvent Red 164	71819-51-7	60-<80	-



UN No: 1307 Hazchem Code: 3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Harmful by inhalation.

Irritating to eyes. Irritating to skin.

Chronic **Health Effects:**

Acute Health

Effects:

Possible risk of impaired fertility.

Harmful in contact with skin.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.

Environment:

Harmful to aquatic organisms.

PROPERTIES







Liquid. Does not mix with water.Flammable.

EMERGENCY









FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice. Do

NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap &

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow,

give oxygen. Medical attention.

Advice To Doctor:

Spills and

Disposal:

Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin.

Fire Fighting:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be

disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water

and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Toxic Radioactive Oxidizing х Х